

Product datasheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 45U, White, 2124H x 600W x 1200D mm

AR3305W

⚠ Discontinued on: 31 Dec 2025

⚠ To be discontinued

Main

| | |
|---------------------------|---|
| Product or component type | Rack enclosure |
| Number of rack unit | 45U |
| Provided equipment | Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels User manual |

Physical

| | |
|----------------------------|---|
| Height | 2124 mm |
| Width | 600 mm |
| Depth | 1200 mm |
| Product weight | 141 kg |
| Colour | White |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| Maximum mounting depth | 1048 mm |
| Minimum mounting depth | 190.5 mm |
| Rack width | 19" |
| Marking | 14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels |
| Permanent permissible load | 1020.6 kg dynamic 1701.0 kg static |

Conformance

| | |
|-----------|-----------------------------------|
| Standards | UL 2416 UL 60950-1 EIA-310E |
|-----------|-----------------------------------|

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

| | |
|-------------------------|----------|
| Package 1 Height | 224 cm |
| Package 1 Width | 133.4 cm |
| Package 1 Length | 74.6 cm |
| Package 1 Weight | 158.4 kg |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 60 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 556 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 531 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 13 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 12 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|---|
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACH Regulation | Free of Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture


| | |
|---------------------------------|---|
| Recyclability potential, in % | 95 |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative





