

# Data Sheet

## FUJITSU Desktop ESPRIMO D956/E94+

Combines highest efficiency with expandability

The FUJITSU ESPRIMO D956/E94+ Desktop provides highest manageability, performance and expandability. The Zero Noise PC function supports a pleasant working environment, and the 94% efficient power supply will reduce your energy bills. With its innovative Low Power Active Mode feature you are ready for instant communication in the modern office. The use of the same software load within the product series ensures perfect infrastructure compatibility. On retirement, the Fujitsu distinctive EraseDisk function securely wipes your data.



### Zero Noise PC

Pleasant working environment due to completely quiet system (solid state disk required)

- Fan stop in standard operations

### Always Available Office PC - stay connected and save power

Be ready for instant communication and a significantly reduced energy bill

- Innovative Low Power Active Mode and highly-efficient integrated power-supply



### Best energy efficiency coupled with performance

Low power consumption combined with high levels of performance

- 6th generation Intel® Core™ processor family, a switched monitor outlet and a power supply with 94% efficiency

### System management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on processor) and DeskView manageability suite

### Green technology

Another example of the Fujitsu commitment to environmental protection and sustainability

- Halogen-free printed circuit board of mainboard, sophisticated product concept for the entire lifecycle



# Components

<b>Processor</b>	Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) * Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) * Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) * Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) Intel® Pentium® processor G4500 (2 Cores / 2 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 530) Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) Intel® Celeron® processor G3900 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics 510) Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors <small>*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)</small> Intel® Smart Response Technology supported by Intel® Core™ i3, i5 and i7 processors
<b>Operating systems</b>	
<b>Operating system</b>	Windows 10 Pro Windows 10 Home Windows 8.1 Pro Windows 8.1 Windows 7 Professional 64-bit Windows 7 Professional 32-bit
<b>Operating system compatible</b>	Windows 10 Pro (license + recovery media only) openSUSE Linux
<b>Microsoft OS support information</b>	This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.
<b>Operating system notes</b>	This system receives full support from Microsoft with Windows 10/Windows 10 Pro only. For any other Microsoft OS installed, this device has limited support from Microsoft. For more information, please see Microsoft's Support Lifecycle FAQ.
<b>Memory modules</b>	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
<b>Hard disk drives (internal)</b>	SSD PCIe 512 GB M.2 Highend SSD PCIe 256 GB M.2 Highend SSD PCIe 128 GB M.2 Highend SSD SATA III 256GB M.2 Mainstream SSD SATA III 128 GB M.2 Mainstream SSD SATA III, 512 GB Mainstream, 2.5-inch SSD SATA III, 256 GB Mainstream, 2.5-inch SSD SATA III, 128 GB Mainstream, 2.5-inch SSD SATA III, 512 GB Mainstream, 2.5-inch, SED SSD SATA III, 256 GB Mainstream, 2.5-inch, SED SSD SATA III, 128 GB Mainstream, 2.5-inch, SED SSD SATA III, 128 GB Entry, 2.5-inch SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch*

<b>Hard disk notes</b>	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
<b>Graphics</b>	VGA Extension Card NVIDIA® NVS™315 LP, 1 GB NVIDIA® GeForce® GTX 745 2 GB LP, 2 GB NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DVI-I to VGA Adapter DP to DVI-D (single link) Adapter Cable
<b>Drives (optional)</b>	BD Triple Writer SATA ultra slim (tray) DVD Super Multi ultra slim (tray) MultiCard Reader 24in1 USB 2.0 3.5"
<b>Interface add on cards/components (optional)</b>	WLAN 802.11ac (2x2) PCIe x1 LP and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version) WLAN 802.11ac (2x2) PCIe x1 LP (dedicated regions only) Parallel Interface Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1

## Base unit

<b>Base unit</b>	ESPRIMO D956/94+
<b>Mainboard</b>	
<b>Mainboard type</b>	D3432
<b>Formfactor</b>	proprietary
<b>Chipset</b>	Intel® Q170
<b>Processor socket</b>	LGA 1151
<b>Processor quantity maximum</b>	1
<b>Supported capacity RAM (max.)</b>	64 GB
<b>Memory slots</b>	4 DIMM (DDR4)
<b>Memory frequency</b>	2,133 MHz
<b>Memory notes</b>	Dual channel support For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.
<b>LAN</b>	10/100/1,000 MBit/s Intel® I219LM
<b>BIOS version</b>	AMI Aptio V
<b>BIOS features</b>	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
<b>Audio type</b>	On board
<b>Audio codec</b>	Realtek ALC671
<b>Audio features</b>	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
<b>I/O controller on board</b>	
<b>Serial ATA total</b>	5
<b>thereof SATA III</b>	5

**I/O controller on board**

thereof eSATA	2
<b>Controller functions</b>	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10

**Interfaces**

Audio: line-in	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.0 total	6
USB front	2x USB 2.0; 2x USB 3.0
USB rear	2x USB 2.0; 4x USB 3.0
USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	1 ; optional: 2nd serial port (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
<b>Interface Module notes</b>	Anytime USB charge functionality

**Input device / components**

<b>Input devices (optional)</b>	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
---------------------------------	--

**Drive bays**

3.5-inch internal bays	1
3.5-inch external bays	1
5.25-inch external bays	1
<b>Drive bay notes</b>	5,25" bay: for slim optical disc drive only; internal 3.5" bay: 1x 3.5" drive (screwless) or 1x 2.5" drive (screws) or optional via adapter for 1x or 2x 2.5" drives (screws); external 3.5" bay: optional as internal 3.5" bay (screws)
M.2-2280	1 x on mainboard (for PCIe or SATA SSD modules)

**Slots**

PCI-Express 3.0 x16	1 x (174 mm / 6.85 inch) Low profile
PCI-Express 2.0 x4 (mech. x16)	1 x (174 mm / 6.85 inch) Low profile
PCI-Express x1	2 x (174 mm / 6.85 inch) Low profile

**Graphics on board**

<b>Graphics brand name</b>	Intel® HD Graphics 510, Intel® HD Graphics 530
<b>Shared video memory</b>	up to 1,782 MB
<b>TFT resolution (VGA)</b>	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel

**Graphics on board**

<b>TFT resolution (DVI)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
-----------------------------	---

<b>TFT resolution (DisplayPort)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
-------------------------------------	---

<b>Graphics features</b>	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
--------------------------	---

<b>Graphics notes</b>	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
-----------------------	--

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 86% / 90% / 94% / 93%
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	280 W
<b>Power factor correction/active power</b>	active
<b>Monitor outlet</b>	Switched

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption
<b>Link to Energy White Paper</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=934c7bf3-7b3b-4f31-9dae-5b92487659c2">http://docs.ts.fujitsu.com/dl.aspx?id=934c7bf3-7b3b-4f31-9dae-5b92487659c2</a>

**Heat dissipation**

<b>Heat dissipation notes</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Noise emission**

<b>Related Processors for noise</b>	Intel® Core™ i7 6700
<b>Standard noise emission</b>	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
<b>Standard noise notes / description</b>	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
<b>Standard noise operation mode: CPU</b>	3.4 B / 20 dB(A) Bystander; 24 dB(A) Operator position
<b>50% load</b>	
<b>Standard noise operation mode: HDD</b>	3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position
<b>load</b>	
<b>Standard noise operation mode: Idle</b>	3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position
<b>mode</b>	

**Noise emission**

**Standard noise operation mode: ODD load** 4.4 B / 31 dB(A) Bystander; 35 dB(A) Operator position

**Standard noise operation mode: Office applications 2.0** 3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position

**Blue angel noise emission according certification** According to ISO 7779:2010, ECMA-74 for max. possible configuration

**Blue angel noise notes / description** A-weighted sound power level Lwad (in B); 1B = 10dB

**Blue angel noise operation mode: HDD load** 3.4 B = 34 dB (A)

**Blue angel noise operation mode: Idle mode** 3.3 B = 33 dB (A)

**Blue angel noise operation mode: ODD load** 4.5 B = 45 dB (A)

**Dimensions / Weight / Environmental**

**Dimensions (W x D x H)** 332 x 338 x 89 mm  
12.68 x 13.31 x 3.51 inch

**Operating position** horizontal / vertical (optional, feet needed)

**Weight** 8 kg

**Weight (lbs)** 17.64 lbs

**Weight notes** Actual weight may vary depending on configuration

**Operating ambient temperature** 10 - 35 °C (50 - 95 °F)

**Operating relative humidity** 5 - 85 % (relative humidity)

**Compliance**

**Product** ESPRIMO D956/94+

**Model** DTF

**Germany** TÜV GS

**Europe** CE

**USA/Canada** FCC Class B  
cCSAus

**Global** RoHS (Restriction of hazardous substances)  
WEEE (Waste electrical and electronic equipment)  
Microsoft Operating Systems (HCT / HCL entry / WHQL)  
ENERGY STAR® 6.1 (dedicated regions)  
EPEAT® Gold (dedicated regions)

**China** CCC (planned)

**Compliance link** <http://globalsp.ts.fujitsu.com/sites/certificates>

**Additional Software**

**Additional software (preinstalled)** Adobe® Reader® (pdf reader)  
McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version)  
Win7: Fujitsu Recovery (hard disk based recovery)  
Win8: Microsoft Push Button Recovery (hard disk based recovery)  
Microsoft Office (buy license to activate the pre-installed Microsoft Office)

**Additional software (optional)** Recovery DVD for Windows®  
Drivers & Utilities DVD (DUDVD)  
CyberLink PowerDVD BD (playback software for Blu-ray Disc™)  
CyberLink PowerDVD DVD (playback software for DVD)  
Nero Essentials XL

**Manageability**

**Manageability technology** DeskUpdate Driver management  
PXE 2.1 Boot code  
Wake up from S5 (off mode)  
Intrusion switch (optional)  
WoL (Wake on LAN)  
iAMT 11.0 (depending on processor)

**Manageability**

<b>Manageability software</b>	DeskView Client DeskView Instant BIOS Management
<b>DeskView components</b>	Inventory Management BIOS Management Driver Management Security Management Alarm Management
<b>Supported standards</b>	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)

**Security**

<b>Physical Security</b>	Kensington Lock support Eye for padlock Integrated cabinet lock (optional)
<b>System and BIOS Security</b>	Embedded security (TPM 2.0) EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
<b>User Security</b>	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
<b>Workplace Embedded Tools</b>	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) Easy Restore (optional)

**Miscellaneous**

Keyboard on (Special Fujitsu keyboard required)
Thermal management
Low Power Active Mode
Extended lifetime

**Serviceability**

EasyFix
EasyChange for HDD
EasyChange for optical drives

**Packaging information**

<b>Packaging dimension (mm)</b>	467 x 265 x 540 mm
<b>Packaging dimension (inch)</b>	18.39 x 10.43 x 21.26 inch
<b>Max. quantity / pallet</b>	28
<b>Material - Weight (g) Carton</b>	1180 g
<b>Material - Weight (lbs) Carton</b>	2.6 lbs
<b>Material - Weight (g) EPS / PS</b>	180 g
<b>Material - Weight (lbs) EPS / PS</b>	0.4 lbs
<b>Material - Weight (g) PE</b>	60 g
<b>Material - Weight (lbs) PE</b>	0.13 lbs
<b>Packaging notes</b>	printed user documentation is bleached in chlorine free process

**Warranty**

<b>Warranty period</b>	3 years (depending on country)
<b>Warranty type</b>	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)

<b>Warranty</b>	
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>
<b>Product Support Services - the perfect extension</b>	
<b>Recommended Service</b>	9x5, Onsite Response Time: Next Business Day
<b>Spare Parts availability</b>	5 years after end of product life
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>

## Recommended Accessories

# More information

## Fujitsu OPTIMIZATION Services

In addition to FUJITSU Desktop ESPRIMO D956/E94+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

## Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

## Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

## Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Desktop ESPRIMO D956/E94+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)

© 2016 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

FUJITSU Technology Solutions GmbH

Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)

2016-05-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)

© 2016 Fujitsu Technology Solutions GmbH