

CE750

USB KVM Extender

- The CE750 is a USB based KVM Extender with automatic signal compensation and RS-232 serial functionality that allows access to a computer system from a remote USB console (USB keyboard, monitor, and USB mouse).

Because it allows access to a computer system from a remote console, the CE750 is perfect for use in any type of installation where you need to place the console where it is conveniently accessible, but you want the system equipment to reside in a safe location – away from the dust and dirt of the factory floor, or the harsh environmental influence of a construction site, for example.

The CE750 improves on previous designs by the addition of an RS-232 port, on both the Local and Remote Units, that allows you to connect to a serial terminal for configuration (Local Unit), or serial devices such as touchscreens and barcode scanners (Remote Unit)



CE750R






CE750L

Features

- Local and Remote Units connect at distances up to 200 m using Cat 5e cable
- Dual console operation – control your system from both the local and remote USB keyboard, monitor, and mouse consoles
- Built-in ASIC for greater reliability and compatibility
- USB Keyboard and USB Mouse Ports
- RS-232 serial ports - allows you to connect to a serial terminal for configuration (Local Unit), or serial devices such as touchscreens and barcode scanners (Remote Unit)
- Supports stereo speakers and stereo microphone
- USB overcurrent detection and prevention
- Pushbutton operating mode selection (Local Unit only) – select between Local and Auto operating modes.
- Built-in 8KV/15KV ESD protection (Contact voltage 8KV; Air voltage 15KV) and 2KV surge protection
- Adjustable gain control – automatically and manually adjusts signal strength to compensate for distance
- High resolution video – up to 1920x1200@60Hz at 30m, 600x1200@60Hz at 150m, 1280x1024@60Hz at 200m
- Supports VGA, SVGA, SXGA (1280 x 1024) and UXGA(1600 x 1200) and multisync monitors; local monitors supports DDC; DDC2; DDC2B
- Hot pluggable
- Rack mountable
- Easy to install – no software required – connecting cables to the devices is all it takes
- Supports Wide Screen formats *

*The EDID data for a widescreen is sent from the local video output port. For widescreen modes and displays connect the monitor to the local video output port or use an ATEN EDID emulator.



Specification

Function	CE750L	CE750R	
Connectors	Console Ports	Keyboard 1 x USB Type A Female (White)	Video 1 x HDB-15 Female (Blue)
		Mouse 1 x USB Type A Female (White)	Speakers 1 x Mini Stereo Jack Female (Green)
		Speakers 1 x Mini Stereo Jack Female (Green)	Mic. 1 x Mini Stereo Jack Female (Pink)
	KVM Ports	KB / Video / Mouse 1 x SPHD-15 Female (Yellow)	N/A
		Speakers 1 x Mini Stereo Jack (Green)	
	Mic. 1 x Mini Stereo Jack (Pink)		
	RS-232 1 x DB-9 Female (Black)	1 x DB-9 Male (Black)	
	Power 1 x DC Jack (Black)		
	Unit to Unit 1 x RJ45 Female (Black)		
LEDs	Local 1 (Green)	N/A	
	Remote 1 (Green)	1 (Green)	
	Link N/A	1 (Green)	
	Picture Compensation N/A	1 (Orange)	
Pushbuttons	Operating Mode Selection 1 x Pushbutton	N/A	
	Picture Compensation N/A	2 x Pushbuttons	
Emulation	Keyboard / Mouse	USB	
Video		1920x1200@60Hz at 30m, 1600x1200@60Hz at 150m, 1280x1024@60Hz at 200m; DDC2, DDC2B	
Power Consumption	DC5.3V/3.0W	DC5.3V/4.2W	
Environment	Operating Temp.	0-50°C	
	Storage Temp	-20-60°C	
	Humidity	0-80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	0.49 kg	0.49 kg
	Dimensions (L x W x H)	20.00 x 8.36 x 2.63 cm	20.00 x 8.36 x 2.63 cm

* The specifications and pictures are subject to change without notice.

