

Form Factor 2U rackmount Host Interface USB 3.0 (Type B)  LED Indicators Power, link, status  Buttons Power switch  Dimensions (HxWxD) 89 × 482 × 534 mm  Weight (Net) 9.9 kg  Weight (Gross) 12.74 kg  Max. number of HDDs/SSDs supported HDDs/SSDs supported 0 - 40 °C (32°F - 104°F)  Relative Humidity 5-95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure 4. Smart fan control by detecting system and hard drive temperature		
Host Interface  LED Indicators  Power, link, status  Buttons  Power switch  Dimensions (HxWxD)  89 × 482 × 534 mm  Weight (Net)  9.9 kg  Weight (Gross)  12.74 kg  Max. number of HDDs/SSDs supported  Hard Drive Type  3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature  0 - 40 °C (32°F - 104°F)  Relative Humidity  5 - 95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit  Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level  Management  Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	UX-800U-RP	
Buttons Power switch  Dimensions (HxWxD) 89 × 482 × 534 mm  Weight (Net) 9.9 kg  Weight (Gross) 12.74 kg  Max. number of HDDs/SSDs supported  Hard Drive Type 3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature 0 - 40 °C (32°F - 104°F)  Relative Humidity 5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating M4.63 W  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Form Factor	2U rackmount
Buttons Power switch  Dimensions (HxWxD) 89 × 482 × 534 mm  Weight (Net) 9.9 kg  Weight (Gross) 12.74 kg  Max. number of HDDs/SSDs supported  Hard Drive Type 3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature 0 - 40 °C (32°F - 104°F)  Relative Humidity 5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Host Interface	USB 3.0 (Type B)
Dimensions (HxWxD) 89 × 482 × 534 mm  Weight (Net) 9.9 kg  Weight (Gross) 12.74 kg  Max. number of HDDs/SSDs 8 supported 8.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature 0 - 40 °C (32°F - 104°F)  Relative Humidity 5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	LED Indicators	Power, link, status
Weight (Net)  9.9 kg  Weight (Gross)  12.74 kg  Max. number of HDDs/SSDs supported  8  Hard Drive Type  3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature  0 - 40 °C (32°F - 104°F)  Relative Humidity  5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit  Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level  44.1 db(A)  Management  Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Buttons	Power switch
Weight (Gross)  12.74 kg  Max. number of HDDs/SSDs supported  Hard Drive Type  3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature  0 - 40 °C (32°F - 104°F)  Relative Humidity  5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit  Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level  44.1 db(A)  Management  Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Dimensions (HxWxD)	89 × 482 × 534 mm
Max. number of HDDs/SSDs supported  Hard Drive Type  3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature  0 - 40 °C (32°F - 104°F)  Relative Humidity  5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit  Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level  44.1 db(A)  Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Weight (Net)	9.9 kg
supported  Hard Drive Type 3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs  Operating temperature 0 - 40 °C (32°F - 104°F)  Relative Humidity 5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep 61.24 W  Mode  Power Consumption: Operating Mode, Typical 84.63 W  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Weight (Gross)	12.74 kg
Operating temperature 0 - 40 °C (32°F - 104°F)  Relative Humidity 5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical 84.63 W  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure		8
Relative Humidity 5~95% RH non-condensing, wet bulb: 27°C.  Power Supply Unit Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Hard Drive Type	3.5" SATA 6Gb/s, 3Gb/s hard drive or 2.5" SATA 6Gb/s, 3Gb/s SSDs
Power Supply Unit  Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz  Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  84.63 W  Sound Level  44.1 db(A)  Management  Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Operating temperature	0 - 40 °C (32°F - 104°F)
Power Consumption: HDD Sleep Mode  Power Consumption: Operating Mode, Typical  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Relative Humidity	5~95% RH non-condensing, wet bulb: 27°C.
Mode  Power Consumption: Operating Mode, Typical  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS  1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	Power Supply Unit	Redundant ATX power supply, 300W, input: 100-240V AC, 50/60Hz
Mode, Typical  Sound Level 44.1 db(A)  Management Managed via QNAP QTS OS  1. Supports disk S.M.A.R.T. information 2. Locate RAID expansion enclosures 3. Locate hard disks on RAID expansion enclosure	·	61.24 W
Management  Managed via QNAP QTS OS  1. Supports disk S.M.A.R.T. information  2. Locate RAID expansion enclosures  3. Locate hard disks on RAID expansion enclosure		84.63 W
<ol> <li>Supports disk S.M.A.R.T. information</li> <li>Locate RAID expansion enclosures</li> <li>Locate hard disks on RAID expansion enclosure</li> </ol>	Sound Level	44.1 db(A)
	Management	<ol> <li>Supports disk S.M.A.R.T. information</li> <li>Locate RAID expansion enclosures</li> <li>Locate hard disks on RAID expansion enclosure</li> </ol>

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Designs and specifications are subject to change without notice.

<sup>\*</sup> Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.