



PowerEdge C6320

Greater performance and improved energy efficiency with optimized compute, processors and memory for the most demanding high-performance computing and scale-out workloads. Features the Intel Xeon processor E5-2600 v4 product family and iDRAC8 with Lifecycle Controller.

Optimized for HPC

High-performance computing workloads such as scientific simulations, seismic processing and data analytics rely on compute performance, memory bandwidth and overall server efficiency to reduce processing time and data center costs. The next-generation Dell PowerEdge C6320 provides an optimized compute and storage platform for HPC and scale-out workloads with up to four independent two-socket servers with flexible 24 x 2.5" or 12 x 3.5" high-capacity storage in a compact 2U shared infrastructure platform.

With up to 44 cores per node, dynamic drive assignment, dual-port Intel 82559ES 10GbE LOM, and embedded systems management automation with the iDRAC8 with Lifecycle Controller, the C6320 is a scale-out modular compute workhorse.

Ideal balance of compute, memory, local storage and management automation

Computationally intense workloads demand performance, from processors to memory to connected devices. In addition to a leap in processor performance with the next-generation Intel® Xeon® processor E5-2600 v4 product family, the C6320 has increased core counts over prior E5-2600 v3 models. C6320 supports up to 512GB of memory per server node, for a total of 2TB of memory in a highly dense and modular 2U solution.

The C6320 leverages the scale and cost efficiencies of the integrated Dell Remote Access Controller 8 (iDRAC8) with Lifecycle Controller, proven by operation in millions of servers worldwide. iDRAC8 with Lifecycle Controller delivers intelligent management and configuration automation for hyper-converged solutions and appliances, and enables you to select the management functions you need, to streamline operations by reducing the time and number of steps to deploy, monitor, and update C6320 servers throughout their entire life cycle.

Flexibly mix workloads in one chassis

With numerous options for compute, storage and connectivity in one advanced shared infrastructure 2U chassis, the C6320 provides flexibility to configure servers for your specific workloads. Tailor the C6320 for your scale-out workload requirements with up to 44 cores per node, memory bandwidth up to 2133MT/s and dynamic drive assignment.

The C6300 enclosure supports up to 24 x 2.5" or 12 x 3.5" drives with multiple SATA, SAS and SSD options for up to 72TB of local storage capacity.³ With the expander backplane option, dynamic drive assignment for 2.5" drives provides even more flexibility by zoning any number of drives to each node, giving nodes additional or fewer storage resources as workloads demand. The x8 PCIe 3.0 mezzanine slot in each node supports a variety of options for 1Gb and 10GbE, Mellanox® InfiniBand®, or additional drive controllers while the x16 PCIe 3.0 slot adds even more flexibility.

The PowerEdge C6320 server joins Dell's award-winning and groundbreaking PowerEdge C server line. The C6320 is designed to bring the most compute power in the least amount of space with the least energy draw to lower operational costs. These performance-optimized servers are purpose-designed for the most demanding HPC, Web 2.0, hosting, data analytics and cloud building use cases.

PowerEdge C6320

- Intel Xeon processor E5-2600 v4 product family
- Support for 2400MT/s DDR4 DIMMs
- Flexible 2.5" or 3.5" high-capacity drive configurations
- iDRAC8 with Lifecycle Controller (Express or Enterprise)

Feature	PowerEdge C6320 technical specification	
Form factor	2U rack mount	
Processor	Intel® Xeon® processor E5-2600 v4 product family Up to 4 x 2-socket servers: 4, 6, 8, 10, 12, 14, 16, 18, 20, 22 cores per processor Intel C612 chipset	
Memory	16 DIMM slots for up to 512GB per node: 8GB/16GB/32G DDR4 DIMM (up to 2400MT/s)	
Primary storage	Maximum internal storage: 72TB SATA3 or nearline 48TB SAS	
Drive bays/hard drives	24 x 2.5" or 12 x 3.5" hard drive options 24 x 2.5" hard drive option with variable drive allocation Supports 7.2K, 10K, 15K RPM 2.5"/3.5" SAS Supports 7.2K RPM 2.5"/3.5" SATA	2.5" SATA (7.2K): 250/500GB, 1TB/2TB 2.5" SAS (7.2K): 1TB/2TB 2.5" SAS (10K): 600GB/1.2TB 2.5" SAS (SAS12): 200/400/800GB 2.5" SATA SSD: 120/160/200/400/800/960GB 2.5" SAS SSD: 200/400/800GB 3.5" SATA (7.2K): 1TB/4TB/6TB
Connectivity	Intel 82599ES 10GbE dual-port SFP+	
USB ports	1 external rear port	
I/O slots	1 x16 PCIe 3.0 half-height, half-length 1 x8 PCIe 3.0 mezzanine	
I/O adapter options	1GbE: Intel Powerville I350 dual-port 1GbE (PCIe adapter) Intel Powerville I350 dual-port 1GbE PCIe (mezzanine) 10GbE: Intel X540 Dual Port 10GbE 10Base-T (mezzanine) Mellanox ConnectX-3 Pro dual-port 10GbE SFP+ (mezzanine)	InfiniBand: Mellanox ConnectX®-3 VPI single-port FDR/40GbE QSFP+(PCIe adapter) Mellanox ConnectX-3 VPI dual-port FDR/40GbE QSFP+(PCIe adapter) Mellanox ConnectX-3 VPI single-port FDR/40GbE QSFP+(mezzanine)
Drive and RAID controllers	Intel C612 chipset SATA: AHCI SATA drives RAID: 0, 1,5,10 PERC H330: SATA and SAS drives, x8 PCIe 3.0 RAID: 0, 1,5,10, 50 (optional) PERC H730: SATA and SAS drives, x8 PCIe 3.0 RAID: 0, 1,5,10, 50, 60 (optional) LSI® SAS 2008 Controller 6Gbs: mezzanine (optional) RAID: 0, 1, 10, JBOD (optional) SATA DOM boot device (64Mb) SAS SSD boot device (120Gb)	
Power supplies	Dual hot-plug redundant high-efficiency 1400W or 1600W power supplies (200–220 VAC, 240VDC)	
Fans	Shared cooling with quick-disconnect 4x 60mm speed fans	
Operating systems	Microsoft® Windows Server® 2012 Microsoft Windows Server 2012 R2	Novell® SUSE® Linux Enterprise Server Red Hat® Enterprise Linux®
Hypervisors	Microsoft Windows Server 2012 (with Hyper-V® enabled) VMware® vSphere® ESXi®	
Systems management	Remote management: iDRAC8 with Lifecycle Controller iDRAC8 Express (default) iDRAC8 Enterprise (upgrade option)	Systems management: IPMI 2.0 compliant Dell OpenManage Essentials Dell OpenManage Mobile
Services (Availability varies by region. Please contact your sales representative for details.)	Data Center Consulting Services Rack Integration (U.S. only, not available in China) Rack Design Verification Configuration Services/CFI Onsite Online Self Dispatch Basic Support ProSupport Plus ProSupport Flex for Data Center	4-Hour Support Keep Your Hard Drive Support Assist: Proactive Automated Support Enterprise Wide Contract IT Remote Advisory Service Certified Data Destruction Specialized Onsite Services
Dimensions and weight	H: 8.68 cm (3.42 in), W: 44.8 cm (17.6 in), D: 79.0 cm (31.1 in) Weight (maximum configuration) 41 kg (90.4 lbs) Weight (empty) 15.1 kg (33.3 lbs)	

End-to-end technology solutions

Reduce IT complexity, lower costs and eliminate inefficiencies by making IT and business solutions work harder for you. You can count on Dell for end-to-end solutions to maximize your performance and uptime. A proven leader in Servers, Storage and Networking, Dell Enterprise Solutions and Services deliver innovation at any scale. And if you're looking to preserve cash or increase operational efficiency, Dell Financial Services™ has a wide range of options to make technology acquisition easy and affordable. Contact your Dell Sales Representative for more information.**

Learn More at Dell.com/PowerEdge.

©2015 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind. **Leasing and financing provided and serviced by Dell Financial Services L.L.C. or its affiliate or designee ("DFS") for qualified customers. Offers may not be available or may vary in certain countries. Where available, offers may be changed without notice and are subject to product availability, credit approval, execution of documentation provided by and acceptable to DFS, and may be subject to minimum transaction size. Offers not available for personal, family or household use. Dell and the DELL logo are trademarks of Dell Inc.

