ThinkPad L460 Platform Specifications

Processor	Intel® Cele	eron® r	rocessoi	r or 6th Ger	neration In	tel Core	e™ i3 / i5 / i7	Processor	Smart card reade	r <i>Optional:</i> Smart c	ard reader				
	Processor Number		# of	Base Frequency	Max Turbo Frequency	Cache	Memory Types	Processor Graphics Intel HD graphics	Media reader Ports	4-in-1 reader (MMC, SD, SDHC, SDXC) Three USB 3.0 (one Always On), VGA, Mini DisplayPort, Ethernet (RJ-45), Dock connector (integrated models only)					
	Cel 3855U		2	1.6 GHz	-	2MB	DDR3L-1600	510		//HD720p resolution, low light sensitive, fixed focus HD Audio, Realtek® ALC3245 codec / stereo speakers, 2W x 2 / dual array microphone, combo audio/microphone jack					
	i3-6100U i5-6200U			2.3 GHz 2.3 GHz	- 2.8 GHz	Hz 3MB		Intel HD graphics 520	Audio support						
	i5-6300U	2	4	2.4 GHz	3.0 GHz				Keyboard UltraNav™	6-row, spill-resistant, multimedia Fn keys TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad					
	i7-6500U i7-6600U			2.5 GHz 2.6 GHz	3.1 GHz 3.4 GHz	4MB 4MB			Security	Power-on password, hard disk password, supervisor password, security keyhole					
Graphics	Intel HD Graphics 510 or 520 in processor only, or Intel HD Graphics 520 in processor and AMD Exo Pro Radeon R5, 2GB memory; supports external analog monitor via VGA and digital monitor via Mini DisplayPort; supports three independent displays; Max resolution: 3840x2160@60Hz (DP via mDP cable); 1920x1200@60Hz (VGA)								Security chip ThinkEngine vPro (optional) Fingerprint readel	Trusted Platform Module, TCG 1.2-compliant Delivers improved thermal and power efficiency, up to 30 day standby, faster resume time, enhanced security, as well as anti-tampering measures Intel vPro Technology er Optional: Swipe style fingerprint reader on the keyboard bezel					
Chipset					`	71 OGD1	0), 1020/120	70 001 12 (10,1)	Battery Max battery life ¹⁰	Li-Ion 3-cell (23Wi			0 11 7014/1-	,	
Memory	Intel SoC (System on Chip) platform 32GB max ⁷ / PC3-12800 1600MHz DDR3L, non-parity, dual-channel capable, two DDR3L SO-DIMM sockets								(MobileMark® 2014)	Max battery life	3-cell 6.93 hr	6-cell 48Wh 12.7 hr	6-cell 72Wh 20.53 hr]	
Display	Some: 14.0" (355mm) HD (1366x768), anti-glare, LED backlight, 220 nits, 16:9 aspect ratio, 400:1 or 500:1 contrast ratio Some: 14.0" (355mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 250 nits, 16:9 aspect ratio, 600:1 or 700:1 contrast ratio, 170° viewing angle								AC adapter Preload	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2					
Multi-touch	None	oo mis,	10.5 asp	Ject ratio, o	00.1 01 70	0.1 0011	liastralio, T	vo viewing angle		Lenovo Solution Center Lenovo Setting					
Storage	Some: HI	DD / S. nock M	ATA 6.0G lounted F	ab/s, 2.5" wi ab/s, 2.5" w Hard Drive, NAND flash	ide, 7mm of Active Prof	or 9.5m				 ThinkVantage Product Recovery Rescue and Recovery™ ThinkVantage System Update Adobe® Reader® Microsoft® Office preloaded; Microsoft® Office preloaded; 					
Optical	None purchase a product key to activate											e			
Ethernet	Non-vPro vPro mod			hernet Con hernet Con			ıcksonville) Jacksonville)		McAfee® LiveSafe™ (30-day trial) Limited warranty¹² One of the following, configurable by model:						
WLAN⁴ Bluetooth™	One of the following, configurable by model: • 11ac+BT, Broadcom BCM4356, 2x2, M.2 card • 11ac+BT, Intel Dual Band Wireless-AC 8260, 2x2, M.2 card Bluetooth 4.1 wireless, integrated in Wi-Fi + Bluetooth combo adapter								Limited warranty	1-year depot repair service 3-year/1-yr battery limited onsite service 3-year/1-yr battery limited onsite service 3-year/1-yr battery limited onsite service, OID (Onsite International Delivery)					
WWAN (optional)	One of the following, configurable by model:								Mil-Spec test	MIL-STD-810G mi		, ,	note internation	iai Delivery)	
SIM card (opt)	Wireless WAN upgradable								Environment	EPEAT™ Gold (US	,		EENGUARD®; F	RoHS-compliant	
Dimensions ³ Weight ² Case material	WxDxH: Models Integrated discrete me	model odel	4.25 lt 4.3 lb	" x 0.95"; 3-cell b / 1.93 kg b / 1.95 kg ile-Butadiel	4.45 lb	<i>cell</i> / 2.02 kç / 2.04 kg	3								