ideacentre Y900-34ISZ Platform Specifications

Processor	6th Generation Intel® Core™ i5 / i7 Processors	Security features • Security slot (in rear for Kensington® MicroSaver® cable)						
	Processor Cores / Frequency Cache Memory Types Integrated Graphics	,	Power-on password Administrator password					
	Core i5-6600K 4 / 4 3.5 GHz / 3.9 GHz 6 MB DDR4-2133 Intel HD Graphics Core i7-6700 4 / 8 3.4 GHz / 4.0 GHz 8 MB DDR4-2133 Intel HD Graphics Core i7-6700K 4 / 8 4.0 GHz / 4.2 GHz 8 MB DDR4-2133 530	Keyboard Mouse	Some: full-size, Gaming K800 USB keyboard , Fn keys, black Some: full-size USB keyboard, Fn keys, black silk Some: USB mouse Gaming M800, black Some: USB optical mouse, black silk					
Memory Disk	32GB max, PC4-17000 2133MHz DDR4, four 288-pin UDIMM sockets	Mechanical	 Tower (34L), black color Dimensions (WxDxH): 8.12" x 19.82" x 18.85"; 206.4mm x 503.5mm x 478.9mm Weights (net weight): 33.1 lb (15 kg) Top water cooling (under top) Bay 1: 5.25", access, optical (optional) Bay 2: 5.25", no access, disk Bay 3~bay 6: 3.5", no access, disk (with 3.5" to 2.5" bracket) Slot 1: half-length, full-height, PCle x1 Slot 2: half-length, full-height, PCle x16, for discrete graphics Slot 3: half-length, full-height, PCle x1 Slot 4: half-length, full-height, PCle x1 Slot 5: half-length, full-height, PCle x1 Slot 5: half-length, full-height, PCle x1 Slot 6: half-length, full-height, PCle x1 Slot 7: half-length, full-height, PCle x1 Slot 7: half-length, full-height, PCle x1 					
M.2 SSD (opt) Optical Onboard SATA Media reader Graphics	Some: Solid State Hybrid Drive (SSHD) with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 7200 rpm, 3.5" wide Some: SATA 6.0Gb/s, 3.5" wide, 7200 rpm Some: SSD / 2.5" wide, SATA 6.0Gb/s M.2 Solid State Drive (SSD), via M.2 card slot Some: DVD±RW SATA Some: Blu-ray burner DVD±RW SATA SATA 6.0Gb/s controller (integrated in chipset), six SATA 6.0Gb/s connectors 7-in-1 media reader (SD, SDHC, SDXC, MMC, MMC plus, MS, MS Pro) Intel HD Graphics 530 in processor, uses main memory, DirectX® 12,							
	one VGA, one HDMI, one DVI, supports three independent displays; Some: NVIDIA Geforce GTX960, 2GB GDDR5, PCIe 3.0 x16 adapter, DirectX 12, DP x1, HDMI x1, DVI x2							
	Some: NVIDIA Geforce GTX970, 4GB GDDR5, PCIe 3.0 x16 adapter, DirectX 12, DVI x1, HDMI x1, DP x3 Some: NVIDIA Geforce GTX980, 4GB GDDR5, PCIe 3.0 x16 adapter, DirectX 12,	Power supply	Some: 625 watts, autosensing, 85% PSU, EnergyStar 6.1, universal (110V-220V) Some: 450 watts, autosensing, 85% PSU, EnergyStar 6.1, universal (110V-220V)					
	DVI x1, HDMI x1, DP x3	Limited warranty	1-year, limited onsite service / service upgrades available					
	Some: AMD Radeon R9 370X, 4GB GDDR5, PCle 3.0 x16 adapter, DirectX 12, DP x1, HDMI x1, DVI x2 Some: Dual NVIDIA Geforce GTX1070, 8GB GDDR5, PCle 3.0 x16 adapter, DirectX 12, DP x3, HDMI x1, DVI x1 Some: NVIDIA Geforce GTX1080, 8GB GDDR5, PCle 3.0 x16 adapter, DirectX 12, DP x3, HDMI x1, DVI x1	Preload	Preloaded operating system Windows® 10 Home 64 Preloaded applications (only some listed) • Lenovo® Rescue System • Steam Game Portal • Lenovo SHAREit • Lenovo Companion • Lenovo Solution Center • McAfee® LiveSafe™ (30 days trial) (optional) • Microsoft Office 2013 preloaded; (30 days trial) (optional)					
Chipset	Intel Z170 Chipset							
Front ports	Two USB 3.0 (one for Always On Charging), two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)							
Rear ports	Four USB 3.0, two USB 2.0, ethernet (RJ-45), PS/2 keboard port, power connector, one VGA, one HDMI, one DVI additional VGA, DVI, DP or HDMI on optional graphic card on some models *Onboard VGA, HDMI and DVI are unavailable on discrete models	Environment	ENERGY STAR® 6.1 (Need 85% PSU); RoHS-compliant					
Rear audio port	s Line-in (3.5mm), line-out (3.5mm), microphone-in (3.5mm), surround-out (3.5mm),							
IEEE 1394	center/low frequency-out (3.5mm), S/PDIF-out None							
Audio support	High Definition (HD) Audio, Realtek ALC892							
WLAN Bluetooth™ Ethernet Modem	11ac, M.2 Card, Wi-Fi + Bluetooth combo adapter, 2x2 Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Realtek RTL8111GN None							
See footnotes for more detailed information								

ideacentre Y900 RE-34ISZ Platform Specifications

Processor	6th Generation Intel® Core™ i7 Processor						Security features	s • Security slot (in rear for Kensington® keyhole)
	Processor	Cores / Threads	Frequency (Base/Max)	Cache	Memory Types	Graphics		Power-on passwordAdministrator password
	Core i7-6700K	4/8	4.0 GHz / 4.2 GHz	8 MB	DDR4-2133	Intel HD Graphics 530	Keyboard Mouse	Full-size, Razer [™] BlackWidow Chroma mechanical keyboard, USB, Fn keys, black Razer Mamba tournament edition mouse, USB, black
Memory	32GB max, PC4-17000 2133MHz DDR4, four 288-pin UDIMM sockets						_	 Tower (34L), black color Dimensions (WxDxH): 8.12" x 19.82" x 18.85"; 206.4mm x 503.5mm x 478.9mm Weights (net weight): 35.3 lb (16 kg) Top water color of the co
Disk M.2 SSD	SATA 6.0Gb/s, 3.5" wide, 7200 rpm Some: M.2 SSD / PCle 3.0 x 4 Some: M.2 SSD / SATA							
Optical	Some: DVD±RV Some: Blu-ray b	N SATA burner D\	VD±RW SATA					Bay 1: 5.25", access, optical Bay 2: 5.25", no access Bay 3~bay 6: 3.5", no access, disk (with 3.5" to 2.5" bracket) Slot 1: half-length, full-height, PCle x1 Slot 2: half-length, full-height, PCle x16, for discrete graphics Slot 3: half-length, full-height, PCle x1 Slot 4: half-length, full-height, PCle x1 Slot 5: half-length, full-height, PCle x16, for discrete graphics Slot 6: half-length, full-height, PCle x1 Slot 7: half-length, full-height, PCle x1
Onboard SATA Media reader	SATA 6.0Gb/s co 7-in-1 media rea	ontroller (der (SD,	(integrated in chipse SDHC, SDXC, MM	t), six S C, MMC	SATA 6.0Gb/s o plus, MS, MS	onnectors Pro)		
Graphics	one VGA, one H	DMI, one Geforce G	processor, uses mae DVI, supports three GTX1080, 8GB GDD DP x3	e indep	endent display	s;		
Chipset	Intel Z170 Chips	et						
Front ports	Two USB 3.0 (one for Always On Charging), two USB 2.0,						Power supply	625 watts, autosensing, 85% PSU, EnergyStar 6.1, universal (110V-220V)
Rear ports	microphone (3.5mm), headphone (3.5mm) Four USB 3.0, two USB 2.0, ethernet (RJ-45), PS/2 port, power connector,				port, power co	nnector.	Limited warranty	, ,
one VGA, one HDMI, one DVI *Onboard VGA, HDMI and DVI are unavailable on discrete models Rear audio ports Line-in (3.5mm), line-out (3.5mm), microphone-in (3.5mm), surround-out (3.5mm),						Preload	Preloaded operating system Some: Windows® 10 Home 64 Some: Windows 10 Pro 64 Preloaded applications (only some listed)	
IEEE 1394	center/low frequency-out (3.5mm), S/PDIF-out None							 Lenovo® Rescue System Razer™ Synapse
Audio support	High Definition (I	HD) Audi	io, Realtek ALC892					Razer Comms
WLAN Bluetooth™	Bluetooth 4.0 wir	ac, M.2 Card, Wi-Fi + Bluetooth combo adapter, 2x2 uetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter				oter		Lenovo Nerve Center Lenovo Solution Center
Ethernet Modem	One gigabit ethernet port, Řealtek RTL8111GN None						Environment	ENERGY STAR® 6.1 (Need 85% PSU); RoHS-compliant

See footnotes for more detailed information

© Lenovo

(ideacentre Y900 RE-34ISZ Spec) October 2016