

# Data Sheet

## FUJITSU Server PRIMERGY TX2540 M1 Dual socket Intel® Xeon® processor tower server

Well-balanced price- performance

FUJITSU Server PRIMERGY will give you the servers you need to power any workload and changing business requirements. As business processes expand so does the need for applications. Each has its own resource footprint, so you need a way to optimize your computing to better serve your users. PRIMERGY systems will help you match your computing capabilities to your business priorities with our complete portfolio of expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as hyper-converged scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, provide more agility in daily operations, and integrate seamlessly to let help you concentrate on core business functions.

Perfect for small and medium businesses as well as branch offices, FUJITSU Server PRIMERGY TX tower systems are robust and cost-efficient servers by providing rock solid reliability. Additionally they are characterized by simple IT operations, low power consumption and quiet operation so that they can be handled by non-technically trained staff and can be used in standard office environments. By the way: Almost all PRIMERGY TX servers can be rack-mounted to offer best flexibility.

### PRIMERGY TX2540 M1

The FUJITSU PRIMERGY TX2540 M1 is the perfect Tower Server for small and medium-sized companies (SMB) as well as branches. It supports up to two processors of the Intel Xeon E5-2400 v2 family, thus combining affordable performance with balanced expandability. Its maximum 24 hard disks and 192 GB of RAM is ideal as a starting-point for server virtualization or as a database and communication server. Furthermore, optional redundancy secures stable and reliable

operation. Thanks to its minimum operational noise, the server is ideal for offices, for example under the desk. Furthermore, the comprehensive Fujitsu ServerView® Suite provides support for administrators during server installation, deployment and administration.



# Features & Benefits

Main Features	Benefits
<p><b>Cost effective performance</b></p> <ul style="list-style-type: none"><li>■ Intel® Xeon® E5-2400 v2 product family with up to 10 cores</li><li>■ Up to 192 GB memory (12 DIMM slots) and up to 6 PCIe slots, 768GB RAM on special release</li></ul>	<ul style="list-style-type: none"><li>■ Provides a well-balanced price / performance ratio for SMBs and branch offices</li><li>■ Optimized for server-based computing, virtualization, databases and ERP &amp; CRM software, collaboration &amp; messaging solutions</li><li>■ High levels of expandability and the performance of two processors – perfect for virtualization</li><li>■ Tailor the level of redundancy to your needs and your budget</li><li>■ When the company grows your PRIMERGY TX2540 M1 can easily be converted into a rack server</li><li>■ Silent operation for use in offices or showrooms</li><li>■ So small and silent that it might even be placed under desks</li><li>■ The comprehensive tools of the Fujitsu ServerView Suite eases the administrators life</li></ul>
<p><b>Solid expandability and redundancy</b></p> <ul style="list-style-type: none"><li>■ Expanded scalability of up to 24 2.5-inch or 8 3.5-inch storage drives, 5 PCIe Gen2/3 and 1 PCI slot</li><li>■ Optional redundant power supply units and fans</li><li>■ Optional rack mount kit</li></ul>	
<p><b>Silent, compact, and easy to deploy</b></p> <ul style="list-style-type: none"><li>■ Low noise emissions through optimized air flow and Fujitsu's Cool-safe® technology</li><li>■ Compact 4U chassis</li><li>■ Fujitsu ServerView Suite including tools for installation and deployment, permanent status monitoring and control</li></ul>	

# Technical details

## PRIMERGY TX2540 M1

Base unit	PRIMERGY TX2540 M1 LFF	PRIMERGY TX2540 M1 LFF	PRIMERGY TX2540 M1 SFF	PRIMERGY TX2540 M1 LFF	PRIMERGY TX2540 M1 SFF
Housing types	Tower	Tower	Tower	Rack	Rack
Storage drive architecture	3.5-inch	3.5-inch	2.5-inch	3.5-inch	2.5-inch
Power supply	Standard	Hot-plug	Hot-plug	Hot-plug	Hot-plug

## Mainboard

Mainboard type	D3099-B
Chipset	Intel® C602
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2400 v2 product family

Processor	Intel® Xeon® processor E5-2403v2 (4C/4T, 1.80 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
	Intel® Xeon® processor E5-2407v2 (4C/4T, 2.40 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
	Intel® Xeon® processor E5-2420v2 (6C/12T, 2.20 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
	Intel® Xeon® processor E5-2430Lv2 (6C/12T, 2.40 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 60 W)
	Intel® Xeon® processor E5-2430v2 (6C/12T, 2.50 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
	Intel® Xeon® processor E5-2440v2 (8 Cores / 16 Threads, 1.90 GHz, TLC: 20 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1,600 MHz, 95 W)
	Intel® Xeon® processor E5-2450v2 (8C/16T, 2.50 GHz, TLC: 20 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 95 W)
	Intel® Xeon® processor E5-2470v2 (10C/20T, 2.40 GHz, TLC: 25 MB, Turbo: Yes, 8.0 GT/s, Mem bus: 1,600 MHz, 95 W)

Memory slots	12 (6 DIMMs per CPU, 3 channels with 2 slots per channel)
Memory slot type	DIMM (DDR4)
Memory capacity (min. - max.)	4 GB - 192 GB
Memory protection	Advanced ECC SDDC (Chipkill™)
Memory notes	On project release max 768 GB possible Performance Mode requires identical modules in all channels of each bank per CPU.

Memory options	4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
	8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
	16 GB (1 module(s) 16 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank

<b>Interfaces</b>	
USB 2.0 ports	9 x USB 2.0 (2 x front UHCI USB, 4 x rear UHCI USB 2 x internal for backup, 1x UFM and internal USB)
Graphics (15-pin)	1 x VGA
Serial 1 (9-pin)	1 x serial RS-232-C (9 pin), usable for iRMC S4 or system or common use
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet (Intel i210)
Management LAN (RJ45)	Management LAN traffic can be switched to shared onboard Gbit LAN port 1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s)

<b>Onboard or integrated Controller</b>	
RAID controller	All hardware storage controller options are described under Components
SATA Controller	Intel® C602, 6-port SATA (4 x for internal hard disks, 2 x for accessible drives)
SATA controller type notes	On board SATA controller supports RAID levels 0, 1, 10
LAN Controller	2 x 10/100/1000 Mbit/s Ethernet. 2 x Intel i210
Remote management controller	IPMI 2.0 compatible Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller)
Trusted Platform Module (TPM)	Infineon / TPM 1.2 module; TCG compliant (option)

<b>Slots</b>	
PCI-Express 3.0 x4 (mech. x8)	2 x Full height 280 mm length
PCI-Express 3.0 x16	2 x Full height first slot: 280 mm length, second slot: 170 mm length (only available with second CPU)
PCI-Express 2.0 x4 (mech. x8)	1 x Full height 230 mm length; preferred RAID slot
PCI-slots	1 x PCI 32Bit/33 MHz (support for 3.3V and 3.3V/5V cards; no support of 5V only cards)

<b>Slots</b>			
Slot Notes	in SAS configuration 1x PCI-Express occupied by modular RAID controller		
<b>Drive bays</b>			
Storage drive bays	3.5-inch or 2.5-inch hot-plug SAS/SATA		
Accessible drive bays	3 x 5.25/1.6-inch		
Notes accessible drives	All possible options described in relevant system configurator.		
Storage drive bays	Max. 8 x 3.5-inch	Max. 24 x 2.5-inch	Max. 24 x 2.5-inch
Accessible drive bays	3 x 5.25/1.6-inch for 1 x backup drive + 1 x ODD	3 x 5.25/1.6-inch for 1 x backup drive + 1 x ODD	3 x 5.25/1.6-inch for 1 x backup drive + 1 x ODD
<b>Fan Configuration</b>			
Number of fans	4		
Fan configuration	3 fans as standard plus 1 additional fan for redundancy operation possible (option)		
Fan notes	redundant fan configuration depends on base unit and is only available in combination with redundant PSU		
<b>Operating panel</b>			
Operating buttons	On/off switch NMI button Reset button		
Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) CPU status Fan status Hard disk error Temperature CSS (yellow) Memory status PSU status (green/ amber) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)		
Service display	Optional: ServerView Local Service Display (LSD)		
<b>BIOS</b>			
BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support		

## Operating Systems and Virtualization Software

<b>Certified or supported operating systems and virtualization software</b>	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Server® 2012 R2 Essentials
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Server® 2012 Essentials
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Web Server 2008
	VMware vSphere™ 6.0
	VMware vSphere™ 5.5
	VMware vSphere™ 5.1 Embedded
	VMware vSphere™ 5.1
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
Red Hat® Enterprise Linux 5 with XEN	
Citrix® XenServer®	
Univention Corporate Server 4	
Univention Corporate Server 3.x	
<b>Operating system release link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473">http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfb3230473</a>
<b>Operating system notes</b>	Support of other Linux derivatives on demand

## Server Management

<b>Standard</b>	<ul style="list-style-type: none"> <li>ServerView Suite - Deploy <ul style="list-style-type: none"> <li>Installation Manager</li> <li>Scripting Toolkit</li> </ul> </li> <li>ServerView Suite - Control <ul style="list-style-type: none"> <li>Operations Manager incl. PDA and ASR &amp; R (Prefailure and Analysis; Automatic Server Recovery and Restart)</li> <li>Agents and CIM Providers / Agentless Service</li> <li>System Monitor</li> <li>RAID Manager</li> <li>Capacity Management</li> <li>Power Management</li> <li>Storage Support</li> </ul> </li> <li>ServerView Suite - Maintain <ul style="list-style-type: none"> <li>Remote Management (iRMC in combination with Intel® Node Manager)</li> <li>Update Management (BIOS, Firmware, Windows Drivers, Agents and CIM Providers)</li> <li>Performance Measurement</li> <li>Asset Management</li> <li>Online Diagnostics</li> </ul> </li> <li>ServerView Suite - Integrate <ul style="list-style-type: none"> <li>Integration packs for Microsoft System Center, VMware vCenter, VMware vRealize, Nagios, and HP SIM</li> </ul> </li> <li>Deployment tools and others</li> </ul>
-----------------	---

**Server Management**

<b>Option</b>	ServerView embedded Lifecycle Management Enhanced management functionalities for simplified, highly integrated and automated management processes ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media
<b>Server Management notes</b>	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.

**Dimensions / Weight**

<b>Floor-stand (W x D x H)</b>	177 x 651 x 456 mm
<b>Rack (W x D x H)</b>	483 x 611 x 177 mm
<b>Dimension notes</b>	Floorstand Width 177 mm without tilt protection (420 mm with tilt protection); depth measured includes handles on redundant PSU. Rack depth includes handles of redundant PSU, excludes rack handles / front
<b>Height Unit Rack</b>	4 U
<b>Weight</b>	16 kg - 32 kg
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Rack integration kit</b>	Rack integration kit as option

**Environment**

<b>Operating ambient temperature</b>	10 - 35 °C
<b>Operating relative humidity</b>	10 - 85 % (non condensing)
<b>Operating environment</b>	FTS 04230 – Guideline for Data Center (installation specification)
<b>Operating environment link</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe">http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe</a>
<b>Noise emission</b>	Measured according to ISO 7779 and declared according to ISO 9296
<b>Sound pressure (LpAm)</b>	Noise minimum configuration: 22 dB(A) (idle) / 24 dB(A) (operating) Noise typical configuration: 29 dB(A) (idle) / 30 dB(A) (operating)
<b>Sound power (LWAd; 1B = 10dB)</b>	Noise minimum configuration: 3.9 B (idle) / 4.2 B (operating) Noise typical configuration: 4.8 B (idle) / 4.9 B (operating)
<b>Noise notes</b>	Noise emissions depends on operation modes, system configuration and ambient temperature. Operating mode measured based on OLTIS with 50% load. *OLTIS = FUJITSU Load Profile which stresses all components of a server with a given load level.

**Electrical values**

<b>Power supply configuration</b>	1 x standard power supply or 1 x hot-plug power supply or 2 x hot-plug power supply for redundancy depending on model
<b>Hot-plug power supply redundancy</b>	Optional
<b>Active power (max. configuration)</b>	432 W
<b>Apparent power (max. configuration)</b>	435 VA
<b>Heat emission (max. configuration)</b>	1555.2 kJ/h (1474.0 BTU/h)
<b>Rated current max.</b>	7.6 A (100 V) / 3.7 A (240 V)
<b>Active power note</b>	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: <a href="http://configurator.ts.fujitsu.com/public/">http://configurator.ts.fujitsu.com/public/</a>
<b>Power supply</b>	800W standard, 90% (Gold efficiency), 100-240V, 50 / 60Hz 450W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 94% (Platinum efficiency), 100-240V, 50 / 60Hz 800W hot-plug, 96% (Titanium efficiency), 200-240V, 50 / 60Hz
<b>Power supply notes</b>	Power Safeguard adapts system performance in case the power requirements exceeds supply limits. !96% Titanium Power supply unit is only released for 200-240V

**Compliance**

<b>Global</b>	CB RoHS (Substance limitations in accordance with global RoHS regulations) WEEE (Waste electrical and electronic equipment)
<b>Germany</b>	GS
<b>Europe</b>	CE
<b>USA/Canada</b>	CSAc/us ULc/us FCC Class A
<b>Japan</b>	VCCI:V3 Class A + JIS 61000-3-2

Compliance	
China	CCC
Australia/New Zealand	C-Tick
Taiwan	BSMI
Compliance link	<a href="http://globalsp.ts.fujitsu.com/sites/certificates">http://globalsp.ts.fujitsu.com/sites/certificates</a>
Compliance notes	<p>There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.</p> <p>* Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.</p>

## Components

Backup Drives	LTO3HH Ultrium, 400 GB, 60 MB/s, half height, SAS 3Gb/s
	LTO4HH Ultrium, 800 GB, 120 MB/s, half height, SAS 6Gb/s
	LTO5HH Ultrium, 1,500 GB, 140 MB/s, half height, SAS 6Gb/s
	LTO6HH Ultrium, 2,500 GB, 160 MB/s, half height, SAS 6Gb/s
	RDX Drive, 320 GB, 500 GB, 1 TB , 25 MB/s, half height, USB 3.0
Optical drives	Blu-ray Disc™ Triple Writer, (6x BD-ROM; 8x DVD; 24x CD), slimline, SATA I
	DVD-ROM, (16xDVD; 48xCD), half height, SATA I
	DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I
	DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I

## Hard disk drives

HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, 512n, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 6 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 4 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 3.5-inch, business critical
HDD SAS, 12 Gb/s, 2 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
HDD SAS, 12 Gb/s, 1.8 TB, 10,000 rpm, 512e, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 12 Gb/s, 1 TB, 7,200 rpm, 512e, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical



<b>Solid-State-Drive</b>	SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 960 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 480 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 240 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
	SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
	SSD SATA, 6 Gb/s, 120 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
	SSD SATA, 6 Gb/s, 120 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise, 0.3 DWPD (drive writes per day for 5 years)
SSD SATA, 6 Gb/s, 120 GB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)	
SSD SATA, 6 Gb/s, 120 GB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)	
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 3.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)	
SSD SATA, 6 Gb/s, 1.92 TB, Mixed-use, hot-plug, 2.5-inch, enterprise, 3 DWPD (drive writes per day for 5 years)	
<b>SCSI / SAS Controller</b>	LSI SAS Ctrl 6G 8ext PCIe FH SAS Ctrl. 6 Gbit/s 8 ports ext. PCIe 2.0 x8
<b>RAID Controller</b>	RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache
	Fujitsu RAID Ctrl SAS 6G 1GB (D3116C), RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 1 GB, Optional FBU (based on LSI SAS2208)
	Fujitsu RAID Ctrl SAS 6G 0/1 (D2607), RAID 0/1 Ctrl., SAS/SATA 6 Gbit/s, 8 ports int. RAID level: 0, 1, 10, No BBU support
	Fujitsu PRAID CP400i, RAID Ctrl., SAS/SATA 12 Gbit/s, 8 ports int. RAID level: 0, 1, 1E, 10, 5, 50, No FBU support
<b>Communication, Network</b>	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.0 x8 SFP+ ( Fujitsu )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 2.1 x8 RJ45 ( Intel® )
	Ethernet Ctrl. 2 x 10 Gbit/s PCIe 3.0 x8 SFP+ ( Intel® )
	Ethernet Ctrl. 2 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
	Ethernet Ctrl. 4 x 1 Gbit/s PCIe 2.1 x4 RJ45 ( Intel® )
<b>Graphics add on cards</b>	NVIDIA® NVS™ 315, PCIe x16, 2x DVI/VGA
<b>Rack infrastructure</b>	Rack Mount Kit
	Cable Management for 19-inch DataCenter / PRIMECENTER Racks
	Cable Arm 2U for PRIMECENTER- and 3rd-party racks

---

**Warranty**

Warranty period	3 years
Warranty type	Onsite warranty Warranty conditions tbd
Warranty Terms & Conditions	<a href="http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM">http://support.ts.fujitsu.com/warranty/Index.asp?LNG=COM</a>

**Product Support Services - the perfect extension**

Support Pack Options	Globally available in major business areas: 9x5, Next Business Day Onsite Response Time 9x5, 4h Onsite Response Time 24x7, 4h Onsite Response Time
Recommended Service	24x7 Onsite Service with 4h Onsite Response Time
Service Lifecycle	5 years after end of product life
Service Weblink	<a href="http://www.fujitsu.com/fts/products/product-support-services/">http://www.fujitsu.com/fts/products/product-support-services/</a>

## More information

### Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY TX2540 M1, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu PRIMERGY TX2540 M1, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://www.fujitsu.com/primergy>

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
©2016 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

**Contact**  
FUJITSU LIMITED

Website: [www.fujitsu.com](http://www.fujitsu.com)  
2016-09-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
©2016 Fujitsu Technology Solutions GmbH