Fujitsu recommends Windows 10 Pro.

Data Sheet FUJITSU Notebook LIFEBOOK E556

Reliable Business Performer

Enjoy reliability and powerful performance with FUJITSU Notebook LIFEBOOK E556 through latest technology enhancements. A comprehensive business feature-set with common port replicator and connectivity options support you to work with ease and efficiency on your notebook wherever your meeting room or workplace is situated. Choose a 39.6 cm (15.6-inch) or 35.6 cm (14.0-inch) display and even reduce weight with an interchangeable modular bay element

Reliable and powerful performance

Technology enhancement offer advanced functionality

Latest processors, DDR4 RAM boost performance empowering you to work faster

Secure and solid protection

Smart security and resistant design

Integrated fingerprint sensor, SmartCard reader, TPM, among other security options protect your data, a solid housing and spill-resistant keyboard your notebook

Family concept continuity

Reduce complexity and drive down evaluation and deployment costs

■ BIOS and mainboard for one bit image, components, modular bay elements, accessories and port replicator are shared across the LIFEBOOK E5 Series. Unique to Fujitsu, one port replicator befits 8 devices across the LIFEBOOK Ultrabook[™], notebook, 2 in 1 and mobile workstation and is compatible with the predecessor

Different high-capacity battery packs

Long lasting performance for extra working hours

Choose from three different high-capacity battery packs to support efficient working in business environments

Compatible with existing equipment

Reuse existing equipment and reduce TCO by connecting the notebook and equipment without adapter

A native Serial Port RS-232 option













Components

Base unit	LIFEBOOK E556 non vPro	LIFEBOOK E556 vPro
Operating systems		
Operating system	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional pre-installed (available through downgrade rights from Windows 10 Pro)	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional pre-installed (available through downgrade rights from Windows 10 Pro)
Operating system compatible	Windows 8.1 Pro (available through downgrade rights from Windows 10 Pro)	Windows 8.1 Pro (available through downgrade rights from Windows 10 Pro)
Operating system notes	Operating system compatible Windows 7 Professional 64- bit (with 6th generation Intel® processors) Windows 7 Professional 32-bit (with 6th generation Intel® processors)	Operating system compatible Windows 7 Professional 64- bit (with 6th generation Intel® processors) Windows 7 Professional 32-bit (with 6th generation Intel® processors)
Processor	Intel® Core™ i7-6500U processor (2.5 GHz, up to 3.1 GHz, 4	+ MB) *
	Intel® Core™ i5-6300U processor (2.4 GHz, up to 3.0 GHz, 3 MB)	
	Intel [®] Core™ i5-6200U processor (2.3 GHz, up to 2.8 GHz, 3 MB) *	
	Intel [®] Core™ i3-6100U processor (2.3 GHz, 3 MB) *	
	Intel® Core™ i3-6006U processor (2.0 GHz, 3 MB) *	
	*Processor only for retail, SMB, education and governmen	t
	Intel [®] Core™ vPro™ Processor - Best Platform for Businesse	
Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,133 MHz, SO DIMM	
	8 GB (1 module(s) 8 GB) DDR4, 2,133 MHz, SO DIMM	
	16 GB (1 module(s) 16 GB) DDR4, 2,133 MHz, SO DIMM	
Hard disk drives (internal)	SSHD, 5,400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.	A R T
hard disk drives (internal)	SSD SATA III, 512 GB, 2.5-inch, OPAL capable	
	SSD SATA III, 256 GB, 2.5-inch, OPAL capable	
	SSD SATA III, 256 GB, 2.5-inch	
	SSD SATA III, 230 GB, 2.5-inch, OPAL capable	
	SSD SATA III, 120 GB, 2.5-Inch	
	SATA, 7,200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.	
	SATA, 5,400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.	
	SATA, 5,400 rpm, 1 TB, 2.5-inch, S.M.A.R.T.	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to h Accessible capacity may vary, also depending on used soft Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III (6GBit/s) If configured with an HDD, the drive has an integrated sho	ware.
Modular bay options	2nd hard disk drive	
	SuperMulti-format DVD burner (with double layer support)	
	Weight saver	
Interface add on cards/components (optional)		
3G/4G (optional)	Sierra Wireless EM8805 (Downlink speed 42 Mbit/s, Uplink	speed 5.76 Mbit/s)
	LTE Sierra Wireless EM7305 (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s)	
WLAN (optional)	Intel® Dual Band Wireless-AC8260 11ac with integrated Bl	uetooth 4.1
Display	39.6 cm (15.6-inch),LED backlight,(HD),Anti-glare display,compound,1,366 x 768 pixel,350:1,220 cd/m²	
· · ·	39.6 cm (15.6-inch),LED backlight, (Full HD),Anti-glare IPS	
Multimedia		
Camera	Optional: Built-in webcam, HD (Microsoft® Lync™)	

Base unit

Base unit	LIFEBOOK E556 non vPro	LIFEBOOK E556 vPro
General system information		
Chipset	Integrated	Integrated
Chipset notes		Supports iAMT 11.0 Intel® vPro™ requires Core i5-63xx & i7-66xx CPU, Intel WLAN 8260ac, TPM module
Supported capacity RAM (max.)	32 GB	32 GB
Memory slots	2 DIMM (DDR4)	2 DIMM (DDR4)
Memory notes	DDR4 - 2133 MHz	DDR4 - 2133 MHz
LAN	10/100/1,000 MBit/s Intel® I219V	10/100/1,000 MBit/s Intel® I219LM
BIOS features	InsydeH20 Bios	InsydeH20 Bios
Audio type	On board	On board
Audio codec	Realtek ALC255	Realtek ALC255
Audio features	Stereo speakers	Stereo speakers
Display		
Display notes	ISO 9241-307 - Pixel class II HD - Viewing angle: Left/Right 40°, Top 10°, Bottom 30°; Color Gammut: 42% FHD - Viewing angle: Left/Right 80°, Top 80°, Bottom 80°; Color Gammut: 45%	ISO 9241-307 - Pixel class II HD - Viewing angle: Left/Right 45°, Top 15°, Bottom 35°; Color Gammut: 45% FHD - Viewing angle: Left/Right 80°, Top 80°, Bottom 80°; Color Gammut: 45%
Graphics		
Base unit	LIFEBOOK E556 non vPro	LIFEBOOK E556 vPro
TFT resolution (DisplayPort)	up to 4,096 × 2,160	up to 4,096 × 2,160
TFT resolution (VGA)	up to 1,920 x 1,200	up to 1,920 x 1,200
TFT resolution (DVI on Port Replicator)	up to 1,920 x 1,200	up to 1,920 x 1,200
Graphics brand name	Intel [®] HD Graphics 520	Intel [®] HD Graphics 520
Graphics features	3 Display Support (2 external, 1 internal)	3 Display Support (2 external, 1 internal)
Graphics notes	Shared memory depending on main memory size and operating system	Shared memory depending on main memory size and operating system
Interfaces		
DC-in	1	
Audio: line-out / headphone	1	
Audio: line-in / microphone	1	
Internal microphones	2x digital microphones (array)	
USB 3.1 Gen1 (USB 3.0) total	3 (1 with Anytime USB Charge functionality)	
VGA	1	
DisplayPort	1	
Serial (RS-232)	1x optional	
Ethernet (RJ-45)	1	
Memory card slots	1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB)	
SmartCard slot	1 (optional)	
SIM card slot	1	
Port Replicator interfaces (optional)		
DC-in	1 (19V)	
Power on switch	1	
Audio: headphone	1	
Audio: microphone	1	

Point Reputation Instructs (points) 4 DisplayPoint 2 - 10 P (meet to DV) is shared with DV), works when DV (not connected DV 1 DVI 1 shared with DV (next to DV) - works when DV (not connected Ethemet (B+S) 1 (Pointrep & System) SAIA 1 SAIA 1 Notes Point replicator supports 0-Wests functionality Keyboard and pointing devices SystE-essional keyboard keys 104, Keyboard pitch: 19.0 mm, Keyboard stroke: 1.7 mm Tooch point have mouse buttors SystE-essional keyboard keys Automas 2 Dual band WLAN antennas, 2 UMISULE antennas optional Blaetooth v4.2 WLAN encryption WP WP, WA, WA2 WLAN encryption YP WP, WA3, 100V 2-AWIX Stole 2 0H L2, 3 pin (grounded) With And Alapter antennas optional Blaetooth v4.2 WLAN encryption YP WP, WA3, 100V 2-AWIX Stole 2 0H L2, 3 pin (grounded) West ACAdapter antennas optional Blaetooth v4.2 WLAN encryption YP WP, WA3, 100V		
DisplayPort 2.1 DP (next to DVI) is shared with DV, works when DVI not connected VGA 1 DVI 1-shared with DP [next to DVI] - works when DP (next to DVI] not connected Ethernet (QFAS) 1 (DV 1000) Reminigtion Lock 1 (DV 1000) extration to Lock Point replicator supports O-Hist's functionality Keyboard and pointing devices Spl1-sestiant keyboard with number to Marks Spl1-sestiant keyboard with number to Marks Number of heyboard keys 104, Keyboard pitch: 19.0 mm, Keyboard stoke: 1.7 mm Notes Spl1-sestiant keyboard keys: 104, Keyboard pitch: 19.0 mm, Keyboard stoke: 1.7 mm Noteless technologies Sonta LED Application buttors Power Binton Will All exception WEP, WAN WPA2 WLAH encyption WEP, KPA, MPA2 WLAH encyption WEP, KPA, WPA2 WLAH encyption WEP, KPA, MPA2 WLAH encyption WEP, KPA, MPA2 WLAH encyption WEP, KPA, MPA2<	Port Replicator interfaces (optional)	· · · · · · · · · · · · · · · · · · ·
Yu 1 DV 1 - shared with DP (next to DV) - work's when DP (next to DV) not connected Exemited (9,45) 1 (1011001000) Kensington Lock support 1 (Potterg & System) SAIA 1 Notes Pott replicator supports 0-Wats functionality Keyboard and pointing devices Spill resistant keyboard with number block Mumber of keyboard keys: 106, Keyboard pitch: 19.0 mm, Keyboard sinke: 1.7 mm Douchged with vom moue buttors Spall sistant keyboard with number block Murdees technologies Application buttons Power Button Y4.2 WLAN encryption WEY, WPA, WP2 WLAN encryption VEY, WP4, WP2 WLAN encryption WEY, WPA, WP2 WLAN encryption VEY, WP4, W		
DVI I shared with DP (next to DVI) works when DP (next to DVI) not connected Ethernet (R4-5) I 10110011000] Rendington Lock support I (Portrop & System) eSATA I Notes Poit replicator supports 0-Watts functionality Keyboard and pointing devices Spill accisant keyboard with number black Number of keyboard keys: 104, "Reposed picht: 10.0 mm, Keyboard stoke: 1.7 mm Touchpad with two mouse buttors Status EED Application buttors Application buttors Power Buttor WitAM encryption WE, WPA, WPA2 WitAM encryptin (Cack AL, 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grou	• •	
Etherer (9) 45) 1 (10001000) Kensington Luck support 1 (Portep & System) SATA 1 Notes Potreplicator supports 0 Watts functionality Keyboard and pointing devices Spill-resistant keyboard with number block Number of keyboard keys: 106, Keyboard pitch: 190 mm, Keyboard stoke: 1.7 mm Touchpad with no mouse buttors Status LD Application buttors Power Button Witeless technologies Antennas 2 Dual band WLAN antennas, 2 UMISUE antennas optional Bluetooth v/.2 WLAN notes Import and usage according to country-specific regulations. WID support Wes (with Intel W LAN) Power supply AC Adapter 19.V / 05 W (3.42 A), 100 V - 240 V, 50 H - 60 H 2, 3-pin (grounded) AWAIT ACApper (and and and and and and and and and and		
Kensing biols support 1 (Partep & System) eSATA 1 Notes Port replicator supports 0.Watts functionality Keyband and pointing devices Spill-resistant keyboard with number block Number of keyboard keys: 10%. Keyboard pitch 19.0 mm, Keyboard Stoke: 1.7 mm Tauchpad with two mouse buttons Status LED Application buttons Power Buttons Application buttons Power Buttons VIMAN notes WitAM notes WitAM notes Status LED VIMAN notes Status VIMAN notes VIMAN notes Status VIMAN notes VIMAN notes Status VIMAN notes Status VIMAN notes VIMAN notes Status VIMAN notes Sta		
eSATA 1 Notes Port replicator supports 0-Watts functionality Keyboard and pointing devices Splil-resistant keyboard with number block Number of keyboard with number block Number of keyboard strokes 10, Keyboard hitch 19.0 mm, Keyboard strokes 1.7 mm Touchgad with two mouse buttons Status (FD Application buttoms Power Button Wileless technologies Antennas 2 Dual band WLAN antennas, 2 UMIS/LIE antennas optional Bloetooth vk 2 ULAN encryption WUAN encryption WUAN encryption WUAN encryption WEP WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WID support Ves (until Intel W-LAN) Power supply AC Adapter 19 V 56 W (3.42 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter 19 V/ 80 W (A22 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter 19 V/ 80 W (A22 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter 19 V/ 80 W (A22 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter 19 V/ 80 W (A27 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter 19 V/ 80 W (A27 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter 19 V/ 80 W (A27 A), 100 V- 240 V, 50 Hz 50 Hz, 3 pin (grounded) Stim and light AC Adapter Notes 65W AC Adapter for usage with system 80 8 90W AC Adapter for usage with Port Replicator 14 Hon battery 6-cell, 5,000 Stim, A; 9 Wh Runtine 1st battery up to 21 Hon battery 6-cell, 5,000 Stim, A; 9 Wh Runtine 1st battery up to 12 Hon battery 6-cell, 5,000 Stim, A; 9 Wh Runtine 1st battery Notes Weight notes Hey Option Hey		
Notes Port replicator supports 0. Watts functionality Keyboard and pointing devices Splil-resistant keyboard with number block Number of keyboard keys: 104, Keyboard pitch: 19.0 mm, Keyboard stroke: 1.7 mm Touchpad with two muse buttons Status LED Application buttors Power Button Vireless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LE antennas optional Bluebooth v4.2 WLAN encryption WFP, WPA/2 WLAN encryption WFP, WPA/2 WLAN encryption WFP, WPA/2 WDM notes Import and usage according to contry-specific regulations. WDN notes 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Sim and light AC-Adapter 19 V / 60 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Ad-Adapter 19 V / 60 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Ad-Adapter 19 V / 60 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Ad-Adapter 11 Jon battery for cell, 5,600 S,000 mAb, 73 Wh 11 Jon battery for cell, 5,600 S,000 mAb, 73 Wh 11 Jon battery for cell, 4,500 mAb, 63 WA WDise emission Notes emission Dimensions (Wx D x H) Meas relet to the Eco Declaration Dimensions (Wz D x H) Meas relet to the Eco Declaration		
Keyboard and pointing devices Spill-resistant keyboard with number block Number of keyboard keys: 100, Keyboard pitch: 19.0 mm, Keyboard stoke: 1.7 mm Toudrpad with two mouse buttons Status ED Application buttons Power: Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Bluetooth V4.2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WEP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WEP, WPA, WPA2 WLAN encryption Towe fidea decording to contry-specific		
Spill resistant keyboard with number block Number of keyboard keys: 104, Keyboard pitch: 13.0 mm, Keyboard stroke: 1.7 mm Touchpad with two mouse buttons Status LED Application buttons Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Bluetooth v/, 2 WLAN notes Import and usage according to country-specific regulations. WUIN support Ves (with Intel W-LAN) Power Supply	Notes	Port replicator supports U-Watts functionality
Number of keyboard keys: 104, Keyboard pitch: 19.0 mm, Keyboard stroke: 1.7 mm Torchpad with two mouse buttons Status: 1FD Application buttons Power Button Witeless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Buteooth v4.2 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WDI support Ves (with Intel WLAN) Power supply	Keyboard and pointing devices	
Tockpad with two mouse buttons Status 1FD0 Application buttons Power Button Workers technologies Wireless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Bluetooth v4.2 WLAN encryption WFP, WPA 2 WLAN encryption HPY 19.0 W 14, 22.4, 1.00 V - 24.0 V, 50 Hz - 60 Hz, 3 pin (grounded) Slim and light AC Adapter Netes 65W AC Adapter for usage with system/ 80.8 90W AC Adapter for usage with Port Replicator Totas abstety changing time -150 min (53Mh) -180 min (72Mh) Battery changing time -150 min (53Mh) -180 min (72Mh) Battery changing time dontonat peaker feet to the Eco Declaration <th></th> <th></th>		
Status IED Application buttons Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Buetooth v4.2 WLAN encryption WFP, WPA, WPA2 WLAN encryption WFP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WDD support Ves (with Intel W-LAN) Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) of Wat AC Adapter (19 V / 90 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Wat AC Adapter (19 V / 90 W (4.24 A), 100 V - 240 V, 20 W A (24 D) HZ - 90 N MC Adapter for Usage with system / 00 8 90W AC Adapter for Usage with Port Replicator Is battery options Li-Ion battery 6-cell - 4, 0006, 700 mAh, 72 Wh Ruttine Is t		
Application buttons Power Button Wireless technologies Antennas 2 Dual band WLAN antennas, 2 UMIS/LTE antennas optional Bluetooth v4.2 WLAN encryption WEP, WPA, WPA2 WDisupport Ves (with Intel W-LAN) Power supply		
Power Button Wielest echnologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Biseleooth v4,2 WLAN encryption WFP, WPA, WPAZ WLAN notes Import and usage according to country-specific regulations. WIDI support Yes (with Intel W-LAN) Power supply		
Wieless technologies Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Bluetooth v4.2 WLAN encryption WEP, WPA, WPAZ WLAN notes Import and usage according to country-specific regulations. WDi support Yes (with Intel WLAN) Power supply A Adapter A Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0.4 Adapter (adapter (adapter) Notes 65 W A (Adapter for usage with system / 80 A 90 WA (Adapter (adapter) Notes 65 W A (Adapter for usage with system / 80 A 90 WA (Adapter for usage with Port Replicator Ist battery options Li lon battery 6 cell, 5,6005;800 mAh, 63 Wh Li lon battery 6 cell, 4,500 mAh, 63 Wh Li lon battery 6 cell, 4,500 mAh, 63 Wh Battery runne information is based on worldwide acknowledged BAPCo* MobileMark* 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCO* MobileMark* Poids ensults that enable direct product comparisons between manufactures. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases singlify with every re-change and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration </th <th></th> <th></th>		
Antennas 2 Dual band WLAN antennas, 2 UMTS/LTE antennas optional Bluetooth v4.2 WLAN encryption WEP, WPA, WPA2 WLAN totas Import and usage according to country-specific regulations. WDI support Ves (with Intel W LAN) Power supply	With the back of the start	
Bluetooth v4.2 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WDD support Ves (with Intel W-LAN) Power supply		2 Dual band WI AN aptropage 2 LIMTS/LTF aptropage aptional
WLAN encryption WEP, WPA, WPA2 WIAN notes Import and usage according to country-specific regulations. WiDi support Yes (with Intel V-LAN) Power supply Ac Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Wath AC Adapter technology 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Ac Adapter technology Notes 65W AC Adapter for usage with system / 80 8 90W AC Adapter for usage with Port Replicator Ist battery options Li-Ion battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-Ion battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-Ion battery 6-cell, 5,600/5,800 mAh, 63 Wh Battery options Li-Ion battery 6-cell, 5,600/5,800 mAh, 63 Wh Runtime 1st battery up to 12 h Battery charging time ~150 min (53Wh) ~ 180 min (72Wh) Battery charging time ~150 min (53Wh) ~ 180 min (72Wh) Battery charging time ~150 min (53Wh) ~ 180 min (72Wh) Battery charging time ~150 min (53Wh) ~ 180 min (72Wh) Battery notes Battery charging time specific battery charging time specific battery pruntime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity depending on product model, configuration, application and power management settings.		
WLAN notes Import and usage according to country-specific regulations. WDD support Yes (with Intel W-LAN) Power supply		
WiDi support Yes (with Intel W-LAN) Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator 1st battery options Li-lon battery 6-cell, 5,600,500 mAh, 63 Wh Li-lon battery 6-cell, 6,600,670 mAh, 72 Wh Li-lon battery 6-cell, 6,400,670 mAh, 72 Wh Li-lon battery 6-cell, 6,400,670 mAh, 72 Wh Li-lon battery 6-cell, 6,400,670 mAh, 72 Wh Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery untime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufactures. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, conliguration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions (W × D × H) 374 × 250 × 24.2 - 31.4 mm 14.72 × 9.84 × 0.95 - 1.23 inch Weight Weight from 2.2 kg	/1	
Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Watt AC Adapter technology 19 V / 90 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system 80 & 90W AC Adapter for usage with Port Replicator 1st battery options Li-lon battery 6-cell, 6,4006,700 mAh, 72 Wh Li-lon battery 6-cell, 6,4006,700 mAh, 72 Wh Battery charging time ~ 150 min (63Wh) ~ 180 min (72Wh) Battery that for wow baptor com for additional details. Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to wow baptor com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufactures. It does not guarantee any specific battery institute with actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions (Weight / Environmental) Tor 2, 2 Si X 4, 2- 31, 4 mm Dimensions (W x D x H) 14, 72 x 9, 84 x 0.95 - 1, 23 inch Weight fore from 2, 2 kg		
AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator 1st battery options Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Battery charging time Battery charging time -150 min (63Wh) - 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases sliptly with ever y re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch 40.9 ki Weight (Ibs) from 4.9 lbs Weight (Ibs) from 4.9 lbs Weight kteres Incl. weight saver. Weight may vary depending on actua		Yes (with Intel W-LAIN)
19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 80 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator 1st battery options Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 4,500 mAh, 72 Wh Ethor battery 6-cell, 4,500 mAh, 72 Wh Runtime 1st battery up to 12 h Battery charging time -150 min (63Wh) - 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to swow.bapco.com for additional details. The BAPCo® MobileMark® Enchmark provides results that enable direct product comparisons between manufactures: It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity depending on product model, configuration, application and power management settings. The battery capacity depending on product model, configuration, application and power management settings. The battery capacity depending on product model, configuration, application and power management settings. The battery capacity depending on product model, configuration. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight (bs) <td< th=""><th></th><th></th></td<>		
19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz, -60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator 1st battery options Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery up to 12 h Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery notion in 63Wh) ~ 180 min (72Wh) Battery notes Battery notion com for additional details. Rome ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery notion com for additional details. Ref to www.bapco com for additional details. The BAPCo® MobileMark® 2014 (office productivity). Ref to www.bapco com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery nuttime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 4.9 lbs Weight	AC Adapter	
Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator Ist battery options Li-Ion battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-Ion battery 6-cell, 6,400/6,700 mAh, 72 Wh Runtime Ist battery up to 12 h Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® feenchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight (Ibs) from 4.9 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance E Germany GS (Full HD Display only)		
1st battery options Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Runtime 1st battery up to 12 h Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental 374 x 250 x 24.2 - 31.4 mm Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg Weight from 2.2 kg from 4.9 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance G Germany GS (Full HD Display only) Europe CE G		
Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Runtime 1st battery up to 12 h Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance Cemany Gas CE Gas CE		
Li-ion battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery up to 12 h Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg from 4.9 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 & 80 % Compliance Ce Germany CS (Full HD Display only)	1st battery options	
Runtime 1st battery up to 12 h Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Please refer to the Eco Declaration Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight (lbs) from 2.2 kg Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature Operating relative humidity 20 - 80 % Compliance Germany Germany CS (Full HD Display only) Europe CE (B		
Battery charging time ~150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental 374 x 250 x 24.2 - 31.4 mm Meight from 2.2 kg Weight (lbs) from 4.9 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity Operating relative humidity GS (Full HD Display only) Europe CE (B		
Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Dimensions / Weight / Environmental Please refer to the Eco Declaration Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg Weight (Ibs) from 4.9 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance CE (B		
Refer to www.bapco.com for additional details. The BAPCo* Mobile/Mark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental Its 250 x 24.2 - 31.4 mm Its 72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg Weight from 2.2 kg Weight (Ibs) from 4.9 lbs Weight notes Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance Germany GS (Full HD Display only) Europe CE CB CB	, , , ,	
Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg 14.72 x 9.84 x 0.95 - 1.23 inch Weight (lbs) from 4.9 lbs Weight notes Uncl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) 0perating relative humidity 20 - 80 % Compliance GS (Full HD Display only) Europe Europe CE CB	Battery notes	Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity
Dimensions / Weight / Environmental Dimensions (W x D x H) 374 x 250 x 24.2 - 31.4 mm 14.72 x 9.84 x 0.95 - 1.23 inch Weight from 2.2 kg Weight (Ibs) from 4.9 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance GS (Full HD Display only) Europe CE (B CE	Noise emission	
Dimensions (W x D x H) $374 x 250 x 24.2 - 31.4 \text{ mm}$ 14.72 x 9.84 x 0.95 - 1.23 inchWeightfrom 2.2 kgWeight (lbs)from 4.9 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %Compliance GermanyGS (Full HD Display only)EuropeCE CB	Noise emission	Please refer to the Eco Declaration Please refer to the Eco Declaration
Dimensions (W x D x H) $374 x 250 x 24.2 - 31.4 \text{ mm}$ 14.72 x 9.84 x 0.95 - 1.23 inchWeightfrom 2.2 kgWeight (lbs)from 4.9 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %Compliance GermanyGS (Full HD Display only)EuropeCE CB	Dimensions / Weight / Environmental	
14.72 x 9.84 x 0.95 - 1.23 inchWeightfrom 2.2 kgWeight (lbs)from 4.9 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %ComplianceGS (Full HD Display only)EuropeCE CB		374 x 250 x 24.2 - 31.4 mm
Weightfrom 2.2 kgWeight (lbs)from 4.9 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %ComplianceGS (Full HD Display only)EuropeCE CB	· ·	14.72 x 9.84 x 0.95 - 1.23 inch
Weight (lbs)from 4.9 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %ComplianceGermanyGS (Full HD Display only)EuropeCE CB	Weight	from 2.2 kg
Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 % Compliance GS (Full HD Display only) Europe CE CB		
Operating relative humidity 20 - 80 % Compliance Germany GS (Full HD Display only) Europe CE CB		Incl. weight saver. Weight may vary depending on actual configuration.
Compliance Germany GS (Full HD Display only) Europe CE CB	Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Germany GS (Full HD Display only) Europe CE CB	Operating relative humidity	20 - 80 %
Germany GS (Full HD Display only) Europe CE CB		
Europe CE CB	· · · ·	GS (Full HD Display only)
CB	· · · · ·	
USA/Canada FCC (depending on configuration)	· 	СВ
	USA/Canada	FCC (depending on configuration)

Compliance		
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) ENERGY STAR® 6.1 EPEAT® Gold (dedicated regions) Microsoft Operating Systems (HCT / HCL entry / WHQ	L)
China	CCC (depending on configuration)	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional Software		
Additional software (preinstalled)	Adobe® Reader® (pdf reader) Win7 or Win 8.1 only McAfee Internet Security and Antivirus Software (60 Fujitsu LIFEBOOK Application Panel Fujitsu Display Manager Power Saving Utility Fujitsu Plugfree Network (network management util EasyGuide online user documentation Microsoft Office (buy license to activate the pre-insta Win10 and Win 8.1: Microsoft Push Button Recovery Win7: Fujitsu Recovery (hard disk based recovery)	ity) alled Microsoft Office)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows® LTE / UMTS Connection Manager (if configured with 4 DVD playback software CyberLink YouCam (webcam software)	4G/LTE or 3G/UMTS)
Manageability		
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intel® vPro™ technology WoL (Wake on LAN) Intel® SBA Manageability Solution (see details: http:// www.intel.com/go/sba) iAMT 11.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management	
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management	
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model) BootP (made4you)	
Manageability link	http://www.fujitsu.com/fts/manageability	
Security		
Physical Security	Kensington Lock support	Kensington Lock support
System and BIOS Security	Absolute Persistence® technology capable BIOS Optional: Trusted platform module (TPM 1.2 or 2.0) EraseDisk (optional)	Absolute Persistence [®] technology capable BIOS Optional: Trusted platform module (TPM 1.2 or 2.0) EraseDisk (optional)

User Security		
,	Access protection via internal SmartCard reader (optional) Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution) SystemLock 3 SmartCard Security (optional): BIOS based pre-boot/ two-factor authentication for high level of access protection	Access protection via internal SmartCard reader (optional Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution) SystemLock 3 SmartCard Security (optional): BIOS based pre-boot/ two-factor authentication for high level of access protection

Warranty	
Warranty period	1 year (for countries in EMEIA)
Warranty type	Collect & Return Service / Bring-in Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfe	ect extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://ts.fujitsu.com/Supportservice

Recommended Accessories

Port Replicator for LIFEBOOK U745, T7, E5, E7 Series and CELSIUS H730, H760	Flexibility, expandability, desktop replacement, investment protection - to Order Code: name just a few benefits of Fujitsu's docking options. S26391-F1337-L109
Sneaker Sleeve 15.6	The Sneaker Sleeve 15.6 protects notebooks with up to 15.6-inch screens. Order Code: The front half of the bag has dedicated compartments for your notebook, power cord, office supplies and personal items. The back half of the bag has an expanding, divided compartment for your files.
Prestige Case 15	The Prestige Case 15 protects notebooks with up to 15.6-inch screens. The Order Code: front half of the bag has compartments for your notebook, power cord and office supplies. Through the nylon pockets you can see your modular bay accessories. The back half of the bag has a divided file compartment.
Second Hard Disk Drive or SSD Carrier for Modular Bay	Modern business generates more and more data everyday so you may find yourself needing some extra storage space for critical data. Extend your storage with this 2nd HDD or SSD option by simply sliding this carrier into the modular bay slot on your Fujitsu LIFEBOOK. Choose the storage capacity to suit your needs and order separately from the list of options.
Wireless Notebook Mouse WI610	The Wireless Notebook Mouse WI610 uses the latest wireless 2.4 GHz technology, and an ultra-high resolution switchable sensor to give you the precision and reliability you need (1000/1500/2000 dpi). Sporting a stylish silver-black finish, the WI610 wireless mouse is well suited to all environments.

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code: S26391-F7128-L600

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Notebook LIFEBOOK E556, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Notebook LIFEBOOK E556, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2017-04-01 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH