

Heavy-Duty PDU Power Cord, C13 to C14 - 15A, 250V, 14 AWG, 3 ft. (0.91 m), Green

MODEL NUMBER: P005-003-AGN











Computer power extension cord connects devices with C13/C14 power connectors or extends your existing power connection by 3 ft.

Features

C14-to-C13 Power Cable for Network Devices That Require a Heavy-Gauge ConnectionThis IEC-320-C14 to IEC-320-C13 cable features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This C14 male to C13 female cord can be used to connect a computer, server, monitor or drive to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The three-foot length helps reduce cable clutter and minimize the risk of tripping.

Color-Coded to Avoid Misidentification That Can Cause Costly DowntimeThis computer power extension cord features a green SJT jacket and fully molded green ends. The color-coding allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Recommended for powering computers, servers and other network devices
- 3-ft. (0.91 m) length allows flexibility in placing devices, while avoiding cable clutter
- PDU-style cord replaces or upgrades standard power cord provided by manufacturer
- Color-coded green for fast, easy identification in a crowded rack or workstation
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, servers and monitors to a PDU up to 3 ft. away in your data center
- Extend an existing power connection up to 3 ft. to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P005-003-AGN Heavy-Duty C13 to C14 PDU-Style Power Extension Cable, 3 ft., Green

Specifications

| OVERVIEW | | |
|-----------------------------|---|--|
| UPC Code | 037332198983 | |
| Device Compatibility | Computer; Monitor/HDTV; Printer; Server; Router; Network Switch; UPS; PDU | |
| Country/Region | Global | |
| INPUT | | |
| Maximum Input Amps | 15 | |
| Voltage Compatibility (VAC) | 100-250 | |
| PHYSICAL | | |



| Plug Color | Green | |
|---|-------------------------------------|--|
| Cable Jacket Color | Green | |
| Cable Jacket Material | PVC | |
| Cable Jacket Rating | FT2 | |
| Power Cord Jacket Type | SJT | |
| Cable Outer Diameter (OD) | 9.2mm | |
| Number of Conductors | 3 | |
| Wire Gauge (AWG) | 14 | |
| Wire Gauge (AWG) Wire Gauge (OD - mm²) | | |
| | 2.08 | |
| Cable Length (ft.) | 3 | |
| Cable Length (m) | 0.91 | |
| Cable Length (cm) | 91.44 | |
| Shipping Dimensions (hwd / in.) | 9.90 x 7.00 x 0.50 | |
| Shipping Dimensions (hwd / cm) | 25.15 x 17.78 x 1.27 | |
| Shipping Weight (lbs.) | 0.44 | |
| Shipping Weight (kg) | 0.20 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Storage Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Operating Humidity Range | 20% to 80% RH | |
| Storage Humidity Range | 20% to 80% RH | |
| CONNECTIONS | | |
| Side A - Connector 1 | IEC-320-C14 | |
| Side B - Connector 1 | IEC-320-C13 | |
| FEATURES & SPECIFICATIONS | | |
| Antibacterial | No | |
| Angled Plug | No | |
| High Voltage | Yes | |
| Locking Plug | No | |
| Coiled Power Cord | No | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | CSA (Canada); cUL Listed; UL Listed | |
| Product Compliance | RoHS; REACH | |
| | | |



| /ARRANTY & SUPPORT | |
|-------------------------------------|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.