

ThinkServer RS160 Platform Specifications

Product Specifications Reference (PSREF)

Components	Specification	Components	Specification
Dimensions	1U rack. Height: 43.2 mm (1.7 in), width: 438.5 mm (17.26 in), depth: 393.7 mm (15.5 in)	Power supply	One fixed 300 watts power supply, Non-hot swap. 80 PLUS Gold qualified
Weight	Minimum configuration: 6.2 kg (13.67 lb), maximum: 7.6 kg (16.76 lb)	Graphics	Onboard Aspeed AST2400
Processor	Up to one Intel Xeon E3-1200 v5, Core i3, Pentium, or Celeron family processor.	Front ports	Two USB 2.0
	Xeon E3-1280 v5 4C/3.7GHz/8MB/80W/DDR4-2133	Rear ports	One VGA, four USB 3.0, one RJ-45 (dedicated mgmt), two ethernet, one serial (9-pin)
	Xeon E3-1270 v5 4C/3.6GHz/8MB/80W/DDR4-2133	Cooling	3 fans for processor, PCIe slot, and disk drives
	Xeon E3-1240 v5 4C/3.5GHz/8MB/80W/DDR4-2133	Noise emissions	Operating: < 5.9 Bels. Idle: < 5.2 Bels (Maximum configuration)
	Xeon E3-1230 v5 4C/3.4GHz/8MB/80W/DDR4-2133	Environmental specification	Temperature - operating 50 °F to 95 °F (10 °C to 35 °C)
	Xeon E3-1220 v5 4C/3GHz/8MB/80W/DDR4-2133		Temperature - non operating (with package) -40 °C to 60 °C
	Xeon E3-1260L v5 4C/2.9GHz/8MB/45W/DDR4-2133		Altitude - operating (Unpressurized): 0-10000ft (0-3048m)
	Xeon E3-1240L v5 4C/2.1GHz/8MB/25W/DDR4-2133		Humidity - operating 8%~80%, non-condensing
	Xeon E3-1225 v5 4C/3.3GHz/8MB/80W/DDR4-2133		Humidity - storage (with package) 10%~90%, non-condensing
	Core i3-6320 2C/3.9GHz/4MB/51W/DDR4-2133	Expansion slots and disk bays	
	Core i3-6300 2C/3.8GHz/4MB/51W/DDR4-2133	Supports one PCIe slot via optional riser card, PCIe 3.0 x16, half length, half height	
	Core i3-6100 2C/3.7GHz/3MB/51W/DDR4-2133	Core options for ThinkServer RS160 (partial)	
	Pentium G4520 2C/3.6GHz/3MB/51W/DDR4-2133	ThinkServer 8GB 2RX8 PC4-2133-E CL15 DDR4-2133 ECC-UDIMM	4X70G88316
	Pentium G4500 2C/3.5GHz/3MB/51W/DDR4-2133	ThinkServer 16GB 2RX8 PC4-2133-E CL15 DDR4-2133 ECC-UDIMM	4X70G88317
	Pentium G4400 2C/3.3GHz/3MB/54W/DDR4-2133	ThinkServer 3.5" 8TB 7.2K Enterprise SATA 6Gbps 512e Hard Drive for RS-Series	4XB0K12297
	Celeron G3920 2C/2.9GHz/2MB/51W/DDR4-2133	ThinkServer 2.5" 1.2TB 10K Enterprise SAS 12Gbps Hard Drive for RS-Series	4XB0K12306
	Celeron G3900 2C/2.8GHz/2MB/51W/DDR4-2133	ThinkServer 2.5" 2TB 7.2K Enterprise SATA 6Gbps Hard Drive for RS-Series	4XB0K12302
	Celeron G3900T 2C/2.6GHz/2MB/35W/DDR4-2133	ThinkServer 2.5" 480GB S3510 Enterprise Entry SATA 6Gbps SSD for RS-Series	4XB0K12321
Chipset	Intel C232 Platform Controller Hub (PCH)	ThinkServer M.2 32GB Value Read-Optimized SATA 6Gbps Solid State Drive	4XB0K12310
Memory DIMMs	4 DIMM sockets with 2 channels, 2 DIMMs per channel. UDIMM . DDR4-2133	ThinkServer RAID 520i RAID 5 Upgrade	4XC0G88841
Memory capacity	64GB (16GB x 4)	ThinkServer RS160 Slim SATA DVD-RW Optical Disk Drive	4XA0G88613
Memory protection	ECC	Lenovo ThinkServer Gen 5 Trusted Platform Module v1.2 (Worldwide except China)	4XF0G45868
RAID controller	RAID controller	Drive type	RAID support
	Onboard RAID12i	6Gbs SATA	0/1/5/10
	RAID520i PCIe	12Gbs SAS/SATA	0/1/10, 5 with optional key
	RAID720i PCIe	12Gbs SAS/SATA	0/1/10/5, 6 with optional cache
Optional cache for RAID720i: 1GB memory. 1GB, 2GB, or 4GB flash with super capacitor.			
Disk drive bays	Supports two 3.5" or four 2.5" disk drive bays. Non-hot swap. Cables are connected to onboard SATA connectors or PCIe RAID controller. Also supports one M.2 SATA SSD		
Supporting storage	3.5" HDD, 7.2K SATA6Gbs	1TB/2TB/4TB/6TB/8TB	
	3.5" HDD, 7.2K SAS12Gbs	1TB/2TB/4TB/6TB/8TB	
	2.5" HDD, 7.2K SATA6Gbs	1TB/2TB	
	2.5" HDD, 10K SAS12Gbs	300GB/600GB/900GB/1.2TB	
	2.5" SSD, SATA6Gbs	120GB/240GB/480GB/960GB	
	M.2 SATA SSD	32GB/128GB	
Optical drive	Optional one 9.5mm optical. DVD-ROM or DVD±RW		
Network interfaces	One dedicated management port, two Gigabit Ethernet ports. Supports optional discrete network adapters via riser card		
Security features	Power-on and administrator password. Optional TPM, TCG 1.2 or 2.0 compliant. UEFI. Onboard Aspeed AST2400 graphics/management processor, IPMI 2.0-compliant baseboard management controller (BMC).		
Systems management	Control Panel LEDs shows the status of power, ID, disk drives, network, system. Supports the following management software: EasyStartup, Power Planner. On November 2016, EasyUpdate, Lenovo ThinkServer Diagnostics Standalone, ToolsCenter Suite CLI inventory module on ThinkServer, and Lenovo xClarity Administrator will be available		
Operating systems	Microsoft Windows Server 2016 (Standard and Essentials)/2012 R2/2012. Windows 10 Pro. Red Hat Enterprise Linux 6.7/6.8/7.2. SUSE Linux Enterprise Server 11/12. VMware vSphere (ESXi) 6.0Ub/U2		
Base warranty	1 or 3-year limited onsite service with 9x5/NBD		

Model	70TE000CEA
Product	ThinkServer RS160
Region	EMEA
Machine Type	70TE
TopSeller	TopSeller
Processor	Xeon E3-1240 v5 4C/3.5GHz/8MB/80W/DDR4-2133
Memory	1x16GB UDIMM DDR4-2133 ECC
RAID Controller	RAID 121i
Disk Bays	4x2.5" NHS
Storage	2x2TB HDD 7.2K 2.5" SATA6Gbs
Optical	None
Add-on NIC	None
Slots	1xHHHL
TPM	None
Operating System	None
Warranty	3-year
Power Supply	300W 85% Fixed
Ann Date (mm/yy)	09/16

