

300Mbps

Wireless N ADSL2+ Modem Router
TD-W8960N

Highlights


- **All-in-One** – ADSL modem, NAT router, 4-port switch and wireless access point in one device provides one-stop networking solution
- **300Mbps Wi-Fi** – Great for faster downloads and Internet gaming, or even streaming HD video
- **Easy to Use** – Easy Setup Assistant provides quick & hassle free installation
- **Great Coverage** – 2 * 5dBi external antennas provide great omni-directional wireless coverage and reliability
- **ADSL/EWAN** – ADSL port supports ADSL connections via phone cable and the LAN/WAN port supports cable/fiber modem connections via Ethernet cable
- **Parental Control** – Allows parents or administrators to establish restricted access policies for children or staff



300Mbps
2.4GHz



EWAN
Connection



Parental
Control



Guest
Network



6000V Lightning
Protection

Features

Speed

- 300Mbps Wireless Speed – Great for faster downloads and Internet gaming, or even streaming HD video

Wi-Fi Range

- Great Coverage – 2 * 5dBi external antennas provide great omni-directional wireless coverage and reliability

Reliability

- QoS – Advanced QoS automatically recognizes & prioritizes streaming & gaming applications

Ease of Use

- Wireless Schedule – Wireless Schedule lets you turn the Wi-Fi radio on or off based on a preset timetable
- Fast Encryption – WPS button provides easy, one-touch wireless encryption
- Wi-Fi On/Off Button – Easily turn off your Wi-Fi radio by a push of the Wi-Fi On/Off button


Security

- Guest Network Access – Guest Network Access provides secure Wi-Fi access for guests
- Parental Control – Establish restricted access policies for all connected devices
- SPI and NAT Firewall – Protects end-user devices from potential attacks from the Internet
- 6000V Lightning Protection – Helps your device to avoid the damage of tough thunderstorm

Specifications

Hardware

- **Ethernet Ports:** 1 RJ11 Port, 3 10/100Mbps RJ45 LAN Ports, 1 10/100Mbps RJ45 WAN/LAN Port
- **Button:** WPS/Reset Butt on, Wi-Fi On/Off Button, Power On/Off Button
- **External Power Supply:** 9VDC/0.85A
- **Dimensions (W x D x H):** 7.1 x 4.9 x 1.4 in. (181.6 x 125.7 x 36.2 mm)
- **IEEE Standards:** IEEE 802.3, 802.3u
- **ADSL Standards:** Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1
- **ADSL2 Standards:** ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis)
- **ADSL2+ Standards:** ITU-T G.992.5
- **Antenna Type:** 2 external antennas
- **Antenna Gain:** 2 x 5dBi



Wireless

- **Wireless Standards:** IEEE 802.11b, 802.11g, 802.11n
- **Frequency:** 2.400-2.4835GHz
- **Signal Rate:** 300Mbps at 2.4GHz
- **Transmit Power:** <20dBm(EIRP)
- **Wireless Function:** Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
- **Wireless Security:** 64/128-bit WEP,WPA / WPA2,WPA-PSK/ WPA2-PSK encryption, Wireless MAC Filtering

Specifications

Software

- **Operation Modes:** ADSL Modem Router, Wireless Router
- **DHCP:** Server, Client, DHCP Client List, Address Reservation
- **Quality of Service:** QoS Remarking based on IPP/ToS, DSCP, 802.1p
ATM QoS, Traffic Control(IP QoS)
- **Port Forwarding:** Virtual Server, Port Triggering, DMZ, ALG
- **Dynamic DNS:** DynDns, NO-IP
- **ATM/PPP Protocols:** ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364),
PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER\IPoE (RFC 1483
Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
- **Security:** NAT Firewall, Access Control, MAC / URL Filtering, IP and MAC
Address Binding
- **Advanced Functions:** Parental Control, Network Address Translation(NAT),
Port Mapping(Grouping), Static Routing, DNS Relay, DDNS, IGMP
V1/V2/V3
- **Management:** Web Based Configuration(HTTP), Remote management,
Command Line Interface, SSL for TR-069, SNMP v1/2c, Web Based
Firmware Upgrade, Diagnostic Tools
- **Guest Network:** 2.4GHz guest network
- **Protocols:** Supports IPv4 and IPv6

Others

Package Contents

- 300 Wireless N ADSL2+ Modem Router TD-W8960N
- External Splitter
- RJ-11 Telephone Cable
- RJ-45 Ethernet Cable
- Quick Installation Guide
- Resource CD
- Power Adapter

Certification

- CE, FCC, RoHS

System Requirements

- Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC
OS, NetWare, UNIX or Linux
- Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other
Java-enabled browser
- Cable or DSL Modem
- Subscription with an Internet Service Provider (for Internet access)

Environment

- Operating Temperature: 0°C ~40°C (32°F ~104°F)
- Storage Temperature: -40°C ~70°C (-40°F ~158°F)
- Operating Humidity: 10%~90% non-condensing
- Storage Humidity: 5%~90% non-condensing

Others

Ideal to use with



- 300Mbps High Gain Wireless USB Adapter TL-WN822N



- 300Mbps Wireless N USB Adapter TL-WN821N

Similar Products



- 300Mbps Wireless N Gigabit ADSL2+ Modem Router TD-W8970



- 300Mbps Wireless N USB ADSL2+ Modem Router TD-W8968



For more information, please visit

http://www.tp-link.com/en/products/details/cat-15_TD-W8960N.html

or scan the QR code left

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies CO., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.

www.tp-link.com