Alienware Area-51



Views

Specifications

NOTE: The images in this document may differ from your computer depending on the configuration you ordered.

Copyright © 2016 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2016 - 12 Rev. A02

Regulatory model: D03X | Type: D03X001 Computer model: Alienware Area-51 R2







Front



Back



Back panel

Front

1 Power button (Alien head button)

Press to turn on the computer if it is turned off or in sleep state.

Press to shut down the computer if it is turned on.

Press and hold for 4 seconds to force shut-down the computer.

2 Optical-drive eject button

Press to eject the media from the optical drive.



3 Optical drive

Reads from and writes to CDs, DVDs, and Blu-ray discs.

4 Headphone port

Connect a headphone or speakers.

5 Microphone port

Connect an external microphone to provide sound input.

6 USB 3.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.

7 Media-card reader

Reads from and writes to media cards.





Front




Back



Back panel

Back



1 Rear I/O accessibility lighting button

Press to illuminate the back panel ports.

2 Back panel

Connect USB, audio, video, and other devices.

3 Expansion bays

Connect external displays or projectors via graphics cards or other peripherals via their respective PCI-Express cards.

TE: If you have two graphics cards, the top graphics slot will be the primary graphics card. If you have three graphics cards, the bottom graphics slot will be the primary graphics card.

4 Power cable port

Connect a power cable to provide power to your computer.

5 Power-supply diagnostics button

Press to check the power-supply state.

6 Power-supply diagnostics light

Indicates the power-supply state.

7 Security-cable slot

Connect a security cable to prevent unauthorized movement of your computer. This prevents the latch from opening.

8 Security-cable slot latch

Release to allow opening the side panel.





Front




Back



Back panel

Back panel



1 Hard-drive activity light

Turns on when the computer reads from or writes to the hard drive.

2 USB 2.0 ports (4)

Connect peripherals, such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

3 USB 3.0 port (4)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.

4 Optical S/P DIF port

Connect an amplifier, speakers, or a TV for digital audio output through optical cables.

5 Audio ports

Connect speakers.

6 Coaxial S/P DIF port

Connect an amplifier, speakers, or a TV for digital audio output through coaxial cables.

7 Network port

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

The two lights next to the connector indicate the connectivity status and network activity.



Dimensions and Weight

Height	569.98 mm (22.44 in)
Width	638.98 mm (25.15 in)
Depth	272.71 mm (10.73 in)
Weight (maximum)	28 kg (61.73 lbs)
	NOTE : The weight of your desktop varies depending on the configuration ordered and the manufacturing variability.









Connectors











Audio









System Information

Computer model Alienware Area-51 R2

Intel Core i7 Processor

Chipset Intel X99 Express







Information



Memory



Ports and Connectors







Video



Audio



Storage









Memory

Connector	Four internally-accessible DDR4 DIMM socket
COMMOCION	Tour internally accessible DDIT I DITTING SOCKET

DDR4 Type

Speed 2133 MHz and 2400 MHz

Configurations supported:

4 GB (2133 MHz only), 8 GB, and 16 GB Per memory module slot

Total memory 8 GB, 16 GB, 32 GB, and 64 GB







Memory











Reader







Ports and Connectors


External:	
Network	One RJ45 port
USB	Four USB 2.0 portsSix USB 3.0 port
Audio	 Four audio output/headphone ports One audio input/microphone port One optical S/P DIF port One coaxial S/P DIF port
Media-card reader	One 9-in-1 card slot
Internal:	
M.2	 One M.2 card slot for WLAN and Bluetooth
Storage	Six SATA ports



















Audio









Communications

Ethernet

10/100/1000 Mbps Ethernet controller integrated on system board

Wireless

• Wi-Fi 802.11 ac

Bluetooth 4.0









Connectors









Storage

Video









Video

Туре	 Up to three PCI-Express x16, single-/double-width, full length graphics card
Controller (Discrete)	 Single AMD and NVDIA Also supports Dual/Triple AMD and NVIDIA (SLI)
	NOTE : The graphics configuration of your desktop varies depending on the power supply and graphics card configuration ordered.



















Audio









Audio

Controller

Creative Sound Core 3D

Туре

- Integrated 5.1 channel
- Intel High Definition Audio with S/PDIF support

















Connectors Communications









Externally accessible	One 5.25-inch drive bay for DVD+/-RW, Blu-ray Disc combo (optional), or Blu-ray Disc writer (optional)
Internally accessible	 Three 3.5-inch drive bay for SATA hard drives

- Three 3.5-inch drive bay for SAIA hard drives
- Two 2.5-inch drive bay for SATA solid-state drives



















Storage









Media-Card Reader

Туре

Cards supported

One 9-in-1 slot

- Secure Digital (SD)
- Secure Digital Input Output (SDIO)
- Secure Digital High Capacity (SDHC)
- SD Extended Capacity (SDXC 3.0)
- MultiMedia Card (MMC)/MultiMedia Card (MMC) Plus
- Memory Stick (MS)
- Memory Stick PRO (MS PRO)
- Memory Stick PRO Duo (with adapter)
- Memory XC Duo (with adapter)









Ports and Connectors











Storage

Audio









Power Ratings

Туре	850 W	1500 W	1500 W
Input voltage	100 VAC-240 VAC	100 VAC-240 VAC	200 VAC-240 VAC
Input frequency	50 Hz-60 Hz	50 Hz-60 Hz	50 Hz-60 Hz
Input current (maximum)	10 A	15 A	10 A
Output current	+3.3 V/20 A, +5 V/20 A, +12 VA/32 A, +12 VB/48 A, +12 VD/16 A, -12 V/0.5 A, +5 Vaux/4 A	+3.3 V/20 A, +5 V/25 A, +12 VA/32 A, +12 VB/48 A, +12 VC/48 A, +12 VD/16 A, -12 V/0.5 A, +5 Vaux/4 A	+3.3 V/20 A, +5 V/25 A, +12 VA/32 A, +12 VB/48 A, +12 VC/48 A, +12 VD/16 A, -12 V/0.5 A, +5 Vaux/4 A
Rated output voltage	+3.3 V, +5 V, +12 VA, +12 VB, +12 VD, -12 V, +5 Vaux	+3.3 V, +5 V, +12 VA, +12 VB, +12 VC, +12 VD, -12 V, +5 Vaux	+3.3 V, +5 V, +12 VA, +12 VB, +12 VC, +12 VD, -12 V, +5 Vaux

Temperature range:

Operating 5°C to 50°C (41°F to 122°F)

Storage $-40^{\circ}\text{C to }70^{\circ}\text{C }(-40^{\circ}\text{F to }158^{\circ}\text{F})$



Dimensions and Weight



System Information



Memory



Ports and Connectors



Communications



Video



Audio











Computer Environment

Airborne contaminant level	G2 or lower as defined by ISA-S71.04-1985	
	Operating	Storage
Temperature range	5°C to 35°C (41°F to 95°F)	-40°C to 65°C (-40°F to 149°F)
Relative humidity (maximum)	10% to 90% (non-condensing)	0% to 95% (non-condensing)
Vibration (maximum)	0.26 grms	1.37 grms
Shock (maximum)	40 G for 2 ms with a change in velocity of 20 in/s (51 cm/s) [†]	105 G for 2 ms with a change in velocity of 52.5 in/s (133 cm/s)
Altitude (maximum)	-15.24 m to 3048 m (-50 ft to 10,000 ft)	-15.24 m to 10,668 m (-50 ft to 35,000 ft)

^{*} Measured using a random vibration spectrum that simulates user environment.







Information



Memory



Ports and Connectors







Video



Audio



Storage







[†] Measured using a 2 ms half-sine pulse when the hard drive is in use.