


ThinkServer TD350 Platform Specifications

Product Specifications Reference (PSREF)

Components	Specification	Components	Specification																																									
Dimensions	Tower or 4U rack. Tower: Height: 459 mm (18.1 in), width: 251 mm (9.9 in), depth: 686 mm (27 in) Rack: height: 173 mm (6.8 in), width: 482 mm (19 in), depth: 686 mm (27 in)	Maximum internal storage	3.5" model: up to 120TB with 7.2K SATA or SAS HDD, up to 27TB with 10K SAS HDD, up to 9TB with 15K SAS HDD, or up to 24TB with SATA or SAS SSD. 2.5" model: up to 64TB with 7.2K SATA HDD, up to 57.6TB with 10K SAS HDD, up to 19.2TB with 15K SAS HDD, or up to 51.2TB with SATA or SAS SSD																																									
Weight	Minimum configuration: 22 kg (48.5 lb), maximum: 41.4 kg (91.27 lb)	SD module	Up to 2 SDHC flash cards via optional SD module, 8GB or 32GB each																																									
Processor	Up to two 135W Intel Xeon E5-2600 v4 or E5-2600 v3 family processors.	Optical drive	Two 5.25" bays for optical drive. DVD-ROM or DVD±RW. Half-height or 9.5mm																																									
	E5-2698 v4	20C/2.2GHz/50MB/135W/DDR4-2400	Network interfaces	One dedicate management port, two gigabit ethernet ports. Supports optional discrete network adapters via PCIe slots																																								
	E5-2695 v4	18C/2.1GHz/45MB/120W/DDR4-2400	Security features	Power-on and administrator password. Optional TPM (TCG 1.2 or 2.0-compliant)																																								
	E5-2690 v4	14C/2.6GHz/35MB/135W/DDR4-2400	Systems management	Supports ThinkServer System Manager (TSM), optional TSM Premium for remote presence. UEFI. Onboard Aspeed AST2400 graphics/management processor, IPMI 2.0-compliant baseboard management controller (BMC). Control Panel LEDs shows the status of power, ID, network, system. Supports ThinkServer Diagnostics, ThinkServer Deployment Manager, ThinkServer Energy Manager, ThinkServer System Manager CLI, Lenovo ThinkServer Partner Pack for VMware vCenter and Microsoft System Center Operations Manager, ThinkServer Power Planner.																																								
	E5-2683 v4	16C/2.1GHz/40MB/120W/DDR4-2400		Operating systems supported	Microsoft Windows Server 2016/2012 R2/2012/2008 R2. Windows Small Business Server 2011. Red Hat Enterprise Linux 6.5/6.6/7. SUSE Linux Enterprise Server 11. VMware vSphere (ESXi) 5.1 P5/5.5 U2/6.0																																							
	E5-2680 v4	14C/2.4GHz/35MB/120W/DDR4-2400		Base warranty	1 or 3-year limited onsite service with 9x5/NBD.																																							
	E5-2667 v4	8C/3.2GHz/25MB/135W/DDR4-2400		Power supply	Up to two redundant hot-swap 450W/550W/750W/1100W power supplies. 450 W is 80 PLUS Gold qualified. 550W and 1100W are 80 PLUS Platinum qualified. 750W is 80 PLUS Platinum or Titanium qualified. 750W Titanium is 200V - 240V, others are 110V - 240V.																																							
	E5-2660 v4	14C/2GHz/35MB/105W/DDR4-2400	<table><tr><td>Disk bay configuration</td><td colspan="4">PSU requirements</td></tr><tr><td></td><td>450W</td><td>550W</td><td>750W</td><td>1100W</td></tr><tr><td>5x3.5" ES</td><td>• (up to 1 CPU)</td><td>•</td><td>•</td><td>•</td></tr><tr><td>5x3.5" HS</td><td>• (up to 1 CPU)</td><td>•</td><td>•</td><td>•</td></tr><tr><td>15x3.5" HS</td><td></td><td></td><td>•</td><td>•</td></tr><tr><td>8x2.5" HS</td><td>• (up to 1 CPU)</td><td>•</td><td>•</td><td>•</td></tr><tr><td>16x2.5" HS</td><td>• (up to 1 CPU)</td><td>•</td><td>•</td><td>•</td></tr><tr><td>32x2.5" HS</td><td></td><td></td><td>•</td><td>•</td></tr></table>		Disk bay configuration	PSU requirements					450W	550W	750W	1100W	5x3.5" ES	• (up to 1 CPU)	•	•	•	5x3.5" HS	• (up to 1 CPU)	•	•	•	15x3.5" HS			•	•	8x2.5" HS	• (up to 1 CPU)	•	•	•	16x2.5" HS	• (up to 1 CPU)	•	•	•	32x2.5" HS			•	•
	Disk bay configuration	PSU requirements																																										
		450W	550W		750W	1100W																																						
	5x3.5" ES	• (up to 1 CPU)	•		•	•																																						
	5x3.5" HS	• (up to 1 CPU)	•		•	•																																						
	15x3.5" HS				•	•																																						
	8x2.5" HS	• (up to 1 CPU)	•		•	•																																						
	16x2.5" HS	• (up to 1 CPU)	•		•	•																																						
	32x2.5" HS				•	•																																						
	E5-2650L v4	14C/1.7GHz/35MB/65W/DDR4-2400	Graphics	Onboard Aspeed AST2400 with 16MB memory, one VGA on rear																																								
	E5-2650 v4	12C/2.2GHz/30MB/105W/DDR4-2400	Front ports	Two USB 2.0																																								
	E5-2643 v4	6C/3.4GHz/20MB/135W/DDR4-2400	Rear ports	One VGA, four USB 3.0, one RJ-45 (dedicate/share mgmt), two ethernet (RJ-45), one serial (9-pin)																																								
	E5-2640 v4	10C/2.4GHz/25MB/90W/DDR4-2133	Cooling	4 (3+1), hot-swap																																								
	E5-2637 v4	4C/3.5GHz/15MB/135W/DDR4-2400	Noise emissions	Operating: < 6.5 Bels. Idle: < 6 Bels (Maximum configuration)																																								
	E5-2630L v4	10C/1.8GHz/25MB/55W/DDR4-2133	Environmental specification	<table><tr><td>ASHRAE Class</td><td>A4</td><td>A3</td><td>A2</td></tr><tr><td>Temperature - operating</td><td>41 °F to 113 °F (5 °C to 45 °C)</td><td>41 °F to 104 °F (5 °C to 40 °C)</td><td>50 °F to 95 °F (10 °C to 35 °C)</td></tr><tr><td>Temperature - storage (with package)</td><td colspan="3">-40 °C to 60 °C</td></tr><tr><td>Altitude - operating</td><td colspan="3">(Unpressurized): 0-10000ft (0-3048m)</td></tr><tr><td>Humidity - operating (non-condensing)</td><td>8%~90%</td><td>8%~85%</td><td>20%~80%</td></tr><tr><td>Humidity - storage (with package)</td><td colspan="3">8%~90%, non-condensing</td></tr></table> <i>ASHRAE Class A4: ES or 8x2.5" HS bays/Lenovo-qualified CPU; maximum of 120W thermal design power; not low-power type (no L-suffix in the CPU name)/No internal tape/Two PSU installed for redundancy/ Lenovo-qualified PCIe card; power consumption of each PCIe card does not exceed 15W. 32 x 2.5" models support ASHRAE Class A2, the other models support ASHRAE Class A3.</i>	ASHRAE Class	A4	A3	A2	Temperature - operating	41 °F to 113 °F (5 °C to 45 °C)	41 °F to 104 °F (5 °C to 40 °C)	50 °F to 95 °F (10 °C to 35 °C)	Temperature - storage (with package)	-40 °C to 60 °C			Altitude - operating	(Unpressurized): 0-10000ft (0-3048m)			Humidity - operating (non-condensing)	8%~90%	8%~85%	20%~80%	Humidity - storage (with package)	8%~90%, non-condensing																		
	ASHRAE Class	A4		A3	A2																																							
	Temperature - operating	41 °F to 113 °F (5 °C to 45 °C)		41 °F to 104 °F (5 °C to 40 °C)	50 °F to 95 °F (10 °C to 35 °C)																																							
	Temperature - storage (with package)	-40 °C to 60 °C																																										
	Altitude - operating	(Unpressurized): 0-10000ft (0-3048m)																																										
	Humidity - operating (non-condensing)	8%~90%		8%~85%	20%~80%																																							
	Humidity - storage (with package)	8%~90%, non-condensing																																										
	E5-2630 v4	10C/2.2GHz/20MB/85W/DDR4-2133		RAID controller	<table><tr><th>RAID controller</th><th>Drive type</th><th>RAID support</th><th>Compatible models</th></tr><tr><td>Onboard RAID110i</td><td>6Gbs SATA</td><td>0/1/10,5 with optional key</td><td>5x3.5" HS/ES, 8x2.5" HS</td></tr><tr><td>RAID520i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>RAID720i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 510i</td><td>6Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720i</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720ix</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50/6/60</td><td>15x3.5" HS, 16/32x2.5" HS</td></tr></table> Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, Cache-Cade Pro, and FastPath. 720ix must have cache.	RAID controller	Drive type	RAID support	Compatible models	Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS											
	RAID controller	Drive type			RAID support	Compatible models																																						
	Onboard RAID110i	6Gbs SATA			0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS																																						
	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key		5x3.5" HS, 8x2.5" HS																																							
	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache		5x3.5" HS, 8x2.5" HS																																							
	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key		5x3.5" HS, 8x2.5" HS																																							
	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache		5x3.5" HS, 8x2.5" HS																																							
	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60		15x3.5" HS, 16/32x2.5" HS																																							
E5-2623 v4	4C/2.6GHz/10MB/85W/DDR4-2133	Disk drive bays	Up to 15 3.5" or 32 2.5" hot-swap bays, or up to 5 3.5" easy-swap bays, on front. Up to 2 M.2 SSD drives via optional M.2 module. Up to one internal LTO-6 SAS tape drive on 720ix model, or external RDX tape drive via USB.																																									
E5-2620 v4	8C/2.1GHz/20MB/85W/DDR4-2133		Expansion slots		<table><tr><td>Slot 1 (CPU1)</td><td>PCIe 3.0 x16, full height, full length, double-wide</td></tr><tr><td>Slot 2 (CPU1)</td><td>PCIe 3.0 x16 (x8 elec), full height, full length</td></tr><tr><td>Slot 3 (CPU1)</td><td>PCIe 3.0 x16 (x8 elec), full height, full length</td></tr><tr><td>Slot 4 (CPU2)</td><td>PCIe 3.0 x16 (x8 elec), full height, full length</td></tr><tr><td>Slot 5 (CPU2)</td><td>PCIe 3.0 x16, full height, full length</td></tr><tr><td>Slot 6 (CPU2)</td><td>PCIe 3.0 x16 (x8 elec), full height, full length</td></tr><tr><td>Slot 7 (CPU2)</td><td>PCIe 3.0 x16 (x8 elec), full height, full length</td></tr></table>	Slot 1 (CPU1)	PCIe 3.0 x16, full height, full length, double-wide	Slot 2 (CPU1)	PCIe 3.0 x16 (x8 elec), full height, full length	Slot 3 (CPU1)	PCIe 3.0 x16 (x8 elec), full height, full length	Slot 4 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length	Slot 5 (CPU2)	PCIe 3.0 x16, full height, full length	Slot 6 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length	Slot 7 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length																									
Slot 1 (CPU1)	PCIe 3.0 x16, full height, full length, double-wide																																											
Slot 2 (CPU1)	PCIe 3.0 x16 (x8 elec), full height, full length																																											
Slot 3 (CPU1)	PCIe 3.0 x16 (x8 elec), full height, full length																																											
Slot 4 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length																																											
Slot 5 (CPU2)	PCIe 3.0 x16, full height, full length																																											
Slot 6 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length																																											
Slot 7 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length																																											
E5-2609 v4	8C/1.7GHz/20MB/85W/DDR4-1866			Components	<table><tr><td>Slot 7</td><td></td></tr><tr><td>Slot 6</td><td></td></tr><tr><td>Slot 5</td><td></td></tr><tr><td>Slot 4</td><td></td></tr><tr><td>Slot 3</td><td></td></tr><tr><td>Slot 2</td><td></td></tr><tr><td>Slot 1</td><td></td></tr></table>	Slot 7		Slot 6		Slot 5		Slot 4		Slot 3		Slot 2		Slot 1																										
Slot 7																																												
Slot 6																																												
Slot 5																																												
Slot 4																																												
Slot 3																																												
Slot 2																																												
Slot 1																																												
E5-2603 v4	6C/1.7GHz/15MB/85W/DDR4-1866	Memory DIMMs	16 DIMM sockets (8 DIMMs per processor), 8-channel capable (4-channel per processor). RDIMM and LRDIMM (cannot be intermixed), DDR4, up to 2400MHz																																									
E5-2698 v3	16C/2.3GHz/40MB/135W/DDR4-2133		Memory capacity		512GB (RDIMM, 32GB x 16)/1024GB (LRDIMM, 64GB x 16), 2nd CPU is needed																																							
E5-2695 v3	14C/2.3GHz/35MB/120W/DDR4-2133			Memory protection	ECC, memory mirroring, lockstep, and memory sparing																																							
E5-2690 v3	12C/2.6GHz/30MB/135W/DDR4-2133				RAID controller	<table><tr><th>RAID controller</th><th>Drive type</th><th>RAID support</th><th>Compatible models</th></tr><tr><td>Onboard RAID110i</td><td>6Gbs SATA</td><td>0/1/10,5 with optional key</td><td>5x3.5" HS/ES, 8x2.5" HS</td></tr><tr><td>RAID520i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>RAID720i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 510i</td><td>6Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720i</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720ix</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50/6/60</td><td>15x3.5" HS, 16/32x2.5" HS</td></tr></table> Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, Cache-Cade Pro, and FastPath. 720ix must have cache.	RAID controller	Drive type	RAID support	Compatible models	Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS										
RAID controller	Drive type					RAID support	Compatible models																																					
Onboard RAID110i	6Gbs SATA					0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS																																					
RAID520i PCIe	12Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
RAID720i PCIe	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 510i	6Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720i	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60				15x3.5" HS, 16/32x2.5" HS																																						
E5-2685 v3	12C/2.6GHz/30MB/120W/DDR4-2133	Disk drive bays	Up to 15 3.5" or 32 2.5" hot-swap bays, or up to 5 3.5" easy-swap bays, on front. Up to 2 M.2 SSD drives via optional M.2 module. Up to one internal LTO-6 SAS tape drive on 720ix model, or external RDX tape drive via USB.																																									
E5-2683 v3	14C/2GHz/35MB/120W/DDR4-2133		Expansion slots	<table><tr><td>Slot 7</td><td></td></tr><tr><td>Slot 6</td><td></td></tr><tr><td>Slot 5</td><td></td></tr><tr><td>Slot 4</td><td></td></tr><tr><td>Slot 3</td><td></td></tr><tr><td>Slot 2</td><td></td></tr><tr><td>Slot 1</td><td></td></tr></table>		Slot 7		Slot 6		Slot 5		Slot 4		Slot 3		Slot 2		Slot 1																										
Slot 7																																												
Slot 6																																												
Slot 5																																												
Slot 4																																												
Slot 3																																												
Slot 2																																												
Slot 1																																												
E5-2680 v3	12C/2.5GHz/30MB/120W/DDR4-2133			Memory DIMMs	16 DIMM sockets (8 DIMMs per processor), 8-channel capable (4-channel per processor). RDIMM and LRDIMM (cannot be intermixed), DDR4, up to 2400MHz																																							
E5-2670 v3	12C/2.3GHz/30MB/120W/DDR4-2133	Memory capacity			512GB (RDIMM, 32GB x 16)/1024GB (LRDIMM, 64GB x 16), 2nd CPU is needed																																							
E5-2667 v3	8C/3.2GHz/20MB/135W/DDR4-2133		Memory protection		ECC, memory mirroring, lockstep, and memory sparing																																							
E5-2660 v3	10C/2.6GHz/25MB/105W/DDR4-2133				RAID controller	<table><tr><th>RAID controller</th><th>Drive type</th><th>RAID support</th><th>Compatible models</th></tr><tr><td>Onboard RAID110i</td><td>6Gbs SATA</td><td>0/1/10,5 with optional key</td><td>5x3.5" HS/ES, 8x2.5" HS</td></tr><tr><td>RAID520i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>RAID720i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 510i</td><td>6Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720i</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720ix</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50/6/60</td><td>15x3.5" HS, 16/32x2.5" HS</td></tr></table> Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, Cache-Cade Pro, and FastPath. 720ix must have cache.	RAID controller	Drive type	RAID support	Compatible models	Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS										
RAID controller	Drive type					RAID support	Compatible models																																					
Onboard RAID110i	6Gbs SATA					0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS																																					
RAID520i PCIe	12Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
RAID720i PCIe	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 510i	6Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720i	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720ix	12Gbs SAS/SATA			0/1/10,5/50/6/60		15x3.5" HS, 16/32x2.5" HS																																						
E5-2650L v3	12C/1.8GHz/30MB/65W/DDR4-2133	Disk drive bays		Up to 15 3.5" or 32 2.5" hot-swap bays, or up to 5 3.5" easy-swap bays, on front. Up to 2 M.2 SSD drives via optional M.2 module. Up to one internal LTO-6 SAS tape drive on 720ix model, or external RDX tape drive via USB.																																								
E5-2650 v3	10C/2.3GHz/25MB/105W/DDR4-2133		Expansion slots	<table><tr><td>Slot 7</td><td></td></tr><tr><td>Slot 6</td><td></td></tr><tr><td>Slot 5</td><td></td></tr><tr><td>Slot 4</td><td></td></tr><tr><td>Slot 3</td><td></td></tr><tr><td>Slot 2</td><td></td></tr><tr><td>Slot 1</td><td></td></tr></table>		Slot 7		Slot 6		Slot 5		Slot 4		Slot 3		Slot 2		Slot 1																										
Slot 7																																												
Slot 6																																												
Slot 5																																												
Slot 4																																												
Slot 3																																												
Slot 2																																												
Slot 1																																												
E5-2643 v3	6C/3.4GHz/20MB/135W/DDR4-2133			Memory DIMMs	16 DIMM sockets (8 DIMMs per processor), 8-channel capable (4-channel per processor). RDIMM and LRDIMM (cannot be intermixed), DDR4, up to 2400MHz																																							
E5-2640 v3	8C/2.6GHz/20MB/90W/DDR4-1866	Memory capacity			512GB (RDIMM, 32GB x 16)/1024GB (LRDIMM, 64GB x 16), 2nd CPU is needed																																							
E5-2637 v3	4C/3.5GHz/15MB/135W/DDR4-2133		Memory protection		ECC, memory mirroring, lockstep, and memory sparing																																							
E5-2630L v3	8C/1.8GHz/20MB/55W/DDR4-1866				RAID controller	<table><tr><th>RAID controller</th><th>Drive type</th><th>RAID support</th><th>Compatible models</th></tr><tr><td>Onboard RAID110i</td><td>6Gbs SATA</td><td>0/1/10,5 with optional key</td><td>5x3.5" HS/ES, 8x2.5" HS</td></tr><tr><td>RAID520i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>RAID720i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 510i</td><td>6Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720i</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720ix</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50/6/60</td><td>15x3.5" HS, 16/32x2.5" HS</td></tr></table> Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, Cache-Cade Pro, and FastPath. 720ix must have cache.	RAID controller	Drive type	RAID support	Compatible models	Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS										
RAID controller	Drive type					RAID support	Compatible models																																					
Onboard RAID110i	6Gbs SATA					0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS																																					
RAID520i PCIe	12Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
RAID720i PCIe	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 510i	6Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720i	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720ix	12Gbs SAS/SATA			0/1/10,5/50/6/60		15x3.5" HS, 16/32x2.5" HS																																						
E5-2630 v3	8C/2.4GHz/20MB/85W/DDR4-1866	Disk drive bays		Up to 15 3.5" or 32 2.5" hot-swap bays, or up to 5 3.5" easy-swap bays, on front. Up to 2 M.2 SSD drives via optional M.2 module. Up to one internal LTO-6 SAS tape drive on 720ix model, or external RDX tape drive via USB.																																								
E5-2623 v3	4C/3GHz/10MB/105W/DDR4-1866		Expansion slots	<table><tr><td>Slot 7</td><td></td></tr><tr><td>Slot 6</td><td></td></tr><tr><td>Slot 5</td><td></td></tr><tr><td>Slot 4</td><td></td></tr><tr><td>Slot 3</td><td></td></tr><tr><td>Slot 2</td><td></td></tr><tr><td>Slot 1</td><td></td></tr></table>		Slot 7		Slot 6		Slot 5		Slot 4		Slot 3		Slot 2		Slot 1																										
Slot 7																																												
Slot 6																																												
Slot 5																																												
Slot 4																																												
Slot 3																																												
Slot 2																																												
Slot 1																																												
E5-2620 v3	6C/2.4GHz/15MB/85W/DDR4-1866			Memory DIMMs	16 DIMM sockets (8 DIMMs per processor), 8-channel capable (4-channel per processor). RDIMM and LRDIMM (cannot be intermixed), DDR4, up to 2400MHz																																							
E5-2609 v3	6C/1.9GHz/15MB/85W/DDR4-1600	Memory capacity			512GB (RDIMM, 32GB x 16)/1024GB (LRDIMM, 64GB x 16), 2nd CPU is needed																																							
E5-2603 v3	6C/1.6GHz/15MB/85W/DDR4-1600		Memory protection		ECC, memory mirroring, lockstep, and memory sparing																																							
Chipset	Intel C610 Series Chipset				RAID controller	<table><tr><th>RAID controller</th><th>Drive type</th><th>RAID support</th><th>Compatible models</th></tr><tr><td>Onboard RAID110i</td><td>6Gbs SATA</td><td>0/1/10,5 with optional key</td><td>5x3.5" HS/ES, 8x2.5" HS</td></tr><tr><td>RAID520i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>RAID720i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 510i</td><td>6Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720i</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720ix</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50/6/60</td><td>15x3.5" HS, 16/32x2.5" HS</td></tr></table> Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, Cache-Cade Pro, and FastPath. 720ix must have cache.	RAID controller	Drive type	RAID support	Compatible models	Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS										
RAID controller	Drive type					RAID support	Compatible models																																					
Onboard RAID110i	6Gbs SATA					0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS																																					
RAID520i PCIe	12Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
RAID720i PCIe	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 510i	6Gbs SAS/SATA					0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720i	12Gbs SAS/SATA					0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																					
AnyRAID 720ix	12Gbs SAS/SATA			0/1/10,5/50/6/60		15x3.5" HS, 16/32x2.5" HS																																						
Memory DIMMs	16 DIMM sockets (8 DIMMs per processor), 8-channel capable (4-channel per processor). RDIMM and LRDIMM (cannot be intermixed), DDR4, up to 2400MHz	Disk drive bays		Up to 15 3.5" or 32 2.5" hot-swap bays, or up to 5 3.5" easy-swap bays, on front. Up to 2 M.2 SSD drives via optional M.2 module. Up to one internal LTO-6 SAS tape drive on 720ix model, or external RDX tape drive via USB.																																								
Memory capacity	512GB (RDIMM, 32GB x 16)/1024GB (LRDIMM, 64GB x 16), 2nd CPU is needed		Expansion slots	<table><tr><td>Slot 7</td><td></td></tr><tr><td>Slot 6</td><td></td></tr><tr><td>Slot 5</td><td></td></tr><tr><td>Slot 4</td><td></td></tr><tr><td>Slot 3</td><td></td></tr><tr><td>Slot 2</td><td></td></tr><tr><td>Slot 1</td><td></td></tr></table>		Slot 7		Slot 6		Slot 5		Slot 4		Slot 3		Slot 2		Slot 1																										
Slot 7																																												
Slot 6																																												
Slot 5																																												
Slot 4																																												
Slot 3																																												
Slot 2																																												
Slot 1																																												
Memory protection	ECC, memory mirroring, lockstep, and memory sparing			Memory DIMMs	16 DIMM sockets (8 DIMMs per processor), 8-channel capable (4-channel per processor). RDIMM and LRDIMM (cannot be intermixed), DDR4, up to 2400MHz																																							
RAID controller	<table><tr><th>RAID controller</th><th>Drive type</th><th>RAID support</th><th>Compatible models</th></tr><tr><td>Onboard RAID110i</td><td>6Gbs SATA</td><td>0/1/10,5 with optional key</td><td>5x3.5" HS/ES, 8x2.5" HS</td></tr><tr><td>RAID520i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>RAID720i PCIe</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 510i</td><td>6Gbs SAS/SATA</td><td>0/1/10,5/50 with optional key</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720i</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50,6/60 with optional cache</td><td>5x3.5" HS, 8x2.5" HS</td></tr><tr><td>AnyRAID 720ix</td><td>12Gbs SAS/SATA</td><td>0/1/10,5/50/6/60</td><td>15x3.5" HS, 16/32x2.5" HS</td></tr></table> Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, Cache-Cade Pro, and FastPath. 720ix must have cache.	RAID controller			Drive type	RAID support	Compatible models	Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS	RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS	AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS	AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS													
RAID controller	Drive type	RAID support	Compatible models																																									
Onboard RAID110i	6Gbs SATA	0/1/10,5 with optional key	5x3.5" HS/ES, 8x2.5" HS																																									
RAID520i PCIe	12Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																									
RAID720i PCIe	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																									
AnyRAID 510i	6Gbs SAS/SATA	0/1/10,5/50 with optional key	5x3.5" HS, 8x2.5" HS																																									
AnyRAID 720i	12Gbs SAS/SATA	0/1/10,5/50,6/60 with optional cache	5x3.5" HS, 8x2.5" HS																																									
AnyRAID 720ix	12Gbs SAS/SATA	0/1/10,5/50/6/60	15x3.5" HS, 16/32x2.5" HS																																									
Disk drive bays	Up to 15 3.5" or 32 2.5" hot-swap bays, or up to 5 3.5" easy-swap bays, on front. Up to 2 M.2 SSD drives via optional M.2 module. Up to one internal LTO-6 SAS tape drive on 720ix model, or external RDX tape drive via USB.	Expansion slots	<table><tr><td>Slot 7</td><td></td></tr><tr><td>Slot 6</td><td></td></tr><tr><td>Slot 5</td><td></td></tr><tr><td>Slot 4</td><td></td></tr><tr><td>Slot 3</td><td></td></tr><tr><td>Slot 2</td><td></td></tr><tr><td>Slot 1</td><td></td></tr></table>		Slot 7		Slot 6		Slot 5		Slot 4		Slot 3		Slot 2		Slot 1																											
Slot 7																																												
Slot 6																																												
Slot 5																																												
Slot 4																																												
Slot 3																																												
Slot 2																																												
Slot 1																																												



Expansion slots

Slot 1 (CPU1)	PCIe 3.0 x16, full height, full length, double-wide
Slot 2 (CPU1)	PCIe 3.0 x16 (x8 elec), full height, full length
Slot 3 (CPU1)	PCIe 3.0 x16 (x8 elec), full height, full length
Slot 4 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length
Slot 5 (CPU2)	PCIe 3.0 x16, full height, full length
Slot 6 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length
Slot 7 (CPU2)	PCIe 3.0 x16 (x8 elec), full height, full length

For a list of all supported options, please see https://download.lenovo.com/pccbbs/options_iso/ocm_september_2016_thinkserver.xlsx sheet

Model	70DG006B++
Product	ThinkServer TD350
Region	EMEA
Machine Type	70DG
TopSeller	TopSeller
Processor	1xE5-2609 v4 8C/1.7GHz/20MB/85W/DDR4-1866
2nd CPU	4XG0G89083
Memory	1x16GB RDIMM DDR4-2400 ECC
RAID Controller	720i PCIe
Disk Bays	5x3.5" HS
Storage	Open
Optical	HH DVD±RW
Add-on NIC	None
Add-on Ports	None
TPM	None
System Management	TSM
Operating System	None
Warranty	3-year
Power Supply	550Wx1 Platinum
Ann Date (mm/yy)	04/16

