



Product Compliance Datasheet

MARKETING NAME.....Latitude 7480/Latitude 7480-01

REGULATORY MODEL.....P73G

REGULATORY TYPE.....P73G001

EMC EMISSIONS CLASS...B

EFFECTIVE DATE.....December 28, 2016

Table of contents

I. Statement of Compliance	2
II. Global Environmental Information	2
III. Power Cords and User Documentation.....	3
IV. Trade (Import/Export) Compliance Data	3
V. Product Dimensions and Weight	3
VI. Performance Data	3
VII. Product Materials Information	3
VIII. Packaging	5
IX. Batteries	5
X. Design for Environment.....	6
XI. Recycling / End-of-Life Service Information	6
XII. Helpful Links	6
A Appendix A: ErP Lot 3 Product Energy Consumption Information.....	7
B Appendix B: ErP Lot 26 Network Standby Energy Consumption Information	9



I. Statement of Compliance

This equipment has been determined to be compliant with the applicable standards, regulations, and directives for the countries where the equipment is marketed. The equipment is affixed with regulatory marking and text as necessary for the country/agency. Dell manufacturers and markets Multimedia Equipment (MME), Information Technology Equipment (ITE), Audio Visual Equipment (A/V), Industrial, Scientific, Medical Equipment (ISM) or combinations of these. Generally, equipment Safety and EMC compliance is based on International IEC and CISPR standards and their national equivalent along with national standards for Radio (wireless), and Energy. Dell products have been verified to comply with the EU RoHS Directive 2011/65/EU. Dell equipment does not contain any of the restricted substances in concentrations and applications not permitted by the RoHS Directive. EMC Emissions Class refers to one of the following use environments:

- EMC Class B equipment is intended for use in residential/domestic environments but may also be used in nonresidential/non-domestic environments.
- EMC Class A equipment is intended for use in non-residential/non-domestic environments. Class A equipment may also be utilized in residential/domestic environments but may cause interference and require the user to take adequate corrective measures.

For Safety and EMC compliance, this equipment has been assigned a unique regulatory model and regulatory type that is imprinted on the equipment regulatory labeling to provide traceability to the regulatory approvals noted on this datasheet. This datasheet applies to any equipment that utilizes the assigned regulatory model and type including marketing names other than those listed on this datasheet. ErP compliance is tied to the CE mark. REACH (Registration, Evaluation, Authorization and Restriction of Chemicals, 1907/2006) is the European Union's (EU) chemical substances regulatory framework. Dell complies with the REACH directive. For information on SVHC (Substances of Very High Concern), see www.dell.com/REACH. Compliance documentation, such as certification or Declaration of Compliance for the equipment is available upon request to product_compliance@dell.com. Please include equipment identifiers such as marketing name, regulatory model, regulatory type and country that compliance information is needed in request.

II. Global Environmental Information

Environmental (Voluntary Marks)		
Country	Approval	Compliance
Global	ENERGY STAR (Configuration Dependent)	Spec Version
Global	TCO Certified Notebook 5.0	Yes
China	CECP	Yes
China	CEC	Yes
Taiwan	Greenmark	Yes
Varies by Country – see EPEAT.net	EPEAT (Configuration Dependent)	Gold
Brazil	INMETRO	Yes



III. Power Cords and User Documentation

Dell products are provided with the power cord and user documentation suitable for the intended country of delivery. Products that are relocated to other countries should use nationally certified power cords and plugs to ensure safe operation of the product. Contact Dell to determine if alternate power cords or user documentation in other languages is available for your market.

IV. Trade (Import/Export) Compliance Data

For any questions related to importing & exporting classification of Dell products, please obtain information from the following link: www.dell.com/import_export_compliance or send request to WW_Export_Compliance@dell.com.

V. Product Dimensions and Weight

Depth, mm/cm	Width, mm/cm	Height, mm/cm	Weight, kg
220.9 mm	331.0 mm	20.87 mm	1.88 Kg (depending upon installed options)

For Display, Imaging products please refer to the user manual for weight and dimension information.

VI. Performance Data

ErP Lot 3 & Lot 26 information is located in section XIV Appendix A

For additional information on ENERGY STAR models refer to the following databases:

<http://www.dell.com/en-us/work/learn/power-and-cooling-energy-star>

USA: <https://www.energystar.gov/productfinder/>

EU: <http://www.eu-energystar.org/db-currentlists.htm>

The battery[ies] in this product cannot be easily replaced by users themselves.

VII. Product Materials Information

Information on Dell's material use is available [here](#).

Dell's Restricted Material for Use guidance document is available [here](#).

- The case material is, cover: >PC-GF50FR(40)< , cover-CF: >EP-(CF70)FR(40)<; >PC-(CF+GF)64FR(40)< , log up: >PC-GF50FR(40)< , Bezel: >TPC-ET, PC+ABS FR(40)<
- This product contains 7% post-consumer recycled plastic/closed loop recycled plastics (Measured as a percentage of total amount of plastic (by weight) in the product as per guidance in EPEAT standard as applies to plastics parts)



Mechanical plastic parts ¹ > 25 g are BFR/PVC free	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> NA
Marking of plastics parts greater than 25 grams is in accordance with ISO 11469 (see below)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> NA
Printed circuit boards (without components) >25g are BFR PVC free ²	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> NA
Insulation materials of external electrical cables are PVC free	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Insulation materials of internal electrical cables are PVC free	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> NA
Product is BFR/PVC Free (Accessories & Options may not be BFR/PVC-Free, refer to spec ENV0199)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

Flame Retardants Used in Motherboard

Part	Flame Retardant
Motherboard	8% DOPO

Flame Retardants Used in Mechanical Plastic Parts > 25 grams

Resin Material Name	Marking per ISO 11469:2016	Flame Retardant Marking per ISO 1043-4 (i.e. FR(16), FR(40), etc.)	Flame Retardant (i.e. TBBPA, triaryl phosphate ester, etc.)	List applicable R-Phrase(s) or Hazard Statement(s) per EU Directive 67/548/EEG or 1272/2008
CAZ20_LCD_BEZEL	>TPC-ET, PC+ABS FR(40)<	FR(40)	Organo Phosphate	NA
CAZ20_LCD_COVER_TS_CF	>PC-GF50FR(40)<	FR(40)	Organo Phosphate	NA
	>PC-(CF+GF)64FR(40)<	FR(40)	Organo Phosphate	NA
CAZ20_LCD_COVER_TS_CF	>PC-GF50FR(40)<	FR(40)	Organo Phosphate	NA
	>EP-CF70FR(40)<	FR(25)	Organo Phosphate	NA
CAZ20_LOG_UP	>PC-GF50FR(40)<	FR(40)	Organo Phosphate	NA

Mercury Information

Number of bulbs	Average per bulb
0	N/A

Additional information:

- RoHS and REACH declaration - see product material information section at: www.dell.com/environmental_information
- Products MSDS (Material Safety Data Sheets):

¹ Mechanical plastic part: plastic parts that do not internally carry an electrical signal such as housings, brackets, bezels, latches, etc. that form the basic structure of the product and/or have mechanical functions. Plastic parts such as fans, connectors, printer fuser assemblies, etc. are not considered "mechanical plastic parts" in the context of this specification. Plastics parts do not contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride (Per Dell Spec ENV0424)

² Dell will adopt the BFR/CFR/PVC-free definition as set forth in the "iNEMI Position Statement on the Definition of 'Low-Halogen' Electronics (BFR/CFR/PVC-Free)." Plastic parts contain <1000 ppm (0.1 percent) of bromine (if the Br source is from BFRs) and <1000 ppm (0.1 percent) of chlorine if the Cl source is from CFRs, PVC or PVC copolymers. All printed circuit board (PCB) and substrate laminates contain bromine/chlorine totaling less than 1,500 ppm (0.15 percent), with maximum chlorine of 900 ppm (0.09 percent) and maximum bromine of 900 ppm (0.09 percent)



Batteries: [Battery MSDS Documentation and Declaration](#)
 Printer Toner and Ink: [MSDS Documentation](#)

VIII. Packaging

Information on Dell's sustainable packaging effort available [here](#).

Additional materials restricted in Packaging as per Dell's Restricted Material Guidance document found [here](#).

Packaging Materials	Total Weight, (kg)	Sustainable Material Content ³ (e.g Recycled content *, bio-based, Sustainable Forested materials)	% Sustainable Material		
			APJ region	DAO region	EMEA region
Corrugated Fiberboard	0.291	Recycled Content	100%	100%	100%
LDPE (Including EPE Foam)	0.001	Recycled Content	0-80%	0-80%	0%
Molded paper pulp	0.14	Recycled content	100%	100%	100%
HDPE (including thermoformed) *	0.012	Recycled Content	0%	0%	0%
Molded Bamboo	N/A	Non-wood, biobased material	NA	NA	NA
Wheat Straw	N/A	Non-wood, biobased material	NA	NA	NA
Mushroom	N/A	Non-wood, biobased material	NA	NA	NA
EPS	N/A	NA	NA	NA	NA
Other, please specify	N/A	NA	NA	NA	NA

IX. Batteries

Below is a listing of batteries that could be present in the product:

Battery Description – Batteries	Battery Type	Battery Weight (kg)
CR-2032 coin cell	Lithium	0.005 (max)
3-cell 42 Wh	Lithium	0.185 (max)
4-cell 60 Wh	Lithium	0.270 (max)

³ Non-wood, biobased material may include, but is not limited to: bagasse, bamboo, mushroom, straw, agricultural waste or byproduct.
 * Recycled content in packaging material is supplier dependent.



X. Design for Environment

Dell systems are, when applicable, designed for easy assembly, disassembly, and servicing. For more information on product Recyclability please visit www.dell.com/environmental_information

XI. Recycling / End-of-Life Service Information

Take back and recycling services are offered for this product in certain countries. If you want to dispose of system components, please visit www.dell.com/recyclingworldwide and select the relevant country.

XII. Helpful Links

- **Environmental Policy**
<http://i.dell.com/sites/content/corporate/corp-comm/en/Documents/dell-global-environmental-policy.pdf>
- **Environment Website**
www.dell.com/environmental_information
- **Corporate Sustainability Report**
<http://www.dell.com/Learn/us/en/uscorp1/report?c=us&l=en&s=corp&delphi:gr=true>
- **ISO 14001 Certification**
<http://i.dell.com/sites/content/corporate/corp-comm/en/Documents/dell-iso14001-worldwide.pdf>
- **Materials Restricted for Use**
http://www.dell.com/downloads/global/corporate/environ/restricted_materials_guid.pdf
- **Chemical Use Policy**
<http://i.dell.com/sites/docontent/corporate/environment/en/Documents/chemical-use-policy.pdf>
- **Product Carbon Footprint**
http://content.dell.com/us/en/corp/d/corp-comm/environment_carbon_footprint_products
- **RoHS Compliance**
www.dell.com/rohsinfo
- **REACH Compliance**
www.dell.com/REACH
- **Recycling Information**
www.dell.com/recycling
- **Supplier Responsibility**
<http://content.dell.com/us/en/corp/d/corp-comm/standards-for-suppliers.aspx>



A Appendix A: ErP Lot 3 Product Energy Consumption Information

ErP Lot 3 (EU No 617/2013)

The ErP Lot 3 regulation includes requirements for certain product specific information to be provided by the manufacturer. This is applicable to Desktops, Integrated Desktops (All-in-One), Notebooks, Tablets, Slates, Notebook Thin Clients, Desktop Thin Clients, Workstations, Mobile Workstations, Computer Servers, and Small Scale Servers.

ErP Lot 3 provides certain exclusions based upon product type, screen size, and/or the amount of power consumed in idle mode. Product energy and acoustic information might be reported for products that are out of scope of ErP Lot 3 for informational purposes only.

Category	Category A
Processor Speed in GHz	2.8
Number of Cores	2
Total Installed System Memory in GB	32
Graphics	Integrated
WOL enabled in "Sleep" Mode	No
WOL enabled in "Off" Mode	No
<i>As Tested:</i> Lowest Power State	0.30
<i>As Tested:</i> Poff(W) WOL Disabled	0.30
<i>As Tested:</i> Poff(W) WOL Enabled	0.30
<i>As Tested:</i> Psleep(W) WOL Disabled	1.24
<i>As Tested:</i> Psleep(W) WOL Enabled	1.27
<i>As Tested:</i> Pidle(W)	5.47
Base TEC Limit (kWh)	27
TEC Adders Limit (kWh)	11.20
Base + Adders TEC Limit (kWh)	38.20
Results TEC	17.01

Power Supply Model #	Internal or External	Link to efficiency report
HA65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=6448362&appliance=EPS&nr=1
LA65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=14644026&appliance=EPS&nr=1
DA65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=8954085&appliance=EPS&nr=1
HK65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=14082454&appliance=EPS&nr=1
DA90PM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=6448377&appliance=EPS&nr=1
LA90PM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=8783126&appliance=EPS&nr=1
FA90PM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details-details&ref=8974774&appliance=EPS&nr=1



* **Energy Consumption** results are based solely upon the laboratory testing of the **System Configuration** listed above. Energy consumption is tested at 230 Volts / 50 Hz.

Energy Consumption*

Energy efficiency benefits the environment and lowers the total cost of equipment ownership by reducing power consumption. Dell offers energy calculators that help estimate power needs, potential emissions avoidance and potential cost savings. Click [here](#) for Dell's Client Energy Savings Calculator, Data Center Capacity Planner, and Monitor Power Savings Calculator. Information on Energy Efficiency is available [here](#)

* This document is informational only and reflects laboratory performance. Your product may perform differently, depending on the software, components and peripherals you ordered. Accordingly, the customer should not rely upon this information in making decisions about electrical tolerances or otherwise. No warranty as to accuracy or completeness is expressed or implied.

For more details visit www.dell.com/environmental_information

Computers Category A:

Service Level	Sound Power (L_{WAd}, bels) (1 bel=10 decibels, re 10^{-12} Watts)	Sound Pressure Bystander Position (L_{pAm}, decibels) (re 2×10^{-5} Pa)
Hard Drive Accessing	2.5	14.6
Optical Drive Accessing	-	-
Idle	2.6	14.6



B Appendix B: ErP Lot 26 Network Standby Energy Consumption Information

ErP Lot 26 (EU No 801/2013)

The ErP Lot 26 regulation includes Network Standby power requirements to be provided by the manufacturer. This is applicable to multiple product categories. If no information is reported, it's assumed it is out of scope of ErP Lot 26.

Cut & Paste section below as a Picture into Dell P/N ENV0023 (EDS) in the bottom in section XIII. APPENDIX A: ErP Lot 3 & Lot 26 Product (Energy Consumption) Info unless information in User	
Network Standby Classification	LoNA
Off/Standby - Watts	0.3
Network Standby - Watts	1.24
Number of Network Ports	1
Location of 'Physical' Network Ports	Back
Network Port Type	Ethernet - TCPIP
Network Port(s) Activated or Deactivated	Network Port(s) "Activated"
Network Port Maximum Performance in GB/s	1000 Mbps
Communication protocol used by equipment	Ethernet - TCPIP
Description of how to assert Network Standby Mode	Information available @ www.dell.com/regulatory_compliance and/or www.dell.com/support
Sequence of events to trigger automatic assertion of Network Standby Mode	
Notes regarding operation of the equipment EX: how the user switches the equipment into network standby	
Default time for PM function to switch equipment into this mode	
Inactivity time required to enter Network Standby	
Re-activation trigger	
Measurement Method	

