

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO P556/E85+

Your Flexible and Economic PC

The FUJITSU ESPRIMO P556/E85+ Desktop provides high-quality computing for your daily office tasks. It supports attractive price points and delivers the continuity needed for daily operations. Your valuable business data is protected by the latest TPM controller and the Erasedisk option. To meet your specific hardware needs it can be either individually configured or customized.

High performance and best price/performance ratio

Powerful and cost-effective microtower

- 6th generation Intel® Core™ processor family

System management

The perfect answer to offload your IT administrators

- DeskView Admin enhances the management of the devices in your IT infrastructure during productive operation – even during remote periods and after hours

Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and functionality tests - all under one roof in Germany

Lifecycle

Hardware continuity for long-lasting project requirements

- Managed lifecycle of up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

- 85% energy efficient power supply



Components

Processor	Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4500 (2 Cores / 2 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) ** Intel® Celeron® processor G3900 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics 510) ** <small>*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)</small> <small>**6th generation Intel® processor</small>
Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home Windows 7 Professional (available through downgrade rights from Windows 10 Pro)
Operating system compatible	Windows 8.1 Pro (available through downgrade rights from Windows 10 Pro) openSUSE Linux
Memory modules	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM
Hard disk drives (internal)	SSD SATA III, 512 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch, SED SSD SATA III, 256 GB, 2.5-inch, SED SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch*
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	VGA Extension Card NVIDIA® NVS™ 315, 1 GB NVIDIA® GeForce® GTX 745 2 GB FH, 2 GB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DVI-I to VGA Adapter DP to DVI-D (single link) Adapter Cable AMD® Radeon R7 340, 2 GB

Drives (optional)	BD Triple Writer SATA ultra slim (tray) DVD-ROM DVD Super Multi DVD Super Multi ultra slim (tray) MultiCard Reader 24in1 USB 2.0 3.5"
Interface add on cards/components (optional)	WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version) WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only) Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1

Base unit

Base unit	ESPRIMO P556/E85+
Mainboard	
Mainboard type	D3400
Formfactor	μATX
Chipset	Intel® H110
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	2,133 MHz
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Realtek RTL8111G
BIOS version	AMI Aptio V
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	3
thereof SATA III	3
thereof eSATA	1
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.1 Gen1 (USB 3.0) total	4

Interfaces

USB front	2x USB 2.0 or/and 2x USB 3.0 (optional)
USB rear	2x USB 2.0; 2x USB 3.0
USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
---------------------------------	--

Drive bays

Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Drive bay notes	3.5" bays can be used for 2.5" drives

Slots

PCI-Express 3.0 x16	1 x (210 mm / 8.27 inch) Full height
PCI-Express x1	2 x (190 mm / 7.48 inch) Full height

Graphics on board

Graphics brand name	Intel® HD Graphics 510, Intel® HD Graphics 530
Shared video memory	up to 1,782 MB
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel

Graphics on board

Graphics features	Dual display support DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
--------------------------	---

Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
-----------------------	--

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85% 0-Watt mode with hard-off switch
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=8fbfcf07-7f86-4c5a-b4d5-22d71672893b

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 6700
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU	3.4 B / 21 dB(A) Bystander; 24 dB(A) Operator position 50% load
Standard noise operation mode: HDD	3.5 B / 21 dB(A) Bystander; 24 dB(A) Operator position load
Standard noise operation mode: Idle mode	3.4 B / 21 dB(A) Bystander; 24 dB(A) Operator position mode
Standard noise operation mode: ODD load	4.5 B / 31 dB(A) Bystander; 36 dB(A) Operator position load
Standard noise operation mode: Office applications 2.0	3.4 B / 21 dB(A) Bystander; 24 dB(A) Operator position load
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level Lwad (in B); 1B = 10dB
Blue angel noise operation mode: HDD load	3.7 B = 37 dB (A)
Blue angel noise operation mode: Idle mode	3.6 B = 36 dB (A)
Blue angel noise operation mode: ODD load	4.7 B = 47 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 425 x 353 mm 6.89 x 16.74 x 13.9 inch
Operating position	Vertical
Weight	9 kg
Weight (lbs)	20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO P556/E85+
Model	MI4W
Germany	TÜV GS
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions)
China	CCC China RoHS
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)

Security

Physical Security	Kensington Lock support Eye for padlock
-------------------	--

Security**System and BIOS Security**

Embedded security (TPM 2.0)
 EraseDisk (optional)
 Boot sector virus protection
 Write protect option for the Flash EPROM
 Control of all USB interfaces
 External USB ports can be disabled separately
 Control of external interfaces

User Security

User and supervisor BIOS password
 Hard disk password
 Access protection via external SmartCard reader (optional)
 Access protection via internal SmartCard reader (optional)
 Workplace Protect (secure authentication solution)

Workplace Embedded Tools

Auto BIOS Update via Fujitsu Server
 Auto BIOS Update via customer server (optional)
 Easy PC Protection (optional)

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
 Thermal management

Serviceability

EasyChange for single 3.5" HDD (optional)
 EasyChange for single optical drive (optional)
 Toolless serviceability for cabinet (optional)

Packaging information

Packaging dimension (mm)	516 x 278 x 562 mm
Packaging dimension (inch)	20.31 x 10.94 x 22.13 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1280 g
Material - Weight (lbs) Carton	2.82 lbs
Material - Weight (g) EPS / PS	140 g
Material - Weight (lbs) EPS / PS	0.31 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	1 year (for countries in EMEIA)
Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Mouse M440 ECO

Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code:
 S26381-K450-L200

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:
S26391-F7128-L600

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Desktop ESPRIMO P556/E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO P556/E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions GmbH

Website: www.fujitsu.com/fts

2017-06-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH