

Philips LED Monitor

19"w (48.3 cm) E-line 1440×900 HD+

190EL1SB

LED display: Contrast has never been better!!

This Eco friendly LED display comes with a superb 1000000:1 contrast ratio. Along with Dual inputs, natural colors, SmartContrast and Glossy finish, the 190EL1 is a great choice for all your needs

Great picture quality

- · LED technology ensures natural colors
- · Ready to display HD content
- SmartContrast 1,000,000:1 for incredible rich black details
- 5ms fast response time

Design that complements any interior

- Glossy finish to enhance your decor
- Small footprint to blend into any lifestyle

Environmentally friendly green design

- Mercury Free eco-friendly display
- Energy Star for energy efficiency and low power consumption
- Complies with RoHS standards to care for the environment

Great convenience

- Dual input accepts both analog VGA and digital DVI signals
- Easy picture format control switching in wide and 4:3 format



Highlights

High definition monitor

A high definition monitor is a display device designed to deliver the exceptional picture quality of high definition pictures, one fully prepared for HD sources like HD set top boxes. A HD monitor offers picture quality beyond that of progressive scan, conforming to strict standards for HD screens that display high resolution, top picture quality signals through a universal connection for either analog VGA or uncompressed DVI digital connections and supports HDCP. It displays 720p (1280x720p @ 50 and 60 Hz progressive) and 1080i (1920x1080i @ 50 and 60 Hz interlaced) signals.

LED technologyWhite LED's are solid state devices which light up to full, consistent brightness faster saving startup time. LED's are free from mercury content which allows for eco-friendly recycling and disposal process. LED's allow for better dimming control of LCD backlight, resulting in super high contrast ratio. It also gives superior color reproduction thanks to consistent brightness across the screen.

SmartContrast ratio 1000000:1







Without SmartContrast

You want the LCD flat display with the highest contrast and most vibrant images. Philips advanced video processing combined with unique extreme dimming and backlight boosting technology results in vibrant images. SmartContrast will increase the contrast with excellent blacklevel and accurate rendition of dark shades and colors. It gives a bright, lifelike picture with high contrast and vibrant colors.

5ms on/off response time

On-Off response time is the period required for a liquid crystal cell to go from active (black) to inactive (white) and back to active (black) again. It is measured in milliseconds. Faster is better: Lower response time means faster transitions and, therefore, results in fewer visible image artifacts in the display of transition of texts and graphics. On-Off response time is a more important measure in the display of business content like documents, graphs and photos.

Mercury Free

Philips monitors with LED backlighting are free of Mercury content, one of the most toxic natural substances, which affects humans and animals. This reduces the environmental impact of the display throughout its life-cycle, from manufacturing to disposal.

Energy Star 5.0
Energy Star is a US EPA sponsored energy efficiency program also adopted by many other countries. Energy Star certification ensures that you are buying a product which meets the latest power efficiency standards which operates with maximum power efficiency at all operational levels. New Philips monitors are certified for Energy Star 5.0 specifications and meet or exceed the standard. For example, in sleep mode Energy Star 5.0 requires less than 1watt power consumption, whereas Philips monitors consume less than 0.5 watts. Further details can be obtained from www.energystar.gov

Dual input





DVI connector

Dual input provides connectors to accommodate input of both analog VGA and digital DVI signals.

Easy picture format control





Widescreen format

4:3 format

Philips easy picture format control on OSD is to switch from the 4:3 aspect ratio to the widescreen mode and back again to match the display's aspect ratio with your content for working with wide $\ \, \text{documents} \ \, \text{without scrolling or viewing widescreen}$ media in the widescreen mode and distortion-free, native mode display of 4:3 ratio content.















Issue date 2017-07-04

Version: 1.0.4

12 NC: 8670 000 61411 EAN: 87 12581 53374 8 © 2017 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com

Specifications

Picture/Display

- LCD panel type: TFT-LCD
- Backlight type: W-LED system
- Panel Size: 19 inch / 48.1 cm
- Aspect ratio: 16:10
- Optimum resolution: 1440 x 900 @ 60 Hz
- Response time (typical): 5 ms
- Brightness: 250 cd/m²
- SmartContrast: 1,000,000:1
- Pixel pitch: 0.285 x 0.285 mm
- Viewing angle: 176° (H) / 170° (V), @ C/R > 5
- Display colors: 16.7 M
- Scanning Frequency: 30 -83 kHz (H) / 56 -75 Hz (V)

Connectivity

- Signal Input: VGA (Analog), DVI-D (digital, HDCP)
- · Sync Input: Separate Sync, Sync on Green

Convenience

- · User convenience: Brightness, Menu, Auto, Power On/Off
- · OSD Languages: English, French, German, Spanish, Italian, Russian, Simplified Chinese, Portuguese, Turkish
- Other convenience: VESA mount (100x100mm), Kensington lock
- · Plug & Play Compatibility: DDC/CI, Mac OS X, Windows 7/Vista/XP/2000/98, sRGB

Stand

• Tilt: -5/20 degree

Power

- On mode: <11.3W (EnergyStar 5.0 test method)
- Standby mode: <0.8W
- Off mode: < 0.5 W
- · Power LED indicator: Operation green, Stand by/
- Power supply: Built-in, 100-240VAC, 50/60Hz

Dimensions

- Product with stand (mm): 297 x 445 x 64 mm
- Product without stand (mm): 360 x 518 x 140 mm
- Packaging in mm (WxHxD): $358 \times 445 \times 180$ mm

Weight

- Product with stand (kg): 3.3 kg
- Product without stand (kg): 4.9 kg
- Product with packaging (kg): 3.5 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- MTBF: 50,000 hour(s)

Sustainability

· Environmental and energy: EPEAT Silver, RoHS, EnergyStar 5.0

Compliance and standards

Regulatory Approvals: CE Mark, FCC, Class B, SEMKO, ÚL/cÚL

Cabinet

- · Color: Black
- · Finish: Glossy