



## 5100 Enterprise Entry SATA SSDs Product Guide

The 5100 Enterprise Entry SATA solid-state drives (SSDs) use Micron NAND flash memory technology with a SATA 6Gbps interface. They provide an affordable solution for read-intensive applications such as boot, web servers, lower data rate operational databases and analytics.

The 5100 Enterprise Entry SATA SSD is shown in the following figure.



Figure 1. 5100 Enterprise Entry SATA SSD

### Did you know?

The 5100 Series of SATA SSDs is available from Lenovo in two levels of endurance. The Enterprise Entry SSDs covered in this product guide offer drive write endurance of between 0.5 and 0.9 total drive writes per day (DWPD) whereas the Enterprise Mainstream SSDs covered in [LP0634](#) are more for mixed read/write workloads and offer write endurance of between 2.5 and 5.0 DWPD.

Rigorous testing of the 5100 Series SSDs by Lenovo through the ServerProven program assures a high degree of storage subsystem compatibility and reliability. Providing additional peace of mind, these drives are covered under Lenovo warranty.

## Part number information

The following table lists the ThinkSystem part numbers.

Table 1. ThinkSystem ordering information

Part number	Feature	Description
2.5-inch hot-swap drives - ThinkSystem		
4XB7A08505	B10R	ThinkSystem 2.5" 5100 3.84TB Entry SATA 6Gb Hot Swap SSD
3.5-inch hot-swap drives - ThinkSystem		
4XB7A08509	B10V	ThinkSystem 3.5" 5100 3.84TB Entry SATA 6Gb Hot Swap SSD

The following table lists the System x part numbers and feature codes.

Table 2. System x ordering information

Part number	Feature	Description
2.5-inch hot-swap drives - System x		
01KR511	AXGP	5100 3.84TB Enterprise Entry SATA G3HS 2.5" SSD
3.5-inch hot-swap drives - System x		
01KR531	AXGT	5100 3.84TB Enterprise Entry SATA HS 3.5" SSD

## Features

The 5100 Enterprise Entry SATA SSDs have the following features:

- Industry standard 2.5-inch or 3.5-inch form factors
- Innovative triple-level cell (TLC) 3D NAND technology
- Suitable for read-intensive workloads with an endurance of between 0.5 and 0.9 drive writes per day (DWPD) for 5 years
- 6 Gbps SATA host interface
- High reliability and enhanced ruggedness
- Absence of moving parts to reduce potential failure points in the server
- S.M.A.R.T. support
- Advanced Encrypting Standard (AES) 256-bit encryption

SSDs have a huge but finite number of program/erase (P/E) cycles, which affect how long they can perform write operations and thus their life expectancy. Enterprise Entry SSDs typically have a better cost per read IOPS ratio but lower endurance and performance compared to Enterprise Performance SSDs. SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, which is listed as total bytes written (TBW) in the device specification.

The TBW value that is assigned to a solid-state device is the total bytes of written data that a drive can be guaranteed to complete. Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed. A solid-state device does *not* fail upon reaching the specified TBW. However, at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive reaches the end-of-life point, at which time the drive goes into read-only mode. Because of such behavior, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive is not exceeded before the required life expectancy.

For example, the 5100 1.92TB Enterprise Entry SATA SSD has an endurance of 3,200 TB of total bytes written (TBW). This means that for full operation over five years, write workload must be limited to no more than 1,753 GB of writes per day, which is equivalent to 0.9 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 2,922 GB of writes per day, which is equivalent to 1.5 full drive writes per day.

## Technical specifications

The following table presents technical specifications for the 5100 Enterprise Entry SATA SSDs.

**Tip:** Drives listed in this product guide are the Lenovo versions of the Micron 5100 ECO family of SSDs.

Table 3. Technical specifications

Feature	480 GB drive	960 GB drive	1.92 TB drive	3.84 TB drive
Interface	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA	6 Gbps SATA
Capacity	480 GB	960 GB	1.92 TB	3.84 TB
Endurance (drive writes per day)	0.5 DWPD	0.5 DWPD	0.9 DWPD	0.9 DWPD
Endurance (total bytes written)	450 TB	900 TB	3200 TB	6400 TB
Data reliability	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read	< 1 in 10 <sup>17</sup> bits read
MTBF	2,000,000 hours	2,000,000 hours	2,000,000 hours	2,000,000 hours
IOPS reads (4 KB blocks)	93,000	93,000	93,000	93,000
IOPS writes (4 KB blocks)	31,000	28,000	24,000	18,000
Sequential read rate (128 KB blocks)	540 MBps	540 MBps	540 MBps	540 MBps
Sequential write rate (128 KB blocks)	380 MBps	520 MBps	520 MBps	520 MBps
Read latency (seq)	500 µs	500 µs	500 µs	500 µs
Write latency (seq)	500 µs	500 µs	500 µs	500 µs
Shock, non-operating	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms	1,500 G (Max) at 0.5 ms
Vibration, non-operating	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)	3.13 G <sub>RMS</sub> (5-800 Hz)
Typical power	4.5 W	5 W	5.5 W	6 W

## Server support - ThinkSystem

The following table lists the ThinkSystem servers that are compatible.

Table 4. ThinkSystem server support

Part number	Description	1S Rack & Tower				2S Rack & Tower								4S Rack			Dense/ Blade			
		ST50 (7Y48/7Y50)	ST250 (7Y45/7Y46)	SR150 (7Y54)	SR250 (7Y51/7Y52)	ST550 (7X09/7X10)	SR530 (7X07/7X08)	SR550 (7X03/7X04)	SR570 (7Y02/7Y03)	SR590 (7X98/7X99)	SR630 (7X01/7X02)	SR650 (7X05/7X06)	SR670 (7Y36/7Y37/7Y38)	SR850 (7X18/7X19)	SR860 (7X69/7X70)	SR950 (7X11/12/13)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
4XB7A08505	ThinkSystem 2.5" 5100 3.84TB Entry SATA 6Gb Hot Swap SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	N	Y	Y	
4XB7A08509	ThinkSystem 3.5" 5100 3.84TB Entry SATA 6Gb Hot Swap SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	N	N	N	N	N	N	N	N	

## Server support - System x

The following tables list the System x servers that are compatible.

### Support for System x and dense servers with Xeon E5/E7 v4 and E3 v5 processors

Table 5. Support for System x and dense servers with Xeon E5/E7 v4 and E3 v5 processors

Part number	Description								
		x3250 M6 (3943)	x3250 M6 (3633)	x3550 M5 (8869)	x3650 M5 (8871)	x3850 X6/x3950 X6 (6241, E7 v4)	nx360 M5 (5465, E5 v4)	sd350 (5493)	nx360 M5 WCT (5467, E5 v4)
01KR511	5100 3.84TB Enterprise Entry SATA G3HS 2.5" SSD	Y	Y	Y	Y	Y	Y	Y	N
01KR531	5100 3.84TB Enterprise Entry SATA HS 3.5" SSD	Y	Y	Y	Y	N	N	N	N

### Support for System x and dense servers with Xeon v3 processors

Table 6. Support for servers with Xeon v3 processors

Part number	Description							
		x3100 M5 (5457)	x3250 M5 (5458)	x3500 M5 (5464)	x3550 M5 (5463)	x3650 M5 (5462)	x3850 X6/x3950 X6 (6241, E7 v3)	nx360 M5 (5465)
01KR511	5100 3.84TB Enterprise Entry SATA G3HS 2.5" SSD	N	N	N	N	N	Y	Y
01KR531	5100 3.84TB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N

## Server support - Flex System

The following table lists the compatibility information for Flex System servers.

**Tip:** For the ThinkSystem SN550 and SN850, see the [ThinkSystem table](#).

Table 7. Support for Flex System servers

Part number	Description	x240 (8737, E5-2600 v2)	x240 (7162)	x240 M5 (9532, v3)	x240 M5 (9532, v4)	x440 (7167)	x880/x480/x280 X6 (7903)	x280/x480/x880 X6 (7196)	Storage Expansion Node
01KR511	5100 3.84TB Enterprise Entry SATA G3HS 2.5" SSD	N	N	Y	Y	N	N	N	N
01KR531	5100 3.84TB Enterprise Entry SATA HS 3.5" SSD	N	N	N	N	N	N	N	N

## Operating system support

SSDs operate transparently to users, storage systems, applications, databases, and operating systems.

Operating system support is based on the controller used to connect to the drives. Consult the controller product guide for more information:

- RAID controllers: <https://lenovopress.com/servers/options/raid>
- SAS HBAs: <https://lenovopress.com/servers/options/hba>

## Warranty

The 5100 Enterprise Entry SATA SSDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When the SSDs are installed in a supported server, these drives assume the system's base warranty and any warranty upgrades.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

## Physical specifications

The drives have the following physical specifications (approximate, without the tray):

- Height: 7 mm (0.3 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 70 g (2.5 oz)

Shipping dimensions and weight - 2.5-inch drives (approximate, including the tray):

- Height: 63 mm (2.5 in.)
- Width: 174 mm (6.9 in.)
- Depth: 133 mm (5.2 in.)
- Weight: 434 g (1.0 lb)

Shipping dimensions and weight - 3.5-inch drives (approximate, including the tray):

- Height: 95 mm (3.7 in.)
- Width: 257 mm (10.1 in.)
- Depth: 193 mm (7.6 in.)
- Weight: 484 g (1.1 lb)

## Operating environment

The SSDs are supported in the following environment:

- Operating temperature: 0 to 70°C (32 to 158°F)
- Non-operating temperature: -40 to 85°C (-40 to 185°F)
- Relative humidity: 5 to 95% (non-condensing)

## Agency approvals

The 5100 Enterprise Entry SATA SSDs conform to the following regulations:

- Micron Green Standard
- Built with sulfur resistant resistors
- CE (Europe): EN 55032 Class B, RoHS
- FCC: CFR Title 47, Part 15 Class B
- UL: UL-60950-1, 2nd Edition
- BSMI (Taiwan): approval to CNS 13438
- RCM (Australia, New Zealand): AS/NZS CISPR32 Class B
- KCC RRL (Korea): approval to KN 32 Class B, KN 35 Class B
- W.E.E.E.: Compliance with EU WEEE directive 2002/96/EC.
- TUV (Germany): approval to IEC60950/EN60950
- VCCI (Japan): 2015-04 Class B
- IC (Canada): CISPR32 Class B: Canadian ICES-003:2016



## Related publications and links

For more information, see the following documents:

- Product Guide for 5100 Enterprise Mainstream SATA SSDs  
<http://lenovopress.com/lp0634>
- Lenovo ThinkSystem storage options product page  
<https://lenovopress.com/lp0761-storage-options-for-thinksystem-servers>
- Lenovo System x storage options product page  
<https://www3.lenovo.com/us/en/data-center/servers/server-options/system-x-options/server-storage/c/system-x-storage>
- Micron 5100 series product page  
<https://www.micron.com/products/solid-state-storage/product-lines/5100>
- ServerProven for SSDs  
<http://www.lenovo.com/us/en/serverproven/xseries/storage/hssdmatrix.shtml>
- Lenovo RAID Introduction  
<https://lenovopress.com/lp0578-lenovo-raid-introduction>
- Lenovo RAID Management Tools and Resources  
<https://lenovopress.com/lp0579-lenovo-raid-management-tools-and-resources>
- ServeRAID Adapter Quick Reference  
<http://lenovopress.com/tips0054>

## Related product families

Product families related to this document are the following:

- [Drives](#)

## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
1009 Think Place - Building One  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

**© Copyright Lenovo 2018. All rights reserved.**

This document, LP0633, was created or updated on November 5, 2018.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<http://lenovopress.com/LP0633>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <http://lenovopress.com/LP0633>.

## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Flex System

Lenovo®

NeXtScale

ServeRAID

ServerProven®

System x®

ThinkServer®

ThinkSystem

The following terms are trademarks of other companies:

Xeon® is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries.

Other company, product, or service names may be trademarks or service marks of others.