

HP DreamColor Z31x Studio Display



Designed for the world's elite color professionals, the award-winning HP DreamColor Technology brings the industry's boldest visions to life. Captivate with Cinema 4K resolution, an expansive color gamut for remarkably vivid colors, integrated colorimeter and custom-tailored management tools.



And the award goes to...

- The display that walked the red carpet. The HP DreamColor Technology won the 2015 Scientific and Engineering Award from the Academy of Motion Picture Arts and Sciences.¹ Experience theater-quality color from HP's most precise display yet.

More time creating. Less time calibrating.

- Maintain accurate color with a pop-up sensor that calibrates on demand or on a regular schedule. No longer wonder if your color is correct-it just is.

Designed by pros. For pros.

- HP worked with leading visual effects and animation studios to create customized solutions for the optimal design process. Speed projects to completion with True 2K, onscreen markers and keyboard-based input switching between your devices.

HP DreamColor Z31x Studio Display Specifications Table



Product Number	Z4Y82A4
Display Size (diagonal)	79 cm (31.1")
Viewing Angle	178° horizontal; 178° vertical
Brightness	250 cd/m ² ^{1,3}
Contrast Ratio	1500:1 static ¹
Response Ratio	20 ms on/off ¹
Aspect Ratio	17:9
Native Resolution	4096 x 2160 @ 60 Hz
Resolutions Supported	4096 x 2160; 3840 x 2160; 2048 x 2160; 2560 x 1440; 2048 x 1080; 1920 x 1080; 1366 x 768; 1280 x 1024; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480
Display Features	Anti-glare; BrightView Panel; In plane switching; Language selection; LED Backlights; On-screen controls; Plug and Play; User programmable; Anti-static
Input Signal	2 DisplayPort™ 1.2; 2 HDMI 2.0
Ports and Connectors	1 USB 3.0 Type-B (upstream); 1 USB Type-C™ (DisplayPort™ 1.2, power delivery up to 60 W); 4 USB 3.0 (downstream, two side and two rear) ¹
Input Power	Input voltage: 100 to 240 VAC
Power Consumption	260 W (maximum), 120 W (typical), 0.5 W (standby)
Dimensions with Stand (W x D x H)	29.05 x 9.76 x 22.28 in 73.8 x 24.8 x 56.6 cm
Dimensions without Stand (W x D x H)	29.05 x 3.25 x 16.3 in 73.80 x 8.26 x 41.41 cm Without stand
Weight	33 lb 15 kg With stand
Ergonomic Features	Tilt: -5 to +30°; Swivel: ±45°; Height: 117 mm
Environmental	Arsenic-free display glass; Mercury-free display backlights
What's in the box	AC power cable; CD with User Guide, warranty, drivers; DisplayPort™ 1.2 cable; HDMI cable; Monitor; USB cable (Type A male to Type B male); USB Type-C™ cable; USB Type-C™ to A cable

See important legal notifications on the last page

Accessories and services (not included)

HP Business PC Security Lock Kit



Protect your HP Business PC from tampering or theft in public locations by locking-down peripherals such as keyboards, mice, monitors or USB security devices and preventing the removal of the PC chassis cover.

Product number: PV606AA

HP DisplayPort Cable Kit



Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor.

Product number: VN567AA

HP 4 year Next business day Exchange Large Monitor Service



When you can't afford to wait for your device to be exchanged, let HP Hardware Next Business Day Advance Exchange get you back up and running as quickly as possible. You'll get remote technical assistance to help you resolve problems. Then, if needed, we'll ship you a replacement unit within the next business day 1 – along with a prepaid waybill to ship back your defective unit.

Product number: U0J12E

Messaging Footnotes

¹ The 2015 Scientific and Engineering Award from the Academy of Motion Picture Arts and Sciences went to John Frederick, Bob Myers, Karle Rasche and Tom Lianza for the development of the HP DreamColor LP2480zx Professional Display. This cost-effective display offered a stable, wide color gamut, allowing facility-wide adoption in feature animation and visual effects studios.

Technical Specifications Footnotes

¹ All specifications represent the typical specifications provided by HP's component manufacturers, actual performance may vary either higher or lower.

³ HP applied uniformity compensation to each Z31x display, which brings the typical uniform peak luminance down to 250 cd/m² from a 350 cd/m² native peak brightness. Display supports luminance calibration up to 250 cd/m², reserving any luminance headroom for panel aging compensation.

Sign up for updates
hp.com/go/getupdated

Learn more at
hp.com

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe® is a trademark of Adobe Systems Incorporated. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

