FUJITSU

Data Sheet FUJITSU PRAID EP440i TFM/ EP440i TFM SafeStore

RAID Controller SAS 12Gbit/s 4GB cache based on LSI MegaRAID® for internal storage devices

The RAID concept (Redundant Array of Independent Disks) refers to several independent hard disks which form a large logical drive when switched together.

Redundancy information is calculated from several data blocks (except for RAID 0) and saved distributed to the individual hard disks. Your operating system no longer accesses the individual hard disks, but the array.

The actual objective of the RAID concept is to increase availability and prevent downtimes in the event of a hard disk failure. However, the theoretical security of the RAID concept is only as good as the RAID controller used. Benefit from the Fujitsu RAID controllers where technology, experience and practical implementation all ensure the security that your company needs in the event of an emergency.

PRAID EP440i TFM/ EP440i TFM SafeStore

The Fujitsu RAID Controller PRAID EP440i TFM with 4GB cache and 12Gbit/s SAS ports x (8) improves performance for storage intensive workloads such as databases and sets new speed and data security standards for internal storage drives. The RAID stack is based on the LSI MegaRAID® and offers high data throughput, a comprehensive fault tolerance function and user-friendly management options. Moreover, the Controller management is integrated seamlessly into the Fujitsu server management concept. All controller functions are supported by the Fujitsu ServerView RAID Manager. The PRAID

EP440i TFM is designed for backward compatibility with 3Gbit/s SAS as well as with 6Gbit/s and 3Gbit/s SATA hard drives. Regardless of the drive speed, it delivers significant performance improvements in both read and write applications. SafeStore is supported by different controller- PRAID EP440i TFM SafeStore. MegaRAID® SafeStore software helps manage self-encrypting drives attached to RAID controller cards for higher levels of security. An authentication key is required to lock a drive so that its contents remain safely beyond the reach of hackers and thieves and MegaRAID® SafeStore software helps to create and locally manage those authentication keys. The RAID controller supports all of the important RAID levels including RAID 6 and 60. The optional flash battery backup (FBU) combined with TFM module ensures the integrity of the data stored in the cache on the RAID controller in case of a power outage. In this event, the data will be copied to a non-volatile flash memory (TFM). The FBU provides a low-priced alternative to an uninterruptible power supply (UPS) and, when compared to battery backup up units (BBU), enables a long-term, secure store of data and better serviceability. The TFM module is bundled with the controller, the FBU is optional. Important information for later upgrade from std. SAS controller: Specific cable sets per system are available as L-parts. For upgrade from std. SAS controller see manual. Orders ex factory are configured with appropriate cables.



Main Features

- 12Gbit/s SAS ports PCI Express[®] 3.0 x8
- LSISAS3108 12Gbit/s RAID-on-Chip
- 4GB 1333MHz DDRIII cache memory
- Optional Flash Backup Unit (FBU)
- SafeStore is supported by different controller: PRAID EP440i TFM SafeStore
- User Management Options
- RAID Advanced Software Options LSI CacheCade[®]. Fast Path is supported free of charge by controller firmware

Benefits

- Connect up to 240 HDDs and SSDs
- RAID levels 0, 1, 5 and 6 for more data security, RAID spans 10, 50 and 60 for more data security
- Improves performance for storage intensive workloads (such as databases) and for certain load profiles like random access to databases (especially for SSD drives)
- Ensures the integrity in case of power outage, Long-term, secure store of data and better serviceability compared to BBU
- Safe data encryption and data safety for harddisks in case of removal
- Seamless merging of the RAID management into system management
- Create high performance controller cache pools

Technical details

Technical details

Controller Silicon Controller type	RoC (RAID on Chip)				
Controller type	Noe (IN ID on emp)	LSI SAS3108			
controller type	RAID 5/6 Ctrl.	RAID 5/6 Ctrl.			
Operating system pre-inst		Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.			
Released drivers list link	http://support.ts.fuj	jitsu.com/Download/Index.asp			
Number of ports	8 ports int.				
Connector internal	2x SFF8643 (Mini-S	AS HD)			
Data transfer rate up to	12 Gbit/s				
Bus type	PCIe 3.0				
Bus width	x8				
RAID Management	StorCLI (command-	erverView RAID Manager torCLI (command-line interface) IOS Configuration Utility			
	- Fast initialization - Single controller n - Load Balancing - Configurable strip - Fast initialisation - Check consistency	er of spans is 8 expansion (OCE) Migration (RLM) Floss of system power during arr for quick array setup nultipathing (failover) e size up to 1MB for quick array setup For background data integrity -	ray rebuild or reconstruction (RLM) Make Data Consistent (MDC)		
	- Up to 64 logical di - S.M.A.R.T support - Global and dedica - Automatic rebui - Enclosure affinit - Enclosure manage - SES (inband)	ted Hot Spare with Revertible H Id Y ement	ot Spare support		
RAID level	- Up to 64 logical di - S.M.A.R.T support - Global and dedica - Automatic rebui - Enclosure affinit - Enclosure manage	rives per controller Ited Hot Spare with Revertible H Id Sy ement	ot Spare support		
	- Up to 64 logical di - S.M.A.R.T support - Global and dedica - Automatic rebui - Enclosure affinit - Enclosure manage - SES (inband) - SGPIO (outband	rives per controller Ited Hot Spare with Revertible H Id Sy ement	ot Spare support		
RAID level RAID cache backup unit RAID controller notes	- Up to 64 logical di - S.M.A.R.T support - Global and dedica - Automatic rebui - Enclosure affinit - Enclosure manage - SES (inband) - SGPIO (outband 0, 1, 10, 5, 50, 6, 6	rives per controller Ited Hot Spare with Revertible H Id Y ement) 0	ot Spare support		
RAID cache backup unit RAID controller notes	- Up to 64 logical di - S.M.A.R.T support - Global and dedica - Automatic rebui - Enclosure affinit - Enclosure manage - SES (inband) - SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU	rives per controller Ited Hot Spare with Revertible H Id Y ement) 0	ot Spare support		
RAID cache backup unit RAID controller notes Interface technology	- Up to 64 logical di - S.M.A.R.T support - Global and dedica - Automatic rebui - Enclosure affinit - Enclosure manage - SES (inband) - SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA	rives per controller Ited Hot Spare with Revertible H Id y ement) 0		Number of Connectors	
RAID cache backup unit RAID controller notes Interface technology Order code	 Up to 64 logical di S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA 	rives per controller Ited Hot Spare with Revertible H Id :Y ement) 0 108 Height of bracket	RAID controller cache size		
RAID cache backup unit RAID controller notes Interface technology Order code S26361-F5243-E205	 Up to 64 logical di S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA PRAID EP440i LP TFM 	rives per controller ited Hot Spare with Revertible H Id Y ement 0 08 Height of bracket Low Profile (LP)	RAID controller cache size 4 GB	Number of Connectors 2 2	
RAID cache backup unit RAID controller notes Interface technology Order code S26361-F5243-E205 S26361-F5243-E206	 Up to 64 logical di S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA PRAID EP440i LP TFM PRAID EP440i LP TFM SafeStore 	rives per controller Ited Hot Spare with Revertible H Id Y ement 0 108 Height of bracket Low Profile (LP) Low Profile (LP)	RAID controller cache size 4 GB 4 GB	2	
RAID cache backup unitRAID controller notesInterface technologyOrder code\$26361-F5243-E205\$26361-F5243-E206\$26361-F5243-E5	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i HTFM PRAID EP440i FH TFM	rives per controller Ited Hot Spare with Revertible H Id Sy ement) 0 108 Height of bracket Low Profile (LP) Low Profile (LP) Full Height (FH)	RAID controller cache size 4 GB 4 GB 4 GB 4 GB	2 2 2	
RAID cache backup unit RAID controller notes Interface technology Order code S26361-F5243-E205 S26361-F5243-E206 S26361-F5243-E5 S26361-F5243-E6	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i FH TFM SafeStore PRAID EP440i FH TFM SafeStore 	rives per controller ited Hot Spare with Revertible H Id Y ement) 0 0 08 Height of bracket Low Profile (LP) Low Profile (LP) Full Height (FH) Full Height (FH)	RAID controller cache size 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB	2 2 2 2 2	
RAID cache backup unitRAID controller notesInterface technologyOrder code\$26361-F5243-E205\$26361-F5243-E206	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i HTFM PRAID EP440i FH TFM	rives per controller Ited Hot Spare with Revertible H Id Sy ement) 0 108 Height of bracket Low Profile (LP) Low Profile (LP) Full Height (FH)	RAID controller cache size 4 GB 4 GB 4 GB 4 GB	2 2 2	
RAID cache backup unit RAID controller notes Interface technology Order code \$26361-F5243-E205 \$26361-F5243-E206 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E6 \$26361-F5243-L505	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6i Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i LP TFM SafeStore PRAID EP440i FH TFM PRAID EP440i FH TFM PRAID EP440i FH TFM SafeStore PRAID EP440i TFM	rives per controller Ited Hot Spare with Revertible H Id Y ement 0 0 108 Height of bracket Low Profile (LP) Low Profile (LP) Full Height (FH) Full Height (FH) Full Height / Low Profile	RAID controller cache size 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB	2 2 2 2 2 2	
RAID cache backup unit RAID controller notes Interface technology Order code \$26361-F5243-E205 \$26361-F5243-E206 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E6 \$26361-F5243-L505 \$26361-F5243-L506 Order code	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i FH TFM PRAID EP440i FH TFM PRAID EP440i FH TFM PRAID EP440i TFM SafeStore	rives per controller ited Hot Spare with Revertible H Id y ement) 0 108 Height of bracket Low Profile (LP) Low Profile (LP) Full Height (FH) Full Height (FH) Full Height (FH) Full Height / Low Profile Full Height / Low Profile	RAID controller cache size 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB	2 2 2 2 2 2	
RAID cache backup unit RAID controller notes Interface technology Order code \$26361-F5243-E205 \$26361-F5243-E206 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E6 \$26361-F5243-L505 \$26361-F5243-L506 Order code \$26361-F5243-L506	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i LP TFM SafeStore PRAID EP440i FH TFM PRAID EP440i TFM SAS3.0 cable for RX2530 M2, PR	rives per controller ited Hot Spare with Revertible H Id Sy ement) 0 108 Height of bracket Low Profile (LP) Low Profile (LP) Full Height (FH) Full Height (FH) Full Height (FH) Full Height / Low Profile Full Height / Low Profile Full Height / Low Profile	RAID controller cache size 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB	2 2 2 2 2 2	
RAID cache backup unit RAID controller notes Interface technology Order code \$26361-F5243-E205 \$26361-F5243-E206 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E5 \$26361-F5243-E6 \$26361-F5243-L505 \$26361-F5243-L506 Order code	 Up to 64 logical di - S.M.A.R.T support Global and dedica Automatic rebui Enclosure affinit Enclosure manage SES (inband) SGPIO (outband 0, 1, 10, 5, 50, 6, 6 Optional FBU based on LSI SAS31 SAS/SATA Product Name PRAID EP440i LP TFM PRAID EP440i FH TFM PRAID EP440i FH TFM PRAID EP440i FH TFM PRAID EP440i TFM SafeStore	rives per controller ited Hot Spare with Revertible H Id y ement) 0 108 108 108 108 108 108 108	RAID controller cache size 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB 4 GB	2 2 2 2 2 2	

Order code	Product Name	Notes	
S26361-F5243-E125	RAID Ctrl FBU option for PRAID EP4xx with 25cm cable	installed - Super-capacitor incl. cable	
S26361-F5243-E155	RAID Ctrl FBU option for PRAID EP4xx with 55cm cable	installed - Super-capacitor incl. cable	
S26361-F5243-E170	RAID Ctrl FBU option for PRAID EP4xxwith 70cm cable	installed - Super-capacitor incl. cable	
S26361-F5243-L110	RAID Ctrl FBU option for PRAID EP4xx with 25cm, 55cm, 70cm cable	installed - Super-capacitor incl. cable	
S26361-F5243-L660	RAID Advanced Software Options: LSI CacheCade [®] , Fastpath [®]	option / loose delivery - LSI CacheCade® and Fast Path for modular RAID controller and Mezzanine card with 1GB / 2GB cache Testkey available: PRIMERGY-PM	
Compliance			
Compliance notes	According to the corresponding system		

Compliance link

https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PRAID EP440i TFM/ EP440i TFM SafeStore, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PRAID EP440i TFM/ EP440i TFM SafeStore, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http:// www.fujitsu.com/fts/resources/navigation/ terms-of-use.html Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact Fujitsu Limited Website: www.fujitsu.com/primergy 2019-08-01 WW-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html Copyright 2019 FUJITSU LIMITED