## Hardware Specification



CPU       Intel® Core™ i7-7700 3.6 GHz quad-core processor         System Memory       Total DIMM slots: 4 Maximum memory: 64 GB (16 GB x4) Memory modules pre-installed: 32 GB DDR4 RAM (8 GB x 4)         Flash Memory       512MB DOM         M.2 SSD Slot       2 x M.2 2242/2260/2280/22110 SATA 6Gb/s SSD Note:	TVS-1282-i7-32G	
Maximum memory: 64 GB (16 GB x4) Memory modules pre-installed: 32 GB DDR4 RAM (8 GB x 4)  Flash Memory  512MB DOM  M.2 SSD Slot  2 x M.2 2242/2260/2280/22110 SATA 6Gb/s SSD Note:  1. The M.2 SSD is not included as standard. 2. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.  Drive Bay  4 x 2.5" SSD 8 x 2.5" /3.5" hard drive or SSD  Drive Compatibility  SATA 6Gbps/3Gbps; Hot-swappable  USB Port  1 x USB 3.0 port (Front) 4 x USB 3.0 port (Rear)  Gigabit Ethernet Port  4 x GbE port (10GbE and 40GbE are supported with the purchase and installation of compatible network adapters) Note:  1. For a list of compatible network adapters, please visit the Compatibility-List. 2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP-NAS-Hardware-Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System Seytem: Power button, Reset button, USB one-touch-backup button System Warning  Buzzer	CPU	Intel® Core™ i7-7700 3.6 GHz quad-core processor
M.2 SSD Slot  2 x M.2 2242/2260/2280/22110 SATA 6Gb/s SSD Note:  1. The M.2 SSD is not included as standard.  2. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.  Drive Bay  4 x 2.5" SSD 8 x 2.5" /3.5" hard drive or SSD  Drive Compatibility  SATA 6Gbps/3Gbps; Hot-swappable  USB Port  1 x USB 3.0 port (Front) 4 x USB 3.0 port (Rear)  Gigabit Ethernet Port  4 x GbE port (10GbE and 40GbE are supported with the purchase and installation of compatible network adapters) Note:  1. For a list of compatible network adapters, please visit the Compatibility-List 2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP-NAS-Hardware-Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System Warning  Buzzer	System Memory	Maximum memory: 64 GB (16 GB x4)
Note: 1. The M.2 SSD is not included as standard. 2. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.  Drive Bay  4 x 2.5" SSD 8 x 2.5" /3.5" hard drive or SSD  Drive Compatibility  SATA 6Gbps/3Gbps; Hot-swappable  USB Port  1 x USB 3.0 port (Front) 4 x USB 3.0 port (Rear)  Gigabit Ethernet Port  4 x GbE port (10GbE and 40GbE are supported with the purchase and installation of compatible network adapters) Note: 1. For a list of compatible network adapters, please visit the Compatibility-List. 2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP-NAS-Hardware-Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System: Power button, Reset button, USB one-touch-backup button  System Warning	Flash Memory	512MB DOM
B x 2.5" /3.5" hard drive or SSD  Drive Compatibility  SATA 6Gbps/3Gbps; Hot-swappable  USB Port  1 x USB 3.0 port (Front) 4 x USB 3.0 port (Rear)  Gigabit Ethernet Port  4 x GbE port (10GbE and 40GbE are supported with the purchase and installation of compatible network adapters) Note: 1. For a list of compatible network adapters, please visit the Compatibility List. 2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP-NAS-Hardware-Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System Power button, Reset button, USB one-touch-backup button  System Warning	M.2 SSD Slot	Note:  1. The M.2 SSD is not included as standard.  2. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party
USB Port  1 x USB 3.0 port (Front) 4 x USB 3.0 port (Rear)  4 x GbE port (10GbE and 40GbE are supported with the purchase and installation of compatible network adapters) Note:  1. For a list of compatible network adapters, please visit the Compatibility List. 2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP-NAS-Hardware Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System: Power button, Reset button, USB one-touch-backup button  System Warning	Drive Bay	
Gigabit Ethernet Port  4 x GbE port (10GbE and 40GbE are supported with the purchase and installation of compatible network adapters)  Note:  1. For a list of compatible network adapters, please visit the Compatibility List.  2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP-NAS-Hardware Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System: Power button, Reset button, USB one-touch-backup button  System Warning	Drive Compatibility	SATA 6Gbps/3Gbps; Hot-swappable
and installation of compatible network adapters)  Note:  1. For a list of compatible network adapters, please visit the  Compatibility List.  2. For instructions on how to install network adapters, please refer to Chapter 6 of the QNAP NAS Hardware Manual.  HDMI Output  3  Audio  Input: 2 x 6.3mm MIC In  Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack  Note: Only one of the above audio output ports can work at a time.  If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System: Power button, Reset button, USB one-touch-backup button  System Warning	USB Port	•
Audio  Input: 2 x 6.3mm MIC In  Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack  Note: Only one of the above audio output ports can work at a time.  If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System: Power button, Reset button, USB one-touch-backup button  System Warning  Buzzer	Gigabit Ethernet Port	and installation of compatible network adapters)  Note:  1. For a list of compatible network adapters, please visit the  Compatibility List.  2. For instructions on how to install network adapters, please refer
Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack Note: Only one of the above audio output ports can work at a time. If a speaker is connected, the sound will output through the speaker.  LED Indicators  System status, 2.5" SSD, M.2 SSD, 3.5" HDD  Buttons  System: Power button, Reset button, USB one-touch-backup button  System Warning  Buzzer	HDMI Output	3
Buttons System: Power button, Reset button, USB one-touch-backup button  System Warning Buzzer	Audio	Output: 2 x built-in speaker, 1 x 3.5mm Line-out jack  Note: Only one of the above audio output ports can work at a time.
System Warning Buzzer	LED Indicators	System status, 2.5" SSD, M.2 SSD, 3.5" HDD
	Buttons	System: Power button, Reset button, USB one-touch-backup button
Form Factor Tower	System Warning	Buzzer
	Form Factor	Tower

Dimensions (H x W x D)	234.6 (H) x 369.9 (W) x 319.8 (D) mm 9.23 (H) x 14.56 (W) x 12.59 (D) inch
Weight	Net (NAS only): 11.34 kg Gross (with packing and accessories): 13.65 kg
Sound Level	Sound pressure (LpAm) (bystander position): 21.6 dB (with 8 x Seagate ST2000VN000-1HJ164 hard drive installed)
Operating Temperature & Relative Humidity	0-40°C 5~95% non-condensing, wet bulb: 27°C
Power Supply Unit	Input: 100-240V~, 3-1.5A, 60-50Hz; Output 250W
PCIe Slot	3 (1* PCIe Gen3 x8; 2* PCIe Gen3 x4)
Fan	System: 3 x 8 cm cooling fan CPU: 1 x 9 cm fan

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Designs and specifications are subject to change without notice.

<sup>\*</sup> Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.