



# HP PageWide XL Folder

High-productivity online folding for the HP PageWide XL 8000 Printer and the HP PageWide XL 6000 and 5100 Printer series



## Full online integration

- Control the folder and folding styles from HP SmartStream software, the driver, the scanner, or the printer touchscreen
- Bi-directional communication between the printer and the folder enables reliable operation
- Monitor folder status from the printer or the HP SmartStream software; the job queue halts when the folder has stopped

## High speed

- The HP PageWide XL Folder is designed to match the breakthrough productivity of HP PageWide XL printers
- Stack up to 150 E/A0-size folded package standards<sup>1</sup>

## Versatility

- Opt for the standard HP PageWide XL Folder or for the HP PageWide XL Folder with Tab Applicator if you need to apply reinforcement strips to your documents
- Fold up to 36 in (914 mm) in width and up to 8.2 ft (2.5 m) in length for fully folded packages; fan fold up to 19.7 ft (6 m) in length; add the HP PageWide XL Folder Upgrade Kit for Long Plots for unlimited length fan folding
- Choose from pre-defined folding programs or create your custom folding styles
- Supports DIN, AFNOR, ANSI, and US folding standards

For more information, please visit [hp.com/go/pagewidexlsolutions](http://hp.com/go/pagewidexlsolutions)

<sup>1</sup>Measured on an HP PageWide XL Folder.

# Technical specifications


## HP PageWide XL Folder

<b>Performance</b>	Speed	9 in/sec (23 cm/sec)	
<b>Paper handling</b>	Paper feed	Automatic or manual	
	Paper width	11 to 36 in (297 to 914 mm)	
	Paper length (fan fold)	Up to 19.7 ft (6,000 mm) Unlimited with the HP PageWide XL Folder Upgrade Kit for Long Plots	
	Paper length (cross fold)	Up to 8.2 ft (2,500 mm)	
	Paper weight (folding)	20 to 24 lb (75 to 90 g/m <sup>2</sup> )	
	Paper type (folding)	Plain paper, bond paper	
	Output delivery	Standard belt, capacity for up to 150 E/A0-size folded packages	
	Stacking on folder	Up to 10 pages, up to E/A0-size	
	<b>Folding</b>	Fan fold	6.7 to 12 in (increments of 0.03 in) (170 to 305 mm (increments of 1 mm)) Binding margin adjustable 0 to 1.57 in (increments of 0.03 in) (0 to 40 mm (increments of 1 mm))
		Cross fold	Z-style; panel length 8.3 to 12.2 in (210 mm to 310 mm)
		Book fold	8.5 x 11 in (216 mm x 279.4 mm)
		Folding programs	DIN B 210x297 DIN C 210x297 DIN B 210x305 DIN B 210x310 Fan Fold only DIN A 190/20x297 DIN 185/25x297 INVERSE DIN 210x297 AFNOR 297x210 ANSI 8.5x11 ANSI 7.5+1x11 ARCH 9.0x12 Mailer 7.5x10 Fan Fold only 9.0
<b>Dimensions</b>	Dimensions with packaging	72 x 42 x 55 in (1850 x 1070 x 1420 mm)	
	Dimensions without packaging	70 x 63 x 48 in (1800 x 1620 x 1220 mm)	
<b>Weight</b>	Weight with packaging	804 lb (365 kg)	
	Weight without packaging	683 lb (310 kg)	
<b>Environmental</b>	Operating temperature	50 to 104°F (10 to 40°C)	
	Recommended temperature	59 to 95°F (15 to 35°C)	
	Operating humidity	20% to 80% RH, depending on media type	
<b>Acoustic<sup>2</sup></b>	Sound pressure	63 dB(A) (printing), 35 dB(A) (ready), < 25 dB(A) (sleep)	
	Sound power	8 B(A) (printing), 5.1 B(A) (ready), < 4.2 B(A) (sleep)	
<b>Power</b>	Power requirements	300 W (typical)	
	Requirements	Input voltage (auto ranging) 100-120/200-240 ± 10% VAC, 50/60 ± 3 Hz, 10/5 A	
<b>Certifications</b>	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada; EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC)	
	Environmental	CE marking (including RoHS, WEEE, REACH)	
<b>Ordering</b>	Product number	K5H75A	
	Options	M0V04A HP PageWide XL Folder Upgrade Kit for Long Plots	
	Supported printers	HP PageWide XL 8000 Printer, HP PageWide XL 6000 Printer series, HP PageWide XL 5100 Printer series, HP PageWide XL 4000/4500 Printer series	
<b>Warranty</b>	90 days		


<sup>2</sup>Acoustics based on folding solution with the HP PageWide XL 8000 Printer.

## HP PageWide XL Folder with Tab Applicator


<b>Performance</b>	Speed	9 in/sec (23 cm/sec)	
<b>Paper handling</b>	Paper feed	Automatic or manual	
	Paper width	11 to 36 in (297 to 914 mm)	
	Paper length (fan fold)	Up to 19.7 ft (6,000 mm) Unlimited with the HP PageWide XL Folder Upgrade Kit for Long Plots	
	Paper length (cross fold)	Up to 8.2 ft (2,500 mm)	
	Paper weight (folding)	20 to 24 lb (75 to 90 g/m <sup>2</sup> )	
	Paper type (folding)	Plain paper, bond paper	
	Output delivery	Standard belt, capacity for up to 150 E/A0-size folded packages	
	Stacking on folder	Up to 10 pages, up to E/A0-size	
	<b>Folding</b>	Fan fold	6.7 to 12 in (increments of 0.03 in) (170 to 305 mm (increments of 1 mm)) Binding margin adjustable 0 to 1.57 in (increments of 0.03 in) (0 to 40 mm (increments of 1 mm))
		Cross fold	Z-style; panel length 8.3 to 12.2 in (210 mm to 310 mm)
		Book fold	8.5 x 11 in (216 mm x 279.4 mm)
		Folding programs	DIN B 210x297 DIN C 210x297 DIN B 210x305 DIN B 210x310 Fan Fold only DIN B 210 TAB DIN B 198 TAB DIN A 190/20x297 DIN 185/25x297 INVERSE DIN 210x297 AFNOR 297x210 ANSI 8.5x11 ANSI 7.5+1x11 ARCH 9.0x12 Mailer 7.5x10 Fan Fold only 9.0
<b>Dimensions</b>	Dimensions with packaging	85.8 x 42 x 55 in (2180 x 1070 x 1420 mm)	
	Dimensions without packaging	82 x 63 x 48 in (2100 x 1620 x 1220 mm)	
<b>Weight</b>	Weight with packaging	903 lb (410 kg)	
	Weight without packaging	793 lb (360 kg)	
<b>Environmental</b>	Operating temperature	50 to 104°F (10 to 40°C)	
	Recommended temperature	59 to 95°F (15 to 35°C)	
	Operating humidity	20% to 80% RH, depending on media type	
<b>Acoustic<sup>2</sup></b>	Sound pressure	63 dB(A) (printing), 35 dB(A) (ready), < 25 dB(A) (sleep)	
	Sound power	8 B(A) (printing), 5.1 B(A) (ready), < 4.2 B(A) (sleep)	
<b>Power</b>	Power requirements	300 W (typical)	
	Requirements	Input voltage (auto ranging) 100-120/200-240 ± 10% VAC, 50/60 ± 3 Hz, 10/5 A	
<b>Certifications</b>	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada; EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC)	
	Environmental	CE marking (including RoHS, WEEE, REACH)	
<b>Ordering</b>	Product number	L3M58A	
	Options	M0V04A HP PageWide XL Folder Upgrade Kit for Long Plots	
	Supported printers	HP PageWide XL 8000 Printer, HP PageWide XL 6000 Printer series, HP PageWide XL 5100 Printer series, HP PageWide XL 4000/4500 Printer series	
<b>Warranty</b>	90 days		



Standard folding packages



Standard folding packages with reinforcement stripe



Standard folding packages with binding edge