

HUAWEI FusionServer RH2288 V3



Copyright © Huawei Technologies Co., Ltd. 2017. All rights reserved.
No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice
HUAWEI, and are trademarks or registered trademarks of Huawei Technologies Co., Ltd.
Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer
The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.
Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808
Version No.: M3-035260-20170418-C-3.0
www.huawei.com

HUAWEI TECHNOLOGIES CO., LTD.



HUAWEI FusionServer

RH2288 V3

The HUAWEI FusionServer RH2288 V3 (RH2288 V3 for short) is a new-generation 2U dual-socket rack server. It provides flexible resource expansion capabilities as well as high computing performance. It is an ideal choice for Internet, big data, cloud computing, and enterprise key applications.

- Provides large local storage space to quickly respond to fast data increase.
- Ensures high energy efficiency by using intelligent fine-grained power control technologies.
- Provides a LED digital management panel to open the era of digital management.

Flexible configuration and expansion of local storage

- Provides a maximum of sixteen 3.5-inch hard disks or twenty-eight 2.5-inch hard disks.
- Offers a wide range of hard disk enclosures and RAID controllers, allowing flexible configuration on demand.
- Cope with big data challenges by supporting the latest 12G SAS, which provides 1x higher bandwidth than the 6G SAS.

High performance allows rapid response to business growth

- Supports up to two Intel® Xeon® E5-2600 v3/v4 processors. Each processor supports a maximum of 18 cores and provides two 9.6 GT/s QuickPath Interconnect (QPI) links between processors.
- Supports up to sixteen 2400 MT/s DDR4 DIMMs to provide a maximum memory capacity of 1 TB.
- Provides up to six PCIe slots, offering the space for I/O extension.
- Provides I/O performance surpassing traditional hard disks when used with PCIe SSD cards and NVMe SSD disks.

Intelligent power control increases energy efficiency

- Uses 80 Plus Platinum power supply units (PSUs), meeting Energy Star specifications.
- Uses the dynamic energy management technology (DEMT) to adjust server operating status dynamically and limit the power consumption to an optimal level.
- Uses power capping to allocate cooling and power supply resources on demand, and increase resource utilization and deployment density without affecting services.
- Supports high-voltage DC power supplies, preventing conversion between AC and DC power supplies and minimizing the power loss in power conversion.
- Uses proportion integration differentiation (PID) to control heat dissipation and speed adjustment policies, implements stepless speed regulation and on-demand allocation of heat dissipation resources, minimizing power consumption and noise.

Efficient management and maintenance

- Providing digital LED fault diagnostics panel, so the device management more accurate and more convenient.
- Provides uMate management tool and FDM2.0 fault diagnosis management function, to improve management and troubleshooting efficiency.
- Uses an independent iBMC module to implement Serial over LAN (SOL), remote KVM, and functions such as remote startup and shutdown of the server.



RH2288 V3
(8 hard disks)



RH2288 V3
(12 hard disks)



RH2288 V3
(25 hard disks)

RH2288 V3	
Form factor	2U rack server
Number of processors	1 or 2
Processor model	Intel® Xeon® E5-2600 v3/v4 series processor
Number of memory slots	16 slots for DDR4 RDIMMs or LRDIMMs
Maximum local storage	Supports the following hard disk configurations: <ul style="list-style-type: none">Eight front 2.5-inch SSDs or SAS or SATA HDDsTwelve front 3.5-inch SAS or SATA HDDs and two or four rear 2.5-inch or 3.5-inch SSDs or SAS or SATA HDDsTwelve front 3.5-inch SAS or SATA HDDs (NVMe model supports four NVMe SSD disks) and two rear 2.5-inch or 3.5-inch SSDs or SAS or SATA HDDsTwenty-four front 2.5-inch SAS or SATA HDDsTwenty-five front 2.5-inch SSDs or SAS or SATA HDDs and two or three rear 2.5-inch SSDs or SAS or SATA HDDs Supports built-in Flash: <ul style="list-style-type: none">Two SD cards
RAID	<ul style="list-style-type: none">Supports RAID 0, 1, 10, 5, 50, 6, and 60Uses a supercapacitor to protect RAID cache data from power failuresSupports RAID state migration, configuration memory, self-diagnosis, and web-based remote configuration
Network ports	Supports two or four GE ports or two 10GE ports or two 56G FDR IB ports
PCIe expansion	Supports a maximum of 6 PCIe slots
Fan	Hot-swappable fan modules in N+1 redundancy
Power supply	2 hot-swappable power supplies in 1+1 redundancy
Management	The on-board iBMC module supports Intelligent Platform Management Interface (IPMI), SOL, KVM over IP, and virtual media, and provides a 1 Gbit/s RJ45 management network port supporting NC-SI.
Supported OSs	CentOS Citrix XenServer Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Operating temperature	5°C to 45°C (41°F to 113°F)
Certification	CE, UL, FCC, CCC, and RoHS
Installation suite	Guide rails Holding rails and cable management arm (optional)
Dimensions (W x D x H)	RH2288 V3 with 3.5-inch hard disks: 447 mm x 748 mm x 86.1 mm (17.60 in. x 29.45 in. x 3.39 in.) RH2288 V3 with 2.5-inch hard disks: 447 mm x 708 mm x 86.1 mm (17.60 in. x 27.84 in. x 3.39 in.)