



10 Gigabit Copper SFP+ Transceiver Module

10GBase-T (RJ45) Port, 30 m (98 ft.), up to 10 Gbps Data-Transfer Rate with Cat6a Cabling

Part No.: **508179**

10 Gigabit Copper SFP+ Transceiver Module

The new line of Intellinet Enhanced Small Form Factor Pluggable (SFP+) Transceivers provides customers with a combination of high-performance and affordability. The metal housing of these transceiver modules reduces electromagnetic interference and increases their durability.

10 Gigabit Ethernet connections via Copper RJ45 Cabling

The Intellinet 10 Gigabit Copper SFP+ Transceiver Module provides an impressive data transfer speed of up to 10 Gigabits per second when using Cat6a (augmented Cat6 cabling with improved specifications). This SFP+ copper transceiver is an extremely versatile and ultra-high performing connection point for your server or workstation.

State-of-the-Art NBASE-T™ Technology

With full support of the IEEE 802.3bz standard, the Intellinet 10 Gigabit Copper SFP+ Transceiver Module supports Gigabit speeds using Cat6 and Cat5e network cabling. The former transfers and receives data at up to 5 Gbps whereas the latter still manages an impressive 2.5 Gbps.

Compatibility

Compatibility in your network is essential. The Intellinet SFP+ Transceiver Module can be used with any Intellinet SFP+ equipped network switch or any other MSA-compliant SFP+ enabled switch. And since the Intellinet SFP+ transceiver module is set to broadcast the vendor pn MA-SFP-10GB-SR, compatibility to your Cisco gear is provided.

Hot-Pluggable

The Intellinet 10 Gigabit Fiber SFP+ Optical Transceiver Module is fully hot-pluggable, allowing you to install the module without rebooting your network switch for uninterrupted network traffic.

Features:

- Provides cost-effective and reliable 10 Gigabit Ethernet connections over copper
- Up to 10 Gbps data-transfer rate with Cat6a network cable
- Up to 5 Gbps with Cat6 and 2.5 Gbps with Cat5e network cable
- Adds a 10 Gigabit Ethernet copper connection to a network switch or media converter that supports SFP+ transceivers
- RJ45 port with Auto MDI/MDI-X support

- Compatible with the Cisco Meraki MA-SFP-10GB-SR transceiver
- Fits any Intellinet Gigabit Ethernet switch with SFP+ module slots or any MSA-compliant SFP+ port
- Compliant with the SFP Multi-Source Agreement (MSA)
- Maximum transfer distance of 30 m (98 ft.) at 10 Gbps over Cat6a network cable
- Maximum transfer distance of 50 m (164 ft.) at 5 Gbps over Cat6 cable and at 2.5 Gbps over Cat5e cable
- Maximum transfer distance of 100 m (328 ft.) at 100 Mbps over Cat5e network cable
- Low EMI due to fully metallic housing
- SFP+ standard form factor
- Supports hot-plugging
- Three-Year Warranty

Specifications:

Standards

- IEEE 802.3ab (1000Base-T Gigabit Ethernet)
- IEEE 802.3an (10 Gigabit Ethernet over Cat6a Twisted-pair Copper)
- IEEE 802.3bz (2.5 Gbps over Cat5, 5 Gbps over Cat6 Twisted-pair Copper)

General

- Media support:
 - 1000Base-T Cat5e or higher UTP/STP RJ45
 - 2.5GBASE-T Cat5e or higher UTP/STP RJ45
 - 5GBASE-T Cat6 or higher UTP/STP RJ45
 - 10GBASE-T Cat6a or higher UTP/STP RJ45
- Connector: RJ45 SFP port
- Distance: 30 m (98 ft.) at 10 Gbps over Cat6a
- Design: SFP+ (enhanced small form-factor pluggable), 11.1 Gbps max, 10.3 Gbps typical
- Certifications: FCC Class A, CE Mark, IEC-60825, RoHS

Power

- Power requirement: 3.3 V
- Power consumption: 3.0 W (maximum)

Environmental

- Dimensions: 68 (L) x 13.7 (W) x 13.6 (H) [mm] / 2.68 (L) x 0.54 (W) x 0.54 (H) [in]
- Weight: 25 g (0.9 oz.)
- Operating temperature: 0 – 60°C (32 – 140°F)
- Storage temperature: -40 – 85°C (-40 – 185°F)
- Operating humidity: 5 – 95% RH, non-condensing

Package Contents

- 10 Gigabit Copper SFP+ Transceiver Module

