

Product datasheet

Specifications



17" Rack LCD Console with Integrated 16 Port Analog KVM Switch

AP5816

EAN Code: 0731304278818

Overview

Presentation	The Rack LCD Console with Integrated KVM Switch combines the functionality of Rack LCD Console and Analog KVM switches in one convenient package optimizing U space in the rack environment, eliminating cable clutter, and offering a value of two products functionality in one package. Keyboard is a US English keyboard layout.
--------------	--

Main

Product or component type	Console
Main Input Voltage	120 V 240 V
Network frequency	50/60 Hz
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Number of cables	1
Cable length	1.82 m
Provided equipment	USB KVM cable Single user rack mount kit PS2 KVM cable NEMA 5-15 power cord Installation guide Firmware upgrade cable Documentation CD C13-C14 power cord

Complementary

Mounting location	Front
mounting mode	Rack-mounted
Minimum mounting depth	680 mm
Maximum mounting depth	1049.8 mm
Display type	LCD display
Trackball type	PS/2 touchpad USB mouse
Colour	Black
Height	43 mm
Width	483 mm
Depth	614 mm
Net weight	14 kg
Display colour	16 colours

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Display size	337.9 (H) x 270.3 (V) 17 inch
--------------	----------------------------------

Environmental

Product certifications	cUL listed C-Tick CE Industry Canada KCC UL listed VDE TAA compliance
Standards	EN 60950 FCC part 15 class A IEC 60950
Ambient air temperature for operation	0...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13 cm
Package 1 Width	83 cm
Package 1 Length	66.5 cm
Package 1 Weight	20.14 kg

Logistical informations

Country of origin	TW
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	49 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	47 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



