ThinkPad T580 Platform Specifications

Processor For For For Base Max Turbo Case Throspo Processor Case Throspo Processor Case Throspo Processor Case Throspo Processor Case Cas	Processor	7th Generation Intel® Core™ i5 Processor	Dimensions WxDxH: 14.40" x 9.95" x 0.79-0.80"; 365.8mm x 252.8mm x 19.95-20.2mm
Fig. 1900 1			Weight Integrated model: starting at 4.29 lb / 1.95 kg; Discrete model: starting at 4.39 lb / 1.99 kg
or 8th Generation Intel Core is /i of sease Max Mutubo Processor Processor Processor Processor Processor Processor		i5-7200U 2 2.5 GHz 3.1 GHz 3MB DDR4 3133 Intel HD Graphics	S Case material Display cover: Glass-Fiber Reinforced Plastic (PPS);
Processor Incide Frequency Frequen		or 8th Generation Intel Core i5 / i7 Processor	
Intel UHD Graphics 620 or Intel UHD Graphics 620 intel UHD Graphics 620 or Intel UHD Graphics 620 or Intel UHD Graphics 620 intel UHD Graphics 620 intel UHD Graphics 620 in			Media reader 4-in-1 reader (MMC, SD, SDHC, SDXC) Ports Two USB 3.1 Gen 1 (one Always On), USB 3.1 Type-C Gen 1,
Camera (optional) Camera (optional (optional) Camera (option		1.7 GHz 3.6 GHz 6MB 1.8 GHz 4.0 GHz 8MB DDR4-2400 1.8 GHz 4.0 GHz 8MB DDR4-2400 1.8 GHz 620 1.8 GH	nano-SIM card slot (WWAN models), headphone / microphone combo jack, optional smart card reader, 4-in-1 reader (MMC, SD, SDHC, SDXC), side docking connector, security keyhole
Intel HD Graphics 620 or Intel UHD Graphics 620 in processor and NVDIAP GeForce* MX150, 2GB BDDR5 memory; supports external digital monitor via HDMI or USB Type-C; supports three independent displays: Max resolution: 4096x2304 @60Hz (USB Type-C); 4096x2160 @30Hz (HDMI) Chipset Intel SoC (System on Chip) platform 32GB max / 2400MHz DDP4, dual-channel capable, two DDR4 SO-DIMM sockets 'System clocks down for processors with lower memory controller Some: 15.6° (39smm) FHD (1920x1080), anti-glare, LED backlight, IPS, 200 nits, 163 sepect ratio, 700° intelligence, LED backlight, IPS, 200 nits, 163 sepect ratio, 1000° to contrast ratio, 72° welving angle Null-touch (opt) On-cell touch, supports 10-finger gesture (FHD only) Storage System has one HDD is for one MZ 2280 sid exclusively for storage Some: SDS / SATA 6.0Gb/s, 2.5° wide, 7mm high, Active Protection System™ Some: 120GB MZ 25D SOX 25.1° (SGB), Sox	Graphics	Intel HD Graphics 620 or Intel UHD Graphics 620 in processor only or	(optional) USB-C to DP: Lenovo USB-C to DisplayPort Adapter
Memory 32GB max i 2400MHz DDŘ4, dual-channel capable, two DDR4 SO-DIMM sockets *System clocks down for processors with lower memory controller System clocks down for processors with lower memory controller Some: 15.6" (396mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle Some: 15.6" (396mm) UHD (3840x2160), anti-glare, LED backlight, IPS, 300 nits, 16:9 aspect ratio, 1000:1 contrast ratio, 72% gamut, 170° viewing angle Multi-touch (opt) On-cell touch, supports 10-finger gesture (FHD only) Storage System has one HDD slot or one M.2 2280 slot exclusively for storage Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4ctive Protection System™ Some: S	- γ	Intel HD Graphics 620 or Intel UHD Graphics 620 in processor and NVIDIA® GeForce® MX150, 2GB GDDR5 memory; supports external digital monitor via HDMI or USB Type-C; supports three independent displays;	 HD720p camera with ThinkShutter camera privacy, fixed focus IR camera and HD720p camera, fixed focus Audio support HD Audio, Realtek® ALC3287 codec, Dolby® Audio™ Premium / stereo speakers,
Display Some: 15.6" (396mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle some: 15.6" (396mm) UHD (3940x2160), anti-glare, LED backlight, IPS, 300 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle some: 15.6" (396mm) UHD (3940x2160), anti-glare, LED backlight, IPS, 300 nits, 16:9 aspect ratio, 1000:1 contrast ratio, 170° viewing angle some: 15.6" (396mm) UHD (3940x2160), anti-glare, LED backlight, IPS, 300 nits, 16:9 aspect ratio, 1000:1 contrast ratio, 72% gamut, 170° viewing angle single per control touch, supports 10-finger gesture (FHD only) None: Intell Ethernet Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD) Some: 128GB Mz 2 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s, in WWAN slot as 2nd Storage, mutually exclusive with WWAN Some: 16GB Intel Optane™ memory, PCIe NVMe, PCIe 3.0 x 2, 16Gb/s, in WWAN slot as storage cache for HDD, mutually exclusive with WWAN None: 16GB Intel Optane™ memory, PCIe NVMe, PCIe 3.0 x 2, 16Gb/s, in WWAN slot as storage cache for HDD, mutually exclusive with WWAN None: 16GB Intel Ethernet Connection 1219-V (Jacksonville) VPro model: Intel Ethernet Connection 1219-V (Jacksonville) VPro model: Intel Ethernet Connection 1219-LM (Jacksonville) VPro model: Intel Ethernet Connection 1219-LM (Jacksonville) None of the following, configurable by model: None of the following, co		32GB max / 2400MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets	UltraNav™ TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad
Multi-touch (opt) On-cell touch, supports 10-finger gesture (FHD only) Storage System has one HDD slot or one M.2 2280 slot exclusively for storage Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD) Some: 1286B M.2 SSD / PCle NVMe, PCle 3.0 x4, 32Gb/s Some: 1286B M.2 SSD / PCle NVMe, PCle 3.0 x2, 16Gb/s, in WWAN slot as 2nd Storage, mutually exclusive with WWAN Some: 16GB Intel Optane™ memory, PCle NVMe, PCle 3.0 x 2, 16Gb/s, in WWAN slot as storage cache for HDD, mutually exclusive with WWAN Optical None Ethernet Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) vPro model: Intel Ethernet Connection I219-LM (Jacksonville) WLAN + Intel 8265ac card supports BT4.2 but is limited to BT4.1 by Windows OS WWAN (optional) Near Field Communicătion Dotical Intel Communicătion Optional integrated Li-lon 32Wh, 48Wh, or 72Wh battery and external Li-lon 24Wh, 48Wh, or 72Wh battery Max battery life (Mobile Mark® 2014) Max battery life (Mobile Subtractive Windows 10 Pro 64 Limited warranty One of the following, configurable by model: 1 - year depot repair service 3 - year/1-yr battery limited onsite service 4 - Intel 24Mh 48Wh 7260 (Fibocom L850-GL), M.2 card (EMEA only) Intel Stanta Li-lon 24Wh, 48Wh	Display	Some: 15.6" (396mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle Some: 15.6" (396mm) UHD (3840x2160), anti-glare, LED backlight, IPS, 300 nits,	Security chip Discrete TPM 2.0, TCG Certified vPro (optional) Intel vPro Technology Fingerprint reader Optional: Touch style match on chip fingerprint reader on the palm rest,
Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high, 4.32Gb/s Some: M2 SSD / PCle NVMe, PCle 3.0 x 2, 16Gb/s, in WWAN slot as 2nd Storage, mutually exclusive with WWAN Some: 128GB M.2 SSD / PCle NVMe, PCle 3.0 x 2, 16Gb/s, in WWAN slot as 2nd Storage, mutually exclusive with WWAN None Optical Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) VPro model: Intel Ethernet Connection I219-LM (Jacksonville) VPro model: Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card * Intel 8265ac card supports BT4.2 but is limited to BT4.1 by Windows OS WWAN (optional) None WWAN (optional) None	Multi-touch (opt)	On-cell touch, supports 10-finger gesture (FHD only)	NFC (optional) Near Field Communication
Optical None Ethernet Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) WLAN + Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card Bluetooth™ Intel Substance Ac ard supports BT4.2 but is limited to BT4.1 by Windows OS WWAN (optional) WWAN (optional) One of the following, configurable by model: • 1-year depot repair service • 3-year/1-yr battery depot repair service • 3-year/1-yr battery limited onsite service Mil-Spec test MIL-STD-810G military certification Environment Emired warranty One of the following, configurable by model: • 1-year depot repair service • 3-year/1-yr battery limited onsite service Mil-Spec test MIL-STD-810G military certification EPEAT™ Gold; ENERGY STAR® 6.1; RoHS-compliant Environment	Storage	Some:HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™Some:SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD)Some:M.2 SSD / PCIe NVMe, PCIe 3.0 x4, 32Gb/sSome:128GB M.2 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s, in WWAN slot as 2nd Storage, mutually exclusive with WWANSome:16GB Intel Optane™ memory, PCIe NVMe, PCIe 3.0 x 2, 16Gb/s,	external Li-Ion 24Wh, 48Wh, or 72Wh battery Max battery life (MobileMark® 2014) Max battery life 24Wh 48Wh 72Wh 32Wh + 24Wh 32Wh + 48Wh 32Wh + 72Wh Max battery life 5.8 hr 12.5 hr 18.1 hr 13.8 hr 20.3 hr 26.1 hr * Battery life varies significantly with settings, usage, & other factors 45W or 65W USB Type-C AC adapter
Ethernet Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) WLAN + Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card * Intel 8265ac card supports BT4.2 but is limited to BT4.1 by Windows OS WWAN (optional) WWAN (optional) One of the following, configurable by model: • Integrated Mobile Broadband 4G LTE, Intel XMM™ 7262 (Fibocom L830-EB), M.2 card (EMEA only) • Integrated Mobile Broadband 4G LTE-Intel XMM™ 7360 (Fibocom L850-GL), M.2 card	Optical		
WLAN + Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card **Intel 8265ac card supports BT4.2 but is limited to BT4.1 by Windows OS WWAN (optional) **One of the following, configurable by model: **Integrated Mobile Broadband 4G LTE, Intel XMM™ 7262 (Fibocom L830-EB), M.2 card (EMEA only) **Integrated Mobile Broadband 4G LTE-A, Intel XMM™ 7360 (Fibocom L850-GL), M.2 card **Intel NMM™ 7360 (Fibocom L850-GL), M.2 card **Intel NMM™ 7360 (Fibocom L850-GL), M.2 card **3-year/1-yr battery limited onsite service **MIL-STD-810G military certification **EPEAT™ Gold; ENERGY STAR® 6.1; RoHS-compliant		Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville)	1-year depot repair service
WWAN (optional) One of the following, configurable by model: • Integrated Mobile Broadband 4G LTE, Intel XMM™ 7262 (Fibocom L830-EB), M.2 card (EMEA only) • Integrated Mobile Broadband 4G LTE-A, Intel XMM™ 7360 (Fibocom L850-GL), M.2 card			3-year/1-yr battery limited onsite service
	WWAN (optional)	 Integrated Mobile Broadband 4G LTE, Intel XMM™ 7262 (Fibocom L830-EB), M.2 card (EMEA only) Integrated Mobile Broadband 4G LTE-A, 	-
	SIM card (opt)	Nano-SIM card slot, optional Verizon LTE (US) SIM card	Lenovo