

Philips LCD monitor

V Line

20 (Viewable 19.5" / 49.5 cm)

203V5LSB2

Great LED images in vivid colors

Enjoy vivid LED pictures on this Philips display. Essential features like SmartContrast that ensures rich bright images makes it a great choice!

Vivid pictures every time

• LED technology for vivid colors

Great choice

- Compact design saves space
- Mercury Free eco-friendly display
- · VESA mount allows for flexibility



Highlights

brightness across the screen.

Mercury Free

disposal.

White LED's are solid state devices which light up to

full, consistent brightness faster saving startup time.

LED's are free from mercury content which allows

for eco-friendly recycling and disposal process. LED's

allow for better dimming control of LCD backlight,

resulting in super high contrast ratio. It also gives

superior color reproduction thanks to consistent

Philips monitors with LED backlighting are free of

substances, which affects humans and animals. This

Mercury content, one of the most toxic natural

reduces the environmental impact of the display throughout its life-cycle, from manufacturing to

LED technology

Specifications

Picture/Display

- LCD panel type: TFT-LCD
- · Backlight type: W-LED system
- Panel Size: 19.5 inch / 49.5 cm
- Effective viewing area: 433.9 (H) x 236.3 (V)
- Aspect ratio: 16:9
- Optimum resolution: 1600 x 900 @ 60 Hz
- Response time (typical): 5 ms
- Brightness: 200 cd/m²
- Contrast ratio (typical): 600:1
- Pixel pitch: 0.26 x 0.26 mm
- Viewing angle: 90° (H) / 65° (V), @ C/R > 10
- Display colors: 16.7 M
- Scanning Frequency: 30 -83 kHz (H) / 56 -75 Hz (V)
- sRGB

Connectivity

- Signal Input: VGA (Analog)
- Sync Input: Separate Sync, Sync on Green

Convenience

- User convenience: Power On/Off
- OSD Languages: Brazil Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukranian
- Other convenience: Kensington lock, VESA mount (100×100mm)
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 7, Windows 8

Stand

• Tilt: -3/10 degree

Power

 On mode: 14.52 W (typ.) (EnergyStar 6.0 test method)







- Standby mode: 0.5 W (typ.)
- Off mode: 0.5 W (typ.)
- Power LED indicator: Operation White, Standby mode- White (blinking)
- Power supply: Built-in, 100-240VAC, 50-60Hz

Dimensions

- Product with stand (mm): $465 \times 345 \times 170 \text{ mm}$
- Product without stand (mm): 465 x 285 x 48 mm
- Packaging in mm (WxHxD): 503 x 350 x 109 mm

Weight

- Product with stand (kg): 2.33 kg
- Product without stand (kg): 2.03 kg
- Product with packaging (kg): 3.23 kg

Operating conditions

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF: 30,000 hour(s)

Sustainability

- Environmental and energy: EnergyStar 6.0, EPEAT Silver, RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Compliance and standards

 Regulatory Approvals: BSMI, CE Mark, FCC Class B, GOST, SEMKO, TUV/ISO9241-307, cETLus, WEFF

Cabinet

- Color: Black
- Finish: Hairline (front bezel) / Texture (rear cover)



© 2017 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 16505 EAN: 87 12581 72510 5

www.philips.com

PHILIPS