

ThinkCentre M910x Tiny 10N0000C++

Region	Dust Filter
EMEA	None
Machine Type	Keyboard / Mouse
10N0	USB / USB
TopSeller	VESA Mount
TopSeller	VESA Mount
Processor	Stand
Core i7-7700T (4C, 2.9 / 3.8GHz, 8MB)	None
vPro	Power Supply
vPro	135W 88% Adapter
Graphics	Operating System
AMD Radeon RX 460 4GB	Windows 10 Pro 64
Monitor Cable	Warranty
MiniDP to DP	3-year, Onsite
Memory	Global
16GBx1	No
Storage	Ann Date (mm/yy)
512GB SSD M.2 PCIe NVMe	04/17
External Optical / I/O Box	
None	
WLAN + Bluetooth	
Intel 8265 ac, 2x2, vPro + BT4.1	
Optional Rear Ports	
None	
Chassis Intrusion Switch	
Chassis Intrusion Switch	
Kensington Cable Lock	
None	
Speaker	
2Wx1	
Adapter Cage	
Adapter Cage	
Toolless Chassis Screw	
Toolless Chassis Screw	

Dust Filter	None
Keyboard / Mouse	USB / USB
VESA Mount	VESA Mount
Stand	None
Power Supply	135W 88% Adapter
Operating System	Windows 10 Pro 64
Warranty	3-year, Onsite
Global	No

Ann Date (mm/yy)
04/17

Note:

Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2018. All rights reserved.



ThinkCentre M910x Tiny Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron®, Intel Pentium®, or 6/7th Generation Intel Core™ i3 / i5 / i7 Processor											
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics						
	Core i5-6500T	4 / 4	2.5G / 3.1G	6 MB	DDR4-2133	HD 530						
	Core i7-6700T	4 / 8	2.8G / 3.6G	8 MB	DDR4-2133	HD 530						
	Core i5-7500T	4 / 4	2.7G / 3.3G	6 MB	DDR4-2400	HD 630						
	Core i5-7600T	4 / 4	2.8G / 3.7G	6 MB	DDR4-2400	HD 630						
	Core i7-7700T	4 / 8	2.9G / 3.8G	8 MB	DDR4-2400	HD 630						
	Core i5-6500	4 / 4	3.2G / 3.6G	6 MB	DDR4-2133	HD 530						
	Core i7-6700	4 / 8	3.4G / 4.0G	8 MB	DDR4-2133	HD 530						
	Core i5-7500	4 / 4	3.4G / 3.8G	6 MB	DDR4-2400	HD 630						
	Core i5-7600	4 / 4	3.5G / 4.1G	6 MB	DDR4-2400	HD 630						
	Core i7-7700	4 / 8	3.6G / 4.2G	8 MB	DDR4-2400	HD 630						
Memory	32GB max, DDR4-2400*, two 260-pin SO-DIMM sockets, non-ECC, dual-channel capable											
	* System automatically clocks down for the processors with lower memory controller											
Storage	Some: Hard Drive* / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm, APS Some: Solid State Drive (SSD)* / SATA 6.0Gb/s, 2.5" (* 2.5" HDD/SSD and RX 460 graphics are mutually exclusive)											
	Some: M.2 SSD (support up to two M.2 SSD) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s, RAID 0/1 support (RAID preset only available via special bid model)											
Optical	Some: Intel Optane™ Memory (models with 7th gen Core processor), M.2 Some: DVD-ROM, slim (9.0mm), via USB external ODD box											
Onboard SATA Media reader	Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box One onboard SATA 6.0Gb/s connector											
Graphics	Intel HD Graphics 510/530/610/630 in processor, uses main memory, DirectX® 12, two DisplayPort™, one optional video port (HDMI, VGA, 3rd DP, or USB 3.1 Type-C with DisplayPort Alternate Mode), up to 3 independent displays; Max resolution: 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz; 4096x2160 (HDMI)@24Hz; 1920x1200 (VGA)@60Hz Some: AMD Radeon™ RX 460, DirectX 12, 4GB, PCIe 3.0 x8 adapter (low profile), four mini DisplayPort, 35 watts (TDP), up to 4 independent displays, works along with 2 onboard DisplayPort to support up to 6 independent displays; Max resolution: 5120x2880 @60Hz (up to 2 mini DisplayPort); 4096x2160 @60Hz (up to 4 mini DisplayPort)											
Monitor cable	Optional DP to VGA, DP to DVI-D, DP to dual DP, mini DP to DP, or DP to HDMI 1.4											
Chipset	Intel Q270 Chipset											
Front ports	Two USB 3.1 Gen1 (one is Always On and fast charge), one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)											
Rear ports	Four USB 3.1 Gen1 (optional optical box or I/O box occupies one or two specific USB 3.1 Gen1), ethernet (RJ-45), two DisplayPort, two optional ports (not available for the models with RX 460 graphics): Port 1 for [VGA / 3rd DP / HDMI / serial / USB 3.1 Type-C Gen 1 (with DisplayPort Alternate Mode)]; Port 2 for [serial]											
I/O box	Optional external I/O box, extends two USB 2.0, two USB 3.1 Gen1, and one serial on rear, two USB 2.0 on front, via USB cable (occupy 2 specific USB 3.1 G1 of Tiny)											
Audio support	High Definition (HD) Audio, Realtek ALC294 / optional internal speaker (1w or 2w)											
WLAN ¹³	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377A (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.1 combo adapter, 2x2											
Bluetooth™	Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.1 combo adapter, Intel vPro technology support, 2x2 Some: Bluetooth 4.1 wireless, integrated in Wi-Fi + BT combo adapter											
Ethernet Modem	Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN® None											
Manageability												
Security chip	Intel Active Management Technology 11.0 (Intel AMT 11.0); Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection)											
	TPM (Trusted Platform Module) 2.0*, TCG Certified * Downgrade to TPM1.2 for the models with Win10 DG Win7 32 OS											
Security features	• Security slot (in rear for optional Kensington® MicroSaver® cable) • Smart USB protection, allows keyboard/ mouse only, blocks all storage devices • Power-on password • Administrator password											
	• Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch											
Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black											
	Some: Lenovo Traditional Keyboard (USB connector), black											
Mouse	Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black											
	Some: Lenovo Calliope Mouse (USB connector), black											
Mouse	Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black											
Mechanical	Tiny (1L), black color; metal case											
	• Toolless chassis open • Toolless HDD, SSD, memory removal • Optional toolless chassis screw • Optional dust filter											
Dimensions (WxDxH)	M910 Tiny only											
	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm											
	2.91 lb (1.32 kg), vary by config											
Dimensions (WxDxH)	With VESA mount & ODD box											
	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm											
Dimensions (WxDxH)	With VESA mount & I/O box											
	7.42" X 7.30" X 2.62" 188.4mm X 185.38mm X 66.6mm											
Dimensions (WxDxH)	3.66 lb (1.66 kg), vary by config											
VESA mount												
Optional VESA mount bracket kit, supports VESA 75mm and 100mm												
Floor Stand												
Optional system floor stand for vertical orientation												
Power supply												
135 watts AC/DC adapter, autosensing, 88% PSU												
Limited warranty ³												
Some: 1-year or 3-year, depot service / service upgrades available												
Some: 1-year or 3-year, limited onsite service / service upgrades available												
Preload												
Some: Windows® 7 Professional 32/64 Preloaded applications (only some listed)												
rights in Windows 10 Pro 64-bit (not available with 7th Gen Intel processor)												
Some: Windows 10 Pro 64-bit												
Some: Windows 10 Home 64-bit												
• Microsoft Office preloaded; purchase a product key to activate												
- Only for Window 10												
• Lenovo Companion												
• Intel Unite download link (vPro models only)												
- Only for Window 7												
• Lenovo Solution Center												
• Lenovo ThinkVantage Tools												
• Create Recovery Media												
• Adobe® Reader®												
• Cyberlink PowerDVD Create (DVD±RW)												
• Intel Unite (vPro models only)												
Environment												
ENERGY STAR® 6.1, EPEAT™ Gold rating (North America), ErP Lot 3, GREENGUARD®, RoHS-compliant, TUV low noise verified (on some models)												
MIL-SPEC test												
MIL-STD-810G military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)												
Accessories												
For compatible accessories, please go to http://www.lenovoquickpick.com												

See footnotes for more detailed information

© Lenovo (M910x Tiny-Spec) May 2017

ThinkCentre M910x Tiny

Lenovo[™]

