



### HP EliteDesk 800 G3 Desktop Mini Business PC



1. USB Type-C™ charging port
2. USB 3.1 Gen 1 port (5 Gbit/s data speed)
3. USB 3.1 Gen 1 charging port (5 Gbit/s data speed)
4. Headphone connector
5. Universal Audio Jack with CTIA headset support
6. Hard drive activity light
7. Dual-state power button

### Overview

### HP EliteDesk 800 G3 Desktop Mini Business PC




- |                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ol style="list-style-type: none"> <li>1. Antenna cover</li> <li>2. Cover lock switch</li> <li>3. Cable lock slot</li> <li>4. External antenna connector</li> <li>5. Padlock loop</li> <li>6. (2) Dual-Mode DisplayPort™ 1.2 (DP++)</li> </ol> | <ol style="list-style-type: none"> <li>7. Choice of port (DisplayPort™ 1.2, HDMI, VGA, Serial or USB-C™) (USB-C™ option has alt mode DisplayPort™ 1.2 or 15W output)</li> <li>8. (2) USB 3.1 Gen 1 (5 Gbit/s data speed) (black)</li> <li>9. (2) USB 3.1 Gen 1 (5 Gbit/s data speed) (black), allows for wake from S4/S5 with keyboard/mouse when connected and enabled in BIOS</li> <li>10. RJ-45 Network connector</li> <li>11. Power connector</li> </ol> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Not Shown

- Slots (1) internal M.2 2230 connector for optional wireless NIC  
 (1) internal M.2 SSD storage (2230 or 2280 connector)
- Bays (1) 2.5" internal storage drive bay
- VESA Support for VESA 100 mounting system on bottom of PC chassis

### Overview


#### HP EliteDesk 800 G3 Small Form Factor Business PC



1. Slim optical drive (optional)
2. SD 4 Card Reader (optional)
3. USB Type-C™ charging port
4. (2) USB 3.1 Gen 1 ports (5 Gbit/s data speed)
5. USB 2.0 port
6. USB 2.0 (fast charging port)
7. Headphone connector
8. Universal Audio Jack with CTIA headset support
9. Hard drive activity light
10. Dual-state power button

### Overview

### HP EliteDesk 800 G3 Small Form Factor Business PC



- |                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                         |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ol style="list-style-type: none"> <li>1. Audio-in connector</li> <li>2. Optional serial port</li> <li>3. RJ-45 (network) jack</li> <li>4. Power cord connector</li> <li>5. Audio-out connector for powered audio devices</li> </ol> | <ol style="list-style-type: none"> <li>6. Dual-Mode DisplayPort™ 1.2 (DP++) (2)</li> <li>7. Optional port (DisplayPort™ 1.2, HDMI, VGA or USB-C™) (USB-C™ option has alt mode DisplayPort™ 1.2 or 15W output)</li> <li>8. USB 2.0 ports with wake from S4/S5 (2)</li> <li>9. USB 3.1 Gen 1 x ports (4) (5 Gbit/s data speed)</li> </ol> |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**NOTE:** Your model may have additional optional ports available.



**NOTE:** The serial port is no longer standard to the chassis but is available as an option. A second serial port and PS/2 port PCIe combination are available.

#### Not Shown

- Slots** (2) PCI Express x16 graphics connectors; one wired as an x4  
 (2) PCI Express x1 accessory connectors  
 (1) internal M.2 SSD storage (2230 or 2280 connector)  
 (1) internal M.2 WLAN (2230 connector)
- Bays** (1) 2.5" internal storage drive bay  
 (2) 3.5" internal storage drive bay (convertible to 2.5")  
 (1) 9.5mm slim optical drive bay

Standard Features and Configurable Components (availability may vary by country)

### HP EliteDesk 800 G3 Tower Business PC



1. 5.25-inch Half-Height Drive Bay (behind bezel)
2. Slim optical drive (optional)
3. SD 4 Card Reader (optional)
4. Dual-state power button
5. Hard drive activity light
6. Universal Audio Jack with CTIA headset support
7. Headphone connector
8. USB 2.0 port (fast charging port)
9. USB 2.0 port
10. USB 3.1 Gen1 x ports (2)
11. USB Type-C™ charging port

1. Audio-out jack for powered audio devices
2. Dual-Mode DisplayPort™ 1.2 (DP++) (2)
3. Optional port (DisplayPort™ 1.2, HDMI, VGA or USB-C™) (USB-C™ option has alt mode DisplayPort™ 1.2 or 15W output)
4. USB 2.0 ports with wake from S4/S5 (2)
5. USB 3.1 Gen1 x ports (4)
6. Cable lock slot
7. RJ-45 (network) jack
8. Optional serial port
9. Power cord connector
10. Audio-in jack

**NOTE:** Your model may have additional optional ports available.

**NOTE:** The serial port is no longer standard to the chassis but is available as an option. A second serial port and PS/2 port PCIe combination are available.

#### **Not Shown**

**Slots** (2) PCI Express x16 graphics connectors; one wired as a x4  
 (2) PCI Express x1 connectors  
 (1) internal M.2 SSD storage (2230 or 2280 connector)  
 (1) internal M.2 WLAN (2230 connector)

**Bays** (1) 2.5" internal storage drive bay  
 (2) 3.5" internal storage drive bays (convertible to 2.5")  
 (1) 5.25" half-height drive bay  
 (1) 9.5mm slim optical drive bay

Standard Features and Configurable Components (availability may vary by country)

## HP EliteOne 800 G3 All-in-One Business PC (23.8" Touch and Non-Touch)



- 1. Webcam
- 2. Speakers (optional)

### Infrared (IR) webcam (optional)



- 1. Webcam light
- 2. IR light
- 3. Full High Definition (FHD) webcam
- 4. IR webcam
- 5. Rear webcam adjustment wheel
- 6. Digital microphones
- 7. Webcam light
- 8. FHD webcam


### Full High Definition (FHD) webcam (optional)



- 1. Webcam light
- 2. FHD webcam
- 3. Digital microphones

Standard Features and Configurable Components (availability may vary by country)

### HP EliteOne 800 G3 All-in-One Business PC



- |                                                   |                                          |
|---------------------------------------------------|------------------------------------------|
| 1. Optical disc drive (optional)                  | 4. Headphone connector                   |
| 2. Optical disc drive eject button (optional)     | 5. Fingerprint reader (Touch model only) |
| 3. Universal Audio Jack with CTIA headset support |                                          |




#### Bottom components

- |                                                               |                                                    |
|---------------------------------------------------------------|----------------------------------------------------|
| 1. USB 3.1 Gen 1 Type-A port (5 Gbit/s data speed)            | 4. USB 3.1 Type-C Gen 1 port (5 Gbit/s data speed) |
| 2. USB 3.1 Gen 1 Type-A (charging) port (5 Gbit/s data speed) | 5. Hard drive activity LED                         |
| 3. SD card reader 4.0 (optional)                              | 6. Dual-state power button                         |

Standard Features and Configurable Components (availability may vary by country)

### HP EliteOne 800 G3 All-in-One Business PC



#### REAR/PORTS (BEHIND SECURITY COVER)

- |    |                                                      |    |                                                      |
|----|------------------------------------------------------|----|------------------------------------------------------|
| 1. | Dual-Mode DisplayPort™ 1.2 (DP++)                    | 5. | RJ-45 (network) jack                                 |
| 2. | HDMI connector                                       | 6. | USB 3.1 Gen 1 Type-A ports (2) (5 Gbit/s data speed) |
| 3. | USB 3.1 Gen 1 Type-A ports (2) (5 Gbit/s data speed) | 7. | Audio line-out connector                             |
| 4. | Power connector                                      | 8. | Security lock slot                                   |

#### **Not Shown**

- Slots (1) internal M.2 PCIe x1 connector for optional wireless NIC  
(2) internal M.2 PCIe x4 connector for optional Turbo Drive G2 SSD
- Bays (1) 2.5" internal storage drive bay
- VESA Support for VESA 100 mounting system on bottom of PC chassis\*  
\*Mounting hardware sold separately (see [Accessories](#) section).



Standard Features and Configurable Components (availability may vary by country)

## AT A GLANCE

- Choice of four form factors: Tower, Small Form Factor, Desktop Mini, and All-in-One (touch/non touch)
- New commercial ID on all form factors
- Intel® Q270 chipset supporting Intel® 7th generation Core™ processors and Intel® 6th generation Core™ processors, featuring integrated Intel® HD Graphics and Intel® vPro™ Technology (available with Core i5 and Core i7 processors)<sup>1</sup>
- Processor support up to 65W on SFF, DM and AiO; up to 91W on the 800 G3 TWR
- Support for Windows 10 to Windows 7 Downgrade with Intel® 6th Generation processors
- Intel® HD graphics or optional discrete graphics (except desktop mini)
- Intel® Ethernet Connection I219LM GbE LOM integrated network connection
- DDR4 Synchronous Dynamic Random Access Memory (SDRAM)
- Support for up to three monitors via two standard DisplayPort™ 1.2 connectors and an optional third video port connector which provides the following choices: HDMI, VGA (except AiO models), DisplayPort™ 1.2, or USB Type-C™ with DisplayPort™ 1.2 (see Ports section or pages 1-8 for port availability by platform).
- Configurable 3rd rear I/O video port (HDMI, DisplayPort™ 1.2, VGA, Type-C with DisplayPort™ 1.2) (except AiO)
- Audio by Bang and Olufsen on the 800 G3 All-in-One
- TWR and SFF models can be configured with multiple data drives in a RAID array
- HP Sure Start Gen3
- HP Manageability Integration Kit
- HP WorkWise
- Intel® Unite™ available with EliteDesk 800 G3 DM (35W/65W)
- High efficiency energy saving power supply options
- ENERGY STAR® certified. EPEAT® Gold registered where applicable/supported. Registration may vary by country. See [www.epeat.net](http://www.epeat.net) for registration status by country.
- CCC, CECP and SEPA Certified
- Optimized for Skype for Business; 800 G3 AiO is Skype for Business certified
- TCO Edge for AiO; TCO certified for DM
- PC chassis and all internal components and modules are manufactured with low halogen content<sup>3</sup>
- Arsenic-free
- Dust filter available for all platforms (except EliteDesk 800 G3 DM 65W)
- Protected by HP Services, including limited warranties up to 3-3-3 (terms and conditions vary by country; certain restrictions and exclusions apply); Care Packs available with up to 5 years Next Business Day Onsite Hardware Support

**NOTE:** See important legal disclosures for all listed specs in their respective features sections.

1. Multi-Core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. 64-bit computing system required. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a measurement of higher performance.

2. DisplayPort™ multi-stream monitors 'daisy-chained' together.

3. External power supplies, power cords, cables and peripherals are not low halogen. Service parts obtained after purchase may not be low halogen.

## OPERATING SYSTEMS

### Preinstalled

Windows 10 Pro 64<sup>1</sup>

Windows 10 Pro 64 (National Academic License)<sup>3</sup>

Windows 10 Home 64<sup>1</sup>

Windows 10 Home Single Language 64<sup>1</sup>

Windows 7 Professional 64 (available through downgrade rights from Windows 10 Pro)<sup>2, 4</sup>

Windows 7 Professional 32 (available through downgrade rights from Windows 10 Pro)<sup>2, 4</sup>

### Pre-installed (other)

FreeDOS 2.0

### Standard Features and Configurable Components (availability may vary by country)

NeoKylin Linux® 64

**Web-supported only**

Windows 10 Enterprise 64<sup>1</sup>

Windows 7 Enterprise 64<sup>4</sup>

**NOTE:** In accordance with Microsoft’s support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel® and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.
2. This system is preinstalled with Windows 7 Pro software and also comes with a license and media for Windows 10 Pro software. You may only use one version of the Windows software at a time. Switching between versions will require you to uninstall one version and install the other version. You must back up all data (files, photos, etc.) before uninstalling and installing operating systems to avoid loss of your data.
3. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.
4. Only available with 6<sup>th</sup> generation (Intel) processors.

## CHIPSET

Intel® Q270

## PROCESSORS\*, \*\*

\*NOTE: Your product does not support Windows 8 or Windows 7, In accordance with Microsoft’s support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>

\*\*Note: Multi-Core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. 64-bit computing system required. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel’s numbering is not a measurement of higher performance.

### Intel® 7th Generation Core™ i7 Processors

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
<b>Intel® Core™ i7-7700K Processor</b> 91W Up to 4.5 GHz Max. Turbo Frequency (4.2 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate			<b>X</b>	
<b>Intel® Core™ i7-7700 Processor</b> 65W Up to 4.2 GHz Max. Turbo Frequency (3.6 GHz base frequency) 8 MB cache, 4 cores, 8 threads	<b>X</b> (65W model only)	<b>X</b>	<b>X</b>	<b>X</b>

Standard Features and Configurable Components (availability may vary by country)

<p>Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)</p>				
<p><b>Intel® Core™ i7-7700T Processor</b> 35W Up to 3.8 GHz Max. Turbo Frequency (2.9 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)</p>	<p><b>X</b> <b>(35W model only)</b></p>			

### Intel® 7th Generation Core™ i5 Processors

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
<p><b>Intel® Core™ i5-7500 Processor</b> 65W Up to 3.8 GHz Max. Turbo Frequency (3.4 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)</p>	<p><b>X</b> <b>(65W model only)</b></p>	<p><b>X</b></p>	<p><b>X</b></p>	<p><b>X</b></p>
<p><b>Intel® Core™ i5-7500T Processor</b> 35W Up to 3.3 GHz Max. Turbo Frequency (2.7 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)</p>	<p><b>X</b> <b>(35W model only)</b></p>			
<p><b>Intel® Core™ i5-7600 Processor</b> 65W Up to 4.1 GHz Max. Turbo Frequency (3.5 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)</p>	<p><b>X</b> <b>(65W model only)</b></p>	<p><b>X</b></p>	<p><b>X</b></p>	<p><b>X</b></p>
<p><b>Intel® Core™ i5-7600T Processor</b> 35W Up to 3.7 GHz Max. Turbo Frequency (2.8 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)</p>	<p><b>X</b> <b>(35W model only)</b></p>			

### Intel® 7th Generation Core™ i3 Processors

**DM**                      **SFF**                      **TWR**                      **AiO**

Standard Features and Configurable Components (availability may vary by country)

<b>Intel® Core™ i3-7100 Processor</b> 51W 3.9 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Core™ i3-7100T Processor</b> 35W 3.4 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(35W model only)</b>			
<b>Intel® Core™ i3-7300 Processor</b> 51W 4.0 GHz base frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Core™ i3-7300T Processor</b> 35W 3.5 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(35W model only)</b>			
<b>Intel® Core™ i3-7320 Processor</b> 51W 4.1GHz base frequency 4 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>

### Intel® 7th Generation Pentium® Processors

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
<b>Intel® Pentium® G4560 Processor</b> 54W 3.5 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 610 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Pentium® G4560T Processor</b> 35W 2.9 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 610 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(35W model only)</b>			
<b>Intel® Pentium® G4600 Processor</b> 51W 3.6 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>

Standard Features and Configurable Components (availability may vary by country)

<b>Intel® Pentium® G4600T Processor</b> 35W 3.0 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(35W model only)</b>			
<b>Intel® Pentium® G4620 Processor</b> 51W 3.7 GHz Base Frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 630 Supports DDR4 memory up to 2400 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>

### Intel® 7th Generation Celeron® Processors

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
<b>Intel® Celeron® G3930 Processor</b> 51W 2.9 GHz Base Frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics 610 Supports DDR4 memory up to 2133 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Celeron® G3930T Processor</b> 35W 2.7 GHz Base Frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics 610 Supports DDR4 memory up to 2133 MT/s data rate	<b>X</b> <b>(35W model only)</b>			
<b>Intel® Celeron® G3950 Processor</b> 51W 3.0 GHz Base Frequency 2 MB cache, 2 cores, 2 threads Intel® HD Graphics 610 Supports DDR4 memory up to 2133 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>

### Intel® 6th Generation Core™ i7 Processors

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
<b>Intel® Core™ i7-6700 Processor</b> 65W Up to 4.0 GHz Max. Turbo Frequency (3.4 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Core™ i7-6700T Processor</b> 35W Up to 3.6 GHz Max. Turbo Frequency (2.8 GHz base frequency) 8 MB cache, 4 cores, 8 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)	<b>X</b> <b>(35W model only)</b>			

Standard Features and Configurable Components (availability may vary by country)

### Intel® 6th Generation Core™ i5 Processors

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
<b>Intel® Core™ i5-6500 Processor</b> 65W Up to 3.6 GHz Max. Turbo Frequency (3.2 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Core™ i5-6500T Processor</b> 35W Up to 3.1 GHz Max. Turbo Frequency (2.5 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)	<b>X</b> <b>(35W model only)</b>			
<b>Intel® Core™ i5-6600 Processor</b> 65W Up to 3.9 GHz Max. Turbo Frequency (3.3 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Core™ i5-6600T Processor</b> 35W Up to 3.5 GHz Max. Turbo Frequency (2.7 GHz base frequency) 6 MB cache, 4 cores, 4 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate Supports Intel® vPro™ Technology and Intel® Stable Image Platform Program (SIPP)	<b>X</b> <b>(35W model only)</b>			

### Intel® 6th Generation Core™ i3 Processors

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
<b>Intel® Core™ i3-6100 Processor</b> 51W 3.7 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate	<b>X</b> <b>(65W model only)</b>	<b>X</b>	<b>X</b>	<b>X</b>
<b>Intel® Core™ i3-6100T Processor</b> 35W 3.2 GHz base frequency 3 MB cache, 2 cores, 4 threads Intel® HD Graphics 530 Supports DDR4 memory up to 2133 MT/s data rate	<b>X</b> <b>(35W model only)</b>			

# QuickSpecs

HP EliteDesk 800 G3 and HP EliteOne 800 G3 Business Desktops PCs

---

Standard Features and Configurable Components (availability may vary by country)

--	--	--	--	--

Standard Features and Configurable Components (availability may vary by country)

### MEMORY\*

Form Factor	Type	Maximum	Number of Slots
Desktop Mini	DDR4-2400 (Transfer rates up to 2400 MT/s)	32 GB	2 SODIMM
Small Form Factor	DDR4-2400 (Transfer rates up to 2400 MT/s)	64 GB	4 DIMM
Tower	DDR4-2400 (Transfer rates up to 2400 MT/s)	64 GB	4 DIMM
All-in-One	DDR4-2400 (Transfer rates up to 2400 MT/s)	32 GB	2 SODIMM

Memory modules available. Memory options vary by platform. All slots are customer accessible / upgradeable.

- 2,048 MB (2048 MB x 1) (AMO only)
- 4,096 MB (4096 MB x 1)
- 8,192 MB (8192 MB x 1)
- 16,384 MB (16,384 MB x 1)

\* Full availability of 4 GB or more of memory requires a 64-bit operating system. With Windows 32-bit operating systems, the amount of usable memory is dependent upon your configuration, so that above 3 GB all memory may not be available due to system resource requirements.

Memory modules support data transfer rates up to 2400 MT/s; actual data rate is determined by the system's configured processor. See processor specifications for supported memory data rate.

### STORAGE\*

#### 2.5 inch 7.2k RPM Hard Disk Drives

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
1TB SATA	X	X	X	X
500GB SATA	X	X	X	X

#### 3.5" SATA 7.2k RPM Hard Disk Drives

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
500GB 7200RPM 3.5in		X	X	
1TB 7200RPM 3.5in		X	X	
2TB 7200RPM 3.5in		X	X	

#### 2.5 inch Solid State Hybrid Drives (SSHD)

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
1TB 5400RPM 2.5in 8GB Hybrid	X	X	X	X
500GB 5400RPM 2.5in 8GB Hybrid	X	X	X	X

#### 3.5 inch Solid State Hybrid Drives (SSHD)

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
1TB 7200RPM 3.5in SSHD (SSHD)		X	X	

#### 2.5 inch Self-encrypting Drives (SED HDD)

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
500GB 5400RPM 2.5in Federal Information Processing Standard (FIPS) SED	X	X	X	X
500GB 7200RPM 2.5in SED OPAL 2	X	X	X	X



Standard Features and Configurable Components (availability may vary by country)

### 2.5 inch Self-encrypting Drives (SED SSD)

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
256GB TLC SED SSD OPAL 2 Drive	X	X	X	X
512GB TLC SED SSD OPAL 2 Drive	X	X	X	X
256GB TLC SED SSD 2.5in Federal Information Processing Standard (FIPS) SED	X	X	X	X
512GB TLC SED SSD 2.5in Federal Information Processing Standard (FIPS) SED	X	X	X	X

### PCIe NVMe SSD Drives

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
HP 256GB Turbo Drive G2 PCIe TLC SSD Drive	X	X	X	X
HP 512GB Turbo Drive G2 PCIe TLC SSD Drive	X	X	X	X
HP 1TB Turbo Drive G2 PCIe TLC SSD Drive	X	X	X	X

### 2.5 SATA SSD Drives

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
HP SATA 128GB SSD Drive	X	X	X	X
HP SATA 256GB SSD Drive	X	X	X	X

\*For storage drives, GB = 1 billion bytes, TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30GB of system disk is reserved for system recovery software.

\*\*NOTE: Desktop Mini 2nd HDD only available when 1st storage drive is M2 drive.

### Optical Disc Drives

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
HP 9.5mm G3 800/600 Tower DVD-Writer*			X	
HP 9.5mm G3 800/600 Tower DVD-ROM			X	
HP 9.5mm G3 800/600/400 SFF G4 400 Microtower DVD-Writer*		X		
HP 9.5mm G3 800/600/400 SFF G4 400 Microtower DVD-ROM		X		
HP 9.5mm AIO 800 G3 Slim DVD Writer*				X
HP 9.5mm AIO 800 G3 Slim DVD-ROM				X

\*HD-DVD discs cannot be played on this drive. No support for DVD-RAM. Actual speeds may vary. Don't copy copyright-protected materials. Double Layer discs can store more data than single layer discs. Discs burned with this drive may not be compatible with many existing single-layer DVD drives and players.

### Removable

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
HP 9.5mm Slim Removable SATA 500GB		X	X	X
HP 3.5" Removable SATA HDD Frame/Carrier			X	

### Media Card Reader (optional)\*

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
SD 4 with 5-in-1 Interface from SD option to PCA is USB (Supports SD, SDXC, SDHC, UHS-I, UHS-II)		X	X	
SD 4 with 5-in-1 Interface from SD option to PCA is PCIe (Supports SD, SDXC, SDHC, UHS-I, UHS-II)				X

\*Card sold separately

Standard Features and Configurable Components (availability may vary by country)

### GRAPHICS

#### System Integrated Graphics

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
Intel® HD Graphics 530 (integrated on 6 <sup>th</sup> gen Core i7/i5/i3 processors)	X	X	X	X
Intel® HD Graphics 630 (integrated on 7 <sup>th</sup> gen Core i7/i5/i3 processors and Pentium G4620, 4600, 4600T)	X	X	X	X
Intel® HD Graphics 610 (integrated on Pentium G4560, G4560T, Celeron G3950, G3930, G3930T)	X	X	X	X

#### Optional Discrete Graphics Solutions

(Optional; RX 460 AiO graphics and GT 730 1GB HDMI card must be configured at purchase; RX 480, GTX 1080 must be configured at purchase and will require the 500W PSU and will be available after launch.)

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
AMD Radeon™ R7 430 2GB LP 2DP PCIe x16 GF Card		X	X	
AMD Radeon™ R7 450 4GB FH PCIe x16*			X	
AMD Radeon™ RX 460 2GB FH PCIe x16*			X	
AMD Radeon™ RX 460 2GB GFX				X
AMD Radeon™ RX 480 4GB FH PCIe x16*			X	
NVIDIA® GeForce® GT 730 1GB PCIe x8 HDMI		X	X	
NVIDIA® GeForce® GT 730 2GB PCIe x8 DP		X	X	
NVIDIA® GeForce® GTX 1060 3GB FH PCIe x16*			X	
NVIDIA® GeForce® GTX 1070 8GB FH PCIe x16*			X	
NVIDIA® GeForce® GTX 1080 8GB FH PCIe x16*			X	

\*Requires 500W chassis

#### 2<sup>nd</sup> Graphics Cards

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
AMD Radeon™ R7 430 2GB LP 2DP PCIe x16 GF Card		X	X	
AMD Radeon™ R7 450 4GB FH PCIe x16 G5 2 <sup>nd</sup> **			X	
NVIDIA® GeForce® GT 730 1GB PCIe x8 HDMI 2 <sup>nd</sup> ***		X	X	
NVIDIA® GeForce® GT 730 2GB PCIe x8 DP 2 <sup>nd</sup> ****		X	X	

\*\*Available only with AMD Radeon™ R7 450.

\*\*\*Available only with NVIDIA® GeForce® GT730 1GB.

\*\*\*\*Available only with NVIDIA® GeForce® GT730 2GB.

### Display (All-in-One models only)

23.8" diagonal IPS widescreen WLED backlit anti-glare LCD display  
 Orientation designed to operate in portrait or landscape mode  
 Non-touch or optional touch  
 Projected capacitive in-cell touch supports up to 10 touch-points

<b>Display Panel</b>	Type	IPS WLED Backlit LCD
	Touch Active Area (mm)	527.04 x 296.46 (FHD)
	Screen opening (mm)	535 x 313 (FHD)*
	Native Resolution (HxV)	1920 x 1080 (FHD)
	Aspect ratio	16:9

Standard Features and Configurable Components (availability may vary by country)

Pixel pitch (HxV)(mm)	0.2475 x 0.2475 (FHD)
Contrast ratio (typical)	1000:1
Brightness (typical)	250nits (cd/m2)(FHD)
Viewing angle (typical) (HxV)	178 ° x 178 °
Backlight lamp life (to half brightness)	30,000 hours minimum
Color support	Over 16 million colors (FHD)
Color gamut (typical)	72%
Anti-glare	Yes*
Default color temperature	Warm (6500K)
Measured Response Time	12 ms

\*Without Projected Capacitive Touch Panel

**NOTE:** All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

<b>Webcams</b>	<b>Pop-up Web Camera</b>	2MP FHD webcam, Up to 30 frames/sec, Array Microphone (Fixed 2Mp FHD 1080p)
	<b>IR Camera with rear-facing, 2nd 2MP webcam</b>	Dual Camera 480P IR+1080P RGB Fixed/2MP FHD 1080P Fixed
	<ul style="list-style-type: none"> <li>Supporting Win10 Hello</li> </ul>	
<b>Adjustable Height Stand:</b>	Height - Vertical/Landscape Adjustment	101mm (±2 mm)
	Portrait Adjustment	54mm (±2 mm)
	Tilt Angle	-5° to +20° (±3°) in landscape and portrait
	Rotation (Swivel)	90° (±1°)
	Pivot	Clockwise 90°
<b>Recline Stand:</b>	Height - Vertical Adjustment	178 mm (±2 mm)
	Tilt Angle	-5° to +65° (+/-3°)
	Rotation (swivel)	360° swivel

## WEBCAM & MIC (All-in-One models only)

Optional discrete dual microphone and Optional integrated 2MP webcam and IR sense (front) and 2MP webcam (rear); maximum resolution of 1920 x1080

Optional discrete dual microphone and Optional integrated 2MP webcam; maximum resolution of 1920 x1080

## AUDIO/MULTIMEDIA

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
Conexant CX20632 Audio Codec	<b>X</b>	<b>X</b>	<b>X</b>	
Conexant CX5001 codec- up to 24-bit PCM				<b>X</b>
Headset and Headphone front connectors (3.5mm)*	<b>X</b>	<b>X</b>	<b>X</b>	

Standard Features and Configurable Components (availability may vary by country)

Line-In rear connector (3.5mm) *		X	X	
Line-out rear connector (3.5mm)		X	X	X
Headset side port (3.5mm)				X
Headphone side port (3.5mm)				X
Multi-streaming capable*	X	X	X	X
Internal speaker (standard)	X	X	X	
High performance integrated stereo speakers				X
Bang & Olufsen Audio				X

\* The front headset connector supports CTIA style headsets and is re-taskable as a Line-in, Microphone-in or Headphone-out port. Rear audio input ports are re-taskable as a Line-in or Microphone-in port. External speakers must be powered externally. Multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front and rear jacks or internal speakers. This allows for different audio applications to use separate audio ports on the system. For example, the front jacks could be used with a headset for a communications application while the rear jacks are being used with external speakers and a multimedia application.

**Optional for Desktop Mini** (optional and must be configured at purchase)

HP UC Speaker Phone\*

HP UC Speaker Phone Mounting Bracket\*

\*Available after launch in June 2017

## NETWORKING/COMMUNICATIONS\*

### Ethernet (RJ-45) Integrated

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
Intel® I219LM Gigabit Network Connection LOM (standard)	X	X	X	X

### Ethernet (RJ-45) Optional

Intel® Ethernet I210-T1 PCIe x1 Gb Network Interface Card (optional)		X	X	
----------------------------------------------------------------------	--	---	---	--

**Wireless LAN** (optional and all except for 7265 for SFF/TWR must be bought at purchase)\*

Intel® 8265 802.11AC 2x2 Wi-Fi +Bluetooth® M.2 Combo Card vPro™ (802.11AC Wave 2 supported)	X	X	X	X
Intel® 8265 802.11AC 2x2 Wi-Fi +Bluetooth® M.2 Combo Card non-vPro™ (802.11AC Wave 2 supported)	X	X	X	X
Intel® 7265 802.11AC 2x2 Wi-Fi +Bluetooth® M.2 Combo Card non-vPro™	X	X	X	X
Intel® 7260 802.11 a,b,g,n 2x2 M.2 Bluetooth® Disabled NIC**	X			
Intel® 3168 802.11AC 2x2 Wi-Fi +Bluetooth® M.2 Combo Card non-vPro™	X	X	X	X

\* Wireless access point and Internet service required and not included. Availability of public wireless access points limited.

\*\*Wake on Lan feature is not available.

## SLOTS

DM

SFF

TWR

AiO

Standard Features and Configurable Components (availability may vary by country)

Turbo Drive (M.2 PCIe)	1 ea. M.2 PCIe x1-2230 (for WLAN) 1 ea. M.2 PCIe x4-2280/2230 (for storage)	1 ea. M.2 PCIe x1-2230 (for WLAN) 1 ea. M.2 PCIe x4-2280 (for storage)	1 ea. M.2 PCIe x1-2230 (for WLAN) 1 ea. M.2 PCIe x4-2280 (for storage)	1 ea. M.2 PCIe x1-2230 (for WLAN) 1 ea. M.2 PCIe x4-2280 (for storage) 1 ea. M.2 PCIe x4-2280/2230 combo (for storage)
PCI Express x1 (v3.0)	N/A	2 ea. 2.5" low profile 6.6" length 10W max. power	2 ea. 4.2" full height 6.6" length 10W max. power	N/A
PCI Express x16 (v3.0) (wired as a x4)	N/A	1 ea. 2.5" low profile 6.6" length 35W max. power	1 ea. 4.2" full height 6.6" length 35W max. power	N/A
PCI Express x16 (v3.0)	N/A	1 ea. 2.5" low profile 6.6" length 35W max. power	1 ea. 4.2" full height 6.6" length 75W max. power	N/A

## PORTS

### I/O Ports – Standard

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
USB 2.0	N/A	2 (front) including 1 fast charging; 2 (rear)	2 (front) including 1 fast charging; 2 (rear)	N/A
USB 3.1 Gen1	2 (front) including 1 fast charging; 4 (rear)	2 (front); 4 (rear)	2 (front); 4 (rear)	2 (side) including 1 fast charging, 4 (rear)
USB Type-C™ 3.1 Gen1 port	1 (front); 1 (optional) (rear)	1 (front); 1 (optional) (rear)	1 (front); 1 (optional) (rear)	1 (side)
PS/2	N/A	Optional with PS/2 Serial card	Optional with PS/2 Serial card	N/A
Video	2 DisplayPort™ 1.2 with multi-stream 1 port (choice of DisplayPort™, HDMI, VGA or USB-C™) (USB-C™ option has alt mode DisplayPort™ 1.2 or 15W output)	2 DisplayPort™ 1.2 with multi-stream 1 Optional port (DisplayPort™ 1.2, HDMI, VGA or USB-C™) (USB-C™ option has alt mode DisplayPort™ 1.2 or 15W output)	2 DisplayPort™ 1.2 with multi-stream 1 Optional port (DisplayPort™ 1.2, HDMI, VGA or USB-C™) (USB-C™ option has alt mode DisplayPort™ 1.2 or 15W output)	1 DisplayPort™ 1.2 with multi-stream 1 HDMI
Audio	Front: 1 Headset and Headphone	Front: 1 Audio-out (headphone)/Audio-in (microphone) combo jack 1 Audio-out (headphone) jack Rear: 1 Audio-out jack for powered audio devices; 1 Audio-in jack	Front: 1 Audio-out (headphone)/Audio-in (microphone) combo jack 1 Audio-out (headphone) jack Rear: 1 Audio-out jack for powered audio devices; 1 Audio-in jack	Side: Headset and Headphone (side) 3.5mm diameter
Network Interface	RJ-45	RJ-45	RJ-45	RJ-45

Standard Features and Configurable Components (availability may vary by country)

\*Replaces 1 DisplayPort™ 1.2

**NOTE: HDMI 2.0a with HDR**

### **I/O Ports – Optional**

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
Serial (RS-232)	1 (optional)*	1 (optional)	1 (optional)	
Serial (RS-232) and (2) PS/2 combination**		1 (optional) (rear)	1 (optional) (rear)	

\*Replaces 1 Video optional port

\*This card comes with a Serial Port and 2 PS/2 ports (3 ports total)

### **I/O Ports — Internal ports**

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
DM SATA storage connector	1	N/A	N/A	N/A
AiO SATA storage connector	N/A	N/A	N/A	2
Internal SATA storage connector(s)	N/A	3	5	N/A

## **BAYS**

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
5.25" Half Height**	N/A	N/A	1 ea.	N/A
9mm Slim ODD	N/A	1 ea.	1 ea.	1 ea.
Secure Digital (SD) 4 Reader	N/A	1 ea.	1 ea.	1 ea.
2.5" internal storage drive	1 ea.	1 ea.	1 ea.	1 ea.
3.5" internal storage drive	N/A	2 ea.	2 ea.	N/A

\*\*The HP G2 5.25 ODD is also compatible with the G3 MT Chassis

## **KEYBOARDS AND POINTING DEVICES (optional)**

### **Keyboards**

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
HP Conferencing Keyboard	X	X	X	X
HP USB PS/2 Washable Keyboard*	X	X	X	X
HP USB Business Slim CCID SmartCard Keyboard	X	X	X	X
HP USB Business Slim Keyboard	X	X	X	X
HP PS/2 Business Slim Keyboard*		X	X	
HP USB Business Slim Keyboard (China only)	X	X	X	X
HP USB Business Slim Grey Keyboard	X	X	X	X

### **Mice**

	<b><u>DM</u></b>	<b><u>SFF</u></b>	<b><u>TWR</u></b>	<b><u>AiO</u></b>
HP PS/2 Mouse*		X	X	
HP USB 1000dpi Laser Mouse	X	X	X	X
HP Grey V2 Mouse	X	X	X	X

Standard Features and Configurable Components (availability may vary by country)

HP USB Mouse	X	X	X	X
HP USB PS/2 Washable Mouse*	X	X	X	X
HP USB Mouse (China only)	X	X	X	X
HP USB Hardened Mouse	X	X	X	X
<b>Combo</b>	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
HP Wireless Business Slim Keyboard and Mouse	X	X	X	X
HP USB Keyboard and Mouse (China only)	X	X	X	X
<b>Other</b>	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
HP Mouse Pad	X	X	X	X

\*Note Optional HP Internal Serial/PS/2 Ports is required to support this device.

## ADAPTERS AND CABLES (optional)

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
HP DisplayPort™ 1.2 Cable	X	X	X	X
HP DisplayPort™ 1.2 to DVI-D Adapter	X	X	X	X
HP DisplayPort™ 1.2 to HDMI 4K Adapter	X	X	X	X
HP DisplayPort™ 1.2 to VGA Adapter	X	X	X	X
HP DVI Cable	X	X	X	X
HP 700mm DisplayPort™ 1.2 Cable Kit	X			
HP USB to Serial Port Adapter	X			X

## I/O DEVICES

Optional Ports (only one can be chosen) must be configured at purchase except for PCIe x1 cards.

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
HP DisplayPort™ 1.2 Port	X	X	X	
HP Type-C Port	X	X	X	
HP HDMI Port	X	X	X	
HP VGA Port	X	X	X	
HP Internal Serial Port*		X*	X*	
HP Internal Serial/PS/2 Ports*		X*	X*	
HP PCIe x1 Parallel Port Card		X	X	
HP PCIe x1 SuperSpeed USB 3.1 Gen 2 Type-C Card		X	X	
HP EliteDesk 800 G3 Tower Dust Filter			X	
HP EliteDesk 800 G3 SFF Dust Filter		X		
HP G3 Mini Dust Filter**	X			
HP EliteDesk 800 G3 AiO Dust Filter				X

\* Internal Serial Port and HP Internal Serial/PS/2 Ports can both be selected for TWR and SFF

\*\*Not available with 800 G3 DM 65W

## AIO STANDS (optional)

**DM**      **SFF**      **TWR**      **AiO**

Standard Features and Configurable Components (availability may vary by country)

HP EliteOne 800 G3 AiO Recline Stand				X
HP EliteOne 800 G3 AiO Adjustable Height Stand				X

### DESKTOP MINI ACCESSORIES (optional)

	<u>DM</u>	<u>SFF</u>	<u>TWR</u>	<u>AiO</u>
HP Desktop Mini DVD-Writer ODD Expansion Module	X			
HP Desktop Mini 500GB HDD/ I/O Expansion Module	X			
HP Desktop Mini I/O Expansion Module	X			
HP Desktop Mini Security/Dual VESA Sleeve	X			
HP DM VESA Power Supply Holder	X			
HP DM VESA Quick Deploy Adhesive	X			
HP Desktop Mini Vertical Chassis Stand	X			
HP Desktop Mini Port Cover Kit	X			
HP Quick Release Kit	X			X
HP DM Antenna/Wiring WLAN Kit	X			
HP PC Mounting Bracket for Monitors	X			

### SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS

#### BIOS

HP Sure Start Gen3<sup>1</sup>  
 HP DriveLock | HP Automatic DriveLock  
 BIOS Update via Network  
 Master Boot Record Security  
 Power On Authentication  
 Secure Erase<sup>2</sup>  
 Absolute Persistence Module<sup>3</sup>  
 Pre-boot Authentication  
 HP LAN-WLAN Protection  
 HP Wireless Wakeup

#### Multi Media

CyberLink Power Media Player (select models only)  
 CyberLink Power2Go (select models only)

#### Communication / Connectivity

Native Miracast Support<sup>4</sup>

#### HP Value Add Software

HP ePrint Driver + JetAdvantage<sup>5</sup>  
 HP Hotkey Support - CMIT  
 HP Recovery Manager  
 HP Recovery Disc Creator (Windows 7 only)  
 HP Jumpstart  
 HP Support Assistant  
 HP Noise Cancellation Software  
 HP Velocity



### Standard Features and Configurable Components (availability may vary by country)

#### HP Notifications

#### 3rd Party

Foxit PhantomPDF Express for HP (Windows 7 only)

#### Microsoft Products

Buy Office

Bing Search

Skype<sup>6</sup>

#### Manageability

HP Driver Packs<sup>7</sup>

HP SoftPaq Download Manager (SDM)

HP System Software Manager (SSM)<sup>7</sup>

HP BIOS Config Utility (BCU)<sup>7</sup>

HP Client Catalog<sup>7</sup>

HP Manageability & Integration Kit (MIK)<sup>8</sup>

LANDESK Management<sup>8</sup>

Discover HP Touchpoint Manager<sup>11</sup>

For more information on HP Client Management Solutions refer to: <http://www.hp.com/go/clientmanagement>

#### Client Security Software

HP Client Security Suite Gen3

- HP Security Manager (including Credential Manager and Password Manager)
- HP Drive Lock
- HP Fingerprint Sensor (AiO Touch model only)
- HP Password Manager
- Absolute Persistence Module
- Power On Authentication

Microsoft Security Essentials<sup>9</sup> (Windows 7 only)

Microsoft Defender

HP WorkWise (requires Bluetooth®)<sup>10</sup>

#### Standard

Trusted Platform Module (TPM) 2.0 (Infineon SLB9670). Common Criteria EAL4+ Certified.

Downgradeable to TPM 1.2. Convertible to FIPS 140-2 Certified mode. (TPM 2.0 is not available for Win 7 32-bit.) Restrictions apply; contact your account manager for more details.

HP Fingerprint Reader (available only on 800 G3 AiO touch models)

For more information on HP Client Security Software Suite, refer to <http://www.hp.com/go/clientsecurity>.

1 Available on HP EliteDesk / EliteOne products equipped with Intel® 7th generation processors.

2 For the methods outlined in the National Institute of Standards and Technology Special Publication 800-88.

3 Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: <http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

4 Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming media players that also support Miracast. You can use Miracast to share what you're doing on your PC and present a slide show. For more information: <http://windows.microsoft.com/en-us/windows-8/project-wireless-screen-miracast>

### Standard Features and Configurable Components (availability may vary by country)

5 Requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see [www.hp.com/go/eprintcenter](http://www.hp.com/go/eprintcenter)). Requires optional broadband module. Broadband use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Separately purchased data plans or usage fees may apply. Print times and connection speeds may vary.

6 Skype is not offered in China.

7 Not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>

8 Subscription required.

9 Opt in and internet connection required for updates.

10 HP WorkWise smartphone app will soon be available as a free download on the App Store and Google Play. Requires Windows 10 Build 1607 or higher).

11 HP Touchpoint Manager requires purchase of a subscription and supports Android™, iOS and Windows 7 or higher operating systems and PCs, notebooks, tablets and smartphones from various manufacturers. Not available in all countries see [www.hp.com/touchpoint](http://www.hp.com/touchpoint) for availability information

Standard Features and Configurable Components (availability may vary by country)

### HP BIOS

Key features of the HP BIOS include:

- Deployment and manageability – HP BIOS provides several technologies that help integrate the HP Elite 800 G3 Business PC into the enterprise, such as PXE, remote configuration, remote control, and F10 Setup support for 14 languages.
- Update your BIOS via the cloud or standardize on a BIOS version hosted on Enterprise network.
- Stability – HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- UEFI specification 2.5
- Absolute Persistence agent – For tracking and tracing services, available in select countries, separate software and purchase of a subscription is required.
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies so component temperatures are managed for high reliability and to assist in operating the HP Business Desktop computer in any enterprise environment.
- Acoustic performance – Industry leading acoustic emissions across the range of operating conditions.
- Serviceability – HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Business Desktop computers, including BIOS updates from within Windows (HPBIOSUPDREC), HP Client Manager, and fail-safe recovery. In addition, the HP BIOS Configuration Utility enables replication of BIOS settings within Windows while the Replicated Setup feature provides the same capability within F10 setup. The BIOS Configuration Utility is available from the support website.
- HP BIOS uses PKI signing of the BIOS for trusted BIOS upgrades and recovery.

Additional HP BIOS Features:

- Power-On password – Helps prevent an unauthorized user from powering on the system.
- Administrator password – Also known as the setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS version cannot be changed and changes cannot be made to BIOS settings using F10 setup or under the OS.
- Advanced Configuration and Power Interface (ACPI) – Represents a significant innovation in power and configuration management, allowing operating systems and applications to manage power based on activity and usage. HP Elite models use ACPI to provide power conservation features.

S5 Max Power Savings setting supports EU Lot6 requirement and allows the computer to power down below 0.5W in S5 (when turned off). When S5 Max Power Savings feature is enabled below features are turned off:

- Power to slots
- Wake events other than power buttons (such as Wake on LAN)
- USB charging ports

### SureStart

- BIOS Integrity checking – Sure Start protection ensures that only trusted BIOS code is executed and not rootkits, viruses and malware. Verification is done upon boot up, shutdown and while On.
- Sure Start is set by default to automatically repair the BIOS if corrupted or compromised but is policy driven for better manageability.
- Protecting beyond BIOS – Integrity checking and repair is extended to other data that should be protected such as network configuration parameters (network name), platform specific information (i.e. system IDs) and other code the system needs to boot.
- Audit enabled – System Audit via Sure Start Event Logs capture data such as incident, repair date and time for troubleshooting and investigating.

Standard Features and Configurable Components (availability may vary by country)

## Core™ vPro™ Processors\*

### Intel® 6th & 7th Generation Core™ vPro™ Processors

All HP Elite 800 G3 Business PC models featuring this technology include processors that are part of the Intel® Stable Image Platform Program (SIPP) designed to ensure the stability promise inherent in the value proposition of the HP Elite 800 G3 Business PC, thus making these models the most stable, secure, and manageable platforms available to enterprises today.

**Intel® Advanced Management Technology (AMT) v11\*\*** – An advanced set of remote management features and functionality which provides network administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state. AMT 11 includes the following advanced management functions:

- Support for configuration of Intel® AMT 11.0 new capabilities
- No reset after provisioning
- Support changes to BIOS table 130
- Support for Microsoft Windows Server 2012 R2
- Support for New Microsoft SQL Server Versions including Standard and Enterprise editions
- Support for Intel® SSD Prop 2500 Series
- Support for Intel® Enterprise Digital Fence
- The Platform Discovery Utility can now discover these additional Intel® products:
- Intel® SSD Pro 2500 Series; Enterprise Digital Fence
- Intel® Identity Protection Technology with One Time Password; Public Key Infrastructure; Multi Factor Authentication
- Intel® Identity Protection Technology with Intel® WiGig
- New Profile Editor and Profile Editor Plugin Interface
- New Required Permissions for Solutions Framework

\*Some functionality of this technology, such as Intel Active management technology and Intel Virtualization technology, requires additional 3rd party software in order to run. Availability of future "virtual appliances" applications for Intel vPro™ technology is dependent on 3rd party software providers. Compatibility with future "virtual appliances" is yet to be determined.

\*\* Intel® Active Management Technology requires an Intel® AMT-enabled chipset, network hardware and software, as well as connection with a power source and a corporate network connection. Setup requires configuration by the purchaser and may require scripting with the management console or further integration into existing security frameworks to enable certain functionality. It may also require modifications of implementation of new business processes.

## HARDWARE SECURITY

SATA 0,1 port disablement (via BIOS)

RAID configurations (MT/SFF only)

Serial, USB enable/disable (via BIOS)

Solenoid Lock / Hood Sensor (TWR/SFF only)

Hood Sensor for DM and AiO (integrated in the PCA, can be enabled/disabled through BIOS)

Support for chassis padlocks and cable lock devices

Removable storage write/boot control

Standard Features and Configurable Components (availability may vary by country)

### POWER SUPPLY

	DM	SFF	TWR	AiO
Standard Efficiency	65W EPS, 89% average efficiency at 115V & 230Vac 90W active PFC 89% average efficiency at 115Vac & 230Vac	N/A	N/A	N/A
80 PLUS Bronze	N/A	180W active PFC 82/85/82% efficient at 20/50/100% load (115V)	250W active PFC 82/85/82% efficient at 20/50/100% load (115V)	N/A
80 PLUS Gold	N/A	N/A	500W active PFC 87/90/87% efficient at 20/50/100% load (115V) 88/91/88% efficient at 20/50/100% load (230V)	180W active PFC 87/90/87% efficient at 20/50/100% load (115V) 88/91/88% efficient at 20/50/100% load (230V) <i>*Available on models with integrated graphics.</i>
80 PLUS Platinum	N/A	180W active PFC 90/92/89% efficient at 20/50/100% load (115V) 91/93/90% efficient at 20/50/100% load (230V)	250W active PFC 90/92/89% efficient at 20/50/100% load (115V) 91/93/90% efficient at 20/50/100% load (230V)	210W active PFC 90/92/89% efficient at 20/50/100% load (115V) 91/93/90% efficient at 20/50/100% load (230V) <i>*Available on models with discrete graphics.</i>
Operating Voltage Range	90 – 264 VAC	90 – 264 VAC	90 – 264 VAC	90 – 264 VAC
Rated Voltage Range	100-240V AC	100-240V AC	100-240V AC	100-240V AC
Rated Line Frequency	50/60 HZ	50/60 HZ	50/60 HZ	50/60 HZ
Operating Line Frequency	47 – 63 Hz	47 – 63 Hz	47 – 63 Hz	47 – 63 Hz
Rated Input Current		N/A	N/A	210W : 3A 180W : 2.5A
Rated Input Current with Energy Efficient* Power Supply	65W/1.6A 90W/1.4A 120W/2.2A	2.3A	250W Bronze/3.5A 250W Platinum/3A 500W Gold/6A	210W : 3A 180W : 2.5A
DC Output	+19.5V	+12.1V	_12.1V	+12.1V

### Standard Features and Configurable Components (availability may vary by country)

Current Leakage (NFPA 99: 2102)	Less than 500 microamps of leakage current at 120 Vac with the ground wire disconnected, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.	Less than 500 microamps of leakage current at 120 Vac with the ground wire disconnected, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.	Less than 500 microamps of leakage current at 120 Vac with the ground wire disconnected, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.		
	Less than 100 microamps of leakage current at 120 Vac with the ground wire intact with normal polarity, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.	Less than 100 microamps of leakage current at 120 Vac with the ground wire intact with normal polarity, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.	Less than 100 microamps of leakage current at 120 Vac with the ground wire intact with normal polarity, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.		
Power Supply Fan	N/A	70mm variable speed	70mm variable speed	N/A	
Power cord length	6.0 ft. (1.83 m)	6.0 ft. (1.83 m)	6.0 ft. (1.83 m)	6.0 ft. (1.83 m)	
External Power Adapter	65 W	90 W	N/A	N/A	N/A
Dimensions	30mm x 113.5mm x 55mm	31.1mm x 133mm x 58mm	N/A	N/A	N/A
Total Cord Length	6 ft	6 ft	N/A	N/A	N/A

The harmonic input current requirements must be met under the following operating conditions:

Load Requirements: 50% and 100%

Input Voltage: 230Vac/50Hz.

For active power factor correction the power factor at 50% & 100% loads shall be greater than 0.9 over the entire nominal input voltage range (100-127VAC and 200-240VAC).

Condition	Standard Efficiency	82/85/82%	85/88/85%	87/90/87%	90/92/89%	Input Voltage
10% of Rated Load	-	75%	81%	84%	84%	115Vac/60HZ
20% of Rated Load	-	82%	85%	87%	90%	115Vac/60HZ
50% of Rated Load	-	85%	88%	90%	92%	115Vac/60HZ
	PF>0.9	PF>0.9	PF>0.9	PF>0.9	PF>0.95	
100% of Rated Load	70%	82%	85%	87%	89%	115Vac/60HZ

Standard Features and Configurable Components (availability may vary by country)

	PF>0.9	PF>0.9	PF>0.9	PF>0.9	PF>0.9	230Vac/50HZ
--	--------	--------	--------	--------	--------	-------------

### WEIGHTS & DIMENSIONS

(configured with 1 HDD & 1 ODD; DM configured with 1 HDD only)

	<b>DM</b>	<b>SFF</b>	<b>TWR</b>	<b>AiO</b>
Chassis (W x D x H) Not including bezel	6.97 x 6.88 x 1.35 in 177 x 174.7 x 34.2 mm	3.94 x 13.3 x 12.13 in 100 x 338 x 308 mm	6.1 x 14.6 x 14.4 in 154 x 370 x 365 mm	<b>See table below.</b>
System Volume	64 cu in 1.06 L	634 cu in 10.4 L	1269 cu in 20.8 L	
System Weight*	35W model 2.67 lb 1.21 kg  65W model 2.89 lb 1.31 kg	11.7 lb 5.31 kg	21.79 lb 9.86 kg	
Max Supported Weight (desktop orientation)	N/A	77 lb 35 kg	77 lb 35 kg	
Stand Dimensions	N/A	N/A	N/A	
Stand Weight	N/A	N/A	N/A	
Packaging (W x D x H)	9.1 x 19.6 x 5.7 in 231.2 x 497.8 x 144.8 mm	15.71 x 19.65 x 9.06 in 399 x 499 x 230 mm	11.77 x 18.82 x 20.35 in 299 x 478 x 517 mm	
Shipping Weight	6.1 lb 2.8 kg	19.82 lb 9 kg	24.98 lb 11.34 kg	
Packaging (with Expansion Pack, W x D x H)	10.0 x 19.6 x 7.8 in 255 x 497.8 x 198 mm			
Shipping Weight (fully loaded)	11.5 lbs / 5.22 kg			
Multi-Unit Packaging (10 units)	20.28 x 16.54 x 25 in 515 x 420 x 636 mm			
Shipping Weight	68 lbs / 31 kg			
Palletization Profile	20-units per layer 4 layer max 80-units per pallet Footprint-39.21 x 46.61 in (996 x 1184 mm)	4-units per layer 10-layer max. 40-units per pallet 47.126 x 39.291 x 88.858 in (including pallet)	8-units per layer 4-layer max 32-units per pallet 47.24 x 39.37 x 4.72 in (including pallet)	
	<i>Dependent on 40-Ft Std. Sea Container or 40-Ft High-cube Sea Container is used)</i>			

Standard Features and Configurable Components (availability may vary by country)

### **ALL-IN-ONE WEIGHTS AND DIMENSIONS**

#### **Weight with Touch Panel**

<i>Product Weight</i> <i>Unboxed</i>	<u>Without Stand</u> 13.29 lbs 6.03kg	<u>Adjustable Height Stand</u> 19.24 lbs 8.73kg	<u>Recline Stand</u> 21.12lbs 9.58kg
<i>Shipping Weight</i> <i>Boxed</i>	<u>Without Stand</u> 20.64-21.15lbs 9.4-9.45kg	<u>Adjustable Height Stand</u> 26.68 lbs 12.1kg	<u>Recline Stand</u> 28.66-28.88 lbs 13-13.1kg
<i>Shipping Weight</i> <i>Pallet</i>	<u>Without Stand (10units)</u> 233.73lbs 106kg	<u>Adjustable Height Stand (10units)</u> 293.21lbs 133 kg	<u>Recline Stand (10units)</u> 313.06lbs 142kg

#### **Weight without Touch Panel**

<i>Product Weight</i> <i>Unboxed</i>	<u>Without Stand</u> 13.51-13.62 lbs 6.13-6.18kg	<u>Adjustable Height Stand</u> 19.46-19.68lbs 8.93 kg	<u>Recline Stand</u> 21.34-21.44 lbs 9.68-9.73kg
<i>Shipping Weight</i> <i>Box</i>	<u>Without Stand</u> 20.86-21.06lbs 9.5-9.55kg	<u>Adjustable Height Stand</u> 26.89-27.12 lbs 12.2-12.3 kg	<u>Recline Stand</u> 28.88lbs 13.1kg
<i>Shipping Weight</i> <i>Pallet</i>	<u>Without Stand (10 units)</u> 235.94-237.04 lbs 107-107.5 kg	<u>Adjustable Height Stand (10 units)</u> 295.42-297 lbs 134-135 kg	<u>Recline Stand (10 units)</u> 315.26lbs 143kg

#### **Dimensions (W x D x H)**

<i>Product Dimensions</i>	<u>Without Stand</u> 21.2 x 2.12 x 13.46 in 539.6 x 53.8 x 341.79 mm	<u>Adjustable Height Stand 0 degrees</u> 21.2 x 7.1 x 18.4 in 539.6 x 180.28 x 467.7 mm	<u>Recline Stand 0 degrees</u> 21.2 x 10.3 x 10.63 in 539.6 x 261.8 x 269.98 mm
---------------------------	----------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------

#### **Shipping Dimensions**

<i>Shipping Dimensions</i> <i>Boxed</i>	<u>Without Stand</u> 27.17 x 10.08 x 21.46(H) in	<u>Adjustable Height Stand</u> 27.17 x 10.08 x 26.22(H) in	<u>Recline Stand</u> 27.17 x 10.08 x 26.22(H) in
--------------------------------------------	-----------------------------------------------------	---------------------------------------------------------------	-----------------------------------------------------




Standard Features and Configurable Components (availability may vary by country)

	690 x 256 x 545(H) mm	690 x 256 x 666(H) mm	690 x 256 x 666(H) mm
<i>Shipping Dimensions</i>  <i>Pallet</i>	<u>Without Stand (10 units)</u> 47.24 x 39.37 x 24.02(H) in 1200 x 1000 x 610(H) mm	<u>Adjustable Height Stand (10 units)</u> 47.24 x 39.37 x 28.94(H) in 1200 x 1000 x 735(H) mm	<u>Recline Stand (10 units)</u> 47.24 x 39.37 x 28.94(H) in 1200 x 1000 x 735(H) mm





Standard Features and Configurable Components (availability may vary by country)

### DESKTOP MINI DIMENSIONS






Standard Features and Configurable Components (availability may vary by country)

### SMALL FORM FACTOR DIMENSIONS




Standard Features and Configurable Components (availability may vary by country)

### TOWER DIMENSIONS




Standard Features and Configurable Components (availability may vary by country)

### ALL-IN-ONE ADJUSTABLE HEIGHT STAND DIMENSIONS (LOW POSITION)




Standard Features and Configurable Components (availability may vary by country)

### ALL-IN-ONE ADJUSTABLE HEIGHT STAND DIMENSIONS (HIGH POSITION)




Standard Features and Configurable Components (availability may vary by country)

### ALL-IN-ONE RECLINING STAND DIMENSIONS



Standard Features and Configurable Components (availability may vary by country)

### ALL-IN-ONE NO STAND DIMENSIONS





Standard Features and Configurable Components (availability may vary by country)

### ENVIRONMENTAL & INDUSTRY

#### HP EliteDesk 800 35W G3 Desktop Mini Business PC

<b>Eco-Label Certifications &amp; declarations</b>	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> <li>IT ECO declaration</li> <li>US ENERGY STAR®</li> <li>EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>		
<b>System Configuration</b>	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.		
<b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	8.78 W	9.25 W	8.61 W
Normal Operation (Long idle)	7.88 W	8.08 W	7.78 W
Sleep	0.88 W	0.99 W	0.95 W
Off	0.96 W	0.95 W	0.98 W
	<p>Note:</p> <p>Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	30 BTU/hr	32 BTU/hr	29 BTU/hr
Normal Operation (Long idle)	27 BTU/hr	28 BTU/hr	27 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
	*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.		
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	3.0	20	
Fixed Disk – Random writes	3.3	20	
<b>Batteries</b>	This battery(s) in this product comply with EU Directive 2006/66/EC		

### Standard Features and Configurable Components (availability may vary by country)

	<p>Batteries used in the product do not contain:          Mercury greater than 1ppm by weight          Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell)          Battery type: Lithium</p>		
<b>Additional Information</b>	<ul style="list-style-type: none"> <li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>• Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>• This product contains 24.1% post-consumer recycled plastic (by wt.)</li> <li>• This product is 91.7% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	443 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	38 g
		PLASTIC/Polyethylene High density - HDPE	4 g
	The Plastic packaging material is made from 0% recycled content.		
	The paper packaging materials contains at least 25% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		

Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

### HP EliteDesk 800 65W G3 Desktop Mini Business PC

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>		
<b>System Configuration</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<p><b>115VAC, 60Hz</b></p>	<p><b>230VAC, 50Hz</b></p>	<p><b>100VAC, 50Hz</b></p>

Standard Features and Configurable Components (availability may vary by country)

Normal Operation (Short idle)	8.78 W	9.25 W	8.61 W
Normal Operation (Long idle)	7.88 W	8.08 W	7.78 W
Sleep	0.88 W	0.99 W	0.95 W
Off	0.96 W	0.95 W	0.98 W
	<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	30 BTU/hr	32 BTU/hr	29 BTU/hr
Normal Operation (Long idle)	27 BTU/hr	28 BTU/hr	27 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
	<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>		
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	3.0	21	
Fixed Disk – Random writes	3.0	21	
<b>Batteries</b>	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		

Standard Features and Configurable Components (availability may vary by country)

<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product contains 24.1% post-consumer recycled plastic (by wt.)</li> <li>This product is 91.7% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	443 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	38 g
		PLASTIC/Polyethylene High density - HDPE	4 g
	The Plastic packaging material is made from 0% recycled content.		
	The paper packaging materials contains at least 25% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> <li>Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>Cadmium</li> <li>Chlorinated Hydrocarbons</li> <li>Chlorinated Paraffins</li> <li>Formaldehyde</li> <li>Halogenated Diphenyl Methanes</li> <li>Lead carbonates and sulfates</li> <li>Lead and Lead compounds</li> <li>Mercuric Oxide Batteries</li> <li>Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>Ozone Depleting Substances</li> <li>Polybrominated Biphenyls (PBBs)</li> <li>Polybrominated Biphenyl Ethers (PBBEs)</li> <li>Polybrominated Biphenyl Oxides (PBBOs)</li> <li>Polychlorinated Biphenyl (PCB)</li> <li>Polychlorinated Terphenyls (PCT)</li> <li>Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>Radioactive Substances</li> <li>Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		

Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

### HP EliteDesk 800 G3 Small Form Factor Business PC

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>										
<b>System Configuration</b>  <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p> <table border="1" data-bbox="400 1793 1522 1965"> <thead> <tr> <th></th> <th>115VAC, 60Hz</th> <th>230VAC, 50Hz</th> <th>100VAC, 50Hz</th> </tr> </thead> <tbody> <tr> <td>Normal Operation (Short idle)</td> <td>12.86 W</td> <td>12.52 W</td> <td>12.45 W</td> </tr> </tbody> </table>				115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	Normal Operation (Short idle)	12.86 W	12.52 W	12.45 W
	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz								
Normal Operation (Short idle)	12.86 W	12.52 W	12.45 W								

Standard Features and Configurable Components (availability may vary by country)

Normal Operation (Long idle)	11.72 W	11.69 W	11.82 W
Sleep	1.09 W	1.08 W	1.09 W
Off	0.73 W	0.73 W	0.73 W
	<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	44 BTU/hr	43 BTU/hr	43 BTU/hr
Normal Operation (Long idle)	40 BTU/hr	40 BTU/hr	40 BTU/hr
Sleep	4 BTU/hr	4 BTU/hr	4 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr
	*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.		
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	3.1	22	
Fixed Disk – Random writes	3.2	23	
<b>Longevity and Upgrading</b>	<p>This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:</p> <ul style="list-style-type: none"> <li>• 11 USB ports</li> <li>• 4 PCIe half-length slot</li> <li>• 1 internal M.2 SSD storage (2230 or 2280 connector)</li> <li>• 1 internal M.2 WLAN (2230 connector)</li> <li>• 1 2.5" internal storage drive bay (HDD/SSD/SED/SSHD)</li> <li>• 2 3.5" internal storage drive bay (HDD/SSD/SED/SSHD)</li> <li>• 1 9.5mm slim optical drive bay</li> </ul> <p>Spare parts are available throughout the warranty period and or for up to 5 years after the end of production.</p>		
<b>Batteries</b>	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		

Standard Features and Configurable Components (availability may vary by country)

<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product contains 17.9% post-consumer recycled plastic (by wt.)</li> <li>This product is 94.2% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Paperboard	1158 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	184 g
		PLASTIC/Polyethylene low density - LDPE	28 g
	The Plastic packaging material is made from 75% recycled content.		
	The paper packaging materials contains at least 47.5% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> <li>Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>Cadmium</li> <li>Chlorinated Hydrocarbons</li> <li>Chlorinated Paraffins</li> <li>Formaldehyde</li> <li>Halogenated Diphenyl Methanes</li> <li>Lead carbonates and sulfates</li> <li>Lead and Lead compounds</li> <li>Mercuric Oxide Batteries</li> <li>Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>Ozone Depleting Substances</li> <li>Polybrominated Biphenyls (PBBs)</li> <li>Polybrominated Biphenyl Ethers (PBBEs)</li> <li>Polybrominated Biphenyl Oxides (PBBOs)</li> <li>Polychlorinated Biphenyl (PCB)</li> <li>Polychlorinated Terphenyls (PCT)</li> <li>Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>Radioactive Substances</li> <li>Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		



Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

### HP EliteDesk 800 G3 Tower Business PC

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>										
<b>System Configuration</b>  <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p> <table border="1" data-bbox="400 1793 1522 1965"> <thead> <tr> <th></th> <th>115VAC, 60Hz</th> <th>230VAC, 50Hz</th> <th>100VAC, 50Hz</th> </tr> </thead> <tbody> <tr> <td>Normal Operation (Short idle)</td> <td>15.60 W</td> <td>14.19 W</td> <td>15.88 W</td> </tr> </tbody> </table>				115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	Normal Operation (Short idle)	15.60 W	14.19 W	15.88 W
	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz								
Normal Operation (Short idle)	15.60 W	14.19 W	15.88 W								

Standard Features and Configurable Components (availability may vary by country)

Normal Operation (Long idle)	14.62 W	13.08 W	14.91 W
Sleep	1.23 W	1.17 W	1.22 W
Off	0.81 W	0.79 W	0.81 W
<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>			
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	53 BTU/hr	49 BTU/hr	54 BTU/hr
Normal Operation (Long idle)	50 BTU/hr	45 BTU/hr	51 BTU/hr
Sleep	4 BTU/hr	4 BTU/hr	4 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>			
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	3.3	22	
Fixed Disk – Random writes	3.5	23	
<b>Longevity and Upgrading</b>	<p>This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:</p> <ul style="list-style-type: none"> <li>• 11 USB ports</li> <li>• 4 PCIe half-length slot</li> <li>• 1 internal M.2 SSD storage (2230 or 2280 connector)</li> <li>• 1 internal M.2 WLAN (2230 connector)</li> <li>• 1 2.5"/2 3.5" internal storage drive (HDD/SSD/SED/SSHD)</li> <li>• 1 5.25" external supporting optical drive</li> </ul> <p>Spare parts are available throughout the warranty period and or for up to 5 years after the end of production.</p>		
<b>Batteries</b>	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		

Standard Features and Configurable Components (availability may vary by country)

<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product contains 17.8% post-consumer recycled plastic (by wt.)</li> <li>This product is 95.9% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	1144 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	288 g
		PLASTIC/Polyethylene low density - LDPE	3 g
	The Plastic packaging material is made from 75% recycled content.		
	The paper packaging materials contains at least 47.5% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> <li>Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>Cadmium</li> <li>Chlorinated Hydrocarbons</li> <li>Chlorinated Paraffins</li> <li>Formaldehyde</li> <li>Halogenated Diphenyl Methanes</li> <li>Lead carbonates and sulfates</li> <li>Lead and Lead compounds</li> <li>Mercuric Oxide Batteries</li> <li>Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>Ozone Depleting Substances</li> <li>Polybrominated Biphenyls (PBBs)</li> <li>Polybrominated Biphenyl Ethers (PBBEs)</li> <li>Polybrominated Biphenyl Oxides (PBBOs)</li> <li>Polychlorinated Biphenyl (PCB)</li> <li>Polychlorinated Terphenyls (PCT)</li> <li>Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>Radioactive Substances</li> <li>Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		

Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

### HP EliteOne 800 G3 Touch GPU All-in-One Business PC

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>		
<b>System Configuration</b>  <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p> <p style="text-align: center;"><b>115VAC, 60Hz</b></p>	<p style="text-align: center;"><b>230VAC, 50Hz</b></p>	<p style="text-align: center;"><b>100VAC, 50Hz</b></p>

Standard Features and Configurable Components (availability may vary by country)

Normal Operation (Short idle)	24.53 W	24.16 W	24.51 W
Normal Operation (Long idle)	14.37 W	14.76 W	13.88 W
Sleep	4.30 W	4.20 W	4.33 W
Off	0.88 W	0.87 W	0.89 W
	<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	84 BTU/hr	83 BTU/hr	84 BTU/hr
Normal Operation (Long idle)	49 BTU/hr	50 BTU/hr	47 BTU/hr
Sleep	14 BTU/hr	14 BTU/hr	15 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
	<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>		
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	2.9	20	
Fixed Disk – Random writes	2.9	20	
<b>Longevity and Upgrading</b>	<p>This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:</p> <ul style="list-style-type: none"> <li>• 6 USB ports</li> <li>• 1 Type-C USB port - 15W</li> <li>• 1 SD4.0 card reader</li> <li>• 2 memory slots</li> <li>• 1 M.2 Wireless module slot</li> <li>• 2 M.2 storage slots</li> <li>• 1 2.5" internal bay (HDD/SSD/SED/SSHD)</li> <li>• 1 9.5mm external supporting optical drive</li> </ul>		
<b>Batteries</b>	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		

Standard Features and Configurable Components (availability may vary by country)

<b>Additional Information</b>	<ul style="list-style-type: none"> <li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>• Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>• This product contains 41.9% post-consumer recycled plastic (by wt.)</li> <li>• This product is 98.0 % recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	1191 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	556 g
		PLASTIC/Polyethylene low density - LDPE	94 g
	The Plastic packaging material is made from 80% recycled content.		
	The paper packaging materials contains at least 80% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		

### Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

### HP EliteOne 800 G3 Non Touch GPU All-in-One Business PC

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>										
<b>System Configuration</b>  <b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p> <table border="1" data-bbox="400 1793 1522 1965"> <thead> <tr> <th></th> <th>115VAC, 60Hz</th> <th>230VAC, 50Hz</th> <th>100VAC, 50Hz</th> </tr> </thead> <tbody> <tr> <td>Normal Operation (Short idle)</td> <td>24.53 W</td> <td>24.16 W</td> <td>24.51 W</td> </tr> </tbody> </table>				115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	Normal Operation (Short idle)	24.53 W	24.16 W	24.51 W
	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz								
Normal Operation (Short idle)	24.53 W	24.16 W	24.51 W								

Standard Features and Configurable Components (availability may vary by country)

Normal Operation (Long idle)	14.37 W	14.76 W	13.88 W
Sleep	4.30 W	4.20 W	4.33 W
Off	0.88 W	0.87 W	0.89 W
<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>			
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	84 BTU/hr	83 BTU/hr	84 BTU/hr
Normal Operation (Long idle)	49 BTU/hr	50 BTU/hr	47 BTU/hr
Sleep	14 BTU/hr	14 BTU/hr	15 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>			
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)		Sound Pressure (L <sub>pAm</sub> , decibels)
Typically Configured – Idle	2.9		20
Fixed Disk – Random writes	2.9		20
<b>Longevity and Upgrading</b>	<p>This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:</p> <ul style="list-style-type: none"> <li>• 6 USB ports</li> <li>• 1 Type-C USB port - 15W</li> <li>• 1 SD4.0 card reader</li> <li>• 2 memory slots</li> <li>• 1 M.2 Wireless module slot</li> <li>• 2 M.2 storage slots</li> <li>• 1 2.5" internal bay (HDD/SSD/SED/SSHD)</li> <li>• 1 9.5mm external supporting optical drive</li> </ul>		
<b>Batteries</b>	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		



### Standard Features and Configurable Components (availability may vary by country)

<b>Additional Information</b>	<ul style="list-style-type: none"> <li>• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>• This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>• This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>• Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>• This product contains 41.9% post-consumer recycled plastic (by wt.)</li> <li>• This product is 98.0 % recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	1191 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	556 g
		PLASTIC/Polyethylene low density - LDPE	94 g
	The Plastic packaging material is made from 80% recycled content.		
	The paper packaging materials contains at least 80% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		

Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

### HP EliteOne 800 G3 Non-Touch All-in-One Business PC Healthcare

<b>Eco-Label Certifications &amp; declarations</b>	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• TCO Certified EDGE</li> <li>• EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.</li> </ul>		
<b>System Configuration</b>	<p>The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	24.53 W	24.16 W	24.51 W
Normal Operation (Long idle)	14.37 W	14.76 W	13.88 W

### Standard Features and Configurable Components (availability may vary by country)

Sleep	4.30 W	4.20 W	4.33 W
Off	0.88 W	0.87 W	0.89 W
	<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family . HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>		
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 50Hz</b>
Normal Operation (Short idle)	84 BTU/hr	83 BTU/hr	84 BTU/hr
Normal Operation (Long idle)	49 BTU/hr	50 BTU/hr	48 BTU/hr
Sleep	15 BTU/hr	14 BTU/hr	15 BTU/hr
Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
	<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>		
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)	Sound Pressure (L <sub>pAm</sub> , decibels)	
Typically Configured – Idle	3.0	19	
Fixed Disk – Random writes	3.0	19	
<b>Longevity and Upgrading</b>	<p>This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:</p> <ul style="list-style-type: none"> <li>• 6 USB ports</li> <li>• 2 memory slots</li> <li>• 1 M.2 2230 for WLAN</li> <li>• 2 M.2 2280 for NVMe SSD storage</li> <li>• 1 2.5" internal bay support</li> <li>• 1 5.25" 9.5mm-slim ODD</li> </ul> <p>Spare parts are available throughout the warranty period and or for up to 5 years after the end of production.</p>		
<b>Batteries</b>	<p>This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell) Battery type: Lithium</p>		

Standard Features and Configurable Components (availability may vary by country)

<b>Additional Information</b>	<ul style="list-style-type: none"> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT<sup>®</sup>) standard at the gold level, see <a href="http://www.epeat.net">www.epeat.net</a></li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>This product contains 41.6% post-consumer recycled plastic (by wt.)</li> <li>This product is 98% recycle-able when properly disposed of at end of life.</li> </ul>		
<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	1191 g
	<b>Internal:</b>	PLASTIC/Polyethylene Expanded - EPE	556 g
		PLASTIC/Polyethylene low density - LDPE	94 g
	The Plastic packaging material is made from 80% recycled content. The paper packaging materials contains at least 80% recycled content.		
<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>Asbestos</li> <li>Certain Azo Colorants</li> <li>Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>Cadmium</li> <li>Chlorinated Hydrocarbons</li> <li>Chlorinated Paraffins</li> <li>Formaldehyde</li> <li>Halogenated Diphenyl Methanes</li> <li>Lead carbonates and sulfates</li> <li>Lead and Lead compounds</li> <li>Mercuric Oxide Batteries</li> <li>Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>Ozone Depleting Substances</li> <li>Polybrominated Biphenyls (PBBs)</li> <li>Polybrominated Biphenyl Ethers (PBEBs)</li> <li>Polybrominated Biphenyl Oxides (PBBOs)</li> <li>Polychlorinated Biphenyl (PCB)</li> <li>Polychlorinated Terphenyls (PCT)</li> <li>Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.</li> <li>Radioactive Substances</li> <li>Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		

### Standard Features and Configurable Components (availability may vary by country)

<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>
<b>End-of-life Management and Recycling</b>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
<b>HP, Inc. Corporate Environmental Information</b>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</a>          and  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

- ENERGY STAR® certified models available
- EPEAT® registered where applicable. EPEAT<sup>□</sup> registration varies by country. See <http://www.epeat.net> for registration status by country. Search keyword generator on HP's 3rd party option store for solar generator accessories at <http://www.hp.com/go/options>
- Low halogen (chassis, all internal components and modules)\*
- TAA compliant models available

\* External power supplies, power cords, cables and peripherals are not low halogen. Service parts obtained after purchase may not be low halogen.

Standard Features and Configurable Components (availability may vary by country)

## UNIT ENVIRONMENT AND OPERATING CONDITIONS

### General Unit Operating Guidelines

- Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range.
- Leave a 10.2 cm (4 in) clearance on all vented sides of the computer to permit the required airflow.
- Never restrict airflow into the computer by blocking any vents or air intakes.
- Do not stack computers on top of each other or place computers so near each other that they are subject to each other's re-circulated or preheated air.
- Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow.
- If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply.

Temperature Range	Operating: 50° to 95° F (10° to 35° C)* Non-operating: -22° to 140° F (-30° to 60° C)
Relative Humidity	Operating: 10% to 90% (non-condensing at ambient) Non-operating: 5% to 95% (non-condensing at ambient)
Maximum Altitude (unpressurized)	Operating: 5000m Non-operating: 50000ft (15240 m)

\*Operating temperature is de-rated 1.0 deg C per 300 m (1000 ft) to 3000 m (10,000 ft) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.

## SERVICE AND SUPPORT

On-site Warranty <sup>1</sup>: Three-year (3-3-3) limited warranty delivers three years of on-site, next business day <sup>2</sup> service for parts and labor and complimentary limited technical support.<sup>3</sup> Three-year onsite and labor are not available in all countries. Service offers terms up to 5 years by choosing an optional HP Care Pack.<sup>4</sup> To choose the right level of service for your HP product, visit HP Care Pack Central: [www.hp.com/go/cpc](http://www.hp.com/go/cpc)

**NOTE 1:** Terms and conditions may vary by country. Certain restrictions and exclusions apply. Other warranty variations may be offered in your region.

**NOTE 2:** On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

**NOTE 3:** Technical telephone support applies only to HP-configured and third-party HP qualified hardware and software.

**NOTE 4:** Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit [www.hp.com/go/cpc](http://www.hp.com/go/cpc). HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

## GRAPHICS

<b>Intel® HD Graphics (integrated)</b>			
DisplayPort™ 1.2	Multimode capable; supports HDCP, Display Port Audio (2 streams), HBR2 link rates and Multi-Stream Technology for a maximum of 3 displays (including the integrated panel)		
Memory	The BIOS has options for selecting the dedicated memory size of 128MB, 256MB or 512MB Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.		
Maximum Graphics Memory	Microsoft Windows 7	Windows 8.1	Windows 10
	Up to 1.7GB	Up to 1.8GB	>4 GB
Note: the actual amount of maximum graphics memory can be less than the amounts listed above depending upon your computer's configuration.			
Maximum Color Depth	32 bits/pixel		
Graphics/Video API Support	6th Generation Core™ processors: <ul style="list-style-type: none"> <li>• Next Generation Intel® Clear Video Technology HD Support is a collection of video playback and enhancement features that improve the end user's viewing experience               <ul style="list-style-type: none"> <li>○ Encode/transcode HD content</li> <li>○ Playback of high definition content including Blu-ray Disc</li> <li>○ Superior image quality with sharper, more colorful images</li> </ul> </li> <li>• DirectX Video Acceleration (DXVA) support for accelerating video processing               <ul style="list-style-type: none"> <li>○ Full AVC/VC1/MPEG2/HEVC HW Decode</li> </ul> </li> <li>• Advanced Scheduler 2.0, 1.0</li> <li>• Windows 7, Windows 8.1, Windows 10, Linux OS Support</li> <li>• DirectX 12.1</li> <li>• OpenGL 4.4</li> <li>• Open CL 1.2 (Intel® HD Graphics 510)</li> <li>• Open CL 1.2/2.0 (Intel® HD Graphics 530)</li> </ul>		

### Supported Display Resolutions and Refresh Rates

Note: other resolutions may be available but are not recommended as they may not have been tested and qualified by HP. For All in One platforms, resolutions higher than the integrated panel resolution are not supported on the integrated panel.

Resolution	Refresh Rate	VGA	DisplayPort™ 1.2	HDMI	Standard
640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3

### Technical Specifications – Graphics

1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X*	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X*	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85		X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75		X	X	CVT 3.15M3
2560 x 1440	59.951		X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB		X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3440 x 1440	60		X	X	VESA DMT, CVT 0.31M3
3440 x 1440	75, 85		X		VESA DMT, CVT 0.31M3
3840 x 2160	24		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	X	VESA (SMPTE 274M)
1920 x 1080	50		X	X	SMPTE 274M
1920 x 1080	30		X	X	SMPTE 274M
1920 x 1080	24		X	X	SMPTE 274M



### Technical Specifications – Graphics

1280 x 720	60		X	X	VESA (CEA-770.3)
1280 x 720	50		X	X	SMPTE 296M
720 x 480	60		X	X	MHL (CEA-770.2)
720 x 576	50		X	X	ITU-R BT.1358
640 x 480	60		X	X	CEA (VESA DMT)
* 60Hz refresh rate only on VGA					

### AMD Radeon™ R7 430 2GB LP 2DP PCIe x16 GF card

<b>Memory</b>	1GB/2GB GDDR5 or 2GB/4GB DDR3
<b>Controller Clock Speed</b>	AMD® Radeon™ R7 430 GPU operating up to 780Mhz
<b>Multidisplay Support</b>	A maximum of 2 displays are supported by the card.
<b>Graphics /API support</b>	DIRECTX® 12, Mantle, OpenGL 4.4, Vulkan™
<b>Output Connectors</b>	2x DisplayPort

Resolution	Refresh Rate*	VGA (DVI-VGA adapter)	DisplayPort	Standard
640 x 480	60, 75, 85	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	VESA DMT, CVT 2.76M3

### Technical Specifications – Graphics

2048 x 1536	60,75	X	X	CVT 3.15M3
2560 x 1440	59.951		X	CVT 3.69M9-R
2560 x 1600	60, 60RB		X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24		X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25		X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50		X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60		X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24		X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25		X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30		X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50		X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60		X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	VESA (SMPTE 274M)
1920 x 1080	50		X	SMPTE 274M
1920 x 1080	30		X	SMPTE 274M
1920 x 1080	24		X	SMPTE 274M
1280 x 720	60		X	VESA (CEA-770.3)
1280 x 720	50		X	SMPTE 296M
720 x 480	60		X	MHL (CEA-770.2)

\* >60 refresh rates only for analog (VGA) signaling

### AMD Radeon™ R7 450 4GB PCIe x16 Graphics Card

<b>Memory</b>	4GB 128-bit wide frame buffer operating at 1125MHz.
<b>Controller Clock Speed</b>	AMD® Radeon™ R9 450 GPU operating at 925 MHz
<b>Multi-display Support</b>	A maximum of 4 displays are supported by the card. A maximum of 2 legacy displays (Native VGA, DVI, or displays connected with passive DisplayPort™ 1.2 adapters are considered as legacy)
<b>Graphics /API support</b>	DIRECTX 12, Open GL 4.3, Open CL1.2, UVD 3
<b>Output Connectors</b>	1 x Dual-Link DVI-I, 1x DisplayPort™ 1.2; 1x HDMI; Includes DVI to VGA adapter

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	VGA (DVI-VGA Adapter)	DVI-D	DisplayPort™ 1.2	HDMI	Standard
640 x 480	60, 75, 85	X	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	X	IBM VGA

### Technical Specifications – Graphics

800 x 600	60, 75, 85	X	X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	X	CVT 3.15M3
2560 x 1440	59.951		X	X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB		X	X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50			X		CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60			X		CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50			X		CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60			X		CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	X	X	VESA (SMPTE 274M)
1920 x 1080	50		X	X	X	SMPTE 274M
1920 x 1080	30		X	X	X	SMPTE 274M
1920 x 1080	24		X	X	X	SMPTE 274M
1280 x 720	60		X	X	X	VESA (CEA-770.3)
1280 x 720	50		X	X	X	SMPTE 296M

### Technical Specifications – Graphics

720 x 480	60		X	X	X	MHL (CEA-770.2)
-----------	----	--	---	---	---	-----------------

\* >60 refresh rates only for analog (VGA) signaling

### AMD Radeon™ RX 460 4GB FH PCIe x16 Graphics Card

<b>Memory</b>	2GB 128-bit wide frame buffer operating at 1750MHz.
<b>Controller Clock Speed</b>	AMD® Radeon™ RX 460 GPU operating at up to 1.2GHz
<b>Multi-display Support</b>	A maximum of 4 displays are supported by the card.
<b>Graphics /API support</b>	DIRECTX 12, Open GL 4.5, Open CL 2.0, AMD Video Coding Engine (VCE) 3.4 and AMD Universal Video Decoder( UVD)
<b>Output Connectors</b>	1 x Dual-Link DVI-D, 1x DisplayPort™ 1.2; 1x HDMI

### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*		DVI-D	DisplayPort™ 1.2	HDMI	Standard
640 x 480	60, 75, 85		X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70		X	X	X	IBM VGA
800 x 600	60, 75, 85		X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85		X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85		X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85		X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85		X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85		X	X	X	VESA DMT
1280 x 960	60, 75, 85		X	X	X	VESA DMT
1280 x 1024	60, 75, 85		X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB		X	X	X	VESA DMT
1440 x 900	60, 60RB		X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85		X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75		X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60		X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85		X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85		X	X	X	VESA DMT, 1.92M3

### Technical Specifications – Graphics

1920 x 1440	60, 75, 85		X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60, 75		X	X	X	CVT 3.15M3
2560 x 1440	59.951		X	X	X	CVT 3.69M9-R
2560 x 1600	60, 60 RB		X	X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	X	X	VESA (SMPTE 274M)
1920 x 1080	50		X	X	X	SMPTE 274M
1920 x 1080	30		X	X	X	SMPTE 274M
1920 x 1080	24		X	X	X	SMPTE 274M
1280 x 720	60		X	X	X	VESA (CEA-770.3)
1280 x 720	50		X	X	X	SMPTE 296M
720 x 480	60		X	X	X	MHL (CEA-770.2)

### AMD Radeon™ RX 460 2GB Graphics

#### Memory

2GB 128-bit wide frame buffer operating at 1.5 GHz.

#### Controller Clock Speed

AMD® Radeon™ RX 460 GPU operating at up to 1.053 GHz

#### Multi-display Support

A maximum of 5 displays are supported by the card including the integrated panel

#### Graphics /API support

DIRECTX 12, Open GL 4.5, Open CL 2.0, , AMD Video Coding Engine (VCE) 3.4 and AMD Universal Video Decoder( UVD)

#### Output Connectors

1x DisplayPort™ 1.2; 1x HDMI

DisplayPort™ 1.2 output supports MST and HBR3

DP and HDMI outputs support HDR, HDCP 1.4 and HDCP 2.2

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

### Technical Specifications – Graphics

Resolution	Refresh Rate			DisplayPort™ 1.2	HDMI	Standard
640 x 480	60, 75, 85			X	X	VESA DMT, CVT 0.31M3
720 x 400	70			X	X	IBM VGA
800 x 600	60, 75, 85			X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85			X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85			X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85			X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85			X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85			X	X	VESA DMT
1280 x 960	60, 75, 85			X	X	VESA DMT
1280 x 1024	60, 75, 85			X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB			X	X	VESA DMT
1440 x 900	60, 60RB			X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85			X	X	VESA DMT
1680 x 1050	60, 60RB, 75			X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60			X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85			X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85			X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85			X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60, 75			X	X	CVT 3.15M3
2560 x 1440	59.951			X	X	CVT 3.69M9-R
2560 x 1600	60, 60 RB			X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60			X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M

### Technical Specifications – Graphics

4096 x 2160	24			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60			X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60			X	X	VESA (SMPTE 274M)
1920 x 1080	50			X	X	SMPTE 274M
1920 x 1080	30			X	X	SMPTE 274M
1920 x 1080	24			X	X	SMPTE 274M
1280 x 720	60			X	X	VESA (CEA-770.3)
1280 x 720	50			X	X	SMPTE 296M
720 x 480	60			X	X	MHL (CEA-770.2)

### NVIDIA® GeForce® GT 730 2GB PCIe x8 DP Graphics Card

#### Introduction

Get impressive graphics and high resolution dual-display performance in a low profile, PCI Express x8 graphics add-in card based on the NVIDIA® Kepler™ Graphics Processor. Improve your everyday PC, Web conferencing, and video or photo editing.

#### Memory

2GB GDDR5 64-bit wide frame buffer operating at 900 MHz

#### Controller Clock Speed

NVIDIA® Kepler™ GPU operating at 902 MHz

#### Multi-display Support

A maximum of 4 displays are supported by the card.

#### Graphics /API support

DIRECTX 12, Open GL 4.3, Open CL1.2, UVD 3

#### Output Connectors

1 x Dual-Link DVI-I, 1x DisplayPort™ 1.2; Includes DVI to VGA adapter  
Display Port output is multi-mode capable, support Audio, HBR2 and MST

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	VGA (DVI-VGA adapter)	DVI-D	DisplayPort™ 1.2	Standard
640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3

### Technical Specifications – Graphics

1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	CVT 3.15M3
2560 x 1440	59.951		X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB		X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	X	VESA (SMPTE 274M)
1920 x 1080	50		X	X	SMPTE 274M
1920 x 1080	30		X	X	SMPTE 274M
1920 x 1080	24		X	X	SMPTE 274M
1280 x 720	60		X	X	VESA (CEA-770.3)
1280 x 720	50		X	X	SMPTE 296M
720 x 480	60		X	X	MHL (CEA-770.2)
720 x 576	50		X	X	ITU-R BT.1358



### Technical Specifications – Graphics

640 x 480	60		X	X	CEA (VESA DMT)
-----------	----	--	---	---	----------------

\* >60 refresh rates only for analog (VGA) signaling

### NVIDIA® GeForce® GT 730 1GB PCIe x8 HDMI Graphics Card

<b>Memory</b>	1GB GDDR5 64-bit wide frame buffer operating at 2.5GHz.
<b>Controller Clock Speed</b>	NVIDIA® Kepler™ GPU operating at 901 MHz
<b>Multi-display Support</b>	A maximum of 2 displays are supported by the card
<b>Graphics /API support</b>	Supports Microsoft DirectX 12, OpenGL 4.4 and OpenCL 2 API, Shade Model 5 and DirectCompute 11
<b>Output Connectors</b>	1 x Dual-Link DVI-I; 1x HDMI; Includes DVI to VGA adapter

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	VGA (DVI-VGA adapter)	DVI-D	HDMI	Standard
640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	DMT, CVT 2.30MA/2.30MA-R

### Technical Specifications – Graphics

1600 x 1200	60, 75, 85	X	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	CVT 3.15M3
2560 x 1440	59.951		X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB		X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25			X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50				CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60				CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30			X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50				CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60				CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60		X	X	VESA (SMPTE 274M)
1920 x 1080	50		X	X	SMPTE 274M
1920 x 1080	30		X	X	SMPTE 274M
1920 x 1080	24		X	X	SMPTE 274M
1280 x 720	60		X	X	VESA (CEA-770.3)
1280 x 720	50		X	X	SMPTE 296M
720 x 480	60		X	X	MHL (CEA-770.2)

\* >60 refresh rates only for analog (VGA) signaling

### Technical Specifications – Graphics

#### AMD Radeon™ RX 480 4GB Graphics Card Graphics Card

<b>Memory</b>	<b>4GB 256-bit wide frame buffer operating at 1950 MHz.</b>
<b>Controller Clock Speed</b>	<b>AMD Polaris GPU operating at 1266 MHz</b>
<b>Multi-display Support</b>	<b>A maximum of 6 displays are supported by the card.</b>
<b>Graphics /API support</b>	<b>DIRECTX 12, Open GL 4.5, Open CL 2.0; AMD Video Coding Engine (VCE) 3.4; AMD Universal Video Decoder( UVD) 6.3</b>
<b>Output Connectors</b>	<b>3x Display Port, 1x HDMI</b>

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	DisplayPort™ 1.2	HDMI	Standard
640 x 480	60, 75, 85	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	CVT 3.15M3
2560 x 1440	59.951	X	X	CVT 3.69M9-R

### Technical Specifications – Graphics

2560 x 1600	60, 60RB	X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24	X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25	X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30	X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50	X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60	X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60	X	X	VESA (SMPTE 274M)
1920 x 1080	50	X	X	SMPTE 274M
1920 x 1080	30	X	X	SMPTE 274M
1920 x 1080	24	X	X	SMPTE 274M
1280 x 720	60	X	X	VESA (CEA-770.3)
1280 x 720	50	X	X	SMPTE 296M
720 x 480	60	X	X	MHL (CEA-770.2)

\* >60 refresh rates only for analog (VGA) signaling

### NVIDIA® GeForce® GTX 1060 3GB FH PCIe x16 Graphics Card

<b>Memory</b>	<b>3GB GDDR5 192-bit wide frame buffer operating at 4 GHz.</b>
<b>Controller Clock Speed</b>	<b>Nvidia Pascal GPU operating at 1506 MHz</b>
<b>Multi-display Support</b>	<b>A maximum of 4 displays are supported by the card.</b>
<b>Graphics /API support</b>	<b>DIRECTX 12, Open GL 4.5, Open CL1.2,</b>
<b>Output Connectors</b>	<b>1 x Dual-Link DVI-D, 3x DisplayPort™, 1x HDMI</b>

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	DVI-D	DisplayPort™	HDMI	Standard

### Technical Specifications – Graphics

640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83M4
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	CVT 3.15M3
2560 x 1440	59.951	X	X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB	X	X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30	X	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60	X	X	X	VESA (SMPTE 274M)
1920 x 1080	50	X	X	X	SMPTE 274M
1920 x 1080	30	X	X	X	SMPTE 274M

### Technical Specifications – Graphics

1920 x 1080	24	X	X	X	SMPTE 274M
1280 x 720	60	X	X	X	VESA (CEA-770.3)
1280 x 720	50	X	X	X	SMPTE 296M
720 x 480	60	X	X	X	MHL (CEA-770.2)

\* >60 refresh rates only for analog (VGA) signaling

### NVIDIA® GeForce® GTX 1070 8GB FH PCIe x16 Graphics Card

<b>Memory</b>	<b>8GB GDDR5 256-bit wide frame buffer operating at 4 GHz.</b>
<b>Controller Clock Speed</b>	<b>Nvidia Pascal GPU operating at 1506 MHz</b>
<b>Multi-display Support</b>	<b>A maximum of 4 displays are supported by the card.</b>
<b>Graphics /API support</b>	<b>DIRECTX 12, Open GL 4.5, Open CL1.2,</b>
<b>Output Connectors</b>	<b>1 x Dual-Link DVI-D, 3x DisplayPort™, 1x HDMI</b>

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	DVI-D	DisplayPort™	HDMI	Standard
640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R

### Technical Specifications – Graphics

1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	CVT 3.15M3
2560 x 1440	59.951	X	X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB	X	X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30	X	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	25		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60	X	X	X	VESA (SMPTE 274M)
1920 x 1080	50	X	X	X	SMPTE 274M
1920 x 1080	30	X	X	X	SMPTE 274M
1920 x 1080	24	X	X	X	SMPTE 274M
1280 x 720	60	X	X	X	VESA (CEA-770.3)
1280 x 720	50	X	X	X	SMPTE 296M
720 x 480	60	X	X	X	MHL (CEA-770.2)

\* >60 refresh rates only for analog (VGA) signaling

## NVIDIA® GeForce® GTX 1080 8GB FH PCIe x16 Graphics Card

### Memory

**8GB GDDR5X 256-bit wide frame buffer operating at 5 GHz.**

### Controller Clock Speed

**Nvidia Pascal GPU operating at 1607 MHz**

### Multi-display Support

**A maximum of 4 displays are supported by the card.**

### Graphics /API support

**DIRECTX 12, Open GL 4.5, Open CL1.2,**

### Output Connectors

**1 x Dual-Link DVI-D, 3x DisplayPort™ 1.2, 1x HDMI**

### Technical Specifications – Graphics

#### Supported Display Resolutions and Refresh Rates

**Note:** other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Refresh Rate*	DVI-D	DisplayPort™ 1.2	HDMI	Standard
640 x 480	60, 75, 85	X	X	X	VESA DMT, CVT 0.31M3
720 x 400	70	X	X	X	IBM VGA
800 x 600	60, 75, 85	X	X	X	VESA DMT, CVT0.48M3
1024 x 768	60, 75, 85	X	X	X	VESA DMT, CVT 0.79M3
1152 x 864	60, 75, 85	X	X	X	VESA DMT, CVT 0.83MA
1280 x 720	60, 75, 85	X	X	X	VESA DMT, CVT 0.92M9, CEA-770.3
1280 x 768	60, 60RB, 75, 85	X	X	X	VESA DMT, CVT 0.98M9/0.98M9-R
1280 x 800	60, 75, 85	X	X	X	VESA DMT
1280 x 960	60, 75, 85	X	X	X	VESA DMT
1280 x 1024	60, 75, 85	X	X	X	VESA DMT, CVT 1.31M4
1366 x 768	60, 60RB	X	X	X	VESA DMT
1440 x 900	60, 60RB	X	X	X	VESA DMT
1600 x 900	60, 60RB, 75, 85	X	X	X	VESA DMT
1680 x 1050	60, 60RB, 75	X	X	X	VESA DMT, CVT 1.76MA/1.76MA-R
1920 x 1080	60	X	X	X	VESA DMT, CVT 2.07M9, SMPTE 274M
1920 x 1200	60, 60RB, 75, 85	X	X	X	DMT, CVT 2.30MA/2.30MA-R
1600 x 1200	60, 75, 85	X	X	X	VESA DMT, 1.92M3
1920 x 1440	60, 75, 85	X	X	X	VESA DMT, CVT 2.76M3
2048 x 1536	60,75	X	X	X	CVT 3.15M3
2560 x 1440	59.951	X	X	X	CVT 3.69M9-R
2560 x 1600	60, 60RB	X	X	X	VESA DMT, CVT 4.10MA/4.10MA-R
3840 x 2160	24		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	25		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	30	X	X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	50		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
3840 x 2160	60		X	X	CVT-RBv1/v2 (8.29M9-R), SMPTE 274M
4096 x 2160	24		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M



### Technical Specifications – Graphics

4096 x 2160	25		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	30		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	50		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
4096 x 2160	60		X	X	CVT-RBv1/v2 (8.85M-R), SMPTE 274M
1920 x 1080	60	X	X	X	VESA (SMPTE 274M)
1920 x 1080	50	X	X	X	SMPTE 274M
1920 x 1080	30	X	X	X	SMPTE 274M
1920 x 1080	24	X	X	X	SMPTE 274M
1280 x 720	60	X	X	X	VESA (CEA-770.3)
1280 x 720	50	X	X	X	SMPTE 296M
720 x 480	60	X	X	X	MHL (CEA-770.2)

\* >60 refresh rates only for analog (VGA) signaling

### Technical Specifications – Hard Disk and Solid State Storage

## HARD DISK AND SOLID STATE STORAGE

### Redundant Array of Independent Drives (RAID) – Support RAID 0 and 1

Flexible implementation:

- RAID 0 (Striping)
- RAID 1 (Mirroring)
- Configurable email alerts
- RAID management software
- DPS Self-Test can be executed on physical hard drives while in RAID mode.
- The RAID Setup Utility (accessed through CTRL-R) can be protected by the F10 Setup password.

#### NOTE:

- HP tests and supports RAID 0.
- RAID 1 is the only RAID configuration offered via factory configurations. The pre-configured systems:
  - Are only available on the SFF and TWR form factors. The DM form factors do not support RAID as they do not allow for multiple common storage drives.
  - Are complete RAID systems and have both drives installed.
  - Have the necessary Option ROM configuration.
  - Include a preinstalled operating system that is mirrored mode out of the box.

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

<b>HP 1 TB 7.2K SATA 6.0Gb/s 2.5” Hard Disk Drive</b>		
<b>Capacity</b>	1,000,204,886,016 bytes	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	SATA 6 Gb/s	
<b>Buffer Size</b>	32 MB	
<b>Logical Blocks</b>	1,953,525,168	
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	12 ms
	Full-Stroke:	25 ms
<b>Height</b> (nominal)	0.374 in/9.5 mm	
<b>Width</b> (nominal)	Media diameter: 2.5 in/63.5 mm	
	Physical size: 2.75 in/70 mm	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	

### Technical Specifications – Hard Disk and Solid State Storage

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

#### HP 500 GB 7.2K SATA 6.0Gb/s 2.5” Hard Disk Drive\*

<b>Capacity</b>	500,107,862,016 bytes	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	SATA 6 Gb/s	
<b>Buffer Size</b>	16 MB	
<b>Logical Blocks</b>	976,773,168	
<b>Seek Time</b> (typical reads, includes controller overhead, including settling)	Single Track:	2.0 ms
	Average:	12 ms
	Full-Stroke:	25 ms
<b>Height</b> (nominal)	0.267 in/6.8 mm	
<b>Width</b> (nominal)	Media diameter: 2.5 in/63.5 mm	
	Physical size: 2.75 in/70 mm	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.		

#### 500GB\* 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive

<b>Formatted Capacity</b>	500,107,862,016 bytes	
<b>Spindle Speed</b>	7,200 rpm	
<b>Interface</b>	Serial ATA 3.0 (6.0 Gb/s)	
<b>Buffer Size</b>	16 MB	
<b>Logical Blocks</b>	976,773,168	
<b>Seek Time</b> (average)	Single Track:	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms

### Technical Specifications – Hard Disk and Solid State Storage

<b>Height (nominal)</b>	1 in/2.54 cm
<b>Width (nominal)</b>	Media diameter: 3.5 in/8.89 cm
	Physical size: 4 in/10.2 cm
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)
<p>*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.</p>	

<b>HP 1 TB* 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive*</b>		
<b>Formatted Capacity</b>	1,000,204,886,016 bytes	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	Serial ATA 3.0 (6.0 Gb/s)	
<b>Buffer Size</b>	32 MB	
<b>Logical Blocks</b>	1,953,525,168	
<b>Seek Time (average)</b>	Single Track:	2.0 ms
	Average:	11 ms
	Full-Stroke:	21 ms
<b>Height (nominal)</b>	1 in/2.54 cm	
<b>Width (nominal)</b>	Media diameter: 3.5 in/8.89 cm	
	Physical size: 4 in/10.2 cm	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<p>* For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.</p>		

<b>HP 2 TB* 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive*</b>		
<b>Formatted Capacity</b>	2 TB	
<b>Rotational Speed</b>	7,200 rpm	
<b>Interface</b>	SATA 6Gb/s NCQ	
<b>Cache, Multisegmented (MB)</b>	64 MB	
<b>Seek Time (average)</b>	Read	<8.5 ms
	Write	<9.5 ms

### Technical Specifications – Hard Disk and Solid State Storage

<b>Height</b>	1.028 in/26.11 mm
<b>Width</b>	4.0 in/101.6 mm
<b>Depth</b>	5.787 in/146.99 mm
<b>Weight</b>	1.38 lb/626 g
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

### HP 500 GB SATA 6G 2.5" 8GB Solid State Hybrid Drive (SSHD)\*

<b>Formatted Capacity</b>	500 GB	
<b>Spindle Speed</b>	5,400 rpm +/- 0.2%	
<b>Drive Type</b>	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
<b>Interface</b>	SATA 6 Gb/s	
<b>Cache Buffer</b>	64 MB	
<b>NAND Flash Commercial Multilevel Cell (cMLC)</b>	8 GB	
<b>Number of Sectors</b>	976,773,168	
<b>Seek Time</b> (typical reads)	Single Track:	2.0 ms
	Average:	12 ms
<b>Height</b>	0.268 +/- .008 in (6.8 +/- 0.2 mm)	
<b>Width</b>	2.750 +/- 0.010 in (69.85 +/- 0.25 mm)	
<b>Length</b>	3.951 +0.008 / -0.010 in (100.35 +0.20 / -0.25 mm)	
<b>Weight</b>	0.209 lb/95 g (max)	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

### Technical Specifications – Hard Disk and Solid State Storage

<b>HP 1 TB* SATA 6G 2.5" 8GB Solid State Hybrid Drive (SSHD)*</b>		
<b>Formatted Capacity</b>	1 TB	
<b>Spindle Speed</b>	5,400 rpm +/- 0.2%	
<b>Drive Type</b>	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
<b>Interface</b>	SATA 6 Gb/s	
<b>Cache Buffer</b>	64 MB	
<b>NAND Flash Commercial Multilevel Cell (cMLC)</b>	8 GB	
<b>Number of Sectors</b>	976,773,168	
<b>Seek Time (typical reads)</b>	Single Track:	2.0 ms
	Average:	12 ms
<b>Height</b>	0.374 +/- .008 in (9.5 +/- 0.2 mm)	
<b>Width</b>	2.750 +/- 0.010 in (69.85 +/- 0.25 mm)	
<b>Length</b>	3.951 +0.008 / -0.010 in (100.35 +0.20 / -0.25 mm)	
<b>Weight</b>	0.254 lb/115 g (max)	
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)	
<p>* For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.</p>		

<b>HP 1-TB SATA 6G 3.5" 8GB Solid State Hybrid Drive (SSHD)*</b>		
<b>Formatted Capacity</b>	1 TB	
<b>Spindle Speed</b>	7,200 rpm	
<b>Drive Type</b>	Solid State Hybrid Drive (SSHD) technology with NAND Flash	
<b>Interface</b>	Serial ATA (SATA)	
<b>Cache Buffer</b>	64 MB	
<b>NAND Flash Multilevel Cell (MLC)</b>	8 GB	
<b>Number of Sectors</b>	1,953,525,168	
<b>Seek Time (typical reads)</b>	Single Track:	2.0 ms

### Technical Specifications – Hard Disk and Solid State Storage

	Average:	11 ms
<b>Height</b>	0.783 in / 2.01 cm	
<b>Width</b>	4 in / 10.2 cm	
<b>Length</b>	5.79 in / 14.7 cm	
<b>Weight</b>	0.88 lb/400 g	
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)	
<p><b>*NOTE:</b> For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.</p>		

### 500GB\* 2.5" FIPS 140-2 SED Solid State Drive\*

<b>Formatted Capacity</b>	500 GB	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with SATA interface.	
<b>Interface</b>	Serial ATA (6.0 Gb/s)	
<b>Form Factor</b>	2.5 inch	
<b>Height</b>	6.80 mm ± 0.20	
<b>Width</b>	69.85 mm ± 0.25	
<b>Length</b>	100.35 mm ± 0.25/0.20	
<b>Weight (typical)</b>	<95 g (0.209 lb)	
<b>Bandwidth Performance</b>	Sustained data transfer rate OD	100 MB/s max
	I/O data-transfer rate	600 MB/s max
<b>Power</b>	Power consumption:	Spinup (max): 1.00A
		Idle, active: 0.70W
		Sleep 0.18W
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 140° F (0° to 60° C)
	Relative Humidity:	5% to 95%

### Technical Specifications – Hard Disk and Solid State Storage

	Shock:	Maximum 400 G/2 ms
<p><b>*NOTE:</b> For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.</p>		

<b>256GB* TLC SED SSD 2.5" FIPS Drive*</b>		
<b>Unformatted Capacity</b>	256 GB	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with SATA interface.	
<b>Interface</b>	Serial ATA (6.0 Gb/s)	
<b>Form Factor</b>	2.5 inch	
<b>Height</b>	7 mm	
<b>Width</b>	69.85 mm	
<b>Length</b>	100.45 mm	
<b>Weight (typical)</b>	10 g (0.022 lb) max	
<b>Bandwidth Performance</b>	Sequential read (128KB transfer)	530
	Sequential write (128KB transfer)	500
	Random read (4KB transfer)	55,000
	Random write (4KB transfer)	83,000
<b>Power</b>	SATA Power consumption	Sleep Typical: 2mw
		Idle, average: 55mw
		Active, average: 70mW
		Active maximum (128KB transfer): 3000 mW
	<b>Operating Temperature</b>	32° to 158° F (0° to 70° C)



### Technical Specifications – Hard Disk and Solid State Storage

<b>Environmental</b> (all conditions, non-condensing)	Relative Humidity	5% to 95%
	Non-operating Shock	1500 G/0.5ms
	Non-operating Vibration	5-800Hz @ 3.10G

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

#### 512GB\* TLC SED SSD 2.5" FIPS Drive\*

<b>Unformatted Capacity</b>	512 GB	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with SATA interface.	
<b>Interface</b>	Serial ATA (6.0 Gb/s)	
<b>Form Factor</b>	2.5 inch	
<b>Height</b>	7 mm	
<b>Width</b>	69.85 mm	
<b>Length</b>	100.45 mm	
<b>Weight (typical)</b>	10 g (0.022 lb) max	
<b>Bandwidth Performance</b>	Sequential read (128KB transfer)	530
	Sequential write (128KB transfer)	500
	Random read (4KB transfer)	92,000
	Random write (4KB transfer)	83,000
<b>Power</b>	SATA Power consumption	Sleep Typical: 2mw Idle, average: 55mw

### Technical Specifications – Hard Disk and Solid State Storage

		Active, average: 70mW Active maximum (128KB transfer): 4000 mW
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature	32° to 158° F (0° to 70° C)
	Relative Humidity	5% to 95%
	Non-operating Shock	1500 G/0.5ms
	Non-operating Vibration	5-800Hz @ 3.10G

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

### 256GB Turbo Drive G2 TLC Solid State Drive

<b>Unformatted Capacity</b>	256 GB	
<b>Architecture</b>	Solid State Drive with TLC NAND Flash and PCIE interface. Complies with NVMe Standard Power Saving Modes: L1 substates support Multi Queue support	
<b>Interface</b>	PCI-E Gen3 x 4	
<b>Form Factor</b>	M.2 2280	
<b>Height</b>	3.73 mm	
<b>Width</b>	22.00 ± 0.15 mm	
<b>Length</b>	80.00 ± 0.15 mm	
<b>Weight</b>	Up to 8 g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 2600 MB/s
	Sustained Sequential Write:	Up to 1000 MB/s
<b>Power</b>	Power consumption:	Active: Typical 6.1W; Idle: Typical 80mW L1.2: Typical 5mW

### Technical Specifications – Hard Disk and Solid State Storage

<b>Mean Time Between Failure (MTBF)</b>	1,500,000 hours	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/0.5 ms

### 512GB Turbo Drive G2 TLC Solid State Drive

<b>Unformatted Capacity</b>	512 GB	
<b>Architecture</b>	Solid State Drive with TLC NAND Flash and PCIe interface. Complies with NVMe Standard Power Saving Modes: L1 substates support Multi Queue support	
<b>Interface</b>	PCI-E Gen3 x 4	
<b>Form Factor</b>	M.2 2280	
<b>Height</b>	3.73 mm	
<b>Width</b>	22.00 ± 0.15 mm	
<b>Length</b>	80.00 ± 0.15 mm	
<b>Weight</b>	Up to 8 g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 2600 MB/s
	Sustained Sequential Write:	Up to 1200 MB/s
<b>Power</b>	Power consumption:	Active: Typical 6.1W; Idle: Typical 80mW L1.2: Typical 5mW
<b>Mean Time Between Failure (MTBF)</b>	1,500,000 hours	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%

### Technical Specifications – Hard Disk and Solid State Storage

	Shock:	1,500 G/0.5 ms
--	--------	----------------

<b>1TB Turbo Drive G2 TLC Solid State Drive</b>		
<b>Unformatted Capacity</b>	1 TB	
<b>Architecture</b>	Solid State Drive with TLC NAND Flash and PCIe interface. Complies with NVMe Standard Power Saving Modes: L1 substates support Multi Queue support	
<b>Interface</b>	PCI-E Gen3 x 4	
<b>Form Factor</b>	M.2 2280	
<b>Height</b>	3.73 mm	
<b>Width</b>	22.00 ± 0.15 mm	
<b>Length</b>	80.00 ± 0.15 mm	
<b>Weight</b>	Up to 8 g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 2600 MB/s
	Sustained Sequential Write:	Up to 1400 MB/s
<b>Power</b>	Power consumption:	Active: Typical 6.1W; Idle: Typical 80mW L1.2: Typical 5mW
<b>Mean Time Between Failure (MTBF)</b>	1,500,000 hours	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/0.5 ms

### Technical Specifications – Hard Disk and Solid State Storage

<b>500 GB* SATA 2.5" Self-Encrypting (SED) Opal 2 Solid State Drive*</b>		
<b>Unformatted Capacity</b>	500GB	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with 25nm MLC NAND Flash and SATA interface	
<b>Interface</b>	Serial ATA 2.0 (3.0 Gb/s)	
<b>NAND Flash</b>	25nm MLC NAND Flash	
<b>Height</b>	.275 in/7mm	
<b>Width</b>	2.75 in/69.85 mm	
<b>Length</b>	3.95 in/100.5 mm	
<b>Weight</b>	0.161 lb (73 g)	
<b>Bandwidth Performance</b>	Sustained Sequential 128k Read:	Up to 450 MB/s
	Sustained Sequential 128k Write:	Up to 260 MB/s
	Random 4k Read:	Up to 46K IOPs
	Random 4k Write:	Up to 56K IOPs
<b>Latency</b>	Read:	55 $\mu$ s
	Write:	55 $\mu$ s
<b>Power</b>	SATA power consumption:	160 mW (active average); <85 mW (idle average)
<b>Useful Drive Life</b>	72TB written, up to 40GB/day for 5 years	
	Operating Temperature:	32° to 158° F (0° to 70° C)
<b>Environmental</b> (all conditions, non-condensing)	Relative Humidity:	5% to 95%
	Shock:	1,500 G/1 ms

### Technical Specifications – Hard Disk and Solid State Storage

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

#### 256 GB SATA 2.5" TLC SED SSD Opal 2 Drive\*

<b>Unformatted Capacity</b>	256 GB 500,118,192 (User Addressable Sectors)	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with NAND Flash and SATA interface. Trusted Computing Group (TCG) OPAL 2.0 compliant encrypted solid state drive	
<b>Interface</b>	Serial ATA (6.0 Gb/s)	
<b>Form Factor</b>	2.5 inch	
<b>Height</b>	6.80 mm ± 0.20	
<b>Width</b>	69.85 mm ± 0.25	
<b>Length</b>	100.20 mm ± 0.25	
<b>Typical Weight</b>	37.4 g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 520 MB/s
	Sustained Sequential Write:	Up to 460 MB/s
<b>Power</b>	Power consumption:	Active: 3.891W; Idle: 0.085W
<b>Mean Time Between Failure (MTBF)</b>	1,500,000 hours	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/0.5 ms

\*NOTE: For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.

#### 512 GB SATA 2.5" TLC SED SSD Opal 2 Drive\*

### Technical Specifications – Hard Disk and Solid State Storage

<b>Unformatted Capacity</b>	512 GB 1,000,215,216 (User Addressable Sectors)	
<b>Architecture</b>	Self-Encrypting (SED) Solid State Drive with NAND Flash and SATA interface. Trusted Computing Group (TCG) OPAL 2.0 compliant encrypted solid state drive	
<b>Interface</b>	Serial ATA (6.0 Gb/s)	
<b>Form Factor</b>	2.5 inch	
<b>Height</b>	7 mm ± 0.20	
<b>Width</b>	69.85 mm ± 0.25	
<b>Length</b>	100.20 mm ± 0.25	
<b>Typical Weight</b>	37.4 g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 515 MB/s
	Sustained Sequential Write:	Up to 490 MB/s
<b>Power</b>	Power consumption:	Maximum active power: ≤4,400mW
		Average power: 70mW
		Slumber low power mode: 42mW – 52mW
<b>Mean Time Between Failure (MTBF)</b>	Up to 1,750,000 hours	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	0°C to 70°C (32°F to 158°F)
	Non-operating temperature and storage	-55°C to +85°C (-67°F to 185°F)
	Operating and non-operating shock	1,500 G/0.5 ms
<p><b>*NOTE:</b> For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 16 GB (for Windows 7) and 36 GB (for Windows 8.1/10) of system disk is reserved for the system recovery software.</p>		

### 512GB Turbo Drive G2 TLC OPAL2.0 SED Solid State Drive

<b>Unformatted Capacity</b>	512 GB
-----------------------------	--------

### Technical Specifications – Hard Disk and Solid State Storage

<b>Architecture</b>	Solid State Drive with TLC NAND Flash and PCIE interface. Complies with NVMe Standard Power Saving Modes: L1 substates support Multi Queue support TCG OPAL2.0 compliance	
<b>Interface</b>	PCI-E Gen3 x 4	
<b>Form Factor</b>	M.2 2280	
<b>Height</b>	3.73 mm	
<b>Width</b>	22.00 ± 0.15 mm	
<b>Length</b>	80.00 ± 0.15 mm	
<b>Weight</b>	Up to 8 g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 2200 MB/s
	Sustained Sequential Write:	Up to 1000 MB/s
<b>Power</b>	Power consumption:	Active: Typical 6.1W; Idle: Typical 40mW L1.2: Typical 5mW
<b>Mean Time Between Failure (MTBF)</b>	1,500,000 hours	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/0.5 ms

### 128GB SATA 2.5" Value (Non-SED) Solid State Drive

<b>Unformatted Capacity</b>	128 GB
<b>Architecture</b>	TLC NAND Flash
<b>Interface</b>	SATA 3.2 (6.0 Gb/s)



### Technical Specifications – Hard Disk and Solid State Storage

<b>Form Factor</b>	2.5 inch	
<b>Dimensions (W x D x H)</b>	6.98 x 10.05 x 0.7 cm	
<b>Weight</b>	31g	
<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 510 MB/s
	Sustained Sequential Write:	Up to 330 MB/s
	Random Read:	Up to 38K IOPs
	Random Write:	Up to 70K IOPs
<b>Power</b>	DC power requirement:	5 VDC 5%-100 mV ripple p-p
	Total power consumption:	50mW (active); 20mW (idle)
<b>Useful Drive Life</b>	72TB written, up to 40GB/day for 5 years	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/0.5 ms
NOTE: "For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software."		

### 256GB SATA 2.5" Value (Non-SED) Solid State Drive

<b>Unformatted Capacity</b>	256 GB
<b>Architecture</b>	TLC NAND Flash
<b>Interface</b>	SATA 3.2 (6.0 Gb/s)
<b>Form Factor</b>	2.5 inch
<b>Dimensions (W x D x H)</b>	6.98 x 10.05 x 0.7 cm
<b>Weight</b>	31g

### Technical Specifications – Hard Disk and Solid State Storage

<b>Bandwidth Performance</b>	Sustained Sequential Read:	Up to 510 MB/s
	Sustained Sequential Write:	Up to 330 MB/s
	Random Read:	Up to 38K IOPs
	Random Write:	Up to 70K IOPs
<b>Power</b>	DC power requirement:	5 VDC 5%-100 mV ripple p-p
	Total power consumption:	50mW (active); 20mW (idle)
<b>Useful Drive Life</b>	72TB written, up to 40GB/day for 5 years	
<b>Environmental</b> (all conditions, non-condensing)	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock:	1,500 G/0.5 ms
NOTE: "For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software."		

### 256GB SATA 2.5" TLC Solid State Drive

<b>Formatted Capacity</b>	256 GB
<b>Architecture</b>	Solid State Drive with SATA interface; ATA 8 Compliant and SATA 2.6 compliant
<b>Interface</b>	Serial ATA 3 (6.0 Gb/s)
<b>Form Factor</b>	2.5 inch
<b>Height</b>	7 mm ± 0.20
<b>Width</b>	69.85 mm ± 0.25
<b>Length</b>	100.2 mm ± 0.25
<b>Weight (typical)</b>	36.5 g (+2)

### Technical Specifications – Hard Disk and Solid State Storage

<b>Data Transfer Rate (128k Sequential)</b>	Sequential Read	Up to 500 MB/s
	Sequential Write	Up to 455 MB/s
<b>Power Watts</b>	Power consumption (avg):	Read: 95 mW Write: 95 mW Standby: 70 mW DEVSLP: <7 mW
<b>Environmental (all conditions, non-condensing)</b>	Operating Temperature:	32° to 158° F (0° to 70° C)
	Relative Humidity:	5% to 95%
	Shock (2 m Sec half-sine):	1500 G peak 0.5ms (operating)

### 512 GB SATA 2.5" TLC Solid State Drive\*

<b>Formatted Capacity</b>	512 GB	
<b>Architecture</b>	Solid State Drive with SATA interface; ATA 8 Compliant and SATA 2.6 compliant	
<b>Interface</b>	Serial ATA 3 (6.0 Gb/s)	
<b>Form Factor</b>	2.5 inch	
<b>Height</b>	7 mm ± 0.20	
<b>Width</b>	69.85 mm ± 0.25	
<b>Length</b>	100.2 mm ± 0.25	
<b>Weight (typical)</b>	36.5 g (+2)	
<b>Data Transfer Rate (128k Sequential)</b>	Sequential Read	Up to 500 MB/s
	Sequential Write	Up to 455 MB/s
<b>Power Watts</b>	Power consumption (avg):	Read: 95 mW Write: 95 mW Standby: 70 mW DEVSLP: <7 mW
	Operating Temperature:	32° to 158° F (0° to 70° C)

### Technical Specifications – Hard Disk and Solid State Storage

<b>Environmental</b> (all conditions, non-condensing)	Relative Humidity:	5% to 95%
	Shock (2 m Sec half-sine):	1500 G peak 0.5ms (operating)
<b>*NOTE:</b> For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.		

## Technical Specifications – Optical Disk Drives

<b>HP 9.5mm G3 800/600 Tower DVD-Writer</b> <b>HP 9.5mm G3 8/6/4 SFF G4 400 Microtower DVD-Writer</b> <b>HP 9.5mm AIO 800 G3 Slim DVD-Writer</b>		
<b>Height</b>	9.5 mm height	
<b>Orientation</b>	Either horizontal or vertical	
<b>Interface type</b>	SATA/ATAPI	
<b>Disc recording capacity</b>	Up to 8.5 GB DL or 4.7 GB standard	
<b>Dimensions (W x D x H)</b>	5.04 x 5.0 in x 0.37 (128 x 127 x 9.5 mm) without bezel	
<b>Weight (max)</b>	0.31 lb (140 g)	
	DVD-R DL	Up to 6X
	DVD+R	Up to 8X
	DVD+RW	Up to 8X
	DVD+R DL	Up to 6X
	DVD-R	Up to 8X
	DVD-RW	Up to 6X
	CD-R	Up to 24X
	CD-RW	Up to 10X
	DVD-RW, DVD+RW	Up to 8X
	DVD-R DL, DVD+R DL	Up to 8X
	DVD+R, DVD-R	Up to 8X
	DVD-ROM DL, DVD-ROM	Up to 8X
	CD-ROM, CD-R	Up to 24X
	CD-RW	Up to 24X
<b>Other Media</b>	M disc	DVD media for storage preservation
<b>Access time</b> (typical reads, including settling)	Random	DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical)
	Full Stroke	DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical)
	Stop Time	6 seconds (typical)
<b>Power</b>	Source	Slimline SATA DC power receptacle
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p
	DC Current	5 VDC (< 1000 mA typical, 1600 mA maximum)

### Technical Specifications – Optical Disk Drives

<b>Environmental conditions</b> (operating - non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%
	Maximum Wet Bulb Temperature	84° F (29° C)

#### HP 9.5mm G3 800/600 Tower DVD-ROM Drive

#### HP 9.5mm G3 800/600/400 SFF G4 400 Microtower DVD-ROM Drive

#### HP 9.5mm AIO 800 G3 Slim DVD-ROM Drive

<b>Height</b>	9.5mm	
<b>Orientation</b>	Either horizontal or vertical	
<b>Interface type</b>	SATA/ATAPI	
<b>Dimensions</b> (W x D x H)	5.04 x 5.0 x 0.37 in (128 x 127 x 9.5 mm) without bezel	
<b>Weight</b> (max)	Up to 0.31 lb (140g) without bezel	
<b>Read speeds</b>	DVD+R/-R/+RW/ -RW/+R DL /-R DL	Up to 8X
	DVD-ROM	Up to 8X
	CD-ROM, CD-R	Up to 24X
	CD-RW	Up to 24X
<b>Access time</b> (typical reads, including settling)	Random	DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical)
	Full Stroke	DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical)
<b>Power</b>	Source	Slimline SATA DC power receptacle
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p
	DC Current	5 VDC - <1000 mA typical, < 1600 mA maximum
<b>Environmental</b> (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%
	Maximum Wet Bulb Temperature (operating)	84° F (29° C)

---

## Technical Specifications – Memory

### System Memory Support

The HP EliteDesk 800 G3 Business PC supports DDR4 protocols with two independent, 64-bit wide channels each accessing one or two DIMMs.

- Two channels of non-ECC DDR4 unbuffered dual in-line memory modules (UDIMM) or DDR4 unbuffered small outline dual in-line memory modules (SO-DIMM) with a maximum of two DIMMs per channel
- Single-channel and dual-channel memory organization modes
- Data burst length of eight for all memory organization modes
- Memory data transfer rates of up to 2400 MT/s; actual supported data transfer rate determined by the configured processor.
- 64-bit wide channels
- DDR4 system memory I/O voltage of 1.2V
- Theoretical maximum memory bandwidth of:
  - 21.3 GB/s in dual-channel mode assuming 1333 MT/s
  - 25.6 GB/s in dual-channel mode assuming 1600 MT/s
  - 34.0 GB/s in dual-channel mode assuming 2133 MT/s
  - 38.4 GB/s in dual-channel mode assuming 2400 MT/s

### Platform Memory Support

- The Small Form Factor (SFF) and Microtower (MT) platforms support up to four (4) industry-standard DDR4-SDRAM DIMMs.

**CAUTION:** You must shut down the computer and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the computer is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

**NOTE:** For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.

## Technical Specifications - Networking and Communications

**NETWORKING AND COMMUNICATIONS**

<b>Intel® I219LM Gigabit Network Connection LOM (standard)</b>	
<b>Connector</b>	RJ-45
<b>System Interface</b>	PCIe + SMBus
<b>Controller</b>	Intel® I219LM Gigabit Ethernet Controller
<b>Data rates supported</b>	Supports operation at 10/100/1000 Mb/s data rates
<b>IEEE Compliance</b>	IEEE 802.3 Ethernet interface for 1000BASE-T, 100BASE-TX, and 10BASE-T applications (802.3ab, 802.3u, and 802.3i, respectively). IEEE 802.3az support [Low Power Idle (LPI) mode] IEEE 802.3u auto-negotiation conformance
<b>Performance</b>	Jumbo Frames (up to 9 kB) 802.1Q & 802.1p Receive Side Scaling (RSS) Two Queues (Tx & Rx)
<b>Power</b>	<ul style="list-style-type: none"> <li>• Ultra Low Power at cable disconnect (&lt;1 mW) enables platform support for connected standby</li> <li>• Reduced power consumption during normal operation and power down modes</li> <li>• Integrated Intel® Auto Connect Battery Saver (ACBS)</li> <li>• Single-pin LAN Disable for easier BIOS implementation</li> <li>• Fully integrated Switching Voltage Regulator (iSVR)</li> <li>• Low Power Link-Up (LPLU)</li> </ul>
<b>MAC/PHY Interconnect</b>	<ul style="list-style-type: none"> <li>• PCIe-based interface for active state operation (S0 state)</li> <li>• SMBus-based interface for host and management traffic (Sx low power state)</li> </ul>
<b>Management Interface</b>	<ul style="list-style-type: none"> <li>• MDC/MDIO management interface</li> </ul>
<b>Security &amp; Manageability</b>	<ul style="list-style-type: none"> <li>• Intel® vPro™ support with appropriate Intel® chipset components</li> </ul>

<b>Intel® Ethernet I210-T1 Gigabit Network Card</b>	
<b>Connector</b>	RJ-45
<b>System Interface</b>	PCI Express x1
<b>Controller</b>	Intel® I210 Gigabit Ethernet Controller
<b>Memory</b>	Integrated Dual 48K configurable transmit receive FIFO Buffers
<b>Data rates supported</b>	10/100/1000 Mbps



### Technical Specifications - Networking and Communications

<b>IEEE Compliance</b>	802.1P 802.1Q 802.2 802.3 802.3AB 802.3u 802.3x flow control
<b>Bus architecture</b>	PCI-E 2.1
<b>Data path width</b>	X1, 250 MB/s, Bi-directional interface
<b>Data transfer mode</b>	Bus-master DMA
<b>Hardware certifications</b>	FCC, B, CE, TUV-c, TUVus Mark Canada and United States, TUV-GS Mark for European Union
<b>Power requirement</b>	Aux 3.3 V, 3.0 Watts in 1000 base-T and 1.0 Watts in 100 Base-T
<b>Boot ROM support</b>	Yes
<b>Network Transfer Rate</b>	10BASE-T (half-duplex) 10 Mbps
	10BASE-T (full-duplex) 20 Mbps
	100BASE-TX (half-duplex) 100 Mbps
	100BASE-TX (full-duplex) 200 Mbps
	1000BASE-T (full-duplex) 2000 Mbps (actual rate limited by PCI Bus)
<b>Environmental</b>	Operating Temperature: 32° to 131°F (0° to 55° C)
	Operating Humidity: 85% at 131° F (55° C)
<b>Management</b>	WOL, PXE, DMI, WFM 2.0

### Intel® 8265 802.11ac 2x2 WiFi + Bluetooth® M.2 Combo Card\* (802.11AC Wave 2 supported)

	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	802.11b/g/n <ul style="list-style-type: none"> <li>2.402 – 2.482 GHz</li> </ul> <p>Note: The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.</p> 802.11a/n <ul style="list-style-type: none"> <li>4.9 – 4.95 GHz (Japan)</li> <li>5.15 – 5.25 GHz</li> <li>5.25 – 5.35 GHz</li> <li>5.47 – 5.725 GHz</li> <li>5.825 – 5.850 GHz</li> </ul>

### Technical Specifications - Networking and Communications

		Note: Indonesia no support this band)
<b>Data Rates</b>		<ul style="list-style-type: none"> <li>802.11b: 1, 2, 5.5, 11 Mbps</li> <li>802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)</li> </ul>
<b>Modulation</b>		Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
<b>Security<sup>1</sup></b>		<ul style="list-style-type: none"> <li>IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>AES-CCMP: 128 bit in hardware</li> <li>802.1x authentication</li> <li>WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>WPA2 certification</li> <li>IEEE 802.11i</li> <li>Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>WAPI</li> </ul>
<b>Network Architecture Models</b>		Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>		IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>		<ul style="list-style-type: none"> <li>802.11b : +16dBm minimum</li> <li>802.11g : +14dBm minimum</li> <li>802.11a : +14dBm minimum</li> <li>802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>802.11n HT40(2.4GHz) : +12dBm minimum</li> <li>802.11n HT20(5GHz) : +14dBm minimum</li> <li>802.11n HT40(5GHz) : +12dBm minimum</li> </ul>
<b>Power Consumption</b>		Transmit: 2.0 W (max) Receive: 1.6 W (max) Idle mode (PSP): 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connect Standby: 10 mW (WLAN+BT) Radio disabled: 30 mW
<b>Power Management</b>		ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>		802.11b, 1Mbps : -94dBm maximum 802.11b, 11Mbps : -86dBm maximum 802.11g, 6Mbps : -88dBm maximum 802.11g, 54Mbps : -74dBm maximum 802.11a, 6Mbps : -88dBm maximum 802.11a, 54Mbps : -74dBm maximum 802.11n, MCS07 : -69dBm maximum 802.11n, MCS15 : -66dBm maximum 802.11ac, 1SS, MCS-0 : -86dBm maximum 802.11ac, 1SS, MCS-9 : -61dBm maximum 802.11ac, 2SS, MCS-0 : -83dBm maximum 802.11ac, 2SS, MCS-9 : -58dBm maximum
<b>Antenna type</b>		High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth® communications

### Technical Specifications - Networking and Communications

	<b>Form Factor</b>	PCI-Express M.2 MiniCard	
	<b>Dimensions</b>	Type 2230 : 2.3 x 22.0 x 30.0 mm Or Type 1630 : 2.3 x 16.0 x 30.0 mm	
	<b>Weight</b>	Type 2230 : 2.8g Or Type 1630 : 2g	
	<b>Operating Voltage</b>	3.3v +/- 9%	
	<b>Temperature</b>	Operating	14° to 158° F (-10° to 70° C)
		Non-operating	-40° to 176° F (-40° to 80° C)
	<b>Humidity</b>	Operating	10% to 90% (non-condensing)
		Non-operating	5% to 95% (non-condensing)
	<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)
		Non-operating	0 to 50,000 ft (15,240 m)
	<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON	
		<ol style="list-style-type: none"> <li>1. Check latest software/driver release for updates on supported security features.</li> <li>2. Maximum output power may vary by country according to local regulations.</li> <li>3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li> </ol>	
	<b>HP Integrated Module with Bluetooth® 4.0/4.1/4.2 Wireless Technology</b>		
	<b>Bluetooth® Specification</b>	4.0/4.1/4.2 Compliant	
	<b>Frequency Band</b>	2402 to 2480 MHz	
	<b>Number of Available Channels</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)	
	<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels	
	<b>Transmit Power</b>	The Bluetooth® component shall operate as a Class II Bluetooth® device with a maximum transmit power of +4 dBm for BR and EDR.	
	<b>Receiver Sensitivity</b>	<b>Modulation</b>	<b>0.01% BER</b> <b>0.001% BER</b>
		GFSK	-80 dBm      -70 dBm
		π/4-DQPSK	-80 dBm      -70 dBm
		8DPSK	-80 dBm      -70 dBm
	<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW	
	<b>Range</b>	Legacy Up to 33 ft (10 m) BLE Up to 99 ft (30 m)	
	<b>Electrical Interface</b>	USB 2.0 compliant	
	<b>Bluetooth® Software Supported Link Topology</b>	Microsoft Windows Bluetooth® Software	
	<b>Electrical Interface Bluetooth® Software Supported Security</b>	Point to Point, Multipoint Pico Nets up to 7 slaves Full support of Bluetooth® Security Provisions	
	<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support	
	<b>Power Management Certifications</b>	Self-configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff	
	<b>Security</b>	All necessary regulatory approvals for supported countries, including:	
	<b>Certifications Bluetooth® Profiles Supported</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.249	

### Technical Specifications - Networking and Communications

	<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950
	<b>Certifications Bluetooth® Profiles Supported</b>	UL, CSA, and CE Mark UL, CSA, and CE Mark Serial Port Profile (SPP)1.2 Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN)1,1 Generic Object Exchange Profile (GOEP)1,2 Object Push Profile (OPP)1,2 Hard Copy Cable Replacement (HCRP)1,2 Personal Area Networking Profile (PAN)1.0 Human Interface Device Profile (HID)1.0 Hands Free Profile (HFP) 1.5/1.6 Advanced Audio Distribution Profile (A2DP) 1.3 Audio Video Remote Control Profile (AVRCP) 1.3/1.4
	<b>Bluetooth® V4.1/V4.2 support feature</b>	V4.1: ESR5/6/7 compliant V4.2: ESR8 compliant, LE Secure Connection – Basic
<p>*Wireless access point and internet access required. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.</p>		

<b>Intel® 7265 802.11ac 2x2 DualBand Combo PCIe x1 Card</b>		
	<b>Wireless LAN Standards</b>	IEEE 802.11 a IEEE 802.11 b IEEE 802.11 g IEEE 802.11 n IEEE 802.11 ac
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	802.11b/g/n <ul style="list-style-type: none"> <li>• 2.402 – 2.482 GHz</li> </ul> Note: The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels. 802.11a/n <ul style="list-style-type: none"> <li>• 4.9 – 4.95 GHz (Japan)</li> <li>• 5.15 – 5.25 GHz</li> <li>• 5.25 – 5.35 GHz</li> <li>• 5.47 – 5.725 GHz</li> <li>• 5.825 – 5.850 GHz</li> </ul> Note: Indonesia no support this band)
	<b>Data Rates</b>	<ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>• 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)</li> </ul>

### Technical Specifications - Networking and Communications

<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
<b>Security<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b : +16dBm minimum</li> <li>• 802.11g : +14dBm minimum</li> <li>• 802.11a : +14dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +13dBm minimum</li> <li>• 802.11n HT20(5GHz) : +12dBm minimum</li> <li>• 802.11n HT40(5GHz) : +12dBm minimum</li> <li>• 802.11ac 80MHz(5GHz) : +11dBm minimum</li> </ul>
<b>Power Consumption</b>	Transmit: 2.0 W (max) Receive: 1.6 W (max) Idle mode (PSP): 180 mW (WLAN Associated) Idle mode: 60 mW (WLAN unassociated) Radio disabled: 30 mW
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>	802.11b, 1Mbps : -94dBm maximum 802.11b, 11Mbps : -86dBm maximum 802.11g, 6Mbps : -88dBm maximum 802.11g, 54Mbps : -74dBm maximum 802.11a, 6Mbps : -86dBm maximum 802.11a, 54Mbps : -72dBm maximum 802.11n, MCS07 : -69dBm maximum 802.11n, MCS15 : -66dBm maximum 802.11ac, 1SS, MCS-0 : -86dBm maximum 802.11ac, 1SS, MCS-9 : -61dBm maximum 802.11ac, 2SS, MCS-0 : -83dBm maximum 802.11ac, 2SS, MCS-9 : -58dBm maximum
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth® communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	Type 2230 : 2.3 x 22.0 x 30.0 mm Or Type 1630 : 2.3 x 16.0 x 30.0 mm
<b>Weight</b>	Type 2230 : 2.8g Or Type 1630 : 2g

### Technical Specifications - Networking and Communications

	<b>Operating Voltage</b>	3.3v +/- 9%		
	<b>Temperature</b>	Operating	14° to 158° F (-10° to 70° C)	
		Non-operating	-40° to 176° F (-40° to 80° C)	
	<b>Humidity</b>	Operating	10% to 90% (non-condensing)	
		Non-operating	5% to 95% (non-condensing)	
	<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)	
		Non-operating	0 to 50,000 ft (15,240 m)	
	<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON		
	<p>4. Check latest software/driver release for updates on supported security features.</p> <p>5. Maximum output power may vary by country according to local regulations.</p> <p>6. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</p>			
	<b>HP Integrated Module with Bluetooth® 4.2 Wireless Technology</b>			
	<b>Bluetooth® Specification</b>	4.2 Compliant		
	<b>Frequency Band</b>	2402 to 2480 MHz		
	<b>Number of Available Channels</b>	79 (1 MHz) available channels		
	<b>Data Rates and Throughput</b>	3 Mbps data rate; throughput up to 2.17 Mbps		
		Synchronous Connection Oriented links up to 3, 64 kbps, voice channels		
		Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric		
	<b>Transmit Power</b>	The Bluetooth® component shall operate as a Class II Bluetooth® device with a maximum transmit power of +4 dBm for BR and EDR.		
	<b>Receiver Sensitivity</b>	<b>Modulation</b>	<b>0.01% BER</b>	<b>0.001% BER</b>
		GFSK	-80 dBm	-70 dBm
		π/4-DQPSK	-80 dBm	-70 dBm
		8DPSK	-80 dBm	-70 dBm
	<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW		
	<b>Range</b>	Up to 33 ft (10 m)		
	<b>Electrical Interface</b>	USB 2.0 compliant		
	<b>Bluetooth® Software Supported Link Topology</b>	Microsoft Windows Bluetooth® Software		
	<b>Electrical Interface</b>	Point to Point, Multipoint Pico Nets up to 7 slaves		
	<b>Bluetooth® Software Supported Security</b>	Full support of Bluetooth® Security Provisions		
	<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support		
	<b>Power Management Certifications</b>	Self-configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff		
	<b>Security</b>	All necessary regulatory approvals for supported countries, including:		
	<b>Certifications</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.249		
	<b>Bluetooth® Profiles Supported</b>			
	<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826		
		Low Voltage Directive IEC950		
	<b>Certifications</b>	UL, CSA, and CE Mark		
	<b>Bluetooth® Profiles Supported</b>	Serial Port Profile (SPP) <sup>1</sup> Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN) <sup>1,2</sup> Generic Object Exchange Profile (GOEP) <sup>1,2</sup>		

### Technical Specifications - Networking and Communications

		Object Push Profile (OPP) <sup>1,2</sup> File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) <sup>1,2</sup> Personal Area Networking Profile (PAN) <sup>1,2</sup> Human Interface Device Profile (HID) <sup>1,2</sup> FAX Profile (FAX) Basic Imaging Profile (BIP) <sup>2</sup> Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)
--	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Intel® 3168 802.11ac with PCIe x1 WLAN/ Bluetooth® Combo*</b>		
<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac	
<b>Interoperability</b>	Wi-Fi certification	
<b>Frequency Bands</b>	802.11b/g/n	2.402 – 2.482 GHz  <b>Note:</b> The FCC has declared as of January 1, 2015 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
	802.11a/n	4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz <b>Note: Indonesia only supports 5.725 - 5.825 GHz (CH149 - CH161)</b>
<b>Data Rates</b>	<ul style="list-style-type: none"> <li>802.11b: 1, 2, 5.5, 11 Mbps</li> <li>802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>802.11ac : MCS0 ~ MCS7, (1SS) (20MHz, 40MHz, and 80MHz)</li> </ul>	
<b>Modulation</b>	Direct Sequence Spread Spectrum  BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM	

### Technical Specifications - Networking and Communications

<b>Security<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul> <p><sup>1</sup> <a href="#">Check latest software/driver release for updates on supported security features.</a></p>
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	802.11r Fast Roaming
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b : +16dBm minimum</li> <li>• 802.11g : +14dBm minimum</li> <li>• 802.11a : +14dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +14dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT20(5GHz) : +14dBm minimum</li> <li>• 802.11n HT40(5GHz) : +12dBm minimum</li> <li>• 802.11ac 80MHz(5GHz) : +11dBm minimum</li> </ul> <p><sup>2</sup> <a href="#">Maximum output power may vary by country according to local regulations.</a></p>
<b>Power Consumption</b>	Transmit: 2.0 W (max) Receive: 1.6 W (max) Idle mode (PSP): 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connect Standby: 10 mW (WLAN+BT) Radio disabled: 5 mW
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>	802.11b, 1Mbps : -94dBm maximum 802.11b, 11Mbps : -86dBm maximum 802.11g, 6Mbps : -88dBm maximum 802.11g, 54Mbps : -74dBm maximum 802.11a, 6Mbps : -88dBm maximum 802.11a, 54Mbps : -74dBm maximum 802.11n, MCS07 : -69dBm maximum 802.11n, MCS15 : -66dBm maximum 802.11ac, 1SS, MCS-0 : -86dBm maximum 802.11ac, 1SS, MCS-9 : -61dBm maximum 802.11ac, 2SS, MCS-0 : -83dBm maximum 802.11ac, 2SS, MCS-9 : -58dBm maximum



### Technical Specifications - Networking and Communications

	<sup>3</sup> Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).	
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth® communications	
<b>Form Factors</b>	PCI-Express M.2 MiniCard	
<b>Dimensions</b>	Type 2230 : 2.3 x 22.0 x 30.0 mm Or Type 1630 : 2.3 x 16.0 x 30.0 mm	
<b>Weight</b>	Type 2230 : 2.8g Or Type 1630 : 2g	
<b>Operating Voltage</b>	3.3v +/- 9%	
<b>Temperature</b>	<b>Operating:</b>	14° to 158° F (-10° to 70° C)
	<b>Non-operating:</b>	-40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating:</b>	10% to 90% (non-condensing)
	<b>Non-operating:</b>	5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating:</b>	0 to 10,000 ft (3,048 m)
	<b>Non-operating:</b>	0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON	

\* Wireless access point and Internet service required and not included. Availability of public wireless access points limited.

#### HP Integrated Module with Bluetooth® 4.0/4.1/4.2 Wireless Technology

<b>Bluetooth® Specification</b>	4.0/4.1/4.2 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps
	BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

### Technical Specifications - Networking and Communications

<b>Transmit Power</b>	The Bluetooth® component shall operate as a Class II Bluetooth® device with a maximum transmit power of + 4 dBm for BR and EDR.		
<b>Receiver Sensitivity Legacy</b>	<b>Modulation</b>	<b>0.01% BER</b>	<b>0.001% BER</b>
	GFSK	-80 dBm	-70 dBm
	π/4-DQPSK	-80 dBm	-70 dBm
	8DPSK	-80 dBm	-70 dBm
<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW		
<b>Range</b>	Legacy Up to 33 ft (10 m) BLE Up to 99 ft (30 m)		
<b>Electrical Interface</b>	USB 2.0 compliant		
<b>Bluetooth® Software Supported Link Topology</b>	Microsoft Windows Bluetooth® Software		
<b>Electrical Interface Bluetooth® Software Supported Security</b>	Point to Point, Multipoint Pico Nets up to 7 slaves		
	Full support of Bluetooth® Security Provisions		
<b>Power Management Certifications</b>	Microsoft Windows ACPI, and USB Bus Support		
	Self-configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff		
<b>Security</b>	All necessary regulatory approvals for supported countries, including:		
<b>Certifications Bluetooth® Profiles Supported</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.249		
<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826		
	Low Voltage Directive IEC950		
<b>Certifications Bluetooth® Profiles Supported</b>	UL, CSA, and CE Mark		
	Serial Port Profile (SPP) <sup>1</sup> Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN) <sup>1,2</sup> Generic Object Exchange Profile (GOEP) <sup>1,2</sup> Object Push Profile (OPP) <sup>1,2</sup> Hard Copy Cable Replacement (HCRP) <sup>1,2</sup> Personal Area Networking Profile (PAN) <sup>1,2</sup>		

### Technical Specifications - Networking and Communications

	Human Interface Device Profile (HID) <sup>1,2</sup> Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)
	Audio Video Remote Control Profile (AVRCP)
<b>Bluetooth® V4.1/V4.2 support feature</b>	V4.1: ESR5/6/7 compliant
	V4.2: ESR8 compliant, LE Secure Connection – Basic.

### Technical Specifications - Audio

#### AUDIO DM/SFF/TWR

<b>High Definition Audio</b>	
<b>Type</b>	Integrated
<b>HD Stereo Codec</b>	Conexant CX20632
<b>Audio I/O Ports</b>	Headset connector supports a CTIA style headset and is re-taskable as a Line-in, Line-out, Microphone-in or Headphone-out port All ports are 3.5mm and support stereo ( see above tables for system configurations)
<b>Internal Speaker Amplifier</b>	2W class D mono amplifier for the internal speaker only. External speakers must be powered externally.
<b>Multi-streaming Capable</b>	Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front and rear jacks or integrated speaker.
<b>Sampling</b>	Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1 kHz to 192 kHz for DAC and 44.1 kHz to 96 kHz for ADC
<b>Wavetable Syntheses</b>	Yes - Uses OS soft wavetable
<b>Analog Audio</b>	Yes
<b># of Channels on Line-Out</b>	Stereo (Left & Right channels)
<b>Internal Mono Speaker</b>	Yes


#### AUDIO All-in-One

<b>High Definition Audio AIO</b>	
<b>Type</b>	Integrated
<b>HD Stereo Codec</b>	Conexant 2-channel CX5001 codec
<b>Audio I/O Ports</b>	Side Headset connector supports a CTIA style headset and is re-taskable as a Line-in, Line-out, Microphone-in or Headphone-out port Side Headphone port Rear Line-Out All ports are 3.5mm and support stereo ( see above tables for system configurations)
<b>Internal Speaker Amplifier</b>	2.2W per channel Class D amplifier for the internal speaker only. External speakers must be powered externally.
<b>Multi-streaming Capable</b>	Multi-streaming can be enabled in the audio control panel
<b>Sampling</b>	Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1 kHz to 192 kHz for DAC and 44.1 kHz to 96 kHz for ADC
<b>Wavetable Syntheses</b>	Yes – Uses OS soft wavetable
<b>Analog Audio</b>	Yes
<b># of Channels on Line-Out</b>	Stereo (Left & Right channels)
<b>Internal Stereo Speakers</b>	Yes

## Technical Specifications – Input/Output Devices

### Input/Output Devices

#### HP Conferencing Keyboard



<b>1.</b>	Function Keys	<b>6.</b>	End/Decline a Call
<b>2.</b>	F11 Lync or Skype for Business Contact list *	<b>7.</b>	Answer a Call
<b>3.</b>	F12 Lync or Skype for Business Calendar **	<b>8.</b>	Microphone Mute
<b>4.</b>	Share Screen	<b>9.</b>	Volume Up/Down
<b>5.</b>	Stop Webcam	<b>10.</b>	Audio Mute

\*Microsoft Lync 2013, or Skype for Business, or Microsoft Outlook 2013 Contact list

\*\*Microsoft Lync 2013, or Skype for Business, or Microsoft Outlook 2013 Calendar

<b>Dimensions (H x L x W)</b>	0.85 x 17.34 x 6.10 in (2.16 x 44.05 x 15.50 cm)
<b>Weight</b>	24.69 oz. ( 700 g)
<b>Connectivity</b>	USB cable
<b>Keys</b>	110 (US) Layout, 111 (EU) Layout – depending upon country
<b>Feature Summary</b>	Full-size ultra-quiet keyboard with numerical pad and 12 function keys One-touch simplicity for Microsoft Lync or Skype for Business calls with dedicated keys and LED light indicators
<b>Illuminated keys</b>	Incoming Call – Blinks Green Call in progress –Green Microphone Mute – Orange Audio Mute – Orange Screen Sharing – Orange

### Technical Specifications – Input/Output Devices

	Stop Webcam – Orange
<b>Other Call control keys</b>	End/Decline Call Volume up and down rocker key
<b>Microsoft Lync/Outlook</b>	Fn+F12 – Lync or Skype for Business Calendar will open. If Lync or Skype for Business is not available will bring Outlook Calendar * Fn+F11 – Lync or Skype for Business Contact will open. If Lync or Skype for Business is not available will bring Outlook Contact list *  * Fn+11 and Fn+12 function keys are not supported in Microsoft Windows 8.x Metro mode
<b>Functions Keys</b>	Fn+F10 – System Settings Fn+F9 – Devices Fn+F8 – Search Fn+F7 – Blank Fn+F6 – Up Brightness Adjustment Fn+F5 – Down Brightness Adjustment Fn+F4 – Display Options Fn+F3 – File Explorer Fn+F2 – System Lock Fn+F1 – System Sleep
<b>System requirements</b>	Available USB port Windows 7, Windows 8.x, and Windows 10 Server: Microsoft Lync Server 2010 or 2013 and Skype for Business Server 2015 Client: Microsoft Lync 2013 version 15.0.46xx or newer or Skype for Business Notes: <ul style="list-style-type: none"> <li>Limited support for Microsoft Lync 2010, Microsoft Lync 2013 Basic and Microsoft Metro Mode</li> <li>Screen brightness functions supported in select HP systems</li> </ul>
<b>Approvals EMC Product Safety</b>	FCC; CE; ACA(C-tick); EAC UL, CE Mark

<b>HP USB PS/2 Washable Keyboard</b>		
<b>Physical Characteristics</b>	Keys	104 (US) Layout, 105 (EU) layout - depending upon country
	Dimensions (L x W x H)	17.67x 6.62 x 1.38 in (449 x 168 x 35 mm)
	Weight	1.7 lb (0.77 kg) minimum
<b>Electrical</b>	Operating voltage	+ 5VDC ±5%
	Power consumption	50-mA maximum (with three LEDs ON)
	System interface	USB Type A plug connector
	ESD	CE level 4, 15-kV air discharge

### Technical Specifications – Input/Output Devices

	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft® PC 99 - 2001	Functionally compliant
<b>Mechanical</b>	Keycaps	Stepped -profile design
	Switch actuation	55-g nominal peak force with tactile feedback
	Switch life	20 million keystrokes
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	7 ft (2.2 m)
	Microsoft PC 99 - 2001	Mechanically compliant
	Acoustics	43-dBA maximum sound pressure level
<b>Environmental</b>	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	4° to 149° F (-20° to 65° C)
	Operating humidity	10% to 95% (non-condensing at ambient)
	Non-operating humidity	0% to 95% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence
<b>Approvals</b>	UL, cUL, FCC, CE, TUV GS, VCCI, BSMI, C-Tick, KCC, USB-IF, WHQL, EN/IEC 60601-1, IP66/NEMA4X	
<b>Ergonomic compliance</b>	ANSI HFS 100, ISO 9241-4, and TUVGS	

### HP USB Business Slim Smartcard Keyboard

<b>Physical Characteristics</b>	Keys	104, 105, 109 layout (depending upon country)
	Dimensions (W x D x H)	5.68 x 0.78 x 17.34 in (14.45 x 1.98 x 440.6 cm)
	Weight	1.32 lb (0.6± 0.1 kg)
<b>Electrical</b>	Operating voltage	5V
	Power consumption	200 mA
	System interface	USB Interface
	ESD	Air 12.5kV / Contact 8kV
	EMI - RFI	under 3dB
	Microsoft PC 99 - 2001	Conforms to FCC rules for a Class B computing device
<b>Mechanical</b>	Keycaps	Low-profile design
	Switch actuation	60±15g nominal peak force with tactile feedback
	Switch life	10 million keystrokes (Life tester)

### Technical Specifications – Input/Output Devices

	Switch type	Contamination-resistant switch membrane		
	Key-leveling mechanisms	For all double-wide and greater-length keys		
	Cable length	6 ft (1.8 m)		
<b>Environmental</b>	Acoustics	43-dBA maximum sound pressure level		
	Operating temperature	50° to 122° F (10° to 50° C)		
	Non-operating temperature	-22° to 140° F (-30° to 60° C)		
	Operating humidity	10% to 90% (non-condensing at ambient)		
	Non-operating humidity	20% to 80% (non-condensing at ambient)		
	Operating shock	40 g, six surfaces		
	Non-operating shock	80 g, six surfaces		
	Operating vibration	2-g peak acceleration		
	Non-operating vibration	4-g peak acceleration		
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence		
	Drop (in box)	30 in (76.2 cm) on concrete, 16-drop sequence		
<b>SmartCard Function</b>	Support	All ISO 7816 smart cards		
	Interface	Reads from and writes to all ISO7816-1, 2, 3, 4 memory and microprocessor smart cards (T=0, T=1)		
	Chipset	IDENTIVE CLOUD 2190 F		
	Standard APIs supported	PC/SC, EMV2000, CT-API		
	Power	USB Port		
		Short circuit detection (protects smart card and reader)		
		Power supply compliant with ISO7816 and EMV (5V, 60 mA)		
		Supports 3-V and 5-V cards		
	Power consumption	100-mA maximum draw		
	Communication	From card	9600 bps to 330,000 bps	
		From computer	12 Mbps (USB transfer speed)	
	Landing mechanism	Contact device	Friction contact	
		Card insertions rating	Up to 100,000 insertion cycles	
	Interface modes	CCID protocol		
Reader performance interface	USB connection			
Electro-magnetic standards	Europe	2004/108/EC		
	USA	USAFCC part 15		
<b>Approvals</b>	CE Marking; TUV; EAC; FCC; cULus/CSAus; ICES; RCM; VCCI; KCC; BSMI			
<b>Ergonomic Compliance</b>	ISO 9241-410, TUV GS			
<b>Kit Contents</b>	Keyboard, I/O Security and Documentation CD, warranty card			

### HP USB Business Slim Keyboard

<b>Physical characteristics</b>	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	171.97 x 68.35 x 8.27 in (436.8± 1.5 x 137.6± 1.0 x 21.0± 1.0 cm)



### Technical Specifications – Input/Output Devices

	Weight	1.32 lb (0.6± 0.08 kg)
<b>Electrical</b>	Operating voltage	+ 4.4 – 5.25VDC
	Power consumption	50-mA maximum (with 5 VDC power supplied and three LEDs ON)
	System interface	USB Type A plug connector
	ESD	Contact Discharge: 2, 4,6,8KV Air Discharge: 2, 4, 8,10,12.5KV
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft® PC 99 - 2001	Functionally compliant
<b>Mechanical</b>	Keycaps	Low-profile design
	Switch actuation	60±12.5g nominal peak force with tactile feedback
	Switch life	10 million keystrokes (Life tester)
	Switch type	Contamination-resistant switch membrane
	Key-leveling mechanisms	For all double-wide and greater-length keys
	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
<b>Environmental</b>	Acoustics	43-dBA maximum sound pressure level
	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	20% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration

### Technical Specifications – Input/Output Devices

	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	30 in (76.2 cm) on concrete, 16-drop sequence
<b>Approvals</b>	UL, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC	
<b>Ergonomic compliance</b>	ANSI HFS 100, ISO 9241-4, and TUVGS	
<b>Kit contents</b>	Keyboard	Installation Guide
	Warranty Card	Safety and Comfort Guide

<b>HP PS/2 Business Slim Keyboard</b>		
<b>Physical Characteristics</b>	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	171.97 x 68.35 x 8.27 in (436.8± 1.5 x 137.6± 1.0 x 21.0± 1.0 cm)
	Weight	1.32 lb (600± 80 g)
<b>Electrical</b>	Operating voltage	+ 4.4 – 5.25VDC
	Power consumption	50-mA maximum (with 5 VDC power supplied and three LEDs ON)
	System interface	PS/2 6-pin mini din connector
	ESD	Contact Discharge: 2, 4,6,8KV Air Discharge: 2, 4, 8,10,12.5KV
	EMI - RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC 99 - 2001	Functionally compliant
	Keycaps	Low-profile design
	Switch actuation	60±12.5g nominal peak force with tactile feedback
	Switch life	10 million keystrokes (Life tester)
	Switch type	Contamination-resistant switch membrane
Key-leveling mechanisms	For all double-wide and greater-length keys	

### Technical Specifications – Input/Output Devices

	Cable length	6 ft (1.8 m)
	Microsoft PC 99 - 2001	Mechanically compliant
<b>Environmental</b>	Acoustics	43-dBA maximum sound pressure level
	Operating temperature	50° to 122° F (10° to 50° C)
	Non-operating temperature	-22° to 140° F (-30° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	20% to 80% (non-condensing at ambient)
	Operating shock	N/A
	Non-operating shock	65 inch 2.9 ms, six surface; 30g 266 inch/second; 50g 266 inch/second six surface
	Operating vibration	2-g peak acceleration
	Non-operating vibration	Starting at 5 Hz, vary the frequency of vibration from 5 to 500 Hz and back to 5 Hz at a Logarithmic sweep rate of 1 octave per minute.
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
Drop (in box)	29.93 in (76 cm) on concrete, 16-drop sequence	
<b>Approvals</b>	UL, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC	
<b>Ergonomic compliance</b>	ANSI HFS 100, ISO 9241-4, and TUVGS	

### HP USB (Grey) Business Slim Keyboard

<b>Physical characteristics</b>	Keys	104, 105, 106, 107, 109 layout (depending upon country)
	Dimensions (L x W x H)	17.19 x 5.41 x 0.82 in (43.68±1.5 x 13.76±1.0 x 2.1 ±1.0 cm)
	Weight	1.32 lb (0.6± 0.08 kg)
<b>Electrical</b>	Operating voltage	+ 4.4 – 5.25VDC
	Power consumption	100-mA maximum (with 5 VDC power supplied and three LEDs ON)
	System interface	USB Type A plug connector
	ESD	Contact Discharge: 4, 6, 8 KV
	EMI – RFI	Air Discharge: 8, 10, 12 KV / 15 KV
	Microsoft PC 99 – 2001	Conforms to FCC rules for a Class B computing device; Functionally compliant
<b>Mechanical</b>	Keycaps	Low-profile design
	Switch actuation	Rubber dome + membrane

### Technical Specifications – Input/Output Devices

	Switch life	10 million
	Switch type	Rubber dome
	Key-leveling mechanisms	Link bar
	Cable length	For all double-wide and greater-length keys
	Microsoft PC 99 – 2001	Yes
<b>Environmental</b>	Acoustics	55-dBA maximum sound pressure level
	Operating temperature	10°C to 50°
	Non-operating temperature	-30°C to 90°
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	60% to 80% (non-condensing at ambient)
	Operating shock	40 g, six surfaces
	Non-operating shock	80 g, six surfaces
	Operating vibration	2-g peak acceleration
	Non-operating vibration	4-g peak acceleration
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
	Drop (in box)	30 in (76.2 cm) on concrete, 16-drop sequence
<b>Approvals</b>	FCC; CE; VCCI; BSMI; KC; EAC; RCM; TUV-GS; UL; RoHS; WEEE	
<b>Ergonomic compliance</b>	ANSI HFS 100; ISO 9241-4; and TUVGS	

### HP Wireless Business Slim Keyboard and Mouse

<b>Keyboard</b>	Dimensions ( L x W x H)	171.97 x 68.35 x 8.27 in (436.8± 1.5 x 137.6± 1.0 x 21.0± 1.0 cm)
	Weight – Without Two AA Alkaline Batteries	1.23 lb (560± 80 g)
<b>Mouse</b>	Dimensions (H x L x W)	1.46 x 4.53 x 2.47 in (37 x 115 x 62.9 mm)
	Weight – Without Two AA Alkaline Batteries	0.15 lb (67 g)
<b>Receiver</b>	Dimensions (H x L x W)	0.33x 1.79 x 0.72 in (8.4 x 45.5 x 18.4 mm)
	Weight	0.21 oz (5.9 g)
	Cable Length – Minimum	6 ft (1.8 m)
	Range	32.8 ft (10 m)
<b>System Requirements</b>	Available USB port for the receiver CD-ROM Drive *This system may require upgraded and/or separately purchased hardware and/or a DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality. See <a href="http://www.microsoft.com/windows/windows-7/">http://www.microsoft.com/windows/windows-7/</a> for details.	
<b>Approvals</b>	Product Safety	UL; CSA /TUV (Europe only); CE Mark; CB Report
	Ergonomics	ANSI; ISO (Europe only); GS Mark (Germany only)

### Technical Specifications – Input/Output Devices

	EMC	FCC; CE; ACA (-tick); BSMI; KC ; VCCI
	CE Mark	EN 55022:2010; EN 55024; EN 301489-1; EN 61000
	Design Guidelines for PCs	PC 99 – connector overmold colors; PC 2001 – full functionality
	Telecom	All local telecom requirements and approvals for intended markets
	USA	FCC Title 47 CFR, Par 15, Subpart C; other local requirements
	Country Support	US, Belgium, Switzerland, Spain, Denmark, Netherlands, France, Germany, Italy, Portugal, Sweden, Norway, Finland, UK, Poland, Czech Republic, Turkey, Greece, Austria, Bulgaria, Cyprus, Estonia, Hungary, Ireland, Latvia, Lithuania, Luxemburg, Malta, Romania, Slovakia, Slovenia, Vietnam, HK, Australia, NZ, Malaysia, Singapore, Indonesia, Philippines, Thailand, Canada, China, Japan, Korea, Taiwan, India, Venezuela, Ecuador, Russia, Ukraine, Israel, Croatia, United Arab Emirates, Peru, Brazil, Chile, Argentina, Mexico, South Africa, and up to 193 countries worldwide.
<b>Environmental</b>	Keyboard contains 25% post-consumer recycled plastic material.	

<b>HP PS/2 Mouse</b>		
<b>Dimensions</b> (H x L x W)	1.46 x 2.48 x 4.53 in (3.70 x 6.29 x 11.50 cm)	
<b>Weight</b>	3.53 oz (100g; +10g/- 5 g)	
<b>Environmental</b>	Operating temperature	-32° to 104°F (0° to 40° C)
	Non-operating temperature	-4° to 140°F (-20° to 60° C)
	Operating humidity	10% to 90% (non condensing at ambient)
	Non-operating humidity	10% to 90% (non condensing at ambient)
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
<b>Electrical</b>	Operating voltage	5 VDC ± 10%
	Power consumption	100mA
	System consumption	PS/2 mini-din connector

### Technical Specifications – Input/Output Devices

	ESD	CE level 4, 15 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft PC99 - 2001	Functionally compliant
<b>Mechanical</b>	Resolution	800 DPI
	Tracking speed	10 in/s (25.4 cm/s) maximum
	Acceleration	±15%
	Switch actuation	65±20 gf
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	80 km
	Cable length	6 ft (1.8 m)
	Microsoft PC99 - 2001	Mechanically compliant
<b>Scroll wheel</b>	Width	6 mm
	Diameter	22.5 ± 0.2 mm
	Maximum rotation force	50 gf-cm
	Switch type	Light force micro-switch
	Switch life	1 million operations
	Mechanical life	Minimum 200,000 revolutions
<b>Regulatory Approvals</b>	UL/cUL, FCC, CE Mark, TUV/GS, VCCI, KCC, BSMI, C-Tick	

### HP USB 1000dpi Laser Mouse

<b>Dimensions</b> (H x L x W)	1.47 x 4.53 x 2.47 in (37.3 x 114.97 x 62.86 mm)	
<b>Weight</b>	3.360 oz (102g)	
<b>Cable length</b>	70.9 in (180 cm)	
<b>System requirements</b>	Available USB port	
<b>Environmental</b>	Operating Temperature	32° to 104° F (0° to 40° C)
	Non-operating Temperature	-4° to 140° F (-20° to 60° C)
	Operating Humidity	10% to 90% (non-condensing at ambient)
<b>Mechanical</b>	Resolution	1000dpi
	Tracking Speed	45 cm/sec
	Cable Length	70.9 in (180 cm)

### HP USB PS/2 Washable Mouse

<b>Dimensions</b> (H x L x W)	1.56 x 2.44 x 4.61 in (3.95 x 6.21 x 11.7 cm)	
<b>Weight</b>	4.44 oz (126 g)	
<b>Environmental</b>	Operating temperature	-32° to 104°F (0° to 40° C)

### Technical Specifications – Input/Output Devices

	Non-operating temperature	-4° to 140°F (-20° to 60° C)
	Operating humidity	10% to 90% (non-condensing at ambient)
	Non-operating humidity	10% to 90% (non condensing at ambient)
	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
	Drop (out of box)	80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
<b>Electrical</b>	Operating voltage	5 VDC ± 10%
	Power consumption	100mA
	System consumption	PS/2 mini-din connector
	ESD	CE level 4, 15 kV air discharge
	EMI-RFI	Conforms to FCC rules for a Class B computing device
	Microsoft® PC99 – 2001	Functionally compliant
<b>Mechanical</b>	Resolution	400 ± 20% DPI
	Tracking speed	10 in/s (25.4 cm/s) maximum
	Acceleration	100 in/s/s (2.54 m/s/s)
	Switch actuation	61 g nominal peak force
	Switch life	3,000,000 operations (using Hasco modified tester)
	Switch type	Low force micro-switches
	Tracking mechanism life	155 mi (250 km) at average speed of 10 in/s
	Cable length	6 ft (1.8 m)
	Microsoft PC99 – 2001	Mechanically compliant
<b>Scroll wheel</b>	Width	8 mm
	Diameter	1.01 in (25.6 mm)
	Maximum rotation speed	48 rats/sec
	Switch type	Light force micro-switch
	Switch life	1 million operations
	Mechanical life	Minimum 200,000 revolutions
<b>Regulatory approvals</b>	Compliant	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC

### HP USB Hardened Mouse

### Technical Specifications – Input/Output Devices

Mouse Type	Wired optical mouse		
Interface	USB 2.0		
Dimensions (H x L x W)	114.97 x 62.92 x 37.3 mm (+/-0.3 mm) (11.49 x 6.29 x 1.46 in)		
Weight	92 g (+/-10 g) (3.2 oz)		
Cable length	1.8 M		
Tracking	X-Y Positioning	X-Y Wheel Resolution	1000 DPI
		Tracking Speed	Up to 30 in/sec in either X or Y direction
	Z Axis Wheel	Z Wheel Revolution	24 counts per revolution
		Tracking Speed	0 ~ 120 rpm
Environmental	Operating temperature	0° - 40°C	
	Non-operating temperature	-40° - 65°C	
	Operating humidity	90%	
	Agency Approvals	CE FCC RCM VCCI EMC EAC BSMI UL ICES-003 Class B KCC TUV/GS	
Electrical	Input Voltage & Current	4.4 ~ 5.25 VDC / 100 mA	
	Power Consumption	Under nominal 5 VDC power supplied, max current consumption is 100mA with tracking speed up to 30 in/sec	
Color	Black		
System requirements	Windows 10, Windows 8.1 32/64bit, Windows 7 32/64bit		

<b>HP Grey V2 Mouse</b>			
<b>Dimensions</b> (H x L x W)	1.46 x 4.53 x 2.48 in (3.72 x 11.5 x 6.29 cm) ±1 mm		
<b>Weight</b>	3.53 oz (100g; +10g/- 5 g)		
<b>Environmental</b>	Operating temperature	50° to 122°F (10° to 50° C)	
	Non-operating temperature	-22° to 140°F (-30° to 60° C)	
	Operating humidity	10% to 90% (non condensing at ambient)	
	Non-operating humidity	20% to 80% (non condensing at ambient)	



### Technical Specifications – Input/Output Devices

	Operating shock	40 g, 6 surfaces
	Non-operating shock	80 g, 6 surfaces
	Operating vibration	2 g peak acceleration
	Non-operating vibration	4 g peak acceleration
<b>Electrical</b>	Operating voltage	4.75~5.25 Vdc
	Power consumption (typical)	10mA
<b>Mechanical</b>	Connector	USB 2.0
	Type	3D mouse (3 keys and wheel)
	Resolution	800 DPI
	Sensor	PixArt vendor Optical USB mouse sensor. DIP
	Tracking speed	30 inch/sec (max)
	Tracking acceleration	8G(max), 1G=9.8m/s <sup>2</sup>
	Cable length	6 ft (1.8 m)
<b>Color</b>	Grey	
<b>Regulatory Approvals</b>	FCC, CE, ICES, C-TICK, VCCI, KCC, BSMI, ISO9241, Part 4, Computer Work Station Ergonomics compliance, IEC 801-2, IEC 1000-4-2, EN 55024:1998 + A1:2001 + A2:2003, European Standard EN 55022: 2006 Class B, CE Mark	

<b>HP USB Mouse</b>		
<b>Dimensions</b> (H x L x W)	2.5 x 4.5 x 1.5 in (63.5 x 114.3 x 38.1 mm)	
<b>Weight</b>	0.22 lb (99.79 g)	
<b>Color</b>	Black	
<b>Connector</b>	USB	
<b>Mechanical</b>	Resolution	800 DPI sensitivity
	Buttons	Two primary buttons and clickable scroll wheel

### Technical Specifications – Miscellaneous Features

## MISCELLANEOUS FEATURES

### Management Features

- Advanced Configuration and Power Management Interface (ACPI). Allows the system to wake from a low power mode. Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
- Dual State Power Button; acts as both an on/off button and a suspend-to-sleep button

### Serviceability Features

- Dual colored power LED on front of computer to indicate either normal or fault condition
- Diagnostic LED Explanation Table:
  - Power LED will blink red 2 to 5 times, then blink white 2 or more times, then repeat (with beep tones for each blink initially):
    - 2 red + 2 white User must provide file for BIOS recovery (USB storage typically)
    - 2 red + 3 white User must enter a key sequence to proceed with recovery by policy
    - 2 red + 4 white BIOS recovery is in progress
    - 3 red + 2 white Memory could not be initialized
    - 3 red + 3 white Graphics adaptor could not be found
    - 3 red + 4 white Power supply failure / not connected
    - 3 red + 5 white Processor not installed
    - 3 red + 6 white Current processor does not support an enabled feature
    - 4 red + 2 white Processor has exceeded its temperature threshold / system thermal shutdown
    - 4 red + 3 white System internal temperature has exceeded its threshold
    - 5 red + 2 white System controller firmware is not valid
    - 5 red + 3 white System controller detected BIOS is not executing
    - 5 red + 4 white BIOS could not complete initialization / PCA failure
    - 5 red + 5 white System controller rebooted the system after a health or recovery timer triggered
- HP PC Hardware Diagnostics UEFI:
  - This utility enables hardware level testing outside the operating system on many components. The diagnostics can be invoked by pressing F2 at POST, and is available as a download from HP Support
- System/Emergency ROM
- Flash ROM
- CMOS Battery Holder for easy replacement
- BIOS recovery files are maintained on the local OS drive when updating with HP BIOS Update and Recovery utility (HPBIOSUPDREC)
- 5 Aux Power LED on System PCA
- Processor ZIF Socket for easy Upgrade
- Over-Temp Warning on Screen (Requires IM Agents)
- Clear Password Jumper
- DIMM Connectors for easy Upgrade
- Clear CMOS Button
- NIC LEDs (integrated) (Green & Amber)
- Dual Color Power and HD LED - To Indicate Normal Operations and Fault Conditions
- Color coordinated cables and connectors
- Tool-less Hood Removal
- Front power switch
- System memory can be upgraded without removing the system board or any internal components
- Tool-less Hard Drive, CD & Diskette Removal
- Green Pull Tabs (SFF), and Quick Release Latches for easy Identification

### Technical Specifications – Miscellaneous Features

#### Additional Features

##### Tower Orientation

#### Description

Product can be oriented as either a desktop (horizontal) or a tower (vertical)

##### Drive Lock

Implementation of the industry standard ATA Security feature set. When enabled, it prevents software access to user data on the drive until one or two user-defined passwords are provided.

##### Boot Sectors Protection

MBR and GPT sectors of the hard drive are critical to booting the operating system. By saving the MBR or GPT data (depending on the how the OS was installed), the BIOS will be able to monitor for changes and allow the user to override them with the backup copy at boot-up.

##### Drive Protection System

DPS Access through F10 Setup during Boot

A diagnostic hard drive self- test. It scans critical physical components and every sector of the hard drive for physical faults and then reports any faults to the user. Running independently of the operating system, it can be accessed through a Windows-based diagnostics utility or through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced.

The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types of failures.

##### SMART Technology (Self-Monitoring, Analysis and Reporting Technology)

Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted.

##### SMART I - Drive Failure Prediction

Predicts failures before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count.

##### SMART II - Off-Line Data Collection

By avoiding actual hard drive failures, SMART hard drives act as "insurance" against unplanned user downtime and potential data loss from hard drive failure.

##### SMART III - Off-Line Read Scanning with Defect Reallocation

IOEDC: I/O Error Detection Circuitry

##### SMART IV - End-to-End CRC for hard drives

Detects errors in Read/Write buffers on HDD cache RAM.

Interface in F10 setup provides confirmation of SMART IV support.

After-Market Options (availability may vary by region)

### After Market Options

<b>Business Monitors</b> (sample list)*	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
HP EliteDisplay E272q 27-inch QHD Monitor	X	X		M1P04AA
HP EliteDisplay E242 24-inch Monitor	X	X		M1P02AA
HP EliteDisplay E232 23-inch Monitor	X	X		M1N98AA
*Additional models are available.				
<b>Communication Devices</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
Intel® Ethernet I210 - T1 Gbe NIC	X			E0X95AA
Intel® 7265 802.11ac 2x2 DualBand Combo PCIe x1 Card	X			N4G85AA
<b>Graphics Solutions</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
NVIDIA® GeForce® GT 730 2GB DP PCIe x8 Card	X			Z9H51AA
AMD® Radeon™ R7 450 4GB PCIe x16 Card	MT Only			Z9H52AA
HP UHD USB Graphics Adapter	X	X	X	N2U81AA
HP DisplayPort™ 1.2 Cable Kit	X	X	X	VN567AA
HP DisplayPort™ 1.2 To DVI-D Adapter	X	X	X	FH973AA
HP DisplayPort™ 1.2 To VGA Adapter	X	X	X	AS615AA
HP DisplayPort™ 1.2 To HDMI 4k Adapter	X	X	X	K2K92AA
HP DVI to DVI Cable	X	X	X	DC198A
HP (Bulk) 700mm DisplayPort™ 1.2 Cable Kit		X		V8Y77A6
HP USB-C to VGA Adapter (when Type-C Port is installed)	X	X		N9K76AA
HP USB-C to HDMI Adapter (when Type-C Port is installed)	X	X		N9K77AA
HP USB-C to DisplayPort™ 1.2 Adapter (when Type-C Port is installed)	X	X		N9K78AA
<b>Data Storage Drives</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
HP 500GB 7200PRM SATA 6.0Gb/s 3.5" Hard Drive	X			QK554AA
HP 1TB 7200rpm SATA 6Gb/s 3.5" Hard Drive	X			QK555AA
HP 256GB SATA TLC Solid State Drive	X	X	X	P1N68AA
HP 512GB Turbo Drive G2 TLC M.2 SSD Drive	X	X	X	X8U75AA
HP 9.5mm Slim Removable SATA 500GB	X		X	T7G14AA
HP 256GB SATA Non-SED Solid State Drive	X	X	X	W0U55AA
HP 9.5mm G3 800/600 Tower DVD Writer	MT Only			1CA52AA
HP 9.5mm G3 8/4 SFF G4 400 SFF/MT DVD Writer	SFF Only			1CA53AA
HP 9.5mm AiO 800 G3 Slim DVD Writer			AiO Only	Z9H62AA
<b>Input Devices</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
HP Conferencing Keyboard	X	X	X	K8P74AA

### After-Market Options (availability may vary by region)

HP USB Business Slim Keyboard	X	X	X	N3R87AA
HP PS/2 Business Slim Keyboard	X			N3R86AA
HP Wireless Business Slim Keyboard and Mouse**	X	X	X	QY449AA
HP USB Business Slim Grey Keyboard (EMEA only)	X	X	X	Z9H49AA
HP USB Business Slim Smart Card CCID Keyboard	X	X	X	Z9H48AA
HP USB PS/2 Washable Keyboard and Mouse Kit**	X	X	X	BU207AA
HP USB Grey V2 Mouse (EMEA only)	X	X	X	Z9H74AA
HP USB Business Slim Keyboard and Mouse (China Only)	X	X	X	Z9H50AA
HP USB Hardened Mouse	X	X	X	P1N77AA
HP PS/2 Mouse	X			QY775AA
HP USB Mouse	X	X	X	QY777AA
HP USB 1000dpi Laser Mouse	X	X	X	QY778AA
** Keyboard contains 25% post-consumer recycled plastic material				
<b>Desktop Mini Accessories</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
HP Desktop Mini DVD Super Multi-Writer ODD Expansion Module		X		K9Q83AA
HP Desktop Mini 500GB HDD/ I/O Expansion Module		X		K9Q82AA
HP Desktop Mini Rack Mount Tray Kit		X		G1K21AA
HP Desktop Mini Security/Dual VESA Sleeve		X		G1K22AA
HP Desktop Mini 65W Power Supply Kit		X		L2X04AA
HP Desktop Mini 90W Power Supply Kit		X		L4R65AA
HP Desktop Mini Vertical Chassis Stand		X		G1K23AA
HP Desktop Mini Port Cover Kit		X		1ZE52AA
HP Desktop Mini I/O Expansion Module		X		K9Q84AA
HP Integrated Work Center Desktop Mini/Thin Clients		X		G1V61AA
HP Single Monitor Arm		X	X	BT861AA
HP Quick Release Kit		X	X	EM870AA
HP PC Mounting Bracket for Monitors		X		N6N00AT
<b>System Memory</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
HP 4GB DDR4-2400 DIMM	X			Z9H59AA
HP 8GB DDR4-2400 DIMM	X			Z9H60AA
HP 16GB DDR4-2400 DIMM	X			Z9H57AA
HP 4GB DDR4-2400 SODIMM		X	X	Z9H55AA
HP 8GB DDR4-2400 SODIMM		X	X	Z9H56AA
HP 16GB DDR4-2400 SODIMM		X	X	Z9H53AA
<b>Multimedia Devices</b>	<b>SFF/MT</b>	<b>DM</b>	<b>AiO</b>	<b>Part Number</b>
HP Business Headset v2	X	X	X	T4E61AA
HP USB Business Speakers v2	X	X		N3R89AA

### After-Market Options (availability may vary by region)

<b>Security Devices</b>	<b><u>SFF/MT</u></b>	<b><u>DM</u></b>	<b><u>AiO</u></b>	<b><u>Part Number</u></b>
HP 800 G3 SFF Solenoid Lock and Hood Sensor	SFF only			1CA50AA
HP 800 G3 TWR Solenoid Lock and Hood Sensor	Tower only			J6L42AA
HP Business PC Security Lock v2 Kit	X			N3R93AA
HP Keyed Cable Lock 10mm Kit	X	X	X	T1A62AA
HP Dual Head Keyed Cable Lock Kit	X	X	X	T1A64AA
<b>Stands and Accessories</b>	<b><u>SFF/MT</u></b>	<b><u>DM</u></b>	<b><u>AiO</u></b>	<b><u>Part Number</u></b>
HP (10 Set) 600/800 G3 Tower Bezel Support Kit	Tower only			Z9H63A6
HP (10) 400 G4 600/800 G3 SFF G4 MT Bezel Support Kit	SFF only			Z9H64A6
HP Single Monitor Arm	X	X	X	BT861AA
HP EliteOne G3 800 AIO Recline Stand			X	Z9H67AA
HP EliteOne G3 800 AIO Adjustable Height Stand			X	Z9H66AA
<b>LANDESK Software (e-delivery)</b>	<b><u>SFF/MT</u></b>	<b><u>DM</u></b>	<b><u>AiO</u></b>	<b><u>Part Number</u></b>
Contact your HP representative for available options.				N/A

### After-Market Options (availability may vary by region)

© Copyright 2018 HP Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel, Celeron, Core, Pentium are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth® is a trademark of its proprietor, used by HP, Inc. under license. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. NVIDIA, GeForce and NVS are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. AMD and Radeon are trademarks of Advanced Micro Devices, Inc. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

### Change Log

Date	Version History	Action	Description of Change
January 25, 2017	From v1 to v2	Launch	QS launched
February 13, 2017	From v2 to v3	Update	Controller Clock Speed Updated from Graphics Section
February 20, 2017	From v3 to v4	Added	Added All-in-One models
February 28, 2017	From v4 to v5	Update	Bays section updated (disclaimer added)
March 2, 2017	From v5 to v6	Update	Accessories Updated (accessory added), Environmental Section updated
March 8, 2017	From v6 to v7	Added	Added Environmental Data for AiO models
March 9, 2017	From v7 to v8	Update	Weight and Dimensions updated, After market section updated (added accessory)
March 10, 2017	From v8 to v9	Update	Standard features and configurable components section updated
March 14, 2017	From v9 to v10	Update	Accessories updated
March 16, 2017	From v10 to v11	Update	Display specs updated
March 22, 2017	From v11 to v12	Update	Environmental Section Updated
April 5, 2017	From v12 to v13	Update	Graphics section updated
April 7, 2017	From v13 to v14	Update	OS section updated (note added)
April 17, 2017	From v14 to v15	Update	Ports section updated
April 27, 2017	From v15 to v16	Update	Graphics section updated
May 10, 2017	From v16 to v17	Update	DESKTOP MINI ACCESSORIES (optional) section updated
June 1, 2017	From v17 to v18	Update	Title updated
July 6, 2017	From v18 to v19	Update	SFF and TWR factors: Ports USB 2.0 & USB 3.1 Gen1 information updated
July 13, 2017	From v19 to v20	Update	Desktop Mini Accessories AMO section: P3R65AA deleted; 1ZE52AA added; I/O Ports — Internal ports section: Internal SATA storage connector(s) SFF changed from 4 to 3;
July 20, 2017	From v20 to v21	Update	Audio All-in-One section updated
July 21, 2017	From v21 to v22	Update	Environmental disclaimer updated
July 25, 2017	From v22 to v23	Update	“256GB Turbo Drive G2 TLC OPAL 2.0 SED Solid State Drive” section removal updated
August 9, 2017	From v23 to v24	Update	Dimensions & weight section updated
August 25, 2017	From v24 to v25	Update	Dimensions & weight section updated
September 5, 2017	From v25 to v26	Update	Environmental for 800 G3 SFF and 800 G3 TWR added individually
October 5, 2017	From v26 to v27	Update	DisplayPort™ version updated in the whole document
October 10, 2017	From v27 to v28	Update	Footnotes on “Software components and applications with windows” section fixed
October 16, 2017	From v28 to v29	Update	“Multi-unit packaging” and “Shipping weight” added to Weights and dimensions table
October 17, 2017	From v29 to v30	Update	GTX 1070 and GTX 1060 graphic cards added
October 18, 2017	From v30 to v31	Update	Environmental Data table for 400 G3 Non-touch AiO Business PC added (5 Gbit/s data speed) added to each USB 3.1 Gen1 Port in all call outs
October 31, 2017	From v31 to v32	Update	Power Supply section updated
December 4, 2017	From v32 to v33	Update	I/O Ports section updated
January 3, 2018	From v33 to v34	Update	Power factor information table added to Power supply section



### Change Log

January 24, 2018	From v34 to v35	Update	HP Desktop Mini Lock Box removed from the Accessories section
February 27, 2018	From v35 to v36	Update	Updated image for SFF
March 8, 2018	From v36 to v37	Update	Footnote added to Ports-Standard section
March 13, 2018	From v37 to v38	Update	Optional Discrete Graphics Solutions Graphic cards attached to 800 G3 TWR
April 13, 2018	From v38 to v39	Update	AMD Radeon™ R7 430 2GB LP 2DP PCIe x16 GF card specs added to MT and SFF
April 18, 2018	From v39 to v40	Update	AMD Radeon™ R7 430 2GB LP 2DP PCIe x16 GF card specs updated
April 23, 2018	From v40 to v41	Update	A note added to the below on the AiO 80 PLUS Gold and 80 PLUS Platinum on the power supply section (page 29)
May 2, 2018	From v41 to v42	Update	Removable storage write/boot control added to hardware security section