## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 8718699593537

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

**Product parameters** 

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consump mode (kWh/1000 up to the nearest	) h), rounded	5	Energy efficiency class	F		
Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º)	ers to the flux P), in a wide	500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode por expressed in W	wer (P <sub>on</sub> ),	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked stands for CLS, expresse rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer I	Height	142	Spectral power	See image		
dimensions	Width	112	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	112	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	40
			Chromaticity coordinates (x and y)	0,458 0,410
Parameters for	LED and OLED lig	ht sources:	· ·	
R9 colour rende	ring index value	1	Survival factor	0,90
the lumen main	tenance factor	0,93		
Parameters for	LED and OLED ma	ains light sources:		
displacement fa	ctor (cos φ1)	0,51	Colour consistency in McAdam ellipses	6
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (P	est LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-' : not applicable;

(b)'-' : not applicable;

