HP DesignJet Z6810 42-in Production **Printer**



The fastest high-quality production printing solution¹



IMPRESSIVE - Meet high-quality expectations

- Help your customers stand out from impactful photos to detailed maps/line drawings, with optimised printheads.
- Avoid rework with consistent, accurate colour across prints and printers, with embedded spectrophotometer.3
- Meet your customers' expectations for precise colours with HP Professional PANTONE® colour emulation.4

PRODUCTIVE – Increase your production volumes

- Accommodate production peaks with print speeds up to 16.4 m²/h (177 ft²/h) on glossy and 21.9 m²/h (236 ft²/h) on coated paper.⁵
- Handle more jobs with 500 GB hard disk
- Work without interruption with long media rolls and 775-ml HP ink cartridges.

RELIABLE - No need to change the way you

- Seamlessly integrate with the market-leading RIPs, enabled by HP's RIP certification program.²
- Turn operator efficiency into operating profit with HP SmartStream job preparation and processing
- Enjoy one-click printing that also helps reduce media waste using HP Click printing software.⁶

For more information, please visit http://www.hp.com/go/designjetz6810

Compared with large-format photo inks inkiet printers under €9,000 for graphics applications. Based on the fastest-rated colour speeds as published by manufacturers as of June, 2017. Test methods vary,

² For a list of HP certified RIPs, visit: https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c07798647 ³ Embedded in the HP DesignJet Z6810 Production Printer is an i1 spectrophotometer from X-Rite. Close collaboration between HP and X-Rite ensures a reliable solution that's been thoroughly tested to meet customer demands for ease, quality, and dependability.

4 HP Professional PANTONE® color emulation and Adobe PostScript®/PDF upgrade kit sold separately

⁵ Using glossy paper and Normal mode, HP DesignJet Z6810 42-in Production Printers can achieve print speeds up to 16.4 m²/h (177 ft²/h). Using coated paper and Normal mode, HP DesignJet Z6810 42-in Production Printers can achieve speeds up to 21.9 m²/h (236 ft²/h).

⁶ Requires an HP Applications Center account, internet connection, and connected internet-capable device. For more information, see http://www.hpapplicationscenter.com.

Print speed	Fast: 113.6 m²/hr on plain media Normal: 21.9 m²/hr on coated media Best: 11 m²/hr on glossy media¹
Print resolution	Up to 2400 x 1200 optimised dpi
Technology	HP Thermal Inkjet
Margins	Roll: 5 x 5 x 5 x 5 mm
Ink types	Pigment-based
Printheads	8 (2x matte black/chromatic red, 2x magenta/yellow, 2x light magenta/cyan, 2x photo black/light gray)
Printhead nozzles	2112 per colour
Line accuracy	±0.1%
Minimum line width	0.02 mm (HP-GL/2 addressable)
Color accuracy	Median < 1.25 dE2000, 95% of colors < 2.75 dE2000 ²
Short-term color stability	< 1 dE2000 in less than 5 minutes ²
Long-term print-to-print repeatability	Average < 0.5 dE2000, 95% of colors < 1.25 dE2000 ²
Max optical density	4.5 L* min/2.31 D ²
Media	
Handling	Roll feed, automatic horizontal cutter, media bin, take-up reel (optional)
Roll size	279 to 1067 mm
Maximum roll diameter	170 mm
Grammage	80 to 500 g/m²
Thickness	Up to 0.6 mm
Applications	Exhibition and event graphics; Graphics design; Indoor posters; Layouts and comps; Light boxes - paper; Line drawings Maps; Office Graphics; Orthophotos; Photo maps; Point of sale/display; POP/POS; Posters; Presentations; Renderings; Schematics; Echnical presentations
Memory	64 GB file processing (based on 1 GB RAM)
Hard disk	500 GB
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T); EIO Jetdirect accessory slot
Native print languages	HP-GL/2, HP-RTL, CALS G4
Print languages (optional)	Adobe PostScript 3; Adobe PDF 1.7; TIFF; JPEG
Drivers	Raster driver for Windows PostScript driver for Windows and macOS with optional PostScript/PDF Upgrade Kit
Security features	SNMPv3, Control Panel lock levels, Certificates management, iPsec, SSL, Secure file erase, Secure disk erase
Dimensions (W x D x H)	
Printer	1970 x 690 x 1370 mm
Shipping	2280 x 735 x 1200 mm

HP DesignJet Z6810 42-in Production Printer, spindle, printheads, introductory ink cartridges, maintenance cartridge, printer stand, media bin, 3-in spindle adapter kit, quick reference guide, setup poster, startup software, power cord Free: HP Applications Center, HP Click, printer drivers, HP DesignJet Utility including HP Color Center, HP Partner Link Payper-use, HP Web JetAdmin
Pay: HP SmartStream

Certification

Safety	EU (LVD and EN 60950-1 compliant); Russia (GOST)
Electromagnetic	Compliant with Class A requirements, including: EU (EMC Directive)
Environmental	ENERGY STAR; WEEE; RoHS (EU); REACH; EPEAT Bronze
Warranty	One-year limited hardware warranty

Ordering information

2QU12A	HP DesignJet Z6810 42-in Production Printer	
Accessories		
5EK00A	HP HD Pro 2 42-in Scanner	
5EK01A	HP SD Pro 2 44-in Scanner	
CQ745C	HP DesignJet PostScript/PDF Upgrade Kit	
CQ752A	HP DesignJet Z6200 1067mm Take-Up Reel	
L3J69AAE	HP SmartStream Preflight Manager	
L3J79AAE	HP SmartStream Print Controller for HP DesignJet Z6xx0 Production Printers	
06715A	HP Design let I Iser Maintenance Kit	

Original HP printing supplies

originat in printing supplies		
P2V97A	HP 774 Matte Black/Chromatic Red DesignJet Printhead	
P2V98A	HP 774 Light Magenta/Cyan DesignJet Printhead	
P2V99A	HP 774 Magenta/Yellow DesignJet Printhead	
P2W00A	HP 774 Photo Black/Light Gray DesignJet Printhead	
P2W02A	HP 774 775-ml Chromatic Red DesignJet Ink Cartridge	
C1Q37A	HP 773C 775-ml Matte Black DesignJet Ink Cartridge	
C1Q39A	HP 773C 775-ml Magenta DesignJet Ink Cartridge	
C1Q40A	HP 773C 775-ml Yellow DesignJet Ink Cartridge	
C1Q41A	HP 773C 775-ml Light Magenta DesignJet Ink Cartridge	
C1Q42A	HP 773C 775-ml Cyan DesignJet Ink Cartridge	
C1Q43A	HP 773C 775-ml Photo Black DesignJet Ink Cartridge	
C1Q44A	HP 773C 775-ml Light Gray DesignJet Ink Cartridge	
CLICAAA	UD 771 Decign let Maintenance Cartridge	

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

@@Original HP large format printing materials@@

HP Everyday Matte Polypropylene HP Artist Matte Canvas

HP Arust Matte Carwas
HP Super Heavyweight Plus Matte Paper (FSC® certified)³ (Recyclable)⁴
HP Premium Instant-dry Satin Photo Paper (FSC® certified)³ (Recyclable)⁴
HP Premium Vivid Color Backlit Film

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U9WE3E HP 3 year Next Business Day plus Defective Media Retention Support
U9WE5E HP 5 year Next Business Day plus Defective Media Retention Support
U9WE5E HP 1 year Post Warranty, Next Business Day plus Defective Media Retention Support
U9WE6PE HP 2 year Post Warranty, Next Business Day plus Defective Media Retention Support
H4518E HP Installation Service with Network Setup

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

Mechanical printing time with Original HP Vivid Photo Inks

Mechanical printing time with original HP Vivid Proto Inks.

With HP Premium Instant-dry Satin Photo Paper with HP Vivid Photo Inks.

3 BMG trademark license code FSC®-C115319, see http://www.fs.corg, HP trademark license code
FSC®-C017543, see http://www.fs.corg, Not all FSC®-certified products are available in all regions.

Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices, or can be returned through the HP Large Format Media take-back program.

Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.























Weight Shipping

What's in the box

HP Software and solutions

5 to 40°C

20 to 80% RH -20 to 55ºC

53 dB(A) (operating), 39 dB(A) (idle), 39 dB(A) (sleep)

7.0 B(A) (operating), 5.5 B(A) (idle), 5.5 B(A) (sleep)

270 W (printing); < 48 W (ready); < 5.3 W (sleep); < 0.3 W (off)

Input voltage (auto ranging): 100-127 V (±10%), 5 A; 220-240 V (±10%), 3 A; 50/60 Hz (±3 Hz)

Environmental ranges Operating temperature

Operating humidity

Storage temperature Acoustics

Sound pressure Sound power

Power Consumption