HP DesignJet Z6 PostScript® Printer series



High-definition prints, fast and secure. More quality with fewer inks.



PRECISE—Clearly distinguish subtle details

- Read details more clearly and see high-contrast colour with new high-definition HP printheads.
- No need for light inks with HP's dual drop technology.
- Get smooth gradients, even for challenging colour combinations, with HP Pixel Control.
- Work with water- and fade-resistant prints, indoors and out, with HP Vivid Photo Inks ¹

FAST—Work without delays

- Handle even the most complex files with powerful processing architecture and the Adobe PDF Print Engine.²
- Cut maps to different sizes in fewer steps with the first printer including an integrated vertical trimmer.³
- Print up to 20% faster⁴ with 2400 nozzle-perinch, high-definition HP printheads.
- Spend less time on media changes and adjustments with dual roll support and automatic roll switching.³

SECURE—Protect your work and your information

- Protect printers/data from unauthorized access with HP Secure Boot, whitelisting, and encrypted hard disk.
- Protect documents, preserve confidentiality with authentication solutions like PIN printing, card readers.⁵
- Secure your printers with HP JetAdvantage Security Manager; manage your fleet remotely with HP Web Jetadmin.

For more information, please visit http://www.hp.com/go/designjetZ6

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ Performance may vary based on writing system differences. Print permanence estimates by HP Image Permanence Lab based on the same formulation of HP Vivid Photo Inks used with the HP DesignJet Z6200 Photo Production Printer, using 6 inks. Water resistance performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. Display permanence rating for interior displays/away from direct sunlight by HP Image Permanence Lab on a range of HP media. For more information, see http://www.HPLFMedia.com/printpermanence

² The Adobe PDF Print Engine (APPE) is Adobe's high speed, high sp

³ Vertical trimmer and dual rolls included with the HP DesignJet Z6dr 44-in PostScript® Printer with V-Trimmer only.
4 Based on internal HP testing. Up to 20% faster printing compared to the HP DesignJet Z2600 PostScript® Printer and HP DesignJet Z5600 PostScript® Printer. May vary depending on print mode and media type.

⁵ Card reader functionality enabled through optional third-party solutions.

Technical specifications

D	ri	n	٠	

Piets pessed Ref. 65 9 m²/m on place media Recmit 13 2 m²/m on coated media Recmit 13 2 m²/m on place y media Rechology Ref. 15 m²/m on place y media Rechology Ref. 15 m²/m on place y media Rechology Rechol	Print		
Rechnology AP Thermal Biology Roll 15 x 5 x 5 x 5 mm (borderless on selected media ¹) Select 5 x 17 x 5 x 5 mm (borderless on selected media ¹) Printheology Printh	Print speed	Normal: 15.2 m²/hr on coated media	
Regins Services 5.5 x 5 mm borderless on selected media*) Sheet 5.8 x 1.5 x 5.5 mm borderless on selected media*) Sheet 5.8 x 1.5 x 5.5 mm borderless on selected media*) Sheet 5.8 x 1.5 x 5.5 mm borderless on selected media*) Sheet 5.8 x 1.5 x 5.5 mm borderless on selected media*) Protheads on 7.7 pl duta*-long weight (M, C, POC 6 pl single-drop weight (Y, CR, MK) Protheads nazzles 2.112 per colour; 12,672 in total Line acturary 2.118 per colour; 12,672 in total Line acturary 3. com POF addressable @ 1200 dp) Short-term color stability 3. com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.2 com POF addressable @ 1200 dp) Short-term color stability 4.1 com POF addressable @ 1200 dp) Short-term color stability 4.2 com POF addressable @ 1200 dp) Short-term color stability 4.2 com POF addressable @ 1200 dp) Short-term color stability 4.2 com POF addressable @ 1200 dp) Thischessable gp) 4.3 com POF addressable @ 1200 dp) 4.3 com POF addressable @ 1200 dp) 4.4 com POF addressable @ 1200 dp) 4.5 c	Print resolution	Up to 2400 x 1200 optimised dpi	
Sheet 5 x 17 x 5 x 5 mm bit types Pigranet based Ink drop 7/3 pl dual-drop weight (M, C, PRC, 6 pt single-drop weight (Y, CR, Md) Printheads 3 universal printheads (solar of colours) Printhead nozilor 2 11 2 per colours (12,672 n total Une accuracy 20,1% Printhead nozilor 20,2 mm (PDF addressable @1 200 dp) Ober term color stability 4 color stability 4 color stability 4 color stability 5 color stability 6 color stability 6 color stability 6 color stability 7 color stability 7 color stability 7 color stability 8 color stability 9 color stability 9 color stability 1 color stabilit	Technology	HP Thermal Inkjet	
ink drop 7/3 pl dual-drop weight M.C. PRC; 6 pt single-drop weight (Y. CR, MK) Printheads 3 universal printheads (solar for all colours) Printhead nozales 2112 per colour 12.672 in total Une accuracy 20.1% Minimum line width 30.2 mm PDF addressable @ 1200 dpb Short-term color stability 4.1 mm 20.2000 n less than 5 minutes* Long-term print-to-print repeated by 1.1 mm 20.2000 n less than 5 minutes* Long-term print-to-print repeated by 1.1 mm 20.2000 n less than 5 minutes* Long-term print-to-print repeated by 1.1 mm 20.25 D* Media Heading Roll feed, rear sheef feed, media output bin, automatic horizontal cutter Roll size 279 to 610 - mm Majorium roll diameter 135 mm Shandard sheets A4, A3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.3 mm Applications Bonness; Exhibition and event graphics; Light bowes - filin; Maps, Orthophotos; Point of saleddsplay; Posters Memory 128 08 (virtual)* Interfaces Gagble Ethernet (1000Base-1) (802.3, 802.34, 802.34b); Hi-Speed USS-2.0 certified interface for direct printing from USB than drive Nature print languages Andre Post-Script 3, Adobe PDE 1.7, TRF, PEG, CALS GA, HP-GL/2, HP-STI. Printing paths Applications He Pictures (1000 Sase-1) (802.3, 802.34, 802.34b); Hi-Speed USS-2.0 certified interface for direct printing from USB than drive Nature print languages Applications (1000 Sase-1) (802.3, 802.34, 802.34b); Hi-Speed USS-2.0 certified interface for direct printing from USB than drive Nature print languages Applications (1000 Sase-1) (802.3, 802.34b); Hi-Speed USS-2.0 certified interface for direct printing from USB than drive Nature print languages Applications (1000 Sase-1) (802.3, 802.34b); Hi-Speed USS-2.0 certified interface for direct printing from USB than drive Nature print languages Applications (1000 Sase-1) (802.3, 802.34b); Hi-Speed USS-2.0 certified interface for direct printing from USB than drive Nature printing languages Applications (1000 Sase-1) (1000 Sase-1) (1000 Sase-1) (1000 Sase-1) (1000 Sase-1) (1000 Sase-1) (1000 Sase-	Margins		
Printheads 3 universal printheads (valid for all colours) Printhead nozales 2112 per colour; 12,672 in total Line accuracy 20,13½ Minimum line width 0,02 mm (PDF addressable @ 1200 dp) Short-term color stability 1,02 mm (PDF addressable @ 1200 dp) Short-term color stability 1,02 mm (PDF addressable @ 1200 dp) Short-term color stability 1,00 mm (PDF addressable @ 1200 dp) Short-term color stability 1,00 mm (PDF addressable @ 1200 dp) Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 1.4 dE20007 Max optical density 4 the molor of the warage < 0.5 dE2000, 95% of colours < 0.5 dE	Ink types	Pigment-based	
Printhead nazzles 2112 per colour; 12,672 in total Line accuracy 40,1%* Line accuracy 40,1%* Short-term color stability 0,02 mm PDP addressable @ 1200 dpi) Short-term color stability 1,02 mm PDP addressable @ 1200 dpi) Short-term color stability 1,02 mm PDP addressable @ 1200 dpi) Short-term color stability 1,00 mm PDP addressable @ 1200 dpi) Short-term color stability 1,00 mm PDP addressable @ 1200 dpi) Short-term color stability 1,00 mm PDP addressable @ 1200 dpi) Masc aprical density 4,1 mm/2.5 D7 Media	Ink drop	7/3 pl dual-drop weight (M, C, PK); 6 pl single-drop weight (Y, CR, MK)	
Une accuracy 8.0.1% ** Minimum line width 0.02 mm (PDP addressable @ 1200 dp) Short-term dotor stability 1.1 @2000 in less than 5 minutes? Long-term print-to-print repeat-bability 1.2 (2000 in less than 5 minutes? Long-term print-to-print Average < 0.5 dE2000, 95% of colours < 1.4 dE20007 Repeat delivery 4.1 minutes of 2.7 minutes? Make optical density 4.1 minutes of 2.7 minutes? Media 7.2 (2000 in less than 5 minutes? Planding Roll feed, rear sheet feed, media output bin, automatic horizontal outlet? Roll seas 2.79 to 510-mm Maximum roll dameter 135 mm Sheet size 2.79 to 510 v 179 to 610 x 1676 mm Sheet size 2.70 to 779 to 610 x 1676 mm Sheet size 2.70 to 779 to 610 x 1676 mm Sheet size 2.70 to 779 to 610 x 1676 mm Sheet size 3.7 minutes of 3.7 mi	Printheads	3 universal printheads (valid for all colours)	
Minimum line width	Printhead nozzles	2112 per colour; 12,672 in total	
Short-term color stability	Line accuracy	±0.1% ⁵	
Long-term print-to-print repeatability Average < 0.5 dE2000, 95% of colours < 1.4 dE2000 ⁷ Media Handling Roll feed, rear sheet feed, media output bin, automatic horizontal cutter Roll size 279 d 610-mm Maximum roll diameter 135 mm Sheet size 210 x 279 to 610 x 1576 mm Sandard sheets A4, A3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.8 mm Applications Banness; Exhibition and event graphics; Light boxes - film; Maps, Orthophotos; Point of sale/display; Posters Memory 128 68 februall³ Hard disk 500 GB self-encrypting Connectivity Interfaces Glapbit Ethernet (1000Base-T) (802.3, 802.3a, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive. Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, IPEG, CALS GAI, HP-GL/2, HP-RTL. Apple AirPrint, direct printing from USB flash drive, emal printing, IPE (lisk, HP driver for macOS, HP driver for Windows, HP driver for Windows, HP driver for Windows, HP SmartStream Drivers Raster and PostScript drivers for Windows and macOS PPH driver for Windows and ada above Security features HP Secure Boot, Mishalicting, Role Based Access Control, SMMPA, HTTDS, Secure-IPP) (Dec Firewall, Certificates management, 402.11x, 113. drive). Till 17.1, HP Web Indiamin, HP AIRMARD Security Manager compatible, Secure Disk erase (DoID 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing 1440 × 766 × 718 mm Weight Printer 66 6kg Physiolation of the Boot Script of Post Script Printee, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference, quide, setup poster, power cord HP Software and solutions HP Designale Security Manager (poptonal), HP Smart Fracient (optional), HP Smart Fracient (optional	Minimum line width	0.02 mm (PDF addressable @ 1200 dpi)	
repeatability Max optical density 4th min/2.5 D ⁷ Max optical density 4th min/2.5 D ⁷ Maximum roll diameter 279 to 610-mm Maximum roll diameter 315 mm Sheet size 210 x 279 to 610 mm Sandard sheets A4, A3, A2, A1 Gammage 80 to 500 gim² Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light bowes - film; Maps, Orthophotos, Point of sale/display, Posters Memory 128 GB (virtual) ⁸ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u), 802.3ab); H-Speed USB 2.0 certified interface for direct printing from USB flash drive. Banke print Languages Adobe PostScript 3, Adobe PDF 1-7, TIFF, IPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AliPhot, direct printing from USB flash drive, emal printing, IPE (lisk, IPE driver for maa OS, IPE driver for Windows, HP SmartStream Drivers Roster and DossScript drivers for Windows and macOS PDF driver for Unious, printing support for Chrome OS, HP Print Sevuce Plugin for Android, HP Smart app for iOS and Android, HP SmartStream Britter and DossScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPJ3, HTTPS, Secure-IPP, IPSec/Frewall, Certificates management, 802; IX, TLS 1-1/1, 11/2, IPW bibb letadmin compabilist, HP JertAdvartage Security Manager compabible, Resident for Secure Disk erase (Dob S22.0.22-M), Secure File erase, self-encrypted HDD, PM printing Dimersions (W X D X H) Printer 1293 x 695 x 998 mm HP Click printing software, HP Printer printing and the printing of the Color of the PP Printer Printing and Prover of Color of the PP Printer Printing and Prover of Color of the PP Printer Printing and Prover of Color of the PP Printer Printing and Prover of Color of the PP Printer Printing and Prover of Color of the PP Printing Pri	Short-term color stability	< 1 dE2000 in less than 5 minutes ⁷	
Media		Average < 0.5 dE2000, 95% of colours < 1.4 dE2000 ⁷	
Roll size 279 to 610-mm Maximum roll dameter 135 mm Standard sheets 210 x 279 to 610 x 1676 mm Standard sheets A4, A3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.8 mm Applications Banners: Schabition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display, Posters Memory 128 GB (virtual) [®] Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-1) (802.3, 802.3 ab, 802.3 ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PDS 1.7, TIFF, JPEG, CALS GA, HP-GL/Z, HP-RTL Printing paths Adobe PDS 25cript 3, Adobe PDF 1.7, TIFF, JPEG, CALS GA, HP-GL/Z, HP-RTL Apple ArPinti, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP Smart stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPV3, HTTPS, Secure-PP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.01; 1.17, 2. HP Web Jetadmin compatible, HP peridwantage Security Manager compatible, Secure Disk erase (DoD S 220.22-M), Secure File erase, self-encrypted HDD, PN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Meight HP Designate ZS PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP Printos, HP Washard Stream (pottonal), HP Smart Tsteem (optional), HP Smart Tsteem (optional), HP Smart Tsteem (optional) Environmental ranges Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Oscurd Diverse -42 dB(A) (operating), 33 dB(A) (die), -16 dB(A) (sleep) Occur power -40 dB(A) (operating), 53 dB(A) (die), -16 dB(A) (sleep) Occur power -40 dB(A) (operating), 53 d	Max optical density	4 L* min/2.5 D ⁷	
Roll size 279 to 610-mm Maximum roll diameter 135 mm Sheet size 210 x 279 to 610 x 1676 mm Sheet size 210 x 279 to 610 x 1676 mm Sheet size 210 x 279 to 610 x 1676 mm Sheet size 210 x 279 to 610 x 1676 mm Ad, A3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (witual)² Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ub); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS GA, HP-GL/Z, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Uninx, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPV3, HTTPS, Secure-IPP, IPSec/Frewall, Certificates management, Boz.1, XT, SL 10/1-1/12, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (Dod 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 66 kg What's in the box HP Design.Jet 26 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP (Exprinting) Strives, HP PrintDS, HP Web Islandinin, HP Design.Jet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (optional) HP Software and solutions HP (Exprinting) Strives, HP PrintDS, HP Web Islandinin, HP Design.Jet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (optional) HP Software and so	Media		
Maximum roll diameter 135 mm Sheet size 210 x 279 to 610 x 1676 mm Standard sheets A4, A3, A2, A1 Gammage 80 to 500 g/m² Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) ⁸ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (10008ase-1) (802.3, 802.3a)b; Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF; JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive email printing, HP Click, HP driver for max 05, HP driver for Windows, HP driver for Lunx, printing support for Chrome 05, HP Print Service Plugin for Android, HP Smart App for iOS and Android, HP SmartStream Drivers Raster and PostScript drivers for Windows and max 05 PDF driver for Windows 8 and above Security features HP Secure Book, Whitelisting, Role Based Access Control, SMP43, HTTPS, Secure-IPP IPsec/Frewall, Certificates management, 802.1x, ITS, 30.1.11.12, HP Web Jetadroini compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (Dob 522.02.2-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 66 kg Phinter 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Physiological Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) HP Software and solutions HP Lick printing scheme, HP Printing, HP Web Medical Minior, HP Designiet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Diverating temperature 7.2 to 80% RH Storage temperatu	Handling	Roll feed, rear sheet feed, media output bin, automatic horizontal cutter	
Sheet size 210 x 279 to 610 x 1676 mm Slandard sheets A4, A3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) [©] Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3a, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Clidc, HP driver for maxOS, HP driver for Unixo, printing support for Chrome 05, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP SmartStream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Sacure Boot, Whitelsting, Role Based Access Control, SNMPN3, HTTPS, Secure-IPP, IPBec/Firewall, Certificates management, 802.13, TLS 1.071.171.2 HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoB 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 97 kg What's in the box HP Design, let Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Design, let Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Design, let Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Step (Lick HP PrintOS, HP Web Jetadmin, HP Design, let Ubility including HP Color Center, HP Partner Link, HP Jetadvantage Security Ma	Roll size	279 to 610-mm	
Standard sheets A4, A3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - Rim; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual)³ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1-7, THF; JPEG, CALS GA, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for mac0S, HP driver for Windows, HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP SmartStream Drivers Raster and PostScript drivers for Windows and mac0S PDF driver for Windows B and above Security features HP Secure Boot; Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP; IPSec/Firewall, Certificates management, 802.1k, TLS 1.01-171-2, HP Web Jetadrini compatible, HP JetAdvartage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing or fower. HP Printos, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP Jetadvartage Security Manager (optional), HP SmartTracker (optional) Environmental ranges Sound power 6.0 B(A) (operating), 3.3 dB(A) (idle), <16 dB(A) (sleep) Power Consumption	Maximum roll diameter	135 mm	
Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) [®] Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/Z, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Unious, Printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPy3, HTTPS, Secure-IPP, IP-Sec/Firewall, Certificates management, 802.1X, 11.5 i. (0.1 1.11 z., HP Web Detadmin compatible, HP perAdvantage Security Manager compatible, Secure Disk erase (Dob S220.22-M), Secure File erase, self-encrypted HDD, PN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 97 kg What's in the box HP Designate Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP Designate Utility including HP Color Center, HP Partner Link, HP BetAdvantage Security Manager (optional), HP Smart Tracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature 42 dB(A) (operating), 33 dB(A) (ide), <16 dB(A) (sleep) Count prover Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Sheet size	210 x 279 to 610 x 1676 mm	
Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (wirtual) ²⁸ Hard disk 500 GB self-encrypting Connectivity Interfaces Gligabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for Windows, HP driver for Linux, printing support for Chrome 0S, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP Smart Stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IP-sec/Firewall, Certificates miranagement, 802.1X, TLS 1.0/1.1/1/2, HP Web Jetadmin compatible, HP Jetadvantage Security Manager compatible, Secure Disk erase (0x0 5 220.22-4M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 1440 x 766 x 718 mm Weight Printer 67 kg What's in the box HP DesignJet ZS PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet LIBIty including HP Color Center, HP Partner Link, HP Jetadvantage Security Manager (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature 5 to 40°C Operating humidity 4 2 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound prossure 4 2 dB(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Ou	Standard sheets	A4, A3, A2, A1	
Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (wirtual) ⁸ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Windows, HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP Smart stera and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPSec/Firewall, Certificates management, 802.11, XTS. 1.071.171.172, HP Web Jetadmin compatible, HP Jetadvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility Including HP Color Center, HP Partner Link, HP Jetadvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating humidity 20 to 80% RH Storage temperature 5 to 40°C Operating humidity 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound prossure 42 dB(A) (operating), 53 dB(A) (idle), <16 dB(A) (sleep) Sound prossure 5 to 40°C Operating humidity 410 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Grammage	80 to 500 g/m ²	
Memory 128 GB (virtual) ⁸ Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Unixus, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart Stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above. PBF driver for Windows B and above. Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1x, TLS.10/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (Wx D x H) Printer 1293 × 695 × 998 mm Shipping 1440 × 766 × 718 mm Weight What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Click printing software, power cord HP Click printing software printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Serfware and solutions Fervironmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Fower Consumption < 100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Thickness	Up to 0.8 mm	
Connectivity	Applications	Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters	
Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe POF 1.7, TIFF, IPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPSec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Weight Printer 1293 x 695 x 998 mm Shipping 97 kg What's in the box HP DesignJet 25 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintO5, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating humidity 20 to 80% RH Storage temperature 25 to 40% C Acoustics Ou	Memory	128 GB (virtual) ⁸	
Interfaces Gigabit Ethernet (1000Base–T) (80.2.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for Inux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP SmartStream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.11x, TLS.10/1.1/1.2, HP Web Jetadmin compatible, HP JetaGvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDO, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating hempirature 25 to 55°C Acoustics Sound power 6.0 B(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption	Hard disk	500 GB self-encrypting	
Mative print languages Adobe PostScript 3, Adobe PDF 1.7. TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP SmartStream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference quide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating hemperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature - 25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0. B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <p>Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)</p>	Connectivity		
Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP Smartstream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitesting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Interfaces		
HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP SmartStream Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, Boz. 13, T.15. 10/1.1/1.2, IHP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Dick printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption	Native print languages	Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL	
PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP; IPsec/Firewall, Certificates management, Boot. 13, 123, 101, 112, and IPsec Headmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Power Consumption < 400 W ((printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Printing paths	HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android,	
management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP Jetadvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Drivers		
Printer 1293 x 695 x 998 mm Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference quide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP Peritoronmental ranges Diperating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Security features	management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible,	
Shipping 1440 x 766 x 718 mm Weight Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference quide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Dimensions (W x D x H)		
Weight Printer 66 kg Shipping 97 kg What's in the box HP Design Jet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP Design Jet Utility including HP Color Center, HP Partner Link, HP Jetadvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Printer	1293 x 695 x 998 mm	
Printer 66 kg Shipping 97 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DesignJet Utility including HP Color Center, HP DesignJet	Shipping	1440 x 766 x 718 mm	
Shipping 97 kg What's in the box HP Design Jet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadrmin, HP Design Jet Utility including HP Color Center, HP Partner Link, HP Derating Langer (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0.8 (A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Weight		
What's in the box HP Design Jet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, quick reference quide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintDS, HP Web Jetadrimin, HP Design Jet Utility including HP Color Center, HP Partner Link, HP Jetadvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	Printer	66 kg	
reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (o	Shipping	97 kg	
Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep) Power Consumption <100 W (printing); <3.2 W (ready); <6.5 W (sleep); 0.1 W (off)	What's in the box		
Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	HP Software and solutions		
Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Environmental ranges		
Storage temperature	Operating temperature	5 to 40°C	
Acoustics Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Operating humidity		
Sound pressure 42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Storage temperature	-25 to 55°C	
Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep)	Acoustics		
Sound power 6.0 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep)	Sound pressure	42 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	
Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)			
Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)			
		<100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)	
	Requirements	Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max	

Certification

Safety	USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS)
Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)
Environmental	ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT
Warranty	One-year limited hardware warranty

Ordering information

HP DesignJet Z6 24-in PostScript Printer

Accessories		
1QF38A	HP DesignJet 44-in Take-up Reel	
5EK00A	HP HD Pro 2 42-in Scanner	
5EK01A	HP SD Pro 2 44-in Scanner	
8SW00A	HP SmartStream USB Preflight Manager	
8SW00AAE	HP SmartStream Preflight Manager	
8SW01A	HP SmartStream Print Controller USB for HP DesignJet Printers	
8SW01AAE	HP SmartStream Print Controller for HP DesignJet Printers	
8SW11A	HP SmartTracker USB for DesignJet	
8SW11AAE	HP SmartTracker for DesignJet	
CN538A	HP DesignJet 3-in Core Adapter	
CQ783A	HP DesignJet 24-in Spindle	
G6H50B	HP SD Pro 44-in Scanner	
Q6709A	HP DesignJet 44-in Spindle	

Original HP printing supplies

P2V25A	HP 746 DesignJet Printhead
P2V78A	HP 746 300-ml Magenta DesignJet Ink Cartridge
P2V79A	HP 746 300-ml Yellow DesignJet Ink Cartridge
P2V80A	HP 746 300-ml Cyan DesignJet Ink Cartridge
P2V81A	HP 746 300-ml Chromatic Red DesignJet Ink Cartridge
P2V82A	HP 746 300-ml Photo Black DesignJet Ink Cartridge
P2V83A	HP 746 300-ml Matte Black DesignJet Ink Cartridge

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks

Original HP large format printing materials

06581A HP Universal Instant-dry Satin Photo Paper (FSC® certified)10 (Recyclable)11 1067 mm x 30.5 m (42 in x 100 ft)

E4J57A HP Artist Matte Carwas 1118 mm x 15.2 m (44 in x 50 ft)
C6569C HP Heavyweight Coated Paper (FSC® certified)¹⁰ (Recyclable)¹¹ 1067 mm x 30.5 m (42 in x 100

LU CH025A HP Everyday Matte Polypropylene, 2 Pack (Recyclable) 11 1067 mm x 30.5 m (42 in x 100 ft) CG460B HP Premium Matte Photo Paper (FSC* certified) 10 (Recyclable) 11 914 mm x 30.5 m (36 in x 100 ft)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U9WQ0E HP 3 year Next Business Day plus Defective Media Retention Support
U9YXBE HP 5 year Next Business Day plus Defective Media Retention Support
U9YX9E HP 1 year Post Warranty, Next Business Day plus Defective Media Retention Support
H4518E HP Network Installation Service with Network Setup

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

¹ Maximum rate of output for colour image 100% colour coverage. Printed on maximum roll size, with

Original HP Vivid Photo Inks.

A Mechanical printing time with Original HP Vivid Photo Inks.

Mechanical printing time with Original HP Vivid Photo Inks.

Seorderless printing available on photo gloss, photo satin, polypropylene, and backlit roll media.

5 ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C, 50-60% relative humidity, on A0 HP Matte Film in Best or Normal mode with HP Vivid Photo Inks.

Measured on HP Matte Film.

Measured on Hir Warter-Him.
Based not 4 GB RAM.
Based not 10 Ended not 10 E



















