# HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer



High-definition prints, fast and secure. More quality with fewer inks.



\*Product image may differ from actual product

<ul> <li>PRECISE—Clearly distinguish subtle details</li> <li>Read details more clearly and see high-contrast color with new high-definition HP printheads.</li> <li>No need for light inks with HP's dual drop technology.</li> <li>Get smooth gradients, even for challenging color combinations, with HP Pixel Control.</li> <li>Work with water- and fade-resistant prints, indoors and out, with HP Vivid Photo Inks.<sup>1</sup></li> </ul>	<ul> <li>FAST–Work without delays</li> <li>Handle even the most complex files with powerful processing architecture and the Adobe PDF Print Engine.<sup>2</sup></li> <li>Cut maps to different sizes in fewer steps with the first printer including an integrated vertical trimmer.<sup>3</sup></li> <li>Print up to 20% faster<sup>4</sup> with 2400 nozzle-per-inch, high-definition HP printheads.</li> <li>Spend less time on media changes and adjustments with dual roll support and automatic roll switching.<sup>3</sup></li> </ul>	<ul> <li>SECURE–Protect your work and your information</li> <li>Protect printers/data from unauthorized access with HP Secure Boot, whitelisting, and encrypted hard disk.</li> <li>Protect documents, preserve confidentiality with authentication solutions like PIN printing, card readers.<sup>5</sup></li> <li>Secure your printers with HP JetAdvantage Security Manager; manage your fleet remotely with HP Web Jetadmin.</li> </ul>


This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

### **Messaging Footnotes**

<sup>1</sup> Performance may vary based on writing system differences. Print permanence estimates by HP Image Permanence Lab based on the same formulation of HP Vivid Photo Inks used with the HP DesignJet Z6200 Photo Production Printer, using 6 inks. Water resistance performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. Display permanence rating for interior displays/away from direct sunlight by HP Image Permanence Lab on a range of HP media. For more information, see http://www.HPLFMedia.com/printpermanence <sup>2</sup> The Adobe PDF Print Engine (APPE) is Adobe's high speed, high fidelity print platform. Version 4 extends APPE's leading edge for print reproduction with new performance efficiencies and breakthrough rendering features. APPE 4 enables printers to increase workflow efficiency and capitalize on the profit potential of innovations in inkjet print technology. To learn more, visit https://www.adobe.com/products/pdfprintengine.html

<sup>3</sup> Vertical trimmer and dual rolls included with the HP DesignJet Z6dr 44-in PostScript<sup>®</sup> Printer with V-Trimmer only.
<sup>4</sup> Based on internal HP testing. Up to 20% faster printing compared to the HP DesignJet Z2600 PostScript<sup>®</sup> Printer and HP DesignJet Z5600 PostScript<sup>®</sup> Printer. May vary depending on print mode and media type.
<sup>5</sup> Card reader functionality enabled through optional third-party solutions.

For more information, please visit http://www.hp.com/go/designjetZ6









## **Technical specifications**

Print speed         East: B3 m/th m option media, Named 188 m/th on cooled media, Named 189 m/th on cooled Named 189 m/th on cooled Named 189 m/th on cooled N	Print			printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android, HP SmartStream
Print Presiduition         Up to 2400 x 1200 optimized dpi           Drivers         Reatmoor Presidocity chives the Windows on droub OS           Margins (afted)         Borderless on all media web V immers <sup>4</sup> Margins (afted)         5 x 17 x 5 x 5 mm           Int types         Pigment Sould           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 6 (optimic Carridge Source)         Pigment Source)           Print Carridge/Botte Number 7 (Source)         Pigment Number 7 (Source)           Print Carridge/Botte Number 7 (Source)         Pigment Number 7 (Source)	Print speed		Mobile printing features	Direct print from mobile apps on iOS. Android and Chrome OS: email
Technology         HP Termain Inster         Diff direct for Windows 8 and above           Margins fool         Bodzenies on all model with Vitrimmer*         Bodzenies	Print resolution	Up to 2400 x 1200 optimized dpi	Drivers	
Margine (sheet)         5 x 17 x 5 x 5 mm         In This Secure PP Beach Provide Certificates management, B202, X 1 x 5 x 5 mm           Prix Cortridge/Dotta Number of copx magents adds. photo black, photo black, chromatter ord)         Prix Cortridge/Dotta Number of copx magents, black and the Understand Secure PP Beach Private Cortridge Secure PP Beach Private PP Prix PP Beach Private PP Private PP Private Private PP Private PP Private Private PP	Technology	HP Thermal Inkjet	2	
Multiple large up         5 x 1/x 1/x 5 x mm         This 10/11/2, JP Web, Jetadram compatible, HP JetA downlog, Becure File           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 2 x 605 x 008 mm           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 2 x 605 x 008 mm           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 2 x 605 x 008 mm           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 2 x 605 x 008 mm           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 2 x 605 x 008 mm           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 2 x 605 x 008 mm           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, photo black, chromatic red)         Photo:         180 photo:           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, chromatic red)         Photo:         180 photo:           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matte black, chromatic red)         Photo:         180 photo:           Print cortridges/Bottle Number 6 (sym, magenta, yellow, matter)         Photo:         Photo:           <	Margins (roll)	Borderless on all media with V-Trimmer <sup>4</sup>	Security features	HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 8021X, TLS 10/11/12, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File
Introd         Projection         Projection         Projection           Print Cortridge/Bottle Number 6 (program nagenta, dromatic rad, yellow, matte black, photo black, chromatic rad, yellow, matte black, photo black, chromatic rad, yellow, matte black, photo black S00 ml         Product         1002 x 606 x 08 mm           Print Cortridge/Bottle volter         Prof & int Cortridge/Bottle volter         Product         1002 x 606 x 08 mm           Print Cortridge/Bottle volter         200 print Cortridge/Bottle volter         Product         1002 x 606 x 08 mm           Print Cortridge/Bottle volter         200 print Cortridge/Bottle volter         96 kg         Printing motion with the cortridge printing motion with the cort motion with the cort mice printing motion with the cort mice printing motion with the cort motion with the cort mice printing motion with the co	Margins (sheet)	5 x 17 x 5 x 5 mm		
Print Cartridges/Bottis, Number 6 (eyen, magenta, vellow, mote block, photo block, chonombter ed yellow, mote block photo block (SQ0 m)         Dimensions (W x D x H)           Print cartridges/Bottis, Number 6 (eyen, magenta, elhow block, SQ0 m)         Biophong         1960 x 766 x 708 mm           Ink drop         7/3 pl dud drop weight (M.C, PK), 6 pl single-drop weight (M.C, RM),         Product         96 kg           Printhoadt         8 messal printhoadts (kill for all colors)         Product         96 kg           Printhoadt         000 mm (SOC actions)         Product         96 kg           Inter accuracy         401% s <sup>3</sup> Minimum line width         000 mm (SOC actions)           Courced of human line width         000 mm (SOC actions)         Product         96 kg           Shipping         182 kg         Included         Wholds         HP Dedign, Jet ZS PostScript, Printer, printheods, introductory ink. cartridges, printer stand din media land, spindia din core adopter, actions display including JP Color Cortex (JP Partial Line, HP Dedign, Jet ZS PostScript, Printer, printheods, introductory ink. cartridges, printer stand din media land, spindia din core adopter, actions display including JP Color Cortex (JP Partial Line, HP Dedign, JP Color	Ink types	Pigment-based		
delivered         biodx, photo biox, S00 mill           Ink drop         7/3 pl dual-drop weight (M, C, PK); 6 pl aingle-drop weight (Y, CR, MK)         Weight           Printheads         Subversal printheads (solid for all colors)         Product         96 kg 78 k 78 mm           Printheads         Subversal printheads (solid for all colors)         Printheads         Subversal printer status         96 kg 78 k 78 mm           Une accuracy         ±01%         Colors         128 kg         Included           Minimum line width         0.02 mm (PDF addressable @ 1200 dpl)         What's in the box         Product         96 kg 78 kg           Guaranteed minimum line width         0.02 mm (PDF addressable @ 1200 dpl)         What's in the box         Product         Product         Product         Product         Product         Product         Color Cortex PP PrintDis Print Dis P	Print Cartridges/Bottle, Numbe	9r 6 (cyan, magenta, yellow, matte black, photo black, chromatic red)	Dimensions (W x D x H)	
Ink drop         7/3 pl dud-top weight (M, C, PK): 6 pl aingle-drop weight (Y, CR, MK)         Shipping         1960 / 1960 / 766 / 718 nm           Printheads         3 universal printheods (volif for all colors)         Product         96 kg           Printhead onzzles         2112 per color; 12672 in total         Shipping         152 kg           Line accuracy         40.1% <sup>5</sup> Included         HP Design.let 26 PostScript Printer stant of an Heat bin spirital, 3-h core adopter, qubk reference guida stop poste, power cord         What's in the box         HP Design.let 26 PostScript Printer Stant of an Heat bin spirital, 3-h core adopter, qubk reference guida stop poste, power cord           ShortNerm color stability         < 1 de2000 in isea than 5 minutes <sup>2</sup> HP Software and solution         HP Cole Cherner (HP Parinet Unit, HP Design.let (HP Parinet Unit)         HP Software and solution         HP Software and solution         HP Software and solution         HP Software and solution         HP Cole Cherner (HP Parinet Unit, HP Design.let (HP Parinet Unit)         HP Software and to the solut(HP Parinet Unit)		HP 746 Ink Cartridge: cyan, magenta, chromatic red, yellow, matte	Product	1802 x 695 x 998 mm
Printheads         Surversal printheads (valid for alcolors)         Product         96 kg           Printheads         2112 per color: 2872 in total         Shipping         132 kg           Line accuracy         ±01% <sup>5</sup> Shipping         132 kg           Minimum line width         0.02 mm (PDF addressable @ 1200 dpl)         Whot's in the box         HP Design.Jet 26 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bit, spinda, 34 nore adopter, qualch reference guide, survey are 1.03 dtr2000 g8% of colors < 1.4 dt22000 <sup>7</sup> Short term color stability         <1 dtr2000 gram (PDF addressable @ 1200 dpl)			Shipping	1950 x 766 x 718 mm
Printhead nozzles         2112 per color; 12.672 in total         Shapping         132 kg           Line accurace         ±01% <sup>2</sup> included         included           Minimum line width         0.02 mm (PDF addressable (§ 1200 dp))         included         included         included           StortStem color stability         <1.425000 m less than 5 mutules <sup>1</sup> included         includes         incl	•		Weight	
Line accuracy         ±07% <sup>6</sup> Incluided           Minimum line width         0.02 mm (ISC/IEC 1660.200 (E)) <sup>6</sup> What's in the box         HP Design.let 26 PostScript Printer, printheds, introductory ink, cartridges, printer stand and media bin spindle, 3 <sup>4</sup> no cadpter, quick reference guide, setup poster, power cord           Short term color stability         41 (2000 lines than 5 minutes <sup>7</sup> HP Software and solutions         HP Design.let 26 PostScript Printer, printheds, introductory ink, cartridges, printer stand and media bin spindle, 3 <sup>4</sup> no cadpter, quick reference guide, setup poster, power cord           Max optical density         41 (2000 lines than 5 minutes <sup>7</sup> HP Software and solutions         HP Software and solutions         HP Software and solutions           Macia         Dop-term print-to-print         Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 <sup>7</sup> Environmental ranges           Operating temperature         5 to 40°C         Operating temperature         5 to 40°C           Applications         Banners, Exhibition and event graphics, Light boxes - film; Maps; Orthophates, Pohl of seldigispty, Posters         Sound pressure         Printing, 45 dB/A(loperating), 33 dB/A (lide), -44 B/A (lide), -44			Product	96 kg
Minimum line width         0.02 mm (PDF addressable @) 1200 dp))         Who'f's in the box         HP Design_Jet Z6 PostScript Printer, printheads, introductory ink cortridges, printer stand and media bin, spindle, S-lin core adapter, quick reference guide, setup poster, power cortridges, printer stand and media bin, spindle, S-lin core adapter, quick reference guide, setup poster, power cortridges, printer stand and media bin, spindle, S-lin core adapter, quick reference guide, setup poster, power cortridges, printer stand and media bin, spindle, S-lin core adapter, quick reference guide, setup poster, power cortridges, printer stand and media bin, spindle, S-lin core adapter, quick reference guide, setup poster, power cortridges (ppinoal). HP Sind reference guide, setup poster, power cort poster, HP Print, poster for the print (ppinoal). HP Sind reference guide, setup poster, power cort of the spindlight, Posters           Maximum media width         118 mm         Banners: Exhibition and event graphics: Light baxes - film: Maps: Orthophotes Point of sele/(slight), Posters         Fordard spindle, S-lin Core adapter, quide, S-lin Core adap		2112 per color; 12,672 in total	Shipping	132 kg
Guaranteed minimum line width         Oog 8m m (1500/LEC 13660/200 (1E)) <sup>6</sup> Short+term color stability         <1 dE2000 in less than 5 minutes <sup>7</sup> Long-term print-to-print         Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 <sup>7</sup> medica         HP Software and solutions           Applications         Banners: Exhibition and event graphics: Light baxes - film: Maps: Orthophotos: Point of seld(sip)a/x, Posters           Media         Droy automatic of levels, printer qualified medic, including medica (levels), printer qualified medic, including medica (levels), printer qualified medic, including medica (levels), Prosters           Modia         Droy automatic of levels, printer qualified medic, including medica (levels), Prosters           Modia         Droy automatic of levels, printer qualified medic, including medica (levels), Prosters           Modia         Droy automatic of levels, printer qualified medic, including medica (levels), Prosters           Modia         Droy automatic of levels, printer qualified medic, including medica (levels), Prosters           Modia         Droy automatic of levels, printer qualified medica (levels), Prosters           Modia         Droy automatic (levels), Prosters           Modia rolis: 2: Roll isize: 279 to 1118 rm <t< td=""><td>Line accuracy</td><td>±0.1%<sup>5</sup></td><td>Included</td><td></td></t<>	Line accuracy	±0.1% <sup>5</sup>	Included	
Guidance minimum ine word 0,08 mm (ISO/IEC 1366022001[E)*         quick reference guida, setup poster, power cord           Short-term coils stability         41 dE2000, in lises than 5 minutes <sup>7</sup> HP Software and solutions         HP Cilk printing activater, HP Short(S), HP Wald, blackmin, HP Coler Center, HP Partner, Link, HP Detatability           Max optical density         41 th min/25 D <sup>7</sup> Final Stability         Poilty and the set than 5 minutes <sup>7</sup> Medici         Applications         Banners, Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of soliciligitary, Posters         Final Stability         20 to 80% RH           Mark and the set than 5 minutes in the set than 5 minutes of the set the set than 5 minutes in the set than 5 minutes of the set the set than 5 minutes of the set the set than 5 minutes of the set the set than 5 minutes of the set the set than 5 minutes of the set than 5 minutes of the set the set than 5 minutes of the set than 5 minutes of the set than 5 minutes of the set than 5 minutes of the set than 5 minutes of the set the set the set than 5 minutes of the set the set than 5 minutes of the set the set than 5 minutes of the set the set than 5 minutes of the set the set the set than 5 minutes of the set the set than 5 mi	Minimum line width	0.02 mm (PDF addressable @ 1200 dpi)	What's in the box	
Long-term print-to-print repetability         Average < 0.5 dE2000,95% of colors < 1.4 dE2000 <sup>7</sup> Max optical density         4.1° min/2.5 D <sup>7</sup> Media         Design.3et Utility including HP Calory Center, HP Partner Link, HP JetAXvmtage Socurity Manager (opticnal), HP SmartTracker (optional), HP Smar	Guaranteed minimum line widt	<b>h</b> 0.08 mm (ISO/IEC 13660:2001(E)) <sup>6</sup>		
Long-term print-to-print repeatability         Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 <sup>7</sup> repeatability         Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 <sup>7</sup> Max optical density         4 L° min/2.5 D <sup>7</sup> Media         Design.3et Utility including HP Color Center, HP Partner Link, HP detdix manage Security Manager (potinond)           Applications         Banners, Exhibition and event graphics; Light baxes - film; Maps; Orthophotos, Point of sale/display, Posters         Operating temperature         5 to 40°C           Handling         Two automatic noll eads, smart roll-switching, top sheet feed, media output bin undomatic horizontal cutter and writcol trimmer (victual cuter) HPZ series printer-gualified media, including most carrwas)         Storage temperature         25 to 55°C           Rolls         Media rolls: 2: 2010 size: 270 to 1118 mm; Maximum roll weight: 135 kg; Maximum media width         Storage temperature         25 to 55°C           Standard sheets         210 x 271 to 1118 x 1676 mm         Sound pressure         Printing: 63 B(A) (operating), 33 dB(A) (idle), -16 dB(A) (sleep)           Standard sheets         Up to 0.8 mm         Consumption         -100 W (printing), -32 W (ready); -65 W (sleep); 01 W (off)           Recommended Grammage         80 to 500 gm²         Printing: materials, Belf with PP laner Patrners, Highest WR Print, Permonence Ratings in the dustry; Compatible with FPC: cortellad; E HPA and acid, backit         Souf pover         Sustaindivie Mover         Sustai	Short-term color stability	<1 dE2000 in less than 5 minutes <sup>7</sup>	HP Software and solutions	HP Click printing software, HP PrintOS, HP Web Jetadmin, HP
Media       Operating temperature       5 to 40°C         Applications       Banners: Exhibition and event graphics; Light boxes -film; Maps; Orthophoto; Point of seld(sipplay, Posters       Operating temperature       25 to 56°C         Handling       Two automatic roll feeds, smart roll-switching; top sheet feed, media output bin, automatic horizontal cutter and vertical trimmer (cuts all HP 2-series printer qualified media, including most carvas)       Storage temperature       -25 to 55°C         Rolls       Media rolls: 2: Roll size :279 to 1118-mm; Maximum roll weight: 13.5 kg: Maximum roll diameter: 135 mm;       Storage temperature       -25 to 56°C         Maximum media width       1118 mm       Storage temperature       -25 to 56°C         Maximum media width       1118 mm       Storage temperature       -25 to 56°C         Maximum media width       1118 mm       Storage temperature       -25 to 56°C         Maximum roll diameter: 135 m;       Maximum roll weight: 13.5 kg: Maximum roll diameter: 135 m;       Storage temperature       -100 W (printing); -32 W (ready); <-6.5 W (sleep)		Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 <sup>7</sup>	Design Jet Utility including HP Color Center, HP Partner Lin Jet Advantage Security Manager (optional), HP Smart Stree	DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream
Applications       Banners: Exhibition and event graphics: Light boxes - film: Maps; Orthophotos: Point of sale/display; Posters       Operating humpitties       Operating humpitties         Handling       Two automatic horizont of sale/display; Posters       Operating humpitties       20 to 80% RH         Rolls       Media rolls: 2, Roll size: 27 horiti2s: Posters' 27 horiti3s: And the provide dutter and vertical timmer (cuts off HP 2-series printer-qualified media, including most convas)       Sound pressure       Printing: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Max optical density	4 L* min/2.5 D <sup>7</sup>	Environmental ranges	
Image: Control       Optimizing number of sole (display, Posters' and number of the system of the syst	Media		Operating temperature	5 to 40°C
Handling       Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic rulter and vertical trimmer (cuts all HP Z-series printer-qualified media, including most canvos)       Accustics         Rolls       Media rolls 2: Roll size: 279 to 1118-mm; Maximum roll weight: 13.5 kg; Moximum moll diameter: 135 mm;       Acoustics       Printing: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Applications	Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters	Operating humidity	20 to 80% RH
output bin, automatic horizontal auther and vertical trimmer (automatic)     Accoustics       Rolls     Media rolls 2; Roll size: 279 to 1118-mm; Maximum roll weight: 135 kg; Maximum roll diameter: 135 mm;     Sound pressure     Printing: 45 dB(A) (operating), 33 dB(A) (ide), <16 dB(A) (sleep)	Handling	Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter and vertical trimmer (cuts all	<u> </u>	-25 to 55°C
Rolls       Media rolls: 2; Roll size: 279 to 1118-mm; Maximum roll weight: 13.5 kg; Maximum roll diameter: 135 mm;       Sound pressure       Printing: 45 dBA(l (operating), 33 dBA) (idle), <16 dB(A) (sleep)         Moximum media width       1118 mm       Sound pressure       Printing: 45 dBA(l (operating), 51 BA) (idle), <16 dB(A) (sleep)	·		Acoustics	
Maximum redia width       1118 mm       Sound power       Printing: 63 B(A) (operating), 51 B(A) (idle), <34 B(A) (sleep)         Moximum media width       1118 mm       Power       Consumption       <100 W (printing); <32 W (ready), <6.5 W (sleep); 0.1 W (off)	Dolle			Printing: 45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)
Miximum media wath       1118 mm         Sheet size       210 x 279 to 1118 x 1676 mm         Standard sheets       A4, A3, A2, A1, A0         Recommended Grammage       80 to 500 g/m²         Thickness       Up to 0.8 mm         Media types       Photographic, fine art printing material, self-adhesive, banner and sign, bord and coated, backlit         Embedded controller       Safety         Memory       128 GB (virtual) <sup>6</sup> Hard disk       500 GB self-encrypting         Native print languages       Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL         Connectivity       Electromagnetic       Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (Adobe, Australia (Ado	Kolio			Printing: 6.3 B(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep)
Sheet size       210 x 279 to 1118 x 1676 mm       Requirements       Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A mc         Standard sheets       A4, A3, A2, A1, A0       Recommended Grammage       80 to 500 g/m²       Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A mc         Recommended Grammage       80 to 500 g/m²       Sustainable impact and printhead recycling with HP Planet Period Partners; Highest WR Print.       30% post-consumer recycled plastic; Free, convenient HP ink cartridg and printhead recycling with PCCC rules with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Permanence Ratings in the industry: Compatible with FSC <sup>5</sup> -certified H Ratind disk         Memory	Maximum media width	1118 mm		
Standard sheets       A4, A3, A2, A1, A0         Recommended Grammage       80 to 500 g/m²         Thickness       Up to 0.8 mm       Sustainable impact specifications       30% post-consumer recycled plastic; Free, convenient HP ink cartridg and printhead recycling with HP Planet Partners; Highest WIR Print Permanence Ratings in the Industry Compatible with FSC®-certified H Interfaces         Memory       128 GB (virtual) <sup>8</sup> Soft y       Us and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP- RTL       Safety       USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstra (EAC); Singapore (PSB); China (CCC); Argentina (IRAM); India (IBIS)         Native print languages       Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP- RTL       Electromagnetic       Complicativith Class A requirements, including: USA (FCC rules), Canada (ICSA); EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP	Sheet size	210 x 279 to 1118 x 1676 mm	•	<100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)
Recommended Grammage       80 to 500 g/m²       Certification         Thickness       Up to 0.8 mm       Sustainable impact specifications       30% post-consumer recycled plastic; Free, convenient HP ink cartridg and printhead recycling with HP Planet Partners; Highest WIR Print permanence Ratings in the Industry. Compatible with FSC*-certified I large format printing materials and HP Recycled Satin Canvas, and a range of recycloble HP media with a take-back program; ENERGY STAL         Embedded controller       Safety       USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC); Argentine (IRAM); India (BIS)         Native print languages       Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL       Electromagnetic       Compliant with Class A requirements, including: USA (FCC rules), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)         Interfaces       Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPE/Warranty         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP       Year Limited Warranty (Next Business Day On-Site)	Standard sheets	A4. A3. A2. A1. A0		Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max
Thickness       Up to 0.8 mm       Sustainable impact specifications       30% post-consumer recycled plastic; Free, convenient HP ink cartridge to specifications         Media types       Photographic, fine art printing material, self-adhesive, banner and sign, bond and coated, backlit       30% post-consumer recycled plastic; Free, convenient HP ink cartridge to specifications         Embedded controller       Safety       30% post-consumer recycled plastic; Free, convenient HP ink cartridge to specifications         Memory       128 GB (virtual) <sup>8</sup> Sof 0 GB self-encrypting       Safety       USA and Canada (CSA certified; ULVD and EN 60950-1 compliant); Russia, Belarus, Khazakam (EAC); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS)         Native print languages       Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL       Electromagnetic       Compliant with Class A requirements, including: USA (FCC rules), Canada (ICCS), EU (EMC Directive), Australia (ACMA), New 2ealand (RSM), China (ICCC), South Africa (SABS)         Connectivity       Interfaces       Gigabit Ethernet (1000Base-T) (802.3, 802.3a, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive, email printing, HP       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEA         Varranty       1 Year Limited Warranty (Next Business Day On-Site)       Warranty       1 Year Limited Warranty (Next Business Day On-Site)	Recommended Grammage			
Media types       Photographic, fine art printing material, self-adhesive, banner and sign, bond and coated, backlit       Permanence Ratings in the Industry. Compatible with FSC*.certified I large format printing materials and HP Recycled Satin Canvas, and a range of recyclable HP media with a take-back program, ENERGY STAL certified; EPEAT* registered         Memory       128 GB (virtual) <sup>8</sup> Solo GB self-encrypting       Safety       USA and Canada (CSA certified; LPEAT* registered (ICC); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS)         Native print languages       Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL       Electromagnetic       Compatible (ICC), Support (ICC), Australia (ACMA), New Zealand (ICS), EU (EMC Directive), Australia (ACMA), New Zealand (ICS), EU (EMC CO), Australia (ACMA), New Zealand (ICS), EU (EMC Directive), Australia (ACMA), New Zealand (ICS), Compatible interfaces for direct printing from USB flash drive       Environmental       ENERGY STAL (CC), Australia (ACMA), New Zealand (ICS), Compatible interface for direct printing from USB flash drive         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP		0,		Permanence Ratings in the Industry; Compatible with FSC®-certified HP large format printing materials and HP Recycled Satin Canvas, and a
Embedded controller       certified; EPEAT* registered         Memory       128 GB (virtual) <sup>8</sup> Safety       USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS)         Native print languages       Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP- RTL       Electromagnetic       Compliant with Class A requirements, including: USA (FCC rules), Canada (ICS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)         Connectivity       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEA         Interfaces       Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEA         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP       1 Year Limited Warranty (Next Business Day On-Site)		Photographic, fine art printing material, self-adhesive, banner and sign,		
Ites GB (vir dul) <sup>P</sup> Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC);         Hard disk       500 GB self-encrypting       Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC);         Native print languages       Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP- RTL       Electromagnetic       Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)         Interfaces       Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEA         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP       1Year Limited Warranty (Next Business Day On-Site)	Embedded controller			
Hard disk       500 GB self-encrypting       Argentina (IRAM); India (BIS)         Native print languages       Adobe PostScript 3, Adobe PDF 17, TIFF, JPEG, CALS G4, HP-GL/2, HP- RTL       Electromagnetic       Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Objective), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)         Connectivity       Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEA Warranty         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP       1Year Limited Warranty (Next Business Day On-Site)	Memory	128 GB (virtual) <sup>8</sup>	Safety	
Interfaces     Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive     Environmental     ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPE/ Warranty       Printing paths     Apple AirPrint, direct printing from USB flash drive, email printing, HP	Hard disk	500 GB self-encrypting		
Connectivity       Interfaces       Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive       Environmental       ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEA         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP       IYear Limited Warranty (Next Business Day On-Site)	Native print languages		Electromagnetic	Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand
Interfaces       Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive       Warranty       1Year Limited Warranty (Next Business Day On-Site)         Printing paths       Apple AirPrint, direct printing from USB flash drive, email printing, HP       1Year Limited Warranty (Next Business Day On-Site)	Connectivity		Environmental	
Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP	Interfaces	Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive		
	Printing paths	Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Windows, HP driver for Linux,		

### Ordering information

Product T8W18A HP DesignJet Z6dr 44-in PostScript Printer with V-Trimmer Accessories		Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and	
10F38A 5EK00D 5EK01D 8SW00A 8SW00AAE 8SW01AAE 8SW01AAE 8SW11A 8SW01AAE CN538A	HP DesignJet 44-in Take-up Reel HP HD Pro 2 42-in Scanner HP SD Pro 2 44-in Scanner HP SmartStream USB Preflight Manager HP SmartStream Preflight Manager HP SmartStream Print Controller USB for HP DesignJet Printers HP SmartStream Print Controller for HP DesignJet Printers HP SmartTracker USB for DesignJet HP SmartTracker for DesignJet HP DesignJet 3-in Core Adapter	Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks Original HP large format printing materials HP Universal Instant-dry Satin Photo Paper (FSC* certified) <sup>10</sup> (Recyclable) <sup>11</sup> HP Artist Matte Canvas HP Heavyweight Coated Paper (FSC* certified) <sup>10</sup> (Recyclable) <sup>11</sup> HP Everyday Matte Polypropylene (Recyclable) <sup>11</sup> HP Premium Matte Photo Paper (FSC* certified) <sup>10</sup> (Recyclable) <sup>11</sup> For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.	
Original HP printing supplies		Service and Support	
3WX35A 3WX36A 3WX37A 3WX38A P2V25A P2V25A	3WX36A HP 746B 300-ml Cyan DesignJet link Cartridge 3WX37A HP 746B 300-ml Magenta DesignJet link Cartridge 3WX38A HP 746B 300-ml Yellow DesignJet link Cartridge	U9ZE2E HP 3 year Next Business Day plus Defective Media Retention Support U9ZE4E HP 5 year Next Business Day plus Defective Media Retention Support U9ZE5PE HP 1 year Post Warranty, Next Business Day plus Defective Media Retention Support H4518E HP Network Installation Service with Network Setup	
		HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc	

#### **Specification Footnotes**

Advantage of output for color image 100% color coverage. Printed on maximum roll size, with Original HP Vivid Photo Inks.
 Mechanical printing time with Original HP Vivid Photo Inks.
 Except self-adhesive vinyls and non-cuttable medics.
 Except self-adhesive vinyls and non-cuttable vinyls and non-cutable vinyls and non-cuttable vinyls and non-cuttable vinyls and no

© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

February 2025 ph-en

