

ThinkCentre M715 Tiny 10M3000K**

Product
ThinkCentre M715q Tiny

Region
MEA

Machine Type
10M3

TopSeller
TopSeller

Processor
AMD A6-9500E (2C, 3.0 / 3.4GHz, 1MB)

vPro
No

Graphics
Integrated AMD Radeon R5 Graphics

Monitor Cable
None

Memory
4GBx1

Storage
500GB 7200rpm 2.5"

External Optical / I/O Box
None

WLAN + Bluetooth
None

Optional Rear Ports
None

Speaker
1Wx1

Adapter Cage
None

Toolless Chassis Screw
None

Dust Filter
None

Keyboard / Mouse
USB / USB

VESA Mount
VESA Mount

Stand
None

Power Supply
65W 88% Adapter

Operating System
Windows 10 Pro 64

Warranty
3-year, Onsite

Global
No

End of Support
Nov 25, 2022

Ann Date (mm/yy)
10/16

Note:

* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



WWW.LENOVO.COM

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2017. All rights reserved.

Lenovo

ThinkCentre M715 Tiny Platform Specifications

Product Specifications Reference (PSREF)

| Processor | AMD A6, A10, or A12 series APUs | Keyboard | Some: Fullsize USB Keyboard (USB connector), Lenovo logo Some: Lenovo New Slim USB Keyboard (USB connector), black, Lenovo logo Some: USB Optical Wheel Mouse, black, Lenovo logo | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|--|--|--------------------|---------------------|--------------|---------------------|--------------|---|---------------|------|-----------|------------------|---------------|---|---------------|------|-----------|------------------|---------------|---|---------------|------|-----------|------------------|--------------|---|---------------|------|-----------|------------------|---------------|---|---------------|------|-----------|------------------|---------------|---|---------------|------|-----------|------------------|-------|---|
| | <table border="1"> <thead> <tr> <th>APU</th><th>Cores</th><th>Frequency Base/Max</th><th>L2 Cache</th><th>Memory Types</th><th>Integrated Graphics</th></tr> </thead> <tbody> <tr> <td>PRO A6-9500E</td><td>2</td><td>3.0 / 3.4 GHz</td><td>1 MB</td><td>DDR4-2400</td><td>Radeon R5 Series</td></tr> <tr> <td>PRO A10-9700E</td><td>4</td><td>3.0 / 3.5 GHz</td><td>2 MB</td><td>DDR4-2400</td><td>Radeon R7 Series</td></tr> <tr> <td>PRO A12-9800E</td><td>4</td><td>3.1 / 3.8 GHz</td><td>2 MB</td><td>DDR4-2400</td><td>Radeon R7 Series</td></tr> <tr> <td>PRO A6-8570E</td><td>2</td><td>3.0 / 3.4 GHz</td><td>1 MB</td><td>DDR4-2400</td><td>Radeon R5 Series</td></tr> <tr> <td>PRO A10-8770E</td><td>4</td><td>2.8 / 3.5 GHz</td><td>2 MB</td><td>DDR4-2400</td><td>Radeon R7 Series</td></tr> <tr> <td>PRO A12-8870E</td><td>4</td><td>2.9 / 3.8 GHz</td><td>2 MB</td><td>DDR4-2400</td><td>Radeon R7 Series</td></tr> </tbody> </table> | APU | Cores | Frequency Base/Max | L2 Cache | Memory Types | Integrated Graphics | PRO A6-9500E | 2 | 3.0 / 3.4 GHz | 1 MB | DDR4-2400 | Radeon R5 Series | PRO A10-9700E | 4 | 3.0 / 3.5 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | PRO A12-9800E | 4 | 3.1 / 3.8 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | PRO A6-8570E | 2 | 3.0 / 3.4 GHz | 1 MB | DDR4-2400 | Radeon R5 Series | PRO A10-8770E | 4 | 2.8 / 3.5 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | PRO A12-8870E | 4 | 2.9 / 3.8 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | Mouse | Tiny (1L), black color; metal case M715 Tiny only: 7.05" W X 7.20" D X 1.36" H 179mm W X 182.9mm D X 34.5mm H 2.9 lb (1.3 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 4.12 lb (1.87 kg), weight may vary by configuration With VESA mount & I/O box: 7.42" W X 7.30" D X 2.62" H 188.4mm W X 185.38mm D X 66.6mm H 3.53 lb (1.6 kg), weight may vary by configuration Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation |
| APU | Cores | Frequency Base/Max | L2 Cache | Memory Types | Integrated Graphics | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PRO A6-9500E | 2 | 3.0 / 3.4 GHz | 1 MB | DDR4-2400 | Radeon R5 Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PRO A10-9700E | 4 | 3.0 / 3.5 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PRO A12-9800E | 4 | 3.1 / 3.8 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PRO A6-8570E | 2 | 3.0 / 3.4 GHz | 1 MB | DDR4-2400 | Radeon R5 Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PRO A10-8770E | 4 | 2.8 / 3.5 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PRO A12-8870E | 4 | 2.9 / 3.8 GHz | 2 MB | DDR4-2400 | Radeon R7 Series | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Memory | 32GB max, DDR4 2400, two 260-pin SO-DIMM sockets, dual-channel capable *16GB single SO-DIMM memory is only available via special bid models | Mechanical | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Disk | Some: SATA 6.0Gb/s, 2.5" Wide, 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" | VESA mount | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Optical | Some: M.2 Solid State Drive (SSD) / SATA interface or PCIe NVMe interface Some: DVD-ROM, 9.0mm high, via USB external ODD box Some: DVD±RW, 9.0mm high, via USB external ODD box | Floor Stand | Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Onboard SATA Media reader | One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar None | Power supply | 65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models) 90 watts AC/DC adapter, autosensing, 88% PSU (only for models with I/O box) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Graphics | AMD Radeon™ Graphics in processor, uses main memory, DirectX® 12, two DisplayPort™, one optional port (HDMI, VGA, or 3rd DP), supports 3 independent displays (supports maximum of 2 concurrent HDMI/DVI displays when using HDMI port or DP to DVI/HDMI dongles); Max resolution: 4096x2160 (DP) @60Hz; 4096x2160 (HDMI) @30Hz; 1920x1200 (VGA) @60Hz | Limited warranty ³ | Some: 1-year or 3-year, depot service / service upgrades available Some: 1-year or 3-year, limited onsite service / service upgrades available | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DP cable | Optional DP to VGA, DP to DVI-D (single link), or DP to HDMI 1.4 dongle | Preload | Preloaded operating system Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 10 Pro 64-bit | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Chipset | AMD B300 Chipset | | Preloaded applications (only some listed) - Windows 10 only <ul style="list-style-type: none">Lenovo CompanionMicrosoft Office preloaded; purchase a product key to activate - Windows 7 only <ul style="list-style-type: none">Lenovo Solution CenterThinkVantage System UpdateCreate Recovery MediaLenovo ThinkVantage ToolsCyberlinkPowerDVD Create(DVD±RW)Microsoft Office preloaded; purchase a product key to activateAdobe® Reader® | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Front ports | Two USB 3.0 (one is Always On and fast charge), one microphone (stereo, 3.5mm), one headphone / microphone combo jack (stereo, 3.5mm) | Environment | ENERGY STAR® 6.1*, EPEAT™ Gold rating* (*Not for non-OS models); ErP Lot 3; GREENGUARD®; RoHS-compliant | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rear ports | One USB 3.0 and three USB 2.0 (optional external optical box or I/O box occupies one specific USB 2.0 on some models), ethernet (RJ-45), two DisplayPort, one optional port (VGA, 3rd DP, HDMI, or serial on some models), one headphone | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I/O box | Optional external I/O box, extends four USB 2.0 (two on front and two on rear), one serial, and two PS/2, via USB port (occupy one specific USB 2.0 of M715q Tiny) | Accessories | For compatible accessories, please go to http://www.lenovoquickpick.com | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Audio support | High Definition (HD) Audio, Realtek ALC233-CG / internal speaker (1.5 watt) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WLAN ¹³ | Some: 11ac wireless, M.2 Card, Realtek RTL8821AE (dual band), Wi-Fi + Bluetooth 4.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377 (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Bluetooth™ Ethernet Modem | Some: Bluetooth 4.0 or 4.1 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111EPV, Wake on LAN® None | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Manageability Security chip Security features | DASH 1.0/1.1 Discrete TPM 2.0, TCG Certified <ul style="list-style-type: none">Security slot (in rear for optional Kensington® MicroSaver® cable)Padlock loopSmart USB protection, allows keyboard/mouse only, blocks all storage devicesPower-on password | <ul style="list-style-type: none">Administrator passwordHard disk passwordBoot sequence controlBoot without keyboard and mouseIndividual USB port disablementChassis intrusion switch | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

ThinkCentre M715 Tiny

Lenovo[™]

