



HP Latex R1000 Plus Printer

Help grow your business by printing high-value jobs on one device with white¹, rigid and flexible



Get amazing colors, rigid and flexible up to 64 in

- Grow your business into higher value rigid/flexible jobs with vibrant HP Latex gamut, media look and feel.
- Gain versatility with HP Latex Ink – from indoor/outdoor signage to thermoforming and high-quality decoration.
- Win more jobs with UL ECOLOGO® Certified, water-based HP Latex Inks that produce odorless prints.²

We've removed the barriers to print with white¹

- Expand your portfolio into a wide range of applications with glossiest white that resists yellowing.¹
- No waste between white jobs³ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- You're always ready to print white – automatic recirculation and printhead cleaning eliminate manual purging.

Manage your peaks in-house with smart printing

- Meet production peaks – get high-speed quality up to 15 outdoor boards/hr⁴ with belt system, smart vacuum.
- Help avoid costly operating errors with an easy interface including advanced queuing and multi-board printing.
- Maximise uptime with automatic maintenance and smart service tools for fast diagnosis and issue resolution.

For more information, please visit <http://www.hp.com/go/LatexRseries>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://lkc.hp.com/>

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

¹ Glossiest white based on internal HP testing in January, 2018 compared to leading competitive printers with CMYK configuration under \$350,000 USD. Based on level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure.

² HP Latex Inks are UL ECOLOGO® Certified. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see <http://www.ul.com/EL>). There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use.

⁴ Outdoor mode 3-pass, 70%. On 4 x 8 ft (1.2 x 2.4 m) boards.

Technical specifications

Print	
Printing modes	15 m²/hr - Indoor High Quality (12p 120%) 28 m²/hr - Indoor Production (6p 110%) 56 m²/hr - Outdoor (3p 70%) 25 m²/hr - White Spot (100%) 11 m²/hr - White Overflow (100%) 3.6 m²/hr - 3 layers day & night¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex inks
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, HP Latex Overcoat, white)
Cartridge size	3 L
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimizer, 2 white)
Long-term print-to-print repeatability	Average ≤ 1.0 dE2000, 95% of colors ≤ 2 dE2000²
Media	
Handling	Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance
Media types	Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather
Rigid media size	297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables)
Roll size	60.9 cm to 1.63 m
Maximum roll weight	Up to 68 kg
Maximum roll diameter	Up to 25 cm
Thickness	Up to 50.8 mm
Applications	
Signage: indoor, flat, backlit, thermoformed; Decoration: wall coverings, window decoration; Vehicle decoration: fleet graphics, wraps, decals; Textile: soft signage, frontlit, backlit; POS and Packaging: corrugated displays, short-run customized packaging, prototyping	
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D x H)	
Printer	4.21 x 2.04 x 1.75 m (printer); 4.21 x 3.64 x 1.75 m (including standard input and output tables)
Shipping	4.43 x 2.24 x 2.15 m
Operating area	6.61 x 6.03 x 3 m
Weight	
Printer	1400 kg
Shipping	2400 kg
What's in the box	
HP Latex R1000 Printer; HP Latex R2000 Roll Printing Accessory Kit with 98-in spindles (x2) and pneumatic gun adapter and table top roll holders (x2); HP 886 Latex Printheads; Full set of HP 882 Latex Ink Cartridges; HP Latex Printhead Cleaning Kit; standard and extension input and output tables; foot switch; HP Internal Print Server and displays (x2); printer maintenance kit; warranty and intro docs	
Environmental ranges	
Operating temperature	15 to 30°C
Operating humidity	20 to 70% RH (non-condensing)
Power	
Consumption	8 to 10 kW (typical)
Certification	
Safety	IEC 60950-1 +A1 +A2 compliant; United States and Canada (CSA listed)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES)
Environmental	WEEE; REACH; CA 65 Prop; ErP Ecodesign Directive
Warranty	
Eighteen-month Maintenance and Support covers: 180-day limited hardware warranty; twelve-month HP Standard Service, Maintenance and Support. Warranty may vary by country as required by law. Go to http://www.hp.com/support to learn about HP service and support options in your region.	

Ordering information

Product	
K0Q45A	HP Latex R1000 Plus Printer
Accessories	
D9Z41B T7V21A Y6V16A	HP Large Format Onyx Thrive RIP Software HP Latex R1000 Extension Tables HP Latex R Series Edge Holders Kit
Original HP printing supplies	
G0Z00A G0Z01A G0Z02A G0Z03A G0Z04A G0Z05A G0Z06A G0Z07A G0Z08A G0Z09A G0Z21A G0Z22A G0Z24A	HP 886 Latex Printhead Cleaning Kit HP 872 3-liter Cyan Latex Ink Cartridge HP 872 3-liter Magenta Latex Ink Cartridge HP 872 3-liter Yellow Latex Ink Cartridge HP 872 3-liter Black Latex Ink Cartridge HP 872 3-liter Light Cyan Latex Ink Cartridge HP 872 3-liter Light Magenta Latex Ink Cartridge HP 872 3-liter Optimizer Latex Ink Cartridge HP 872 3-liter Overcoat Latex Ink Cartridge HP 886 3-liter White Latex Ink Cartridge HP 886 White Latex Printhead HP 886 Optimizer Latex Printhead HP 886 Latex Printhead
Original HP large format printing materials	
HP Premium Removable Gloss Adhesive Vinyl HP Permanent Gloss Adhesive Vinyl HP Durable Backlit Fabric (Take-back program)³ HP Backlit Polyester Film (Take-back program)³	
For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com .	
Service and Support	
If you want to extend the support beyond what's included: HOHX4AC HP Standard Service, Maintenance and Support extension contract HOJR1AC HP Enhanced Service, Maintenance and Support extension contract UA5W05 HP Latex R series Level 3 Train to repair and maintain – 5 days training at HP UA3Q7E 3 Years Next Business Day with Defective Media Retention for HP Latex R1000 Plus K0Q45-67269 HP Latex R series Expert spare parts uptime kit	
ECO highlights	
<ul style="list-style-type: none">• Better for print operations—no hazard warning labels or HAPs, no special ventilation needed¹• Better for the environment—HP designs end-to-end sustainability into large-format printing• Water-based inks produce odorless prints²• HP Latex Inks are UL ECOLOGO® and UL GREENGUARD GOLD Certified³	
Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions	
<p>¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.</p> <p>² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.</p> <p>³ UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see http://www.ul.com/EL). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.greenguard.org.</p>	
<p>¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.</p> <p>² Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.</p> <p>³ Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.</p>	

