

ThinkCentre M920 Tower 10SF0005US

Region US	Cable Lock None
Machine Type 10SF	Speaker 2Wx1
TopSeller TopSeller	Dust Filter None
Processor Core i7-8700 (6C, 3.2 / 4.6GHz, 12MB)	Carry Handle Carry Handle
vPro vPro	Stand None
Graphics Integrated Intel UHD Graphics 630	Keyboard / Mouse USB / USB
Monitor Cable None	Power Supply 250W 85%
Memory 8GBx1	TUV Low Noise None
Storage 256GB SSD M.2 PCIe NVMe Opal	Operating System Windows 10 Pro 64
Optional Bay Optional 3.5" bay	Warranty 3-year, Onsite
Front Access HDD None	End of Support Jul 26, 2024
Optical DVD±RW	Ann Date (mm/yy) 06/18
Media Reader None	
WLAN + Bluetooth Intel 9560 ac, 2x2 + BT5.0	Note: Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries
Ethernet Integrated	
Optional Rear Ports None	
Chassis Intrusion Switch None	
Chassis E-Lock None	



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2018. All rights reserved.



ThinkCentre M920 Tower Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron®, Intel Pentium®, or 8th Generation Intel Core™ i3 / i5 / i7 Processor						Bluetooth™ Ethernet Ethernet (Opt.) Manageability Security chip Security features Keyboard Mouse Mechanical Power supply Limited warranty Preload Environment Accessories	<i>Some:</i> 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x2 Bluetooth 4.2/5.0 wireless, integrated in Wi-Fi + BT combo adapter <i>Some:</i> Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN® <i>Some:</i> Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4 <i>Some:</i> Bitland BN8E88, gigabit ethernet, 1x RJ-45, PCIe x1 (special bid only) Intel Active Management Technology 12 (Intel AMT 12); Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection) Discrete TPM 2.0, TCG Certified <ul style="list-style-type: none">• Security slot (in rear for optional Kensington® MicroSaver® cable)• Padlock loop• Optional cable lock to physically lock both keyboard and mouse• Optional chassis intrusion switch• Optional chassis E-Lock• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Individual USB port disablement• Smart USB protection, allows keyboard/mouse only, blocks all storage devices <i>Some:</i> Lenovo Calliope Keyboard (USB connector), black <i>Some:</i> Lenovo Traditional Keyboard (USB connector), black <i>Some:</i> Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Lenovo Keyboard (PS/2 connector), black (only available via special bid) <i>Some:</i> Lenovo Calliope Mouse (USB connector), black <i>Some:</i> Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black <i>Some:</i> Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black <i>Some:</i> Lenovo Mouse (PS/2 connector), black (only available via special bid) <ul style="list-style-type: none">• Tower (18L), black color, metal case• (WxDxH) 6.5" X 12.65" X 16.15"; 165mm X 321.35mm X 410.25mm• Approx. 15.45 lb (7 kg), weight may vary by configuration• Toolless cover, disk, optical, extension card removal• Optional carry handle, dust filter Bay 1: Slim external ODD bay Bay 2: 5.25", 1.6" high, external, ODD / optional front access HDD Bay 3: 3.5", 1" high, internal, HDD/SSD Bay 4: 3.5", 1" high, internal, HDD/SSD (optional bay, bay comes with disk) Bay 5: 2.5", internal, HDD/SSD (optional bay) <i>Notes:</i> M920 Tower supports up to 3 SATA devices (ODD/HDD/SSD) and 1 eSATA device (front access HDD) Slot 1: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x16 Slot 2: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x1 Slot 3: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x16 (x4 signal) Slot 4: no slot, only bracket for optional port extension M.2 card slots: Two (one for WLAN, one for SSD/Optane) <i>Some:</i> 180 watts, autosensing, 85% PSU <i>Some:</i> 250 watts, autosensing, 85% PSU <i>Some:</i> 400 watts, autosensing, 92% PSU (only available via special bid) <i>Some:</i> 1-year or 3-year, depot service / service upgrades available <i>Some:</i> 1-year or 3-year, limited onsite service / service upgrades available Preloaded operating system <i>Some:</i> Windows® 10 Pro 64-bit <i>Some:</i> Windows 10 Home 64-bit Preloaded applications (only some listed) <ul style="list-style-type: none">• Lenovo Vantage• Microsoft Office preloaded; purchase a product key to activate• Cyberlink PowerDVD (only for models with DVD / DVD±RW)• Cyberlink Power2GO (only for models with DVD±RW)• LinkedIn ENERGY STAR® 6.1, EPEAT™ Gold rating (North America), ErP Lot 3, TCO, TUV low noise verified (coming soon, on some models), RoHS-compliant For compatible accessories, please go to http://smartfind.lenovo.com
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics		
	Celeron G4900	2 / 2	3.1G	2 MB	DDR4-2400	UHD 610		
	Celeron G4920	2 / 2	3.2G	2 MB	DDR4-2400	UHD 610		
	Pentium Gold G5400	2 / 4	3.7G	4 MB	DDR4-2400	UHD 610		
	Pentium Gold G5500	2 / 4	3.8G	4 MB	DDR4-2400	UHD 630		
	Pentium Gold G5600	2 / 4	3.9G	4 MB	DDR4-2400	UHD 630		
	Core i3-8100	4 / 4	3.6G	6 MB	DDR4-2400	UHD 630		
	Core i3-8300	4 / 4	3.7G	8 MB	DDR4-2400	UHD 630		
	Core i5-8400	6 / 6	2.8G / 4.0G	9 MB	DDR4-2666	UHD 630		
	Core i5-8500	6 / 6	3.0G / 4.1G	9 MB	DDR4-2666	UHD 630		
	Core i5-8600	6 / 6	3.1G / 4.3G	9 MB	DDR4-2666	UHD 630		
	Core i7-8700	6 / 12	3.2G / 4.6G	12 MB	DDR4-2666	UHD 630		
Memory	64GB max, UDIMM, DDR4-2666*, four 288-pin DIMM sockets, non-ECC, dual-channel capable * System automatically clocks down for the processors with lower memory controller							
Storage	<i>Some:</i> Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm <i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" <i>Some:</i> M.2 Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s <i>Some:</i> Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2 <i>Some:</i> DVD-ROM, SATA 1.5Gb/s Drive, slim (9.0mm) <i>Some:</i> DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm) Four onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only available via special bid model) Optional 7-in-1 media reader							
Optical								
Onboard SATA								
Media reader	Optional 7-in-1 media reader							
Graphics	Intel UHD Graphics 610/630 in processor, uses main memory, DirectX® 12, one VGA, two DisplayPort™, supports 3 independent displays, works along with discrete graphics to support more displays; <i>Max resolution:</i> 4096x2304 (DP)@60Hz; 2048x1536 (VGA)@50Hz <i>Some:</i> NVIDIA GeForce® GT 730 , DirectX 12, 2GB, PCIe 2.0 x8 adapter, two DisplayPort, 35 watts; <i>Max resolution:</i> 3840x2160 (DisplayPort)@60Hz; <i>Some:</i> NVIDIA GeForce GTX 1060 (special bid only), DirectX 12, 6GB, PCIe 3.0 x16 adapter, 1x DVI-D, 1x HDMI, 3x DP, 120 watts, occupies two slots; <i>Max resolution:</i> 2560x1600 (DVI-D)@60Hz; 4096x2160 (HDMI)@60Hz 5120x3200 (DP)@60Hz Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle							
Monitor Cable	Display with intel integrated graphics), or DP to HDMI 1.4 dongle							
Chipset	Intel Q370 Chipset							
Front ports (Std.)	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x USB 3.1 Type-C Gen1 (15W charging), 1x microphone (3.5mm), 1x headphone / microphone combo jack (3.5mm)							
Front ports (Opt.)	<i>Optional:</i> 1x media reader							
Rear ports (Std.)	4x USB 3.1 Gen1, 1x serial (9-pin), 1x ethernet (RJ-45), 1x VGA, 2x DisplayPort, 1x line-out (3.5mm)							
Rear ports (Opt.)	<i>Optional:</i> 2x USB 2.0, 2x USB 3.1 Gen1 via PCIe x1, 2x USB 3.1 Type-C Gen2 via PCIe x4 (special bid only), 1x 2nd serial (9-pin), 4x serial (9-pin) via PCIe x1, 1x parallel (25-pin), 2x PS/2 ports (keyboard/mouse), 1x Thunderbolt 3 (combo USB3.1 Type-C Gen 2 / DisplayPort) via PCIe x4, additional RJ-45 and video ports available on optional graphics or ethernet card							
Audio support	High Definition (HD) Audio, Realtek ALC233VB2 / internal speaker (2 watt)							
WLAN	<i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 <i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 <i>Some:</i> 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 <i>Some:</i> 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2							

Note: The specifications above may not be available in all regions.

Lenovo, July 2018

Lenovo

ThinkCentre M920 Tower

