

AKZ9 6230 S

12NC/Fx: 859991530400

GTIN (EAN) code: 8003437833809

DIMENSION		MEASUR	
OVERALL CABINET			
VIN Height of the wall cabinet niche, including all required space for installation or ventilatio	n 0	mn	
VIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mn	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	on 600	mn	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	on O	mn	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	n 585	mr	
MAX Height of the base cabinet niche, including all required space for installation or ventilat	ion 601	mr	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mr	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mr	
MIN Width of the base cabinet niche, including all required space for installation or ventilatio	n 560	mr	
MAX Width of the wall cabinet niche, including all required space for installation or ventilatio	n 0	mr	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mr	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	on 568	mr	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilatior	n 0	mr	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mr	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	n 550	mr	
Space in front, which is required to install bottom trim	10	mr	
ndicates whether a ventilation opening is needed or not. Default is "N"	Yes		
WALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (wall cabinet)	Rear		
Minimum space or inbound ventilation (wall cabinet)	0	mr	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm	
NALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (wall cabinet)	Rear		
Vinimum space or outbound ventilation (wall cabinet)	0	mr	
Vinimum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (tall cabinet)	Rear		
Vinimum space for inbound ventilation (tall cabinet)	30	mr	
Vinimum area for inbound ventilation cavity (tall cabinet)	150	cm	
TALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
Vinimum space for outbound ventilation (tall cabinet)	0	mr	
Vinimum area for outbound ventilation cavity (tall cabinet)	150	cm	
BASE CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (base cabinet)	Rear		
Vinimum space for inbound ventilation (base cabinet)	30	mr	
Vinimum area for inbound ventilation cavity (base cabinet)	150	cm	
BASE CABINET (vent-shaft outgoing)		5.1	
ndicates the position of the freespace for the outbound airflow (base cabinet)	Rear		
Vinimum space for outbound ventilation (base cabinet)	0	mr	
mininari epuce for outbound ventilation (babe dabinet)	U	cm	

DIMENSION	IEAS	IEASURE	
APPLIANCE			
Height of the front	595	mm	
Width of the front	595	mn	
Depth of the front	20	mm	
Maximum depth all protruding elements, e.g. handles, controls	41	mn	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	37	mn	
Projection of front in relation to housing of appliance	18	mn	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	5	mn	
When product panel is missing, set to 0	97	mn	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	458	mn	
Height from bearing area of appliances and lower handle	442	mn	
Frontal handle thickness	30	mn	
Frontal handle width	521	mn	
MIN Height of the product body	572	mn	
MAX Height of the product body	572	mr	
Width of the product body	546	mn	
Depth of the product body	543	mn	
Full depth of product excluding protruding interface elements	564	mn	
-	-	mn	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Appliance Flap door			
Projection of the opened flap in relation to bearing area	0	mn	
Maximum angle when flap door is opened totally	89	mn	
Appliance Side swing door			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mr	
Lateral projection of opened front at the side where the hinge is fixed	0	mn	
Maximum angle when door is opened totally	0	mr	
Appliance other			
Depth from front end of the niche to the front end of the freespace of the retrace	345	mn	
Height from niche to bottom end of freespace for the retrace	537	mn	