

Product datasheet

Specifications



APC 17" Rack LCD Console

AP5717

EAN Code: 0731304283232

Overview

Presentation	1U rack-mountable keyboard, mouse, and LCD console with US English keyboard layout.
--------------	---

Main

Product or component type	Console
Main Input Voltage	100 V 240 V
Network frequency	50/60 Hz
Number of rack unit	1U
Provided equipment	C13-C14 power cord Documentation CD Firmware upgrade cable Installation guide NEMA 5-15 power cord PS2 KVM cable Single user rack mount kit USB cable USB KVM cable

Complementary

Mounting location	Front Rear
Mounting mode	Rack-mounted
Minimum mounting depth	680 mm
Maximum mounting depth	1049.8 mm
Display type	LCD display
Display power consumption	19 W
Pixel size	0.26
Trackball type	PS/2 touchpad USB mouse
Colour	Black
Height	44 mm
Width	482 mm
Depth	614 mm
Net weight	15.9 kg
Display colour	16 colours
Display size	17 inch

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Product certifications	C-Tick CE Industry Canada KCC NOM UL listed VDE TAA compliance
Standards	EN 55022 class A EN 55024 EN 60950 FCC part 15 class A IEC 60950
Ambient air temperature for operation	0...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.000 cm
Package 1 Width	68.000 cm
Package 1 Length	83.800 cm
Package 1 Weight	17.571 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	56 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	53 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



