

Product datasheet

Specifications



APC Back-UPS Pro External Battery Pack

BR24BPG

EAN Code: 0731304268789

Main

Main Input Voltage	120 V
Product or component type	External battery pack
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual
Range of product	Back-UPS Pro

Batteries & Runtime

Device mounting	Stand alone battery stack
Battery life	4...6 year(s)
Battery voltage	24 V
Battery capacity	18 Ah
Number of battery filled slots	2
Number of battery free slots	0
Number of battery replacement quantity	1
Battery power in VAh	372 VAh

Physical

Colour	Black
Height	301 mm
Width	112 mm
Depth	382 mm
Product weight	13.4 kg
USB compatible	No

Conformance

Product certifications	TÜV
------------------------	-----

Environmental

Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Ambient air temperature for storage	-15...45 °C

Ambient air temperature for operation	0...40 °C
Operating altitude	0...30000 ft
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.000 cm
Package 1 Width	24.000 cm
Package 1 Length	49.100 cm
Package 1 Weight	14.569 kg
Unit Type of Package 2	P06
Number of Units in Package 2	3
Package 2 Height	52.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	50.707 kg
SCC14	10731304268786

Logistical informations

Country of origin	PH
-------------------	----

Contractual warranty

Warranty (in months)	12 Battery 36 UPS
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	67 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	54 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	51 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1068e1eb-6a97-4f67-a95e-95f440cdd7dd
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	End of Life Information
Removable battery	No
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

