Overview

HP Notebook Power Bank

Model

HP Notebook Power Bank



Front 2.

- 1. Fuel gauge indicator LEDs
- 3. USB-A port

Fuel gauge button

4. USB-C[™] port



Back

1. DC Ports Out



N9F71AA

Technical Specifications

HP Notebook Power Bank is a high end backup power for charging notebook and mobile devices which carries 6200mAh-6400mAh * capacity. It has one 19V barrel type output port, USB type-C[™] output port, and USB type A output ports.

Specifications

Part number	N9F71AA
Dimensions (H x W x D)	6.85 x 2.84 x .85 in 174 x 72 x 21.5 mm
Weight	.88 lb (400 g)
Battery Capacity	11,400 mAH, 72 Wh
Connectors	Power In -1 4.5mm, 1 7.4mm Power Out – 1 4.5mm, 1 USB-C, 1 USB-A
Rated Input	19V, Max 2 A
Rated Output	DC 19V, Max 2.35 A (45W max) DC 5V, 3A (15W max) USB Type C DC 5V, 2.4A (12W max) USB Type A
LED Indicator	4 LED/Power Indicators 100%~75% 4 LEDS 75%~50% 3 LEDs 50%-25% 2 LEDs Lower 25% 1 LED
Charging method	HP 45W Power adapter (not included)
Limited Warranty	1 year
Compatibility	HP 200 G3 and G4 Series HP ProBook 400 G2, G3, G4 and G5 HP ProBook 600 G1, G2, and G3 HP EliteBook 700 and 800 G1, G2, G3 and G4 HP EliteBook 1020 G1 HP EliteBook 1040 G2, G3 and G4 HP EliteBook Revolve 810 G3 HP ChromeBook 14 G4 HP Stream 11 Pro G1 and G2 HP Stream 14 Pro G3 HP Chromebook 11 G5 HP Chromebook 13 G1 HP EliteBook 1030 G1 HP Spectre Pro x360

Total mAH calculation based on 6 cells: ~ 3,200 mAh running in parallel – $(2-3,200 \text{ mAh}) = -\frac{6,400 \text{ mAh}}{6,400 \text{ mAh}}$. 3 sets of parallel batteries: 3*6,400= ~19,200 mAh.



Technical Specifications

HP USB-C Notebook Power Bank

Model

HP USB-C Notebook Power Bank

2NA10AA



Front

- 1. Fuel gauge indicator LEDs
- 3. USB-C[™] port (charge out)
- 5. USB-C[™] port (charge in/out)

- 2. Fuel gauge button
- 4. USB-A port (charge out)



Technical Specifications

Charge and power your notebook and your USB devices from one USB-C[™] connection, even when you can't get to a power outlet or stop to change a battery with the HP USB-C Notebook Power Bank.

Specifications

Part number	2NA10AA	
Dimensions (H x W x D)	6.65 x 2.90 x .91 in (169 x 73.6 x 23 mm)	
Weight	0.96 lbs (0.44kg)	
Battery Capacity	20,100 mAh, Wh: 72.36WH	
Connectors	USB-C (3 amps), USB- A (2.4 amps)	
Rated Input	60W maximum	
Rated Output	USB-C Power in: Output voltage:20V/15V/12V/10V/9V/5V; Output current: 3A (Max) USB-C Power Out: Output voltage:5V, Output current: 3A (Max) USB-A Power Out: 5V, Output current: 2.4A (Max)	
Cell Type	Cylindrical SDI 18650 35E; LGC 18650 MJ1	
Voltage	10.8V	
Operating Temperature (charging)	0~45°Qfollowing cell SPEC)	
Operating (discharging)	-10~60°((following cell SPEC)	
Non-operating	Storage Temperature: 1 year 0~23°@following cell SPEC) 3 months 0~45°@following cell SPEC) 1 month 0~60°@following cell SPEC)	
Battery Recharge Time (System in OFF or Standby Mode)	0%-100% Less than 3 hours	
Fuel Gauge LED	Yes	
LED Indicator	4 LED/Power Indicators 100%~75% 4 LEDS 75%~50% 3 LEDs 50%-25% 2 LEDs Lower 25% 1 LED	
Charging method	HP 45W USB-C Power Adapter (not included) HP 65W USB-C Power Adapter (recommended not included)	



Technical Specifications

Limited Warranty

Compatibility

1 year

HP x2 1012 G1, G2 Tablet HP x2 612 G2 Tablet HP EliteBook x360 1020 G2 HP EliteBook Folio G1 HP Elite x3, HP Pro Tablet 608 G1 HP ChromeBook x360 11 G1 EE HP ChromeBook 13 G1 HP EliteBook x360



Technical Specifications

HP USB-C Essential Power Bank

Model

HP USB-C Essential Power Bank

3TB55AA



Charge and power your Windows or macOS[®] notebook and USB devices from a single USB-C[™] connection, even when you can't plug in, with the HP USB-C Essential Power Bank. Enjoy the functionality of an AC adapter and battery with the expansion of a USB hub in one essential device.

Specifications

Part number Cell type Voltage Power in Power out	3TB55AA SAMSUNG SDI INR18650-29E6 14.6V Type C Connect 20V/3A, 15V/3A Type C cable 5V/3A Pogo In 19.5V/1.5A Type C cable 20V/3A, 15V/3A, 12V/3A, 10V/3A, 9V/3A, 5V/3A
	· · · · · · · · · · · · ·
	Type C Connect 5V/3A
	Туре А 5V/2.4А
Operating temperature (charging)	Charge: 0 ~45°C
Operating temperature (discharging)	Discharge: -20 ~ 60°C
Non-operating	Within 1 year :-20~20°C
	Within 3 month :-20~45°C
	Within 1 month :-20~60°C
Battery recharge time (system in off or standby mode)	Battery Recharge Time @ Charge Power Bank only -> 20V/15V , 2.5 HR
Fuel gauge LED	Yes



Change Log

Date of change	Version History		Description of change
Sep 27 2016	V1 to V2		Battery capacity
Sep 28 2016	V2 to V3		"Thunder Bolt Out" to "DC Ports Out"; Dimensions mm size
June 27, 2017	V3 to V4		Compatibility added for EliteBook G4, 820, 840, 850
July 17 2017	V4 to V5	Added	Picture with DC adapter ports added replacing line art
August 14, 2017	V5 to V6	Added	HP USB-C Notebook Power Bank (2NA10AA) added
August 16, 2017	V6 to V7	Added	HP Notebook Power Bank front view picture added replacing line art
August 17, 2017	V7 to V8	Added	Callouts added for HP Notebook Power Bank
August 18, 2017	V8 to V9	Added	Callouts added for HP USB-C Notebook Power Bank
August 22, 2017	V9 to V10	Added	HP USB-C Notebook Power Bank specs added
August 28, 2017	V10 to V11	Added	HP USB-C Notebook Power Bank callouts updated
August 9, 2018	V11 to V12	Change	Battery capacity, Connectors power out and rated output Specs
			updated
November 1,	V12 to V13	Added	HP USB-C Essential Power Bank
2018			

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Bluetooth is a trademark of its proprietor and used by HP Inc. under license. USB Type-C^M and USB-C^M are trademarks of USB Implementers Forum.

