

# Product datasheet

Specifications



## APC SYMMETRA LX 3 BATTERY RACK-MOUNT XR FRAME, 230V



SYBFXR3RMI

EAN Code: 0731304221708

### Overview

**Presentation** Extended run power protection for servers, networks, and telecommunications

### Main

Product or component type	Frame
Number of rack unit	5U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	Installation guide User manual
Range of product	Symmetra Battery Systems

### Batteries & Runtime

Battery location	Battery cabinet
Number of battery free slots	3
Number of battery filled slots	0
Battery manufacturer	Panasonic
Device mounting	Enclosed battery cabinet
Number of battery replacement quantity	3

### Physical

Colour	Black
Height	215 mm
Width	472 mm
Depth	686 mm
Product weight	26.82 kg
Mounting mode	Rack-mounted

### Conformance

Standards	EN 50091-1 EN 50091-2 EN 60950 IEC 60950
Product certifications	BSMI VCCI VDE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environmental

---

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...4572 m
Storage Relative Humidity	0...95 %

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.1 cm
Package 1 Width	60.96 cm
Package 1 Length	99.06 cm
Package 1 Weight	30.7 kg

## Logistical informations

---

Country of origin	PH
-------------------	----

## Contractual warranty

---

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	109 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	104 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---



