



## Main

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                  | Compact                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Product name                           | Compact NSX                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Product or component type              | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Device short name                      | Compact NSX100H                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Device application                     | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Poles description                      | 3P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Protected poles description            | 3t                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Network type                           | AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Network frequency                      | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| [In] rated current                     | 100 A ( 40 °C )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| [Ui] rated insulation voltage          | 800 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| [Uimp] rated impulse withstand voltage | 8 kV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| [Ue] rated operational voltage         | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Breaking capacity code                 | H (70 kA) AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Breaking capacity                      | 50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 600 V AC 50/60 Hz conforming to UL 508<br>65 kA at 480 V AC 50/60 Hz conforming to UL 508<br>85 kA at 240 V AC 50/60 Hz conforming to UL 508 |
| [Ics] rated service breaking capacity  | Ics 10 kA 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>Ics 100 kA 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>Ics 35 kA 525 V AC 50/60 Hz conforming to IEC 60947-2<br>Ics 50 kA 500 V AC 50/60 Hz conforming to IEC 60947-2<br>Ics 65 kA 440 V AC 50/60 Hz conforming to IEC 60947-2<br>Ics 70 kA 380/415 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                                                                                            |
| Suitability for isolation              | Yes conforming to EN 60947-2<br>Yes conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Utilisation category                   | Category A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| Trip unit name                 | TM-D                                                                 |
| Trip unit technology           | Thermal-magnetic                                                     |
| Trip unit protection functions | LI                                                                   |
| Trip unit rating               | 50 A ( 40 °C )                                                       |
| Protection type                | Overload protection (thermal)<br>Short-circuit protection (magnetic) |
| Pollution degree               | 3 conforming to IEC 60664-1                                          |

## Complementary

|                                                        |                                                                                                                                                                                                              |
|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control type                                           | Toggle                                                                                                                                                                                                       |
| Mounting mode                                          | Fixed                                                                                                                                                                                                        |
| Mounting support                                       | Backplate                                                                                                                                                                                                    |
| Upside connection                                      | Front                                                                                                                                                                                                        |
| Downside connection                                    | Front                                                                                                                                                                                                        |
| Auxiliary contact composition                          | Without                                                                                                                                                                                                      |
| Mechanical durability                                  | 50000 cycles                                                                                                                                                                                                 |
| Electrical durability                                  | 10000 cycles 690 V In conforming to IEC 60947-2<br>20000 cycles 690 V In/2 conforming to IEC 60947-2<br>30000 cycles 440 V In conforming to IEC 60947-2<br>50000 cycles 440 V In/2 conforming to IEC 60947-2 |
| Connection pitch                                       | 35 mm                                                                                                                                                                                                        |
| Local signalling                                       | Positive contact indication                                                                                                                                                                                  |
| Long time pick-up adjustment type Ir                   | Adjustable                                                                                                                                                                                                   |
| Long time pick-up adjustment range                     | 0.7...1 x In                                                                                                                                                                                                 |
| Long time delay adjustment type                        | Fixed                                                                                                                                                                                                        |
| [Tr] long-time delay adjustment range                  | 15 s 6 x Ir<br>120...400 s 1.5 x In                                                                                                                                                                          |
| Short-time pick-up adjustment type I <sub>sd</sub>     | Fixed                                                                                                                                                                                                        |
| [I <sub>sd</sub> ] short-time pick-up adjustment range | 500 A                                                                                                                                                                                                        |
| Short-time delay adjustment type                       | Fixed                                                                                                                                                                                                        |
| Height                                                 | 161 mm                                                                                                                                                                                                       |
| Width                                                  | 105 mm                                                                                                                                                                                                       |
| Depth                                                  | 86 mm                                                                                                                                                                                                        |
| Product weight                                         | 2.05 kg                                                                                                                                                                                                      |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Overvoltage category                  | Class II                     |
| Electrical shock protection class     | Class II                     |
| Standards                             | EN/IEC 60947<br>UL 508       |
| Product certifications                | CCC<br>Marine<br>EAC         |
| IP degree of protection               | IP40 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -35...70 °C                  |
| Ambient air temperature for storage   | -55...85 °C                  |

## Offer Sustainability

|                          |                                                                                                                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product                                                                                                                                                                                                     |
| RoHS (date code: YYWW)   | Compliant - since 0819 - Schneider Electric declaration of conformity<br> <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                    | Reference not containing SVHC above the threshold                                                                                                                                                                         |

Reference not containing SVHC above the threshold

|                                  |           |
|----------------------------------|-----------|
| Product environmental profile    | Available |
| Product end of life instructions | Available |

### Contractual warranty

|                 |                     |
|-----------------|---------------------|
| Warranty period | 18 months 18 months |
|-----------------|---------------------|