

## iQ100, Integrated cooker hood, 60 cm, silver LE66MAC00B



B



This fold-out integrated hood with a high extraction rate for powerful performance is hidden in the upper cabinet unit.

✓ LED lights: For optimal visibility and ambience when cooking.

### Features

#### Technical Data

Typology : Pull-out  
Approval certificates : CE  
Length of electrical supply cord (cm) : 150  
Minimum distance above an electric hob : 500  
Minimum distance above a gas hob : 650  
Net weight (kg) : 11.820  
Type of control : mechanical  
Number of speed settings : 3  
Maximum output air extraction (m3/h) : 625  
Number of lights (Stck) : 2  
Noise level (dB(A) re 1 pW) : 70  
Diameter of air outlet (mm) : 150 / 120  
Grease filter material : Washable aluminium  
EAN code : 4242003806500  
Connection rating (W) : 256  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 50; 60  
Plug type : GB plug  
Installation type : Wall-mounted



4 242003 806500

### Optional accessories

LZ10IMA00 Standard odor filter

**iQ100, Integrated cooker hood, 60 cm,  
silver  
LE66MAC00B**

#### Features

**Key performance features:**

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 625 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB\*

**Features**

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- 2 x metal grease filter cassettes

**Design**

- Integrated hood
- Installation between cupboards
- Mechanical

**Performance/technical information**

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 68.4 kWh/year\*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating, chimney (HxWxD): 402-402 x 599 x 271 mm

**Optional accessories**

- Recirculating kit LZ10IMA00

\* In accordance with the EU-Regulation No 65/2014