

Product Compliance Datasheet

MARKETING NAME	Latitude 5490/ Latitude 5490-01
REGULATORY MODEL	P72G
REGULATORY TYPE	P72G002
EMC EMISSIONS CLASS	В
EFFECTIVE DATE	November 30, 2017

Table of contents

I.	Statement of Compliance	2
II.	Global Environmental Information	2
III.	Power Cords and User Documentation	3
IV.	Trade (Import/Export) Compliance Data	3
V.	Product Dimensions and Weight	3
VI.	Performance Data	3
VII.	Product Materials Information	3
VIII	Packaging	5
IX.	Batteries	6
Х.	Design for Environment	6
	Recycling / End-of-Life Service Information	
XII.	Helpful Links	6
А	Appendix A: ErP Lot 3 Product Energy Consumption Information	8
В	Appendix B: ErP Lot 26 Network Standby Energy Consumption Information	11



I. Statement of Compliance

This equipment has been determined to be compliant with the applicable standards, regulations, and directives for the countries where the equipment is marketed. The equipment is affixed with regulatory marking and text as necessary for the country/agency. Dell manufacturers and markets Multimedia Equipment (MME), Information Technology Equipment (ITE), Audio Visual Equipment (A/V), Industrial, Scientific, Medical Equipment (ISM) or combinations of these. Generally, equipment Safety and EMC compliance is based on International IEC and CISPR standards and their national equivalent along with national standards for Radio (wireless), and Energy. Dell products have been verified to comply with the EU RoHS Directive 2011/65/EU. Dell equipment does not contain any of the restricted substances in concentrations and applications not permitted by the RoHS Directive. EMC Emissions Class refers to one of the following use environments:

• EMC Class B equipment is intended for use in residential/domestic environments but may also be used in nonresidential/non-domestic environments.

• EMC Class A equipment is intended for use in non-residential/non-domestic environments. Class A equipment may also be utilized in residential/domestic environments but may cause interference and require the user to take adequate corrective measures.

For Safety and EMC compliance, this equipment has been assigned a unique regulatory model and regulatory type that is imprinted on the equipment regulatory labeling to provide traceability to the regulatory approvals noted on this datasheet. This datasheet applies to any equipment that utilizes the assigned regulatory model and type including marketing names other than those listed on this datasheet. ErP compliance is tied to the CE mark. REACH (Registration, Evaluation, Authorization and Restriction of Chemicals, 1907/2006) is the European Union's (EU) chemical substances regulatory framework. Dell complies with the REACH directive. For information on SVHC (Substances of Very High Concern), see www.dell.com/REACH. Compliance documentation, such as certification or Declaration of Compliance for the equipment is available upon request to product compliance@dell.com. Please include equipment identifiers such as marketing name, regulatory model, regulatory type and country that compliance information is needed in request.

Environmental (Voluntary Marks)				
Global	ENERGY STAR (Configration Dependent)	Energy Star 6.1		
Global	TCO Certified - Notebook 5.0	Yes		
China	CECP	Yes		
China	CEC	Yes		
Taiwan	Greenmark	Yes		
Brazil	INMETRO	Yes		
Japan	Green PC Label	Yes		
South Korea	Eco Label	Yes		
Varies by Country - see EPEAT.netEPEAT (Configuration Dependent)Gold/Silver				

II. Global Environmental Information

III. Power Cords and User Documentation

Dell products are provided with the power cord and user documentation suitable for the intended country of delivery. Products that are relocated to other countries should use nationally certified power cords and plugs to ensure safe operation of the product. Contact Dell to determine if alternate power cords or user documentation in other languages is available for your market.

IV. Trade (Import/Export) Compliance Data

For any questions related to importing & exporting classification of Dell products, please obtain information from the following link: www.dell.com/import_export_compliance or send request to <u>WW Export_Compliance@dell.com</u>.

V. Product Dimensions and Weight

Depth,	Width,	Height,	Weight, kg
mm/cm	mm/cm	mm/cm	
228.9 mm	333.4 mm	22.45 mm	1.60 Kg (depending upon installed options)

For Display, Imaging products please refer to the user manual for weight and dimension information.

VI. Performance Data

ErP Lot 3 & Lot 26 information is located in section XIV Appendix A

For additional information on ENERGY STAR models refer to the following databases:

http://www.dell.com/en-us/work/learn/power-and-cooling-energy-star

USA: https://www.energystar.gov/productfinder/

EU: http://www.eu-energystar.org/db-currentlists.htm

VII. Product Materials Information

Information on Dell's material use is available <u>here</u>. Dell's Restricted Material for Use guidance document is available <u>here</u>.

- The case material is, LCD_COVER:>PC-CF20FR(40)<, ANTENNA WINDOW: >PC-GF50FR(40)<, LCD_BEZEL:>TPC-ET, PC+AB S-FR(40)<, LOG_UP:>PC-I-(MD+TD)25FR(40)<, INNER_FRAME:>PC-I-(MD+TD)25FR(40)<, BIG_DOOR:>PC-CF20FR(40)<
- This product contains <u>10.7</u>% post-consumer recycled plastic/closed loop recycled plastics



(Measured as a percentage of total amount of plastic (by weight) in the product as per guidance in EPEAT standard as applies to plastics parts)

Mechanical plastic parts ¹ > 25 g are BFR/PVC free	⊠ Yes □ No □ NA
Marking of plastics parts greater than 25 grams is in accordance with ISO 11469 (see below)	⊠ Yes □ No □ NA
Printed circuit boards (without components) >25g are BFR PVC free ²	⊠ Yes □ No □ NA
Insulation materials of external electrical cables are PVC free	□Yes ⊠No □NA
Insulation materials of internal electrical cables are PVC free	⊠Yes ∎No ∎NA
Product is BFR/PVC Free (Accessories & Options may not be BFR/PVC-Free, refer to spec ENV0199)	⊠ Yes □ No

Flame Retardants Used in Motherboard

Part	Flame Retardant	
Motherboard	1-6% Phosphoric flame retardants / DOPO	

Flame Retardants Used in Mechanical Plastic Parts > 25 grams

Resin Material Name	Marking per ISO 11469:2016	Flame Retardant Marking per ISO 1043-4 (i.e. FR(16), FR(40), etc.)	Flame Retardant (i.e. TBBPA, triaryl phosphate ester, etc.)	List applicable R-Phrase(s) or Hazard Statement(s) per EU Directive 67/548/EEG or 1272/2008
DDM70_LCD_COVER	>PC-CF20FR(40)<	FR(40)	Organo Phosphate	NA
DDM70_ANTENNA WINDOW	>PC-GF50FR(40)<	FR(40)	Organo Phosphate	NA
DDM70 LCD_BEZEL	>TPC-ET, <u>PC+ABS</u> - FR(40)<	FR(40)	Organo Phosphate	NA
DDM70 Log up	>PC-I- (MD+TD)25FR(40)<	FR(40)	Organo Phosphate	NA
DDM70_INNER_FRAME_U	>PC-I- (MD+TD)25FR(40)<	FR(40)	Organo Phosphate	NA



¹ Mechanical plastic part: plastic parts that do not internally carry an electrical signal such as housings, brackets, bezels, latches, etc. that form the basic structure of the product and/or have mechanical functions. Plastic parts such as fans, connectors, printer fuser assemblies, etc. are not considered "mechanical plastic parts" in the context of this specification. Plastics parts do not contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride (Per Dell Spec ENV0424)
² Dell will adopt the BFR/CFR/PVC-free definition as set forth in the "iNEMI Position Statement on the Definition of 'Low-Halogen' Electronics (BFR/CFR/PVC-

² Dell will adopt the BFR/CFR/PVC-free definition as set forth in the "iNEMI Position Statement on the Definition of 'Low-Halogen' Electronics (BFR/CFR/PVC-Free)." Plastic parts contain <1000 ppm (0.1 percent) of bromine (if the Br source is from BFRs) and <1000 ppm (0.1 percent) of chlorine if the CI source is from CFRs, PVC or PVC copolymers. All printed circuit board (PCB) and substrate laminates contain bromine/chlorine totaling less than 1,500 ppm (0.15 percent), with maximum chlorine of 900 ppm (0.09 percent) and maximum bromine of 900 ppm (0.09 percent)

Resin Material Name	11469:2016 IS (i F		Flame Retardant (i.e. TBBPA, triaryl phosphate ester, etc.)	List applicable R-Phrase(s) or Hazard Statement(s) per EU Directive 67/548/EEG or 1272/2008
DDP70_INNER_FRAME_H	>PC-I- (MD+TD)25FR(40)<	FR(40)	Organo Phosphate	NA
DDP70_INNER_FRAME_HD	>PC-I- (MD+TD)25FR(40)<	FR(40)	Organo Phosphate	NA
CDM70_BIG_DOOR_U	>PC-CF20FR(40)<	FR(40)	Organo Phosphate	NA
CDP70_BIG_DOOR_H	>PC-CF20FR(40)<	FR(40)	Organo Phosphate	NA

Mercury Information

Number of bulbs	Average per bulb
0	NA

Additional information:

 RoHS and REACH declaration - see product material information section at: <u>www.dell.com/environmental_information</u>

• Products MSDS (Material Safety Data Sheets): Batteries: <u>Battery MSDS Documentation and Declaration</u> Printer Toner and Ink: <u>MSDS Documentation</u>

VIII. Packaging

Information on Dell's sustainable packaging effort available here.

Additional materials restricted in Packaging as per Dell's Restricted Material Guidance document found here.

Total Packaging Materials Weight,		Sustainable Material Content ³ (e.g Recycled content *,bio-	% Sustainable Material		
i denaging materiale	(kg)	based, Sustainable Forested	APJ	DAO	EMEA
	(kg)	materials)	region	region	region
Corrugated Fiberboard	0.387	Recycled Content	Min 50%	Min 50%	Min 50%
LDPE (Including EPE Foam)	0.003	Recycled Content	0-80%	0-80%	0%

3 Non-wood, biobased material may include, but is not limited to: bagasse, bamboo, mushroom, straw, agricultural waste or byproduct. * Recycled content in packaging material is supplier dependent.

feeMolded paper pulp	0.150	Recycled content	100%	100%	100%
HDPE (including thermoformed) *	0.013	Recycled Content	0-80%	0-80%	0%
Molded Bamboo	0	Non-wood, biobased material	100%	100%	100%
Wheat Straw	0	Non-wood, biobased material	100%	100%	100%
Mushroom	0	Non-wood, biobased material	100%	100%	100%
LDPE Bags	0	NA	0%	0%	0%
EPS	0	NA	0%	0%	0%
Other, please specify	0				

IX. Batteries

Below is a listing of batteries that could be present in the product:

Battery Description – Batteries	Battery Type	Battery Weight (kg)
CR-2032 coin cell	Lithium	0.005 (max)
Rechargeable Battery 3 cell 42Wh	Lithium Ion	0.210 (max)
Rechargeable Battery 3 cell 51Wh	Lithium Ion	0.250 (max)
Rechargeable Battery 4 cell 68Wh	Lithium Ion	0.340 (max)

X. Design for Environment

Dell systems are, when applicable, designed for easy assembly, disassembly, and servicing. For more information on product Recyclability please visit www.dell.com/environmental_information

XI. Recycling / End-of-Life Service Information

Take back and recycling services are offered for this product in certain countries. If you want to dispose of system components, please visit <u>www.dell.com/recyclingworldwide</u> and select the relevant country.

XII. Helpful Links

Product Compliance Datasheet | ENV0023 | A12 Dell, Inc. www.dell.com



- Environmental Policy
 <u>http://i.dell.com/sites/content/corporate/corp-comm/en/Documents/dell-global-environmental-policy.pdf</u>
- Environment Website www.dell.com/environmental_information
- Corporate Sustainability Report
 http://www.dell.com/Learn/us/en/uscorp1/report?c=us&l=en&s=corp&delphi:gr=true
- ISO 14001 Certification
 http://i.dell.com/sites/content/corporate/corp-comm/en/Documents/dell-iso14001-worldwide.pdf
- Materials Restricted for Use
 http://www.dell.com/downloads/global/corporate/environ/restricted_materials_guid.pdf
- Chemical Use Policy
 <u>http://i.dell.com/sites/doccontent/corporate/environment/en/Documents/chemical-use-policy.pdf</u>
- Product Carbon Footprint
 <u>http://content.dell.com/us/en/corp/d/corp-comm/environment_carbon_footprint_products</u>
- RoHS Compliance
 www.dell.com/rohsinfo
- REACH Compliance
 <u>www.dell.com/REACH</u>
- Recycling Information
 <u>www.dell.com/recycling</u>
- Supplier Responsibility
 <u>http://content.dell.com/us/en/corp/d/corp-comm/standards-for-suppliers.aspx</u>



A Appendix A: ErP Lot 3 Product Energy Consumption Information

ErP Lot 3 (EU No 617/2013)

The ErP Lot 3 regulation includes requirements for certain product specific information to be provided by the manufacturer. This is applicable to Desktops, Integrated Desktops (All-in-One), Notebooks, Tablets, Slates, Notebook Thin Clients, Desktop Thin Clients, Workstations, Mobile Workstations, Computer Servers, and Small Scale Servers.

ErP Lot 3 provides certain exclusions based upon product type, screen size, and/or the amount of power consumed in idle mode. Product energy and acoustic information might be reported for products that are out of scope of ErP Lot 3 for informational purposes only.

inornational purposes only.		
Processor Speed in GHz	1.9	1.9
Number of Cores	4	4
Total Installed System Memory in GB	32	32
Graphics	53(with FB Data Width <= 128-bit	Integrated
Category	Category B	Category A
Total Installed Memory in GB	32	32
Memory Adder	11.2	11.2
'Additional Internal Storage' m	ans any and all internal storage devices, ind included within a cor	cluding hard disk drives (HDD), solid state nputer beyond the first;
Additional Internal Storage?	Yes	Yes
Storage Adder	3.00	3.00
	3(with FB Data Width <= 128-bit	Integrated
1st Discrete Graphics Adder	13.00	0.00
2nd Discrete Graphics Card?	N/A	N/A
2nd Discrete Graphics Adder	0.00	0.00
	n tuner' means a discrete internal compo	onent that allows a computer to receive to
Discrete Television Turner Card?	No	No
Discrete TV Turner Card Adder	0.00	0.00
Category	Category B	Category A
Processor Speed in GHz	1.9	1.9
Number of Cores	4	4
Total Installed System Memory in GB	32	32
Graphics	G3(with FB Data Width <= 128-bit)	Integrated
WOL enabled in "Sleep" Mode	No	No
WOL enabled in "Off" Mode	No	No
As Tested: Lowest Power State	0.09	0.09
As Tested: Poff(W) WOL Disabled	0.35	0.35
As Tested: Poff(W) WOL Enabled	0.22	0.94
As Tested: Psleep(W) WOL Disabled	0.93	1.48
As Tested: Psleep(W) WOL Enabled	();<÷	1.53
As Tested: Pidle(W)	4.60	5.34
Base TEC Limit (kWh)	36	27
TEC Adders Limit (kWh)	27.20	14.20
Base + Adders TEC Limit (kWh)	63.20	41.20
Results TEC	14.71	17.16

Product Compliance Datasheet | ENV0023 | A12 Dell, Inc. www.dell.com



Power Supply Model #	Internal or External	Link to efficiency report
DA65NM111-00	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=5478051&appliance=EPS&nr=1
HA65NS5-00	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=5470487&appliance=EPS&nr=1
LA65NS2-01	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=5485275&appliance=EPS&nr=1
HA65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=6448362&appliance=EPS&nr=1
LA65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=14644026&appliance=EPS&nr=1
DA65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=8954085&appliance=EPS&nr=1
HK65NM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=14082454&appliance=EPS&nr=1 http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=8095191&appliance=EPS&nr=1
DA90PM130	External	http://oee.nrcan.gc.ca/pml-lmp/index.cfm?action=app.formHandler&operation=details- details&ref=6448377&appliance=EPS&nr=1

* **Energy Consumption** results are based solely upon the laboratory testing of the **System Configuration** listed above. Energy consumption is tested at 230 Volts / 50 Hz.

Energy Consumption*

Energy efficiency benefits the environment and lowers the total cost of equipment ownership by reducing power consumption. Dell offers energy calculators that help estimate power needs, potential emissions avoidance and potential cost savings. Click <u>here</u> for Dell's Client Energy Savings Calculator, Data Center Capacity Planner, and Monitor Power Savings Calculator. Information on Energy Efficiency is available <u>here</u>

* This document is informational only and reflects laboratory performance. Your product may perform differently, depending on the software, components and peripherals you ordered. Accordingly, the customer should not rely upon this information in making decisions about electrical tolerances or otherwise. No warranty as to accuracy or completeness is expressed or implied.

For more details visit www.dell.com/environmental information

Internal Power Supplies (not tested by ECOVA)

Declared Noise Emissions in accordance with ISO 9296 (tested in accordance with ISO 7779)

Computers Category A:

Service Level	Sound Power (L _{WAd} , bels) (1 bel=10 decibels, re 10 ⁻¹² Watts)	Sound Pressure Bystander Position (L _{pAm} , decibels) (re 2x10 ⁻⁵ Pa)
Hard Drive Accessing	3.0	17.0
Optical Drive Accessing	-	-
Idle	30	17.0

Computers Category B:

Service Level	Sound Power (L _{WAd} , bels) (1 bel=10 decibels, re 10 ⁻¹² Watts)	Sound Pressure Bystander Position (L _{pAm} , decibels) (re 2x10 ⁻⁵ Pa)
Hard Drive Accessing	2.6	14.0
Optical Drive Accessing	-	-
Idle	2.6	14.0



Β

Appendix B: ErP Lot 26 Network Standby Energy Consumption Information

ErP Lot 26 (EU No 801/2013)

The ErP Lot 26 regulation includes Network Standby power requirements to be provided by the manufacturer. This is applicable to multiple product categories. If no information is reported, it's assumed it is out of scope of ErP Lot 26.

Network Standby ClassificationLoNAOff/Standby - Watts0.346Network Standby - Watts1.531Number of Network Ports1Location of 'Physical' Network PortsSideNetwork Port TypeEthernetNetwork Port(s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port (s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPStandby ModeInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this modeand/or www.dell.com/regulatory_compliance and/orInactivity time required to enter Network Standbywww.dell.com/support		,
Network Standby - Watts1.531Number of Network Ports1Location of 'Physical' Network PortsSideNetwork Port TypeEthernetNetwork Port(s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port (s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPSequence of events to trigger automatic assertion of Network Standby ModeInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this mode Inactivity time required to enter Network Standbyand/orwww.dell.com/supportwww.dell.com/support	Network Standby Classification	LoNA
Number of Network Ports1Location of 'Physical' Network PortsSideNetwork Port TypeEthernetNetwork Port(s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port (s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPSequence of events to trigger automatic assertion of NetworkInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this modeand/orInactivity time required to enter Network Standbywww.dell.com/supportRe-activation triggerNetwork Standby	Off/Standby - Watts	0.346
Location of 'Physical' Network PortsSideNetwork Port TypeEthernetNetwork Port(s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPStandby ModeInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this mode Inactivity time required to enter Network Standbyand/or www.dell.com/support	Network Standby - Watts	1.531
Network Port TypeEthernetNetwork Port(s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPSequence of events to trigger automatic assertion of NetworkInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this modeand/orInactivity time required to enter Network Standbywww.dell.com/support	Number of Network Ports	1
Network Port(s) Activated or DeactivatedNetwork Port(s) "Activated"Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPSequence of events to trigger automatic assertion of NetworkInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this mode Inactivity time required to enter Network Standbyand/or www.dell.com/support	Location of 'Physical' Network Ports	Side
Network Port Maximum Performance in GB/s1000Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeEthernet - TCPIPSequence of events to trigger automatic assertion of Network Standby ModeInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this mode Inactivity time required to enter Network Standbyand/or www.dell.com/supportRe-activation triggerRe-activation trigger	Network Port Type	Ethernet
Communication protocol used by equipmentEthernet - TCPIPDescription of how to assert Network Standby ModeSequence of events to trigger automatic assertion of NetworkStandby ModeInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this modeand/orInactivity time required to enter Network Standbywww.dell.com/support	Network Port(s) Activated or Deactivated	Network Port(s) "Activated"
Description of how to assert Network Standby ModeSequence of events to trigger automatic assertion of NetworkStandby ModeNotes regarding operation of the equipment EX: how the userswitches the equipment into network standbyDefault time for PM function to switch equipment into this modeInactivity time required to enter Network StandbyRe-activation trigger	Network Port Maximum Performance in GB/s	1000
Sequence of events to trigger automatic assertion of Network Information available @ Standby Mode Information available @ Notes regarding operation of the equipment EX: how the user www.dell.com/regulatory_compliance switches the equipment into network standby and/or Default time for PM function to switch equipment into this mode and/or Inactivity time required to enter Network Standby www.dell.com/support	Communication protocol used by equipment	Ethernet - TCPIP
Standby ModeInformation available @Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @Default time for PM function to switch equipment into this mode Inactivity time required to enter Network Standbyand/orRe-activation triggerwww.dell.com/support	Description of how to assert Network Standby Mode	
Notes regarding operation of the equipment EX: how the user switches the equipment into network standbyInformation available @ www.dell.com/regulatory_compliance and/orDefault time for PM function to switch equipment into this modeand/orInactivity time required to enter Network Standby Re-activation triggerwww.dell.com/support	Sequence of events to trigger automatic assertion of Network	www.dell.com/regulatory_compliance and/or
Notes regarding operation of the equipment EX: how the user switches the equipment into network standby Default time for PM function to switch equipment into this mode Inactivity time required to enter Network Standby Re-activation trigger	Standby Mode	
Switches the equipment into fletwork standby and/or Default time for PM function to switch equipment into this mode and/or Inactivity time required to enter Network Standby www.dell.com/support Re-activation trigger Ket and the standby	Notes regarding operation of the equipment EX: how the user	
Inactivity time required to enter Network Standby www.dell.com/support Re-activation trigger www.dell.com/support	switches the equipment into network standby	
Re-activation trigger	Default time for PM function to switch equipment into this mode	
	Inactivity time required to enter Network Standby	
	Re-activation trigger	
Measurement Method	Measurement Method	

