

Power Delivery Wall Charger with Built-in USB-C Cable – 60 W

USB-C Power Delivery Connector (up to 60 W), USB-A Charging Port (up to 2.4 A), White

Part No.: 180245

Power up your devices with a portable, powerful Power-Delivery-capable charger.

Enjoy complete charging power with the Manhattan Power Delivery Wall Charger with Built-in USB-C Cable – 60 W. The charger's attached USB-C cable uses Power Delivery (PD) technology to provide plenty of power to laptops and mobile phones, and the additional USB-A port can quickly charge any handheld device or tablet. The perfect companion for travelers with its stylish, compact and ultra-modern design, the Manhattan Power Delivery Wall Charger with Built-in USB-C Cable – 60 W also intelligently safeguards itself and your devices with its short-circuit-, overvoltage-, overcurrent- and overtemperature-protection functions.

Features:

- Two-device charging solution with USB-C Power Delivery (PD 3.0) and USB-A charging port
- Charges two different devices simultaneously with ideal potential energy
- USB-C cable with PD function delivering up to 60 W to charge a notebook, laptop, Ultrabook, tablet or other USB-C powered device
- USB-A port delivering up to 5 V / 2.4 A to quickly charge a portable device
- Overload, overcurrent and overheating protection
- Compact, portable and stylish design for easy travel

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Three-year warranty

Specifications:

Standards and Certifications
• USB 2.0
• PD 3.0
• FCC
• UL
• CE
• RoHS
• WEEE

Connections
• One built-in USB-C cable with Power Delivery (PD 3.0)
• One USB-A

General
• AC input: 100 – 240 V; 50 – 60 Hz
• USB-C output: 5 – 20 V; maximum 3 A; 60 W
• Voltage/current settings (maximum):
- USB-C:
- 5 V / 3 A
- 9 V / 3 A
- 12 V / 3 A
- 15 V / 3 A
- 19 V / 3 A
- 20 V / 3 A
- USB-A:
- 5 V / 2.4 A

Input Characteristics
• AC rated voltage: 100 – 240 V
• Frequency range: 50 – 60 Hz (±1 Hz)
• Current: ? 1 A at 100 VAC 60 HZ

Output Characteristics
• Rated voltage: 5 / 9 / 12 / 15 / 19 / 20 V
• Current: 3 A maximum (at constant voltage mode)
• Rated power: 60 watts maximum
• Overshoot voltage: ? 5%

Protection Characteristics
• Short circuit (SCP) with auto-recovery mode
• Overvoltage (OVP) with auto-recovery mode
• Overcurrent (OCP) — current limit: 150% (max)
• Overtemperature (OTP)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Physical
• Dimensions: 7 x 7 x 3 cm (2.76 x 2.76 x 1.18 in)
• Weight: 0.22 kg (7.5 oz.)
• Housing: plastic

Operating Environment
• Operation Temperature: 0 – 30°C (32 – 86°F)
• Storage Temperature: -20 – 65°C (-4 – 149°F)
• Humidity (noncondensing): 10 – 90%

Package Contents
• Power Delivery Wall Charger with Built-in USB-C Cable – 60 W
• Quick Instruction Guide









For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.



For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.