

DisplayPort to VGA/DVI/HDMI All-in-One Converter Adapter, DP ver 1.2, 4K 30 Hz HDMI, 50 pack

MODEL NUMBER: P136-06NHDV4KBP











Passive adapter connects your DisplayPort (DP) computer to a VGA, DVI or HDMI display for playing 4K video without separate adapters.

Features

A Smart Solution for Displaying 4K Video in Business and Digital Signage Applications

This set includes 50 P136-06N-HDV-4K DisplayPort 1.2 to VGA/DVI/HDMI passive adapters. Each adapter allows you to play stereo audio and high-definition or Ultra High Definition video from your DisplayPort computer to a VGA, DVI or HDMI display. No more carrying around separate adapters for various monitors, projectors and televisions. The simple all-in-one solution for displaying content on a larger screen, these units are an easy, inexpensive way to play high-quality audio and video in classrooms, conference rooms, trade shows and other on-the-road presentations.

Ready to Use Right Out of the Package

Ideal for displaying video on a large monitor or digital sign, each adapter is perfectly sized for carrying in your pocket, briefcase, purse or laptop bag for convenient use anywhere. Just connect the male DP end to your computer's DisplayPort and the female VGA, DVI or HDMI connector to a compatible cable to begin sharing audio/video signals. Only one display may be connected at a time. The plug-and-play P136-06N-HDV-4K requires no software, drivers or external power.

Enjoy Outstanding Picture Quality up to 4K x 2K

The all-in-one unit contains separate female DVI, HD15 and HDMI ports. It supports video resolutions up to 1920 \times 1080, including 1080p (DVI); 1920 \times 1200, including 1080p (HD15); and 4K \times 2K at 24/30 Hz. The HDMI port also supports 7.1-channel surround sound audio.

Passive Adapters Require DisplayPort++ for HDMI Pass Through

Because they are passive adapters, these units require that the connected source device have a DisplayPort++ (DP++) dual-mode port, which allows HDMI signals to pass through. Check your DisplayPort source's documentation for compatibility.

Highlights

- 50-piece bulk pack of P136-06N-HDV-4K DisplayPort 1.2 converter adapters
- Delivers UHD picture quality resolutions up to 4K x 2K (3840 x 2160) @ 24/30 Hz
- HDMI port supports 7.1-channel surround sound for crystal-clear audio
- Compact unit fits easily into pocket, briefcase or laptop bag for use anywhere
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Play video from your DP laptop or PC on a large display, such as an HDTV
- Access documents and websites across multiple displays
- Design and edit graphics files or production video on a larger monitor
- Using a DisplayPort laptop to deliver presentations in a classroom or conference room
- Display menus, ads, promos, directions and other digital signage applications on an HD monitor

System Requirements

- Source device with DisplayPort output and DP++ port for HDMI pass-through (must support audio to transmit audio signals)
- Display device with VGA, DVI or HDMI input

Package Includes

- (50) P136-06N-HDV-4K DisplayPort 1.2 to VGA/DVI/HDMI All-in-One Converter Adapters
- Quick Start Guide

Specifications

OVERVIEW



UPC Code			
Technology			
VIDEO Max Supported Video Resolution HDMI: 3840 x 2160 (4K) @ 30Hz; DVI, VGA: 1920 x 1200 (1080p) AUDIO Audio Specification 7.1 Channel Surround Sound INPUT Product Length (In.) 5.9 PHYSICAL Color Black Material Construction ABS, PVC Cable Jacket Material PVC			
Max Supported Video Resolution HDMI: 3840 x 2160 (4K) @ 30Hz; DVI, VGA: 1920 x 1200 (1080p) AUDIO Audio Specification 7.1 Channel Surround Sound INPUT Product Length (ft.) 5.9 PHYSICAL Color Black Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (kg.) 0.1 Unit Weight (kg.) 0.5 ENVIRONMENTAL Operating Temperature Range 32* to 113*F (0* to 45°C) Conget Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 10% to 85% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE)	Technology	DVI; HDMI; VGA/SVGA; DisplayPort	
Audio Specification 7.1 Channel Surround Sound INPUT	VIDEO		
Audio Specification 7.1 Channel Surround Sound	Max Supported Video Resolution	HDMI: 3840 x 2160 (4K) @ 30Hz; DVI, VGA: 1920 x 1200 (1080p)	
Product Length (in.) 5.9 Product Length (it.) 0.49 PHYSICAL Color Black Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32* to 113* f (0* to 45*C) Storage Temperature Range 14* to 176* f (-10* to 80*C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side B - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE) (WIRED TO DVI-D SINGLE-LINK)	AUDIO		
Product Length (in.) 5.9 Product Length (it.) 0.49 PHYSICAL Color Black Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Journal Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (kg) 0.5 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 5% to 90% RH, Non-Condensing Storage Humidity Range Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE) (WIRED TO DVI-D SINGLE-LINK)	Audio Specification	7.1 Channel Surround Sound	
PHYSICAL Color Black Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 5% to 90% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	INPUT		
PHYSICAL Color Black Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Journal Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32" to 113"F (0" to 45"C) Storage Temperature Range 14" to 176"F (-10" to 80"C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	Product Length (in.)	5.9	
Color Black Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (kg) 0.5 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE) (WIRED TO DVI-D SINGLE-LINK)	Product Length (ft.)	0.49	
Material of Construction ABS, PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	PHYSICAL		
Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (kg) 0.5 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK)	Color	Black	
Cable Jacket Rating	Material of Construction	ABS, PVC	
Cable Outer Diameter (OD) 4.5mm Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	Cable Jacket Material	PVC	
Shipping Dimensions (hwd / in.) 4.00 x 14.00 x 17.00 Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE) (WIRED TO DVI-D SINGLE-LINK)	Cable Jacket Rating	VW-1	
Shipping Weight (kg) 3.08 Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	Cable Outer Diameter (OD)	4.5mm	
Unit Dimensions (hwd / in.) 1.770 x 0.590 x 3.340 Unit Weight (lbs.) 0.1 Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	Shipping Dimensions (hwd / in.)	4.00 x 14.00 x 17.00	
Unit Weight (lbs.) Unit Weight (kg) 0.05 ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	Shipping Weight (kg)	3.08	
Unit Weight (kg) ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE) HD15 (FEMALE)	Unit Dimensions (hwd / in.)	1.770 x 0.590 x 3.340	
ENVIRONMENTAL Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	Unit Weight (lbs.)	0.1	
Operating Temperature Range 32° to 113°F (0° to 45°C) Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) Side B - Connector 2 HD15 (FEMALE)	Unit Weight (kg)	0.05	
Storage Temperature Range 14° to 176°F (-10° to 80°C) Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 2 HD15 (FEMALE)	ENVIRONMENTAL		
Operating Humidity Range 10% to 85% RH, Non-Condensing Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) Side B - Connector 2 HD15 (FEMALE)	Operating Temperature Range	32° to 113°F (0° to 45°C)	
Storage Humidity Range 5% to 90% RH, Non-Condensing CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) Side B - Connector 2 HD15 (FEMALE)	Storage Temperature Range	14° to 176°F (-10° to 80°C)	
CONNECTIONS Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) Side B - Connector 2 HD15 (FEMALE)	Operating Humidity Range	10% to 85% RH, Non-Condensing	
Side A - Connector 1 DISPLAYPORT (MALE) Side B - Connector 1 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) Side B - Connector 2 HD15 (FEMALE)	Storage Humidity Range	5% to 90% RH, Non-Condensing	
Side B - Connector 1 DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK) Side B - Connector 2 HD15 (FEMALE)	CONNECTIONS		
Side B - Connector 2 HD15 (FEMALE)	Side A - Connector 1	DISPLAYPORT (MALE)	
	Side B - Connector 1	DVI-D DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK)	
Side B - Connector 3 HDMI (FEMALE)	Side B - Connector 2	HD15 (FEMALE)	
	Side B - Connector 3	HDMI (FEMALE)	



Connector Plating	Nickel	
Contact Plating	Gold; Nickel	
FEATURES & SPECIFICATIONS		
Displayport Specification	1.2	
HDCP Specification	1.4	
Driver Required	No	
STANDARDS & COMPLIANCE		
Product Compliance	CE (Europe); FCC (USA); REACH; RoHS; UKCA; WEEE	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	3-year limited warranty	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.