HP Stitch S500 64-in Printer



The robust, efficient printer for highly demanding dye sub users¹



*Product image may differ from actual product

Enjoy reliable, unattended printing	Optimize your uptime with easy	Perfect for fleet environments
 Print an entire shift unattended or overnight with the largest media rolls² and large ink supplies. Get reliable image quality with 2xCMYK printheads and automatic compensation of up to 30% nozzles out.¹ Reduce telescoping and manual media adjustments with the tension sensing winder and media advance sensor. Rely on color consistency from printer to 	 maintenance Reduce downtime and service costs. For the first time, you can replace the printheads yourself.² Stay ready to print outstanding quality, and reduce manual interventions, with automatic maintenance. Simplify and control your print operations and maximize uptime with HP Service and HP PrintOS. 	 Double your unattended printing capacity without increasing your production space.² Efficiently manage your fleet, and remotely monitor printer status and ink and substrate use, with HP PrintOS. Easily observe the status of your printer—at a glance and from afar—with the highly visible beacon.
printer. ²		

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

Messaging Footnotes

¹ Reliable image quality enabled with 2xCMYK printheads and automatic compensation of up to 30% nozzles out based on internal HP testing, July 2020. Unattended printing enabled by large media rolls and large ink

supplies. ² Compared to alternative 64-inch dye-sublimation based textile printers available as of June, 2020. Largest rolls up to 121 lb (55 kg). The HP Stitch S Printer series provides HP SmartColor tools and a built-in spectrophotometer for color consistency. Front media loading saves 50% floor space.

For more information, please visit http://www.hp.com/go/stitchs500



Technical specifications

110 m²/hr - Max Speed (1-pass); 62 m²/hr - Production Fast (2-	Product		
		235 kg	
pass); 43 m²/hr - Production Quality (3-pass); 34 m²/hr - Quality (4-pass); 22 m²/hr - High Quality (6-pass)	Shipping	431 kg	
Up to 1200 x 1200 dpi	Included		
HP Dye Sub Printing Technologies	What's in the box	HP Stitch S500 64-in Printer; Printer stand; Printheads; Maintenance cartridge; Ink collector; Take-up reel; Loading accessory; 2-in adapter kit; Beacon light; Edge holders; User	
5 x 5 x 0 x 0 mm (without edge holders)			
HP Dye Sub Inks		maintenance kit; Quick reference guide; Setup poster; Power cords; Waste bottle; Lockout drawer; HP Ergosoft RIP Color	
4 (cyan, magenta, yellow, black)		Edition	
	U		
3 L, 775 ml	Operating temperature	15 to 30°C	
	Operating humidity	20 to 80% RH (non-condensing) ²	
12 pl	Acoustics		
8 HP Thermal Inkjet (4 cyan/black, 4 magenta/yellow)	Sound pressure	Printing: 55 dB(A) (operating), 38 dB(A) (idle), <16 dB(A) (sleep)	
Average \leq 1 dE2000, 95% of colors \leq 1.5 dE2000 ¹	Sound power	Printing: 7.3 B(A) (operating), 5.6 B(A) (idle), <3.5 B(A) (sleep)	
Interior decoration: Fashion: Sportswear: Soft signage	•	1 kW (printing); 80 W (ready); < 2 W (sleep)	
	Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); one power cord; 13 A max. Not dual voltage, power supply varies by part number with # Option code identifier.	
Media rolls: 1; Roll size: 580 to 1625-mm rolls; Maximum roll weight: 55 kg; Maximum roll diameter: 250 mm;			
1625 mm	Certification		
Up to 0.5 mm	Safety	IEC 60950.1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Ukraîne (UA); Argentina (IRAM)	
Sublimation transfer papers, sublimation polyester fabrics, sublimation film			
Connectivity		Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New	
Gigabit Ethernet (1000Base-T)	F	Zealand (RCM), Japan (VCCI), Korea (KCĆ)	
Dimensions (W x D x H)		ENERGY STAR®; WEEE; EU RoHS; China RoHS; RoHS Korea; RoHS India; RoHS Ukraine; RoHS Turkey; REACH; EPEAT;	
2550 x 810 x 1420 mm		OSHA; CE marking compliant	
2740 x 1070 x 1700 mm	Warranty	One-year limited hardware warranty	
	HP Dye Sub Printing Technologies 5x 5 x 0 x 0 mm (without edge holders) HP Dye Sub Inks 4 (cyan, magenta, yellow, black) 3 L, 775 ml 12 pl 8 HP Thermal Inkjet (4 cyan/black, 4 magenta/yellow) Average ≤ 1 dE2000, 95% of colors ≤ 1.5 dE2000 ¹ Interior decoration; Fashion; Sportswear; Soft signage Roll feed, take-up reel, automatic cutter (for transfer media) Media rolls: 1; Roll size: 580 to 1625-mm rolls; Maximum roll up to 0.5 mm Sublimation transfer papers, sublimation polyester fabrics, sublimation film Gigabit Ethernet (1000Base-T) 2550 x 810 x 1420 mm	Op to 1200 X 1200 XP What's in the box HP Dye Sub Printing Technologies What's in the box 5 x 5 x 0 x 0 mm (without edge holders) Environmental ranges HP Dye Sub Inks Operating temperature 4 (cyan, magenta, yellow, black) Operating temperature 3 L, 775 ml Operating humidity 12 pl Acoustics 8 HP Thermal Inkjet (4 cyan/black, 4 magenta/yellow) Sound pressure Average ≤ 1 dE2000, 95% of colors ≤ 1.5 dE2000 ¹ Sound power Power Consumption Interior decoration; Fashion; Sportswear; Soft signage Requirements Roll feed, take-up reel, automatic cutter (for transfer media) Certification Media rolls: 1; Roll size: 580 to 1625-mm rolls; Maximum roll Certification 1625 mm Sublimation transfer papers, sublimation polyester fabrics, sublimation film Electromagnetic Gigabit Ethernet (1000Base-T) Environmental Environmental	

Product		2LL53A	HP 624 775-ml Black Stitch Dye Sublimation Ink Cartridge
2ET73A	HP Stitch S500 64-in Printer	2LL54A 2LL55A	HP 624 775-ml Cyan Stitch Dye Sublimation Ink Cartridge HP 624 775-ml Magenta Stitch Dye Sublimation Ink Cartridge
Accessories		- 2LL56A	HP 624 775-ml Yellow Stitch Dye Sublimation Ink Cartridge
5JX30A	HP Stitch S300/S500 Ink Collector	2LL57A	HP 636 3-liter Black Stitch Dye Sublimation Ink Cartridge
5QG59A	HP Ergosoft Pro RIP Color Edition	2LL58A	HP 636 3-liter Cyan Stitch Dye Sublimation Ink Cartridge
50G72A	HP Stitch S300/S500 User Maintenance Kit	2LL59A	HP 636 3-liter Magenta Stitch Dye Sublimation Ink Cartridge
F0M64A	HP Series 300/500 Edge Holder Kit	2LL60A	HP 636 3-liter Yellow Stitch Dye Sublimation Ink Cartridge
T7U74A	HP Series 300/500 Ink Collector Foam Kit	2LL61A	HP 614 Stitch Dye Sublimation Printhead Cleaning Kit
Original HP pr	inting supplies	2LL62A	HP 614 Cyan and Black Stitch Dye Sublimation Printhead
		2LL63A	HP 614 Magenta and Yellow Stitch Dye Sublimation Printhead

Use Original HP inks and printheads, and HP large format printing materials, to Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit https://hp.com/go/OriginalHPinks HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

Specification Footnotes

¹ The color variation inside a printed job has been measured at 6-pass mode on transfer media and also in direct-to-fabric situations within this limit: maximum color difference (95% of colors) ≤ 1.5 dE2000. Reflective measurements on a 943 color target under CIE standard IIUminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012.5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results. Results are dependent on sublimation process variability. ² Papers are hygroscopic materials. They can absorb or lose moisture depending on external humidity conditions. A low level of substrate's moisture and external relative humidity is always recommended when printing

on paper based materials. Recommended external relative humidity is between 25% to 50%.

© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

March 2025 ca-en

