



GreenSpace

DN460B LED11S/840 PSE-E C ELP3 WH

GreenSpace Mini UGR22 - LED Module, system flux 1100 lm - 840 neutral white - Power supply unit external, DC compatible for central emergency lighting - Emergency lighting 3 hours duration - White

Customers want to strike the ideal balance between their initial investment and the cost of the installation during its lifetime. GreenSpace is a cost-efficient and sustainable downlight that can be used to replace conventional CFL downlights in general lighting applications. It features the latest LED technology, which enables extremely low power consumption, while delivering consistent light output, stable color performance and high color rendering. The product's long lifetime makes it a true 'fit and forget' solution.


Product data

General Information	
Number of light sources	1 [1 pc]
Lamp family code	LED11S [LED Module, system flux 1100 lm]
Beam angle of light source	120 °
Light source colour	840 neutral white
Cap base	- [-]
Light source replaceable	No
Number of gear units	1 unit
Gear	-
Driver/power unit/transformer	PSE-E [Power supply unit external, DC compatible for central emergency lighting]
Driver included	Yes
Optic type	C [High-gloss mirror]
Luminaire light beam spread	80°

Emergency lighting	EL3 [Emergency lighting 3 hours duration]
Connection	PIP [Push-in connector and pull relief]
Cable	-
Protection class IEC	Safety class II (II)
Glow-wire test	850/5 [Temperature 850 °C, duration 5 s]
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	5 years
Remarks	<p>*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance</p>

between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.	
Constant light output	No
Number of products on MCB	30
RoHS mark	RoHS mark
Product Family Code	DN460B [GreenSpace Mini UGR22]
Light Technical	
Optical cover/lens type accessory	No [-]
Operating and Electrical	
Electrical accessories	No [-]
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Inrush current	14 A
Inrush time	0.24 ms
Power factor (min.)	0.9
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing material	Aluminum
Reflector material	Polycarbonate aluminum coated
Optic material	Polycarbonate
Optical cover/lens material	-
Fixation material	-
Optical cover/lens finish	-
Overall height	77 mm
Overall diameter	166 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Dimensional drawing



GreenSpace gen2 DN460B-DN473B

Initial Performance (IEC Compliant)

Initial luminous flux	1200 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	109.09 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	80
Initial chromaticity	(0.38, 0.38) SDCM <3.5
Initial input power	11 W
Power consumption tolerance	+/-5%

Over Time Performance (IEC Compliant)

Control gear failure rate at median	5 %
useful life 50000 h	
Lumen maintenance at median useful	L80
life* 50000 h	



Application Conditions

Ambient temperature range	+10 to +40 °C
Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Product Data

Full product code	871869624318300
Order product name	DN460B LED11S/840 PSE-E C ELP3 WH
EAN/UPC – product	8718696243183
Order code	24318300
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910500454947
Net weight (piece)	1.260 kg

Photometric data



IFGU1_DN460B1xLED11S840C

IFPC1_DN460B1xLED11S840C

