

**PHILIPS**

**Lighting**



# **ColorGraze QLX Powercore**

## **BCS467 10x60 RGB L914**

10° x 60° - 914 mm - aluminium

Many architectural structures need a linear fixture capable of illuminating several storeys with minimal setback and reduced power consumption. Property owners/end users need a controllable product capable of dynamic illumination to draw attention to their establishments and emphasize their brands. Graze QLX Powercore is capable of illuminating over 10 meters at very close setback distances. Powercore technology enables simple installation and long product run lengths.

### **Product data**

<b>General Information</b>		<b>Controls and Dimming</b>	
Lamp family code	LED-HB [ LED High Brightness]	Dimmable	Yes
Light source replaceable	No		
Driver included	Yes		
Luminaire light beam spread	10° x 60°		
Protection class IEC	Safety class I (I)		
CE mark	CE mark		
UL mark	UL and cUL mark		
Lifetime to 70% luminous flux	100000 h		
<b>Operating and Electrical</b>		<b>Mechanical and Housing</b>	
Input voltage	100 to 277 V	Housing material	Aluminum extruded
Input frequency	50 to 60 Hz	Optic material	Polycarbonate
		Optical cover/lens material	Polycarbonate
		Length	914 mm
<b>Approval and Application</b>			
		Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
		Mech. impact protection code	IK10 [ 20 J vandal-resistant]
		Vibration standard	Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations.

# ColorGraze QLX Powercore

Not compliant to ANSI C136.31, 3G. Special orders are available to conform to the standard. Please contact your Color Kinetics Lighting Sales rep for custom configurations.

## Initial Performance (IEC Compliant)

Initial input power 45 W

## Over Time Performance (IEC Compliant)

Lumen Maintenance 50% at 25°C 100000

Calculated

Lumen Maintenance 50% at 25°C 100000

Reported

Lumen Maintenance 50% at 50°C 80000

Calculated

Lumen Maintenance 50% at 50°C 80000

Reported

Lumen Maintenance 70% at 25°C 60000

Calculated

Lumen Maintenance 70% at 25°C 100000

Reported

Lumen Maintenance 70% at 50°C 60000

Calculated

Lumen Maintenance 70% at 50°C 91000

Reported

## Application Conditions

Ambient temperature range -40 to +50 °C

## Product Data

Full product code 871829160382500

Order product name BCS467 10x60 RGB L914

EAN/UPC – product 8718291603825

Order code 60382500


Numerator – quantity per pack 1

Numerator – packs per outer box 1

Material no. (12NC) 910503703358

Net weight (piece) 3.800 kg

## Dimensional drawing



Graze

