



## LuxSpace, recessed

### DN571B LED24S/830 PSE-E C WH

LUXSPACE 2 COMPACT DEEP - LED Module, system flux 2400 lm - 830 warm white - Power supply unit external, DC compatible for central emergency lighting - High-gloss mirror - White

Customers are looking to optimize all their resources, and that means not just their running costs (energy, etc.) but also their human resources. Energy savings are therefore a priority, but they must not have an adverse effect on the well-being of employees, who need a pleasant environment in order to be more productive, or on customers, who want to enjoy their shopping experience. LuxSpace provides the perfect combination of efficiency, light comfort and design, without compromising on lighting performance (color rendering and color uniformity). It offers a wide choice of options for creating the desired ambience, no matter the application. For office applications LuxSpace supports the general feeling of health and wellbeing having dedicated Tunable White products

#### Product data

General Information	
Number of light sources	1 pc
Lamp family code	LED24S [ LED Module, system flux 2400 lm]
Light source color	830 warm white
Cap-Base	- [ - ]
Light source replaceable	No
Number of gear units	1 unit
Gear	-
Driver/power unit/transformer	Power supply unit external, DC compatible for central emergency lighting
Driver included	Yes
Optic type	
Optical cover/lens type	High-gloss mirror
Luminaire light beam spread	70°
Emergency lighting	-
Connection	Push-in connector and pull relief
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 5 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark


# LuxSpace, recessed

ENEC mark	ENEC mark
UL mark	-
Warranty period	5 years
Decorative accessories	-
Remarks	<p>*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.</p>
Constant light output	No
Number of products on MCB of 16 A type	32
B	
RoHS mark	-
Product family code	DN571B [ LUXSPACE 2 COMPACT DEEP]
<b>Light Technical</b>	
Optical cover/lens type accessory	-
<b>Operating and Electrical</b>	
Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	18 A
Inrush time	0.24 ms
Power Factor (Min)	0.9
<b>Controls and Dimming</b>	
Dimmable	No
<b>Mechanical and Housing</b>	
Housing configuration	Basic version
Housing Material	Aluminum die-cast
Reflector material	Polycarbonate aluminum coated
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Frosted
Overall height	119 mm
Overall diameter	214 mm

<b>Approval and Application</b>	
Ingress protection code	IP20 [ Finger-protected]
Mech. impact protection code	IK02 [ 0.2 J standard]
<b>Initial Performance (IEC Compliant)</b>	
Initial luminous flux (system flux)	2500 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	109 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.43, 0.40) SDCM <3
Initial input power	23 W
Power consumption tolerance	+/-10%
<b>Over Time Performance (IEC Compliant)</b>	
Control gear failure rate at median useful life	5 %
life 50000 h	
Lumen maintenance at median useful life*	L90
life* 50000 h	
<b>Application Conditions</b>	
Ambient temperature range	+10 to +25 °C
Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)
<b>Product Data</b>	
Full product code	871829193145400
Order product name	DN571B LED24S/830 PSE-E C WH
EAN/UPC - Product	8718291931454
Order code	910503596915
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910503596915
Net Weight (Piece)	1.150 kg



# LuxSpace, recessed

## Dimensional drawing



LuxSpace gen2 DN570B-DN572B

## Photometric data



IFGU1\_DN571B PSE-E 1xLED24S830 C.EPS

IFPC1\_DN571B PSE-E 1xLED24S830 C.EPS

